



ASSA ABLOY

Steel-Stiffened Doors

- 18-ga. steel
- 1¾"-thick doors

Designed to take most abuse without failure. 22-ga. steel stiffeners are placed inside the door every 6" and welded every 5" along the length of the stiffener. Fiberglass insulation between the stiffeners helps deaden sound. Door top and bottom are sealed with a 16-ga. steel channel welded in place. Doors are handed; come with closer reinforcement.

Door Opening Width	Door Opening Height	Fire Rating	CHOOSE:	LEFT-HAND Item No.	RIGHT- HAND Item No.	
36 in	84 in	3 hr	Cylindrical, Mortise	D2914	D2915	_



ASSA ABLOY

6-Panel Embossed Steel Doors

- 18-ga. A40 galvanized steel
- 1¾"-thick doors

The durability of steel with the pleasing appearance of a wood door. Polystyrene insulated core is bonded to the interior of the steel skin. Doors have closer reinforcement.

Dull

Bright Dull

ROCKWOOD!


ASSA ABLOY

Door Opening Width 1	Door Opening Height	CHOOSE: Frame Type	CHOOSE: Lock Type	ltem No.
36 in	80 in	1, 2, 3	Cylindrical, Mortise	D2916
36 in	84 in	1, 2, 3	Cylindrical, Mortise	D2917

Dull 316 Dull 304 Diamond Stainless Stainless Tread







Stretcher Plate



Mop Plate

ROCKWOOD®

Door Protection Plates

- Plates are 0.05" thick except Diamond-Tread Aluminum are 0.075"; 6" and 8" widths are 0.040"; 10" widths and above are 0.063"
- Come with mounting holes and screws

Protect doors from scratches and dents caused by collisions from gurneys, carts, hand trucks, or heavy equipment. Choose a plate 2" narrower than door.

			Item	Item	Aluminum	Aluminum	Brass Item	Bronze Item
н	w	Brand	No.	No.	No.	No.	No.	No.
Armor		Diuliu	110.	110.	110.	110.	140.	140.
16 in	34 in	Rockwood	2RFW6	2RFR9	_	2RFZ3	2RGH8	2RGC9
24 in	34 in	Rockwood	2RFU9	_	_	_	2RGG4	2RGA3
34 in	24 in	Rockwood	_	_	_	2RFX6	_	_
34 in	34 in	Rockwood	2RFW7	2RFU2	_	2RFZ4	2RGH9	2RGD1
34 in	36 in	Rockwood	2RFW8	_	_	_	_	2RGD2
34 in	42 in	Rockwood	2RFW9	_	_	_	2RGJ2	2RGD3
34 in	42 in	_	_	_	2RGF7	_	_	_
42 in	34 in	Rockwood	_	_	_	2RFZ6	_	_
Kick/St	tretcher	Plates						
8 in	28 in	Rockwood	2RFV2	2RCH9	_	2RFX8	_	2RGA5
8 in	30 in	Rockwood	2RFV8	_	_	_	5U651	2RGC2
8 in	34 in	Rockwood	_	_	_	2RFY9	_	2RGC6
8 in	36 in	Rockwood	2RFX2	_	_	_	2RGJ4	2RGD5
8 in	40 in	Rockwood	2RFX5	_	_	_	5U653	2RGD8
10 in	28 in	Rockwood	2RFV3	2RFN9	_	2RFX9	_	2RGA6
10 in	30 in	Rockwood	2RFV9	2RFR1	_	2RFY6	2RGH3	2RGC3
10 in	34 in	Rockwood	2RFW4	_	_	2RFZ1	2RGH6	2RGC7
10 in	36 in	Rockwood	2RFX3	2RFU7	_	2RFZ9	2RGJ5	2RGD6
12 in	28 in	Rockwood	2RFV4	2RFP2	_	2RFY1	2RGG8	2RGA7
12 in	30 in	Rockwood	2RFW1	2RFR3	_	2RFY7	2RGH4	2RGC4
12 in	34 in	Rockwood	_	_	_	2RFZ2	2RGH7	2RGC8
12 in	36 in	Rockwood	2RFX4	2RFU8	_	_	2RGJ6	2RGD7
Mop Pl	ates							
6 in	28 in	Rockwood	2RFV1	2RCH8	_	_	2RGG5	2RGA4
6 in	30 in	Rockwood	2RFV7	2RFP8	_	2RFY4	2RGH2	2RGC1
6 in	34 in	Rockwood	2RFW2	_	_	2RFX7	2RGH5	2RGC5



Door Hardware Protectors

Protect door hardware from damage caused by moving carts, gurneys, and hand trucks.

Length	Width	Projection	Center Center Length	Hand	Item No.			
Lever Doo	r Trim Prot	ector Bars						
	_	3 1/4 in	8 in		3HJF9			
_	_	3 1/4 in	12 in	_	3HJF6			
Exit Devic	Exit Device Protector Bars							
	_	3 1/4 in	7 ½ in		3HJF7			
	_	4 ½ in	8 ½ in		3HJF8			
Vertical R	od Covers							
12 in	3 1/4 in	1 5/8 in	_		3HJG1			
24 in	3 1/4 in	1 % in	_		3HJG2			

Lenath	Width	Proiection	Center Lenath	Hand	Item No.
Latch Guar	rd Covers				
10 in	6 in	2 ¾ in	_	Left	3HJG3
10 in	6 in	2 ¾ in	_	Right	3HJG4
12 in	6 in	2 % in	_	Left	3HJG5
12 in	6 in	2 ¾ in	_	Right	3HJG6
16 in	6 in	2 ¾ in	_	Left	3HJG7
16 in	6 in	2 % in	_	Right	3HJG8
Door Coord	dinators				
For IIca M	/ith 72" Do	or Openings			3H IH1

Center to