



Finish	W	H	3-FT. LENGTH Item No.	4-FT. LENGTH Item No.	6-FT. LENGTH Item No.
Saddles—Plain Top					
Aluminum	2 1/2 in	1/4 in	2RRK7 *	3HRN1	3HRN2
Aluminum Mill	3 in	1/4 in	5MUN3	5MUN4	5MUN5
Dark Bronze	3 in	1/4 in	5MUN6	5MUN7	5MUN8
Saddles—Fluted Top					
Aluminum	4 in	1/2 in	3HRN3	3HRN4	3HRN5
Aluminum	4 in	1/2 in	1VZR2 †	—	2RRK8
Aluminum	4 in	1/4 in	3HRP9	3HRR1	3HRR2
Aluminum	5 in	1/2 in	1VZR3 †	3HRP2	2RR2
Aluminum	5 in	1/4 in	3HRN6	3HRP7	3HRN8
Aluminum	5 in	1/4 in	2RRK9 †	—	—
Aluminum	6 in	1/2 in	2RR3 †	3HRP4	2RR4

* Not UL Classified. † Heavy-duty aluminum.

Saddles and Door Thresholds

■ Additional thresholds available on Grainger.com
Fill and cover gaps under doors.

Finish	W	H	3-FT. LENGTH Item No.	4-FT. LENGTH Item No.	6-FT. LENGTH Item No.
Aluminum	6 in	1/4 in	5MFJ4	—	5MFJ5
Aluminum	7 in	1/2 in	3HRP6	3HRP7	3HRP8
Aluminum	6 3/4 in	1/2 in	3HRR3 †	3HRR4 †	3HRR5 †
Nonskid Aluminum	5 in	1/2 in	3HRT3 †	3HRT4 †	3HRT5 †
Mill	5 in	1/4 in	—	—	2RR1
Surface Mount Threshold					
Aluminum	1 3/4 in	1/4 in	5MFH7	—	—
Vinyl Insert Thresholds					
Aluminum	3 1/4 in	1/4 in	1VZR4 *	—	—
Panic Exit Thresholds					
Aluminum	5 in	1/2 in	3HRT8	3HRU1	3HRU2
Solid Vinyl Thresholds					
Matte	3 7/16 in	2 3/8 in	5EPD7	—	—
Door Bumper Thresholds					
Aluminum	3 1/6 in	5/8 in	2RR7 *	—	—
Aluminum	5 in	1/2 in	—	3HRU4	—
Aluminum Mill	5 in	1 in	5MUM1	5MUM2	5MUM3
Aluminum Mill	5 in	7/8 in	5MUM7	5MUM8	5MUM9
Offset Thresholds					
Aluminum Mill	5 1/2 in	1/2 in	5MUN9	5MUP0	5MUP1
Dark Bronze	5 1/2 in	1/2 in	5MUP2	5MUP3	5MUP4

Saddles and Door Thresholds

Features fluted top to fill and cover gaps under doors. Aluminum construction.



W	H	3 ft LENGTH Item No.	4 ft LENGTH Item No.	6 ft LENGTH Item No.
5 in	1/4 in	45AE53	45AC60	44ZZ80
5 in	1/2 in	45AC27	44ZZ27	45AD39
6 in	1/4 in	45AE59	45AA54	45AC82
8 in	1/4 in	45AC22	45AA03	45AA95
8 in	1/2 in	44ZZ50	45AC39	45AC80
10 in	1/2 in	44ZZ65	45AC30	45AD23



Access Doors

Conceal wall openings with a secure cover that can be finished to match wall color.

ACOUSTICAL, FOR DRYWALL

16-ga. steel door with continuous piano hinge. Allen hex head operated cam latch.

ADJUSTABLE

20-ga. steel door. Adjustable by 1 1/2" in height and width. Magnetic latching mechanism.

DRYWALL

16-ga. door and frame with drywall corner bead flange. Flush mounted with concealed pin hinge. Screwdriver operated cam latch.

FIRE-RATED, INSULATED, STANDARD

16-ga. steel frame and 20-ga. steel door with automatic panel closer and inside release. Self

latching tool or ring operated slam latch. 2" mineral wool insulation for a 2-hr. fire barrier and 1 1/2-hr., B label. Fire rating of 1 1/2 hr. in walls, 3 hr. in noncombustible ceilings and 1 hr. in combustible ceilings.

Upward-Swinging—

For ceilings only. Same as fire rated insulated model but the panel swings up and shuts down by way of gravity instead of springs.

FIRE-RATED, UNINSULATED, STANDARD

16-ga. steel door for vertical fire-rated surface only where temperature rise protection is not required. Fire rating of 1 1/2 hr. B-Label for 2-hr. rated walls.

HIDDEN FLANGE

16-ga. exclusive steel door. Flush mount with

european-type hinge. Screwdriver-operated cam latch.

INSULATED, ALUMINUM

16-ga., corrosion-resistant aluminum door and frame. Feature 1"-thick insulation and gasket around perimeter.

MEDIUM SECURITY

14-ga. steel with baked-on paintable prime coat. Continuous piano hinge and key-operated cylinder lock.

PLASTIC

High-impact, noncorrosive ABS plastic doors

are UV stabilized for exterior use. 5YM02 has punch-outs for electric and plumbing.

STANDARD

Steel—16-ga. steel door with flush-mount

doors with pin hinge (continuous piano hinge for 2VE87 and 2VE88). Screwdriver-operated cam latch.

Stainless Steel—

Corrosion-resistant door and frame.

Door Dim.		Rough Opening		Item No.
W	H	W	H	
Acoustical For Drywall Hex Head Cam Latch				
8 in	8 in	8 1/4 in	8 1/4 in	16M220
12 in	12 in	12 1/4 in	12 1/4 in	16M221
24 in	24 in	24 1/4 in	24 1/4 in	16M222
Adjustable (4) Magnets				
14 in to 15 1/2 in	15 1/2 in	14 in	14 in to 15 1/2 in	20TL34
Drywall Screwdriver Operated Cam Latch				
8 in	8 in	8 3/4 in	8 3/4 in	2VE75
12 in	12 in	12 3/4 in	12 3/4 in	2VE72
16 in	16 in	16 1/4 in	16 1/4 in	16M207
18 in	18 in	18 3/4 in	18 3/4 in	2VE73
24 in	24 in	24 3/4 in	24 3/4 in	2VE74
Fire-Rated, Insulated, Standard Self-Latching Tool Key and Ring Operated Slam Latch				
8 in	8 in	8 1/4 in	8 1/4 in	16M205
12 in	12 in	12 1/4 in	12 1/4 in	5YL98
16 in	16 in	16 1/4 in	16 1/4 in	5YL99
18 in	18 in	18 3/4 in	18 1/4 in	2VE76
22 in	30 in	22 1/4 in	30 1/4 in	5YM01
22 in	36 in	22 3/4 in	36 3/4 in	2VE77
24 in	24 in	24 1/4 in	24 1/4 in	16M206
Fire-Rated, Insulated, Upward-Swinging Hex Head Slam Latch Outside and Self-Latching Ring Operated Slam Latch Inside				
22 in	30 in	22 3/4 in	30 3/4 in	2VE78
22 in	36 in	22 3/4 in	36 3/4 in	2VE79
24 in	24 in	24 3/4 in	24 3/4 in	2VE80
Fire-Rated, Uninsulated, Standard Self-Latching Tool Key and Ring Operated Slam Latch				
8 in	8 in	8 1/4 in	8 1/4 in	16M215
12 in	12 in	12 1/4 in	12 1/4 in	16M216
16 in	16 in	16 1/4 in	16 1/4 in	16M217
18 in	18 in	18 1/4 in	18 1/4 in	16M218
24 in	24 in	24 1/4 in	24 1/4 in	16M219
Hidden Flange Screwdriver Operated Cam Latch				
8 1/4 in	8 1/4 in	8 1/2 in	8 1/2 in	16M209
12 in	12 in	12 1/4 in	12 1/4 in	16M210
14 in	14 in	14 1/4 in	14 1/4 in	16M211
16 in	16 in	16 1/4 in	16 1/4 in	16M212
18 in	18 in	18 1/4 in	18 1/4 in	16M213
24 in	24 in	24 1/4 in	24 1/4 in	16M214

* Includes cylinder lock and key.

Door Dim.	W	H	Rough Opening		Item No.
Insulated, Aluminum Cylinder Lock and Key					
8 in	8 in	8 3/4 in	8 3/4 in		2VE89
12 in	12 in	12 3/4 in	12 3/4 in		2VE90
16 in	16 in	16 3/4 in	16 3/4 in		2VE91
18 in	18 in	18 3/4 in	18 3/4 in		2VE92
24 in	24 in	24 3/4 in	24 3/4 in		2VE93
Medium Security, Flush Key Operated Cylinder Cam Latch					
12 in	12 in	12 1/2 in	12 1/2 in		1UEV7
16 in	16 in	16 1/2 in	16 1/2 in		1UEV8
18 in	18 in	18 1/2 in	18 1/2 in		1UEV9
24 in	24 in	24 1/2 in	24 1/2 in		1UEX2
Plastic Snap Friction Catch					
6 in	9 in	6 3/4 in	9 3/4 in		5YM02
14 in	14 in	14 3/4 in	14 3/4 in		5YM03
14 in	29 in	14 3/4 in	29 3/4 in		2VE81
Standard, Stainless Steel Screwdriver Operated Cam Latch					
10 in	10 in	10 3/4 in	10 3/4 in		2VE82
16 in	16 in	16 3/4 in	16 3/4 in		2VE83
Standard, Steel Key Operated Cylinder Cam Latch					
12 in	12 in	12 3/4 in	12 3/4 in		1UEW7 *
14 in	14 in	14 1/4 in	14 1/4 in		1UEW8 *
16 in	16 in	16 3/4 in	16 3/4 in		1UEW9 *
18 in	18 in	18 1/4 in	18 1/4 in		16M208 *
24 in	24 in	24 3/4 in	24 3/4 in		1UEX1 *
Screwdriver Operated Cam Latch					
8 in	8 in	8 1/4 in	8 1/4 in		5YL92
10 in	10 in	10 1/4 in	10 1/4 in		5YL93
12 in	12 in	12 1/4 in	12 1/4 in		5YL94
14 in	14 in	14 1/4 in	14 1/4 in		5YL95
16 in	16 in	16 1/4 in	16 1/4 in		5YL96
16 in	24 in	16 3/4 in	24 3/4 in		2VE84
18 in	18 in	18 3/4 in	18 3/4 in		2VE85
18 in	24 in	18 3/4 in	24 3/4 in		2VE86
24 in	24 in	24 1/4 in	24 1/4 in		5YL97
24 in	36 in	24 1/4 in	36 1/4 in		2VE87
36 in	36 in	36 1/4 in	36 1/4 in		2VE88