



CONTINUED

## Standard Socket Head Cap Screws, Inch

Fastener Length	Head Height	Head Diameter	Thread Style*	Item No.	Pkg. Qty.
<b>5/16"-24 Thread Size, 1/4 in Drive</b>					
1/2 in	0.312 in	0.469 in	FT	4XU56	100
3/4 in	0.312 in	0.469 in	FT	4XU57	100
1 in	0.312 in	0.469 in	FT	22TW30	50
1 1/4 in	0.312 in	0.469 in	PT	22TW34	50
1 1/2 in	0.312 in	0.469 in	PT	22TW44	50
1 3/4 in	0.312 in	0.469 in	PT	6ZU71	50
2 in	0.312 in	0.469 in	PT	5MYC8	50
3 in	0.312 in	0.469 in	PT	22TW66	25
<b>3/8"-16 Thread Size, 5/16 in Drive</b>					
1/2 in	0.375 in	0.562 in	FT	22TR23	50
1/2 in	0.375 in	0.562 in	FT	5TAL9	100
3/4 in	0.375 in	0.562 in	FT	22TR24	50
1 in	0.375 in	0.562 in	FT	5TAN0	100
3/4 in	0.375 in	0.562 in	FT	22TR25	50
3/4 in	0.375 in	0.562 in	FT	5TAN1	100
1 1/2 in	0.375 in	0.562 in	FT	22TR26	50
1 1/2 in	0.375 in	0.562 in	FT	22TR28	50
1 1/4 in	0.375 in	0.562 in	FT	22TR29	50
1 3/8 in	0.375 in	0.562 in	PT	22TR30	50
1 1/2 in	0.375 in	0.562 in	PT	22TR31	25
1 3/4 in	0.375 in	0.562 in	PT	22TP92	25
1 3/4 in	0.375 in	0.562 in	PT	5TAN6	50
2 in	0.375 in	0.562 in	PT	22TR32	25
2 in	0.375 in	0.562 in	PT	5TAN7	50
2 1/4 in	0.375 in	0.562 in	PT	22TR33	25
2 1/4 in	0.375 in	0.562 in	PT	5TAN8	50
2 1/2 in	0.375 in	0.562 in	PT	22TR34	25
2 3/4 in	0.375 in	0.562 in	PT	22TR35	25
3 in	0.375 in	0.562 in	PT	22TR36	10
3 1/4 in	0.375 in	0.562 in	PT	22TR37	10
3 1/2 in	0.375 in	0.562 in	PT	22TR38	10
3 3/4 in	0.375 in	0.562 in	PT	22TR39	10
4 in	0.375 in	0.562 in	PT	5TAN9	50
4 1/4 in	0.375 in	0.562 in	PT	26KW58	10
4 1/2 in	0.375 in	0.562 in	PT	22TR41	10
4 1/2 in	0.375 in	0.562 in	PT	5TAP0	50
4 3/4 in	0.375 in	0.562 in	PT	26KW59	10
5 in	0.375 in	0.562 in	PT	22TR42	10
5 in	0.375 in	0.562 in	PT	5TAP1	50
5 1/2 in	0.375 in	0.562 in	PT	22TR43	10
5 1/2 in	0.375 in	0.562 in	PT	33W070	50
6 in	0.375 in	0.562 in	PT	22TR44	10
6 in	0.375 in	0.562 in	PT	5TAP2	50
6 1/2 in	0.375 in	0.562 in	PT	6ZY24	5
7 in	0.375 in	0.562 in	PT	6ZY27	5
7 1/2 in	0.375 in	0.562 in	PT	26KW60	5
9 in	0.375 in	0.562 in	PT	6ZY33	5
<b>3/8"-24 Thread Size, 5/16 in Drive</b>					
1/2 in	0.375 in	0.562 in	FT	6ZY39	50
3/4 in	0.375 in	0.562 in	FT	6ZY42	50
1 in	0.375 in	0.562 in	FT	22TW69	50
1 1/4 in	0.375 in	0.562 in	PT	6ZY49	50
1 1/2 in	0.375 in	0.562 in	PT	22TW70	25
1 3/4 in	0.375 in	0.562 in	PT	22TW47	25
2 1/4 in	0.375 in	0.562 in	PT	22TW72	25
2 1/2 in	0.375 in	0.562 in	PT	22TW73	25
2 3/4 in	0.375 in	0.562 in	PT	22TW74	25
<b>1/2"-14 Thread Size, 3/4 in Drive</b>					
1/2 in	0.437 in	0.656 in	FT	6ZY71	25
3/4 in	0.437 in	0.656 in	FT	22TR47	25
1 in	0.437 in	0.656 in	FT	22TR49	25
1 1/4 in	0.437 in	0.656 in	FT	22TR50	25
1 1/2 in	0.437 in	0.656 in	FT	22TR51	25
1 3/4 in	0.437 in	0.656 in	PT	22TR52	10
2 in	0.437 in	0.656 in	PT	6ZY89	10
2 1/4 in	0.437 in	0.656 in	PT	6ZY92	10
2 1/2 in	0.437 in	0.656 in	PT	6ZY95	10
2 3/4 in	0.437 in	0.656 in	PT	6ZY98	10
3 in	0.437 in	0.656 in	PT	3MB86	10
3 1/2 in	0.437 in	0.656 in	PT	22TR03	5
4 in	0.437 in	0.656 in	PT	22TR04	5
5 in	0.437 in	0.656 in	PT	22TR19	5
<b>1/2"-20 Thread Size, 3/4 in Drive</b>					
1/2 in	0.437 in	0.656 in	FT	26KW63	25
3/4 in	0.437 in	0.656 in	FT	26KW65	25
1 in	0.437 in	0.656 in	FT	3MB89	25
1 1/4 in	0.437 in	0.656 in	FT	3MB93	25
1 1/2 in	0.437 in	0.656 in	FT	3MB97	25
2 in	0.437 in	0.656 in	PT	3KB78	10
2 1/2 in	0.437 in	0.656 in	PT	22TW82	10
<b>1/2"-13 Thread Size, 3/4 in Drive</b>					
1/2 in	0.5 in	0.75 in	FT	5TAP6	50
1 1/4 in	0.5 in	0.75 in	FT	22TR57	10
1 1/2 in	0.5 in	0.75 in	FT	22TR59	10
1 3/4 in	0.5 in	0.75 in	FT	22TR60	10
2 1/4 in	0.5 in	0.75 in	PT	22TR62	10
2 1/2 in	0.5 in	0.75 in	PT	22TR63	10
2 3/4 in	0.5 in	0.75 in	PT	22TR64	10
3 in	0.5 in	0.75 in	PT	29DU65	5
3 1/4 in	0.5 in	0.75 in	PT	22TR66	5
3 1/2 in	0.5 in	0.75 in	PT	22TR67	5
3 3/4 in	0.5 in	0.75 in	PT	3KE96	5
4 in	0.5 in	0.75 in	PT	22TR69	5
4 1/4 in	0.5 in	0.75 in	PT	3KE99	5
4 1/2 in	0.5 in	0.75 in	PT	22TR70	5
4 3/4 in	0.5 in	0.75 in	PT	3KU14	5
5 in	0.5 in	0.75 in	PT	22TR71	5
5 1/4 in	0.5 in	0.75 in	PT	3KU18	5
5 1/2 in	0.5 in	0.75 in	PT	22TR72	5
5 3/4 in	0.5 in	0.75 in	PT	3KU22	5
6 in	0.5 in	0.75 in	PT	22TR73	5

Fastener Length	Head Height	Head Diameter	Thread Style*	Item No.	Pkg. Qty.
6 1/2 in	0.5 in	0.75 in	PT	22TR74	5
7 in	0.5 in	0.75 in	PT	3KU26	5
7 1/2 in	0.5 in	0.75 in	PT	22TR75	5
8 in	0.5 in	0.75 in	PT	3KU30	5
8 1/2 in	0.5 in	0.75 in	PT	22TR53	1
9 in	0.5 in	0.75 in	PT	22TR56	1
9 1/2 in	0.5 in	0.75 in	PT	22TR65	1
10 in	0.5 in	0.75 in	PT	3KU45	5
<b>1/2"-20 Thread Size, 3/4 in Drive</b>					
3/4 in	0.5 in	0.75 in	FT	22TW84	10
1 in	0.5 in	0.75 in	FT	26KW67	10
1 1/4 in	0.5 in	0.75 in	FT	3FY64	10
1 1/2 in	0.5 in	0.75 in	FT	3FY69	10
1 3/4 in	0.5 in	0.75 in	FT	3FY74	10
2 in	0.5 in	0.75 in	PT	3FY78	10
2 1/2 in	0.5 in	0.75 in	PT	5MYD7	10
<b>5/8"-12 Thread Size, 1/2 in Drive</b>					
1 in	0.562 in	0.843 in	FT	26KT64	10
1 1/4 in	0.562 in	0.843 in	FT	26KT65	10
1 1/2 in	0.562 in	0.843 in	FT	22TR76	10
1 3/4 in	0.562 in	0.843 in	FT	26KT66	10
2 in	0.562 in	0.843 in	FT	26KT67	5
2 1/2 in	0.562 in	0.843 in	PT	26KT68	5
3 in	0.562 in	0.843 in	PT	26KT70	5
3 1/2 in	0.562 in	0.843 in	PT	22TR78	5
<b>5/8"-18 Thread Size, 1/2 in Drive</b>					
1 in	0.562 in	1 in	FT	26KW79	10
1 1/4 in	0.562 in	1 in	FT	26KW80	10
1 1/2 in	0.562 in	0.843 in	FT	26KW81	10
2 in	0.562 in	0.843 in	FT	26KW83	5
3 in	0.562 in	1 in	PT	26KW86	5
4 in	0.562 in	1 in	PT	26KW87	5
<b>5/8"-11 Thread Size, 1/2 in Drive</b>					
3/4 in	0.625 in	0.938 in	FT	26KT80	10
3/4 in	0.625 in	0.938 in	FT	26KT81	10
1 in	0.625 in	0.938 in	FT	22TR79	10
1 1/4 in	0.625 in	0.938 in	FT	22TR80	10
1 1/2 in	0.625 in	0.938 in	FT	22TR81	10
1 3/4 in	0.625 in	0.938 in	FT	22TR82	10
2 in	0.625 in	0.938 in	PT	29DU66	5
2 1/4 in	0.625 in	0.938 in	PT	26KT84	5
2 1/2 in	0.625 in	0.938 in	PT	22TR83	5
2 3/4 in	0.625 in	0.938 in	PT	22TR84	5
3 in	0.625 in	0.938 in	PT	22TR85	5
3 1/4 in	0.625 in	0.938 in	PT	22TR86	5
3 1/2 in	0.625 in	0.938 in	PT	22TR87	5
4 in	0.625 in	0.938 in	PT	22TR88	5
4 1/2 in	0.625 in	0.938 in	PT	22TR89	5
5 in	0.625 in	0.938 in	PT	22TR90	5
5 1/2 in	0.625 in	0.938 in	PT	22TR91	5
6 in	0.625 in	0.938 in	PT	22TR92	5
6 1/2 in	0.625 in	0.938 in	PT	22TR93	5
7 in	0.625 in	0.938 in	PT	22TR94	5
7 1/2 in	0.625 in	0.938 in	PT	22TR95	5
8 in	0.625 in	0.938 in	PT	22TR96	5
9 in	0.625 in	0.938 in	PT	26KT88	1
10 in	0.625 in	0.938 in	PT	26KT90	1
11 in	0.625 in	1 in	PT	26KT91	1
<b>5/8"-18 Thread Size, 1/2 in Drive</b>					
1 1/4 in	0.625 in	0.938 in	FT	26KW92	10
1 1/2 in	0.625 in	0.938 in	FT	26KW93	10
2 in	0.625 in	0.938 in	FT	26KW95	5
2 1/2 in	0.625 in	0.938 in	PT	26KW97	5
3 in	0.625 in	0.938 in	PT	26KW99	5
4 1/2 in	0.625 in	1 in	PT	26KX04	5
5 in	0.625 in	0.938 in	PT	22TW92	5
8 in	0.625 in	0.938 in	PT	26KX09	5
<b>3/4"-10 Thread Size, 3/4 in Drive</b>					
1 in	0.75 in	1.125 in	FT	26KT92	5
1 1/4 in	0.75 in	1.125 in	FT	22TR97	5
1 1/2 in	0.75 in	1.125 in	FT	22TR98	5
1 3/4 in	0.75 in	1.125 in	FT	22TR99	5
2 in	0.75 in	1.125 in	FT	22TR01	5
2 1/4 in	0.75 in	1.125 in	PT	22TR02	5
2 1/2 in	0.75 in	1.125 in	PT	22TR03	5
2 3/4 in	0.75 in	1.125 in	PT	22TR04	5
3 in	0.75 in	1.125 in	PT	22TR05	5
3 1/4 in	0.75 in	1.125 in	PT	22TR06	5
3 1/2 in	0.75 in	1.125 in	PT	22TR07	5
3 3/4 in	0.75 in	1.125 in	PT	1HLJ3	5
4 in	0.75 in	1.125 in	PT	22TR08	5
4 1/4 in	0.75 in	1.125 in	PT	26KT93	5
4 1/2 in	0.75 in	1.125 in	PT	22TR09	5
4 3/4 in	0.75 in	1.125 in	PT	26KT94	5
5 in	0.75 in	1.125 in	PT	22TR10	5
5 1/2 in	0.75 in	1.125 in	PT	22TR11	5
6 in	0.75 in	1.125 in	PT	22TR12	5
6 1/2 in	0.75 in	1.125 in	PT	22TR13	1
7 in	0.75 in	1.125 in	PT	22TR14	1
7 1/2 in	0.75 in	1.125 in	PT	1HLJ4	1
8 in	0.75 in	1.125 in	PT	22TR15	1
9 in	0.75 in	1.125 in	PT	22TR17	1
11 in	0.75 in	1.125 in	PT	22TR20	1
<b>3/4"-16 Thread Size, 3/4 in Drive</b>					
2 in	0.75 in	1.125 in	FT	22TW93	5
2 1/4 in	0.75 in	1.125 in	FT	1AE18	5
2 1/2 in	0.75 in	1.125 in	PT	26KX14	5
3 in	0.75 in	1.125 in	PT	26KX16	5
3 1/2 in	0.75 in	1.125 in	PT	26KX18	5
4 in	0.75 in	1.125 in	PT	26KX19	5