

# Flat Head Socket Cap Screws



Fastener Length	Head Height	Head Diameter	Thread Style*	Item No.	Pkg. Qty.
<b>18-8 Stainless Steel</b>					
<b>#8-32 Thread Size, 1/32 in Drive</b>					
3/8 in	0.112 in	0.312 in	FT	5WEY8	100
1/2 in	0.112 in	0.312 in	FT	5WEZ0	100
<b>#10-24 Thread Size, 1/8 in Drive</b>					
1/2 in	0.127 in	0.411 in	FT	5WEZ5	100
3/8 in	0.127 in	0.411 in	FT	5WEZ6	100
3/4 in	0.127 in	0.411 in	FT	5WEZ7	100
1 in	0.127 in	0.411 in	FT	5WEZ8	100
<b>#10-32 Thread Size, 1/8 in Drive</b>					
3/8 in	0.127 in	0.411 in	FT	5WFA0	100
1/2 in	0.127 in	0.411 in	FT	5WFA1	100
3/4 in	0.127 in	0.411 in	FT	5WFA2	100
1 in	0.127 in	0.411 in	FT	5WFA3	100
1 in	0.127 in	0.411 in	FT	5WFA5	100
<b>1/4"-20 Thread Size, 5/32 in Drive</b>					
1/2 in	0.161 in	0.531 in	FT	5WFA8	100
3/8 in	0.161 in	0.531 in	FT	5WFA9	100
3/4 in	0.161 in	0.531 in	FT	5WFC0	100
1 in	0.161 in	0.531 in	FT	22TX97	100
1 1/4 in	0.161 in	0.531 in	PT	22TX98	100
1 1/2 in	0.161 in	0.531 in	PT	22TX99	100
1 3/4 in	0.161 in	0.531 in	PT	22TY01	100
2 in	0.161 in	0.531 in	PT	26LC12	50
2 1/2 in	0.161 in	0.531 in	PT	22TY02	50
<b>5/16"-18 Thread Size, 3/16 in Drive</b>					
1/2 in	0.198 in	0.656 in	FT	22TY03	100
3/4 in	0.198 in	0.656 in	FT	22TY05	100
1 in	0.198 in	0.656 in	FT	22TY06	50
1 1/4 in	0.198 in	0.656 in	PT	22TY07	50
1 1/2 in	0.198 in	0.656 in	PT	22TY08	50
2 in	0.198 in	0.656 in	PT	22TY10	50
<b>3/8"-16 Thread Size, 1/32 in Drive</b>					
1/2 in	0.234 in	0.781 in	FT	26LC17	50
3/4 in	0.234 in	0.781 in	FT	26LC19	50
1 in	0.234 in	0.781 in	FT	22TY12	50
1 1/4 in	0.234 in	0.781 in	FT	22TY13	50
1 1/2 in	0.234 in	0.781 in	PT	22TY14	25
1 3/4 in	0.234 in	0.781 in	PT	22TY15	25
2 in	0.234 in	0.781 in	PT	22TY16	25
2 1/4 in	0.234 in	0.781 in	PT	26LC21	25
2 1/2 in	0.234 in	0.781 in	PT	26LC22	25
<b>1/2"-13 Thread Size, 1/16 in Drive</b>					
1 1/4 in	0.251 in	0.938 in	FT	5WFE0	10
1 1/2 in	0.251 in	0.938 in	FT	5WFE1	10
1 3/4 in	0.251 in	0.938 in	FT	5WFE2	10
2 in	0.251 in	0.938 in	FT	5WFE3	10
2 in	0.251 in	0.938 in	PT	22TY17	10
<b>5/8"-11 Thread Size, 3/8 in Drive</b>					
1 1/2 in	0.324 in	1.188 in	FT	26LC30	10
2 in	0.625 in	1 in	PT	26LC32	5
3 in	0.625 in	1 in	PT	26LC35	5
<b>3/4"-10 Thread Size, 1/2 in Drive</b>					
1 1/2 in	0.75 in	1.125 in	FT	26LC39	5
<b>M4-0.70 Thread Size, 2.5 mm Drive</b>					
10 mm	2.48 mm	8.96 mm	FT	26LF45	50
<b>M5-0.80 Thread Size, 3 mm Drive</b>					
10 mm	3.2 mm	11.2 mm	FT	26LF53	50
12 mm	3.2 mm	11.2 mm	FT	26LF54	50
16 mm	3.2 mm	11.2 mm	FT	29DJ61	50
20 mm	3.2 mm	11.2 mm	FT	26LF55	50
25 mm	3.2 mm	11.2 mm	FT	26LF56	50
<b>M6-1.00 Thread Size, 4 mm Drive</b>					
10 mm	3.72 mm	13.44 mm	FT	26LF59	50
12 mm	3.72 mm	13.44 mm	FT	26LF60	50
14 mm	3.72 mm	13.44 mm	FT	60DY6	50
16 mm	3.72 mm	13.44 mm	FT	26LF61	50
20 mm	3.72 mm	13.44 mm	FT	26LF62	50
25 mm	3.72 mm	13.44 mm	FT	26LF63	50
30 mm	3.72 mm	13.44 mm	FT	29DJ63	50
<b>M8-1.25 Thread Size, 5 mm Drive</b>					
12 mm	4.96 mm	17.92 mm	FT	26LF66	50
14 mm	4.96 mm	17.92 mm	FT	60DY40	25
16 mm	4.96 mm	17.92 mm	FT	26LF67	50
20 mm	4.96 mm	17.92 mm	FT	26LF68	50
25 mm	4.96 mm	17.92 mm	FT	26LF69	50
30 mm	4.96 mm	17.92 mm	FT	26LF70	50
35 mm	4.96 mm	17.92 mm	FT	26LF71	50
40 mm	4.96 mm	17.92 mm	FT	26LF72	50
45 mm	4.96 mm	17.92 mm	FT	53GJ66	50
50 mm	4.96 mm	17.92 mm	PT	26LF73	50
<b>M10-1.50 Thread Size, 6 mm Drive</b>					
16 mm	6.2 mm	22.4 mm	FT	29DJ65	50
20 mm	6.2 mm	22.4 mm	FT	26LF74	50
25 mm	6.2 mm	22.4 mm	FT	26LF75	50
30 mm	6.2 mm	22.4 mm	FT	26LF76	50
35 mm	6.2 mm	22.4 mm	FT	53GK03	50
40 mm	6.2 mm	22.4 mm	FT	26LF77	25
50 mm	6.2 mm	22.4 mm	FT	26LF78	25
<b>18-8 Stainless Steel NL-19, Foreverbolt</b>					
<b>1/4"-20 Thread Size, 5/32 in Drive</b>					
1 1/4 in	0.161 in	0.531 in	FT	36RJ68	50
1 1/2 in	0.161 in	0.531 in	FT	36RJ69	50
<b>3/8"-16 Thread Size, 1/32 in Drive</b>					
2 in	0.234 in	0.781 in	FT	36RJ77	10
<b>316 Stainless Steel</b>					
<b>M5-0.80 Thread Size, 3 mm Drive</b>					
12 mm	3.2 mm	11.2 mm	FT	38EC03	50
<b>M6-1.00 Thread Size, 4 mm Drive</b>					
25 mm	3.72 mm	13.44 mm	FT	38EC05	50
<b>M8-1.25 Thread Size, 5 mm Drive</b>					
20 mm	4.96 mm	17.92 mm	FT	26LG07	50
25 mm	4.96 mm	17.92 mm	FT	26LG08	50

Fastener Length	Head Height	Head Diameter	Thread Style*	Item No.	Pkg. Qty.
Alloy Steel Black Oxide					
#10-24 Thread Size, 1/8 in Drive					
1/2 in	0.127 in	0.411 in	FT	5MJR0	100
3/4 in	0.127 in	0.411 in	FT	5MJR2	100
#10-32 Thread Size, 1/8 in Drive					
1/2 in	0.127 in	0.411 in	FT	5MJR5	100
3/8 in	0.127 in	0.411 in	FT	5MJR6	100
3/4 in	0.127 in	0.411 in	FT	5MJR7	100
1 in	0.127 in	0.411 in	FT	5MJR8	100
1/4"-20 Thread Size, 5/32 in Drive					
1/2 in	0.161 in	0.531 in	FT	5MJT1	100
3/8 in	0.161 in	0.531 in	FT	5MJT2	100
3/4 in	0.161 in	0.531 in	FT	5MJT3	100
1 in	0.161 in	0.531 in	FT	5MJT4	100
1 1/4 in	0.161 in	0.531 in	FT	5MJT5	100
1 1/2 in	0.161 in	0.531 in	FT	5MJT6	100
1 3/4 in	0.161 in	0.531 in	PT	5MJV4	100
2 in	0.161 in	0.531 in	PT	5MJV5	100
5/16"-18 Thread Size, 3/16 in Drive					
1 1/2 in	0.198 in	0.656 in	FT	5RVL1	100
1 3/4 in	0.198 in	0.656 in	PT	5MJV6	100
2 in	0.198 in	0.656 in	PT	5MJV7	100
3/8"-16 Thread Size, 1/32 in Drive					
1 in	0.234 in	0.781 in	FT	5RVL2	100
2 in	0.234 in	0.781 in	FT	5RVL5	50
2 1/2 in	0.234 in	0.781 in	PT	5MJW1	50
5/8"-11 Thread Size, 3/8 in Drive					
2 1/2 in	0.324 in	1.188 in	FT	5MJU9	25
3 in	0.324 in	1.188 in	FT	5RVN0	25
3/4"-10 Thread Size, 1/2 in Drive					
2 1/2 in	0.396 in	1.438 in	FT	5MJV0	25
3 in	0.396 in	1.438 in	FT	5MJV1	25
1/2"-9 Thread Size, 9/16 in Drive					
3 1/2 in	0.468 in	1.688 in	FT	21EK19	1
Class 10.9 Steel					
M5-0.80 Thread Size, 3 mm Drive					
12 mm	3.2 mm	11.2 mm	FT	29DH62	100
M6-1.00 Thread Size, 4 mm Drive					
20 mm	3.72 mm	13.44 mm	FT	29DH66	100
25 mm	3.72 mm	13.44 mm	FT	29DH67	100
30 mm	3.72 mm	13.44 mm	FT	29DH68	100
35 mm	3.72 mm	13.44 mm	FT	26LF18	100
M8-1.25 Thread Size, 5 mm Drive					
16 mm	4.96 mm	17.92 mm	FT	26LF23	100
25 mm	4.96 mm	17.92 mm	FT	26LF25	100
30 mm	4.96 mm	17.92 mm	FT	29DH71	100
M10-1.50 Thread Size, 6 mm Drive					
20 mm	6.2 mm	22.4 mm	FT	29DH74	100
25 mm	6.2 mm	22.4 mm	FT	29DH75	100
30 mm	6.2 mm	22.4 mm	FT	29DH76	100
M12-1.75 Thread Size, 8 mm Drive					
50 mm	7.4 mm	26.88 mm	FT	29DH83	50
Class 10.9 Steel Black Oxide					
M3-0.5 Thread Size, 2 mm Drive					
5 mm	1.7 mm	6 mm	FT	6DU26	100
M4-0.70 Thread Size, 2.5 mm Drive					
10 mm	2.48 mm	8.96 mm	FT	26LF07	100
12 mm	2.48 mm	8.96 mm	FT	26LF08	100
16 mm	2.48 mm	8.96 mm	FT	26LF09	100
M5-0.80 Thread Size, 3 mm Drive					
10 mm	3.2 mm	11.2 mm	FT	26LF11	100
14 mm	3.2 mm	11.2 mm	FT	60DU54	100
16 mm	3.2 mm	11.2 mm	FT	26LF12	100
20 mm	3.2 mm	11.2 mm	FT	29DH63	100
25 mm	3.2 mm	11.2 mm	FT	26LF13	100
M6-1.00 Thread Size, 4 mm Drive					
10 mm	3.72 mm	13.44 mm	FT	26LF15	100
12 mm	3.72 mm	13.44 mm	FT	26LF16	100
14 mm	3.72 mm	13.44 mm	FT	60DU64	100
16 mm	3.72 mm	13.44 mm	FT	26LF17	100
18 mm	3.72 mm	13.44 mm	FT	60DU65	100
22 mm	3.72 mm	13.44 mm	FT	60DU66	50
M8-1.25 Thread Size, 5 mm Drive					
10 mm	4.96 mm	17.92 mm	FT	26LF21	100
18 mm	4.96 mm	17.92 mm	FT	60DU75	50
20 mm	4.96 mm	17.92 mm	FT	26LF24	100
22 mm	4.96 mm	17.92 mm	FT	60DU76	25
40 mm	4.96 mm	17.92 mm	FT	26LF26	100
50 mm	4.96 mm	17.92 mm	PT	26LF27	100
M10-1.50 Thread Size, 6 mm Drive					
12 mm	5.5 mm	20 mm	FT	60DU86	25
16 mm	6.2 mm	22.4 mm	FT	29DH73	100
50 mm	6.2 mm	22.4 mm	FT	29DH78	50
M12-1.75 Thread Size, 8 mm Drive					
20 mm	7.4 mm	26.88 mm	FT	29DH79	50
30 mm	7.4 mm	26.88 mm	FT	29DH81	50
40 mm	7.4 mm	26.88 mm	FT	29DH82	50
Steel Black Oxide					
#6-32 Thread Size, 5/64 in Drive					
3/8 in	0.097 in	0.307 in	FT	4XU63	100
1/2 in	0.097 in	0.307 in	FT	26KY86	100
#8-32 Thread Size, 5/32 in Drive					
1/2 in	0.112 in	0.312 in	FT	26KZ01	100
3/8 in	0.112 in	0.312 in	FT	26KZ02	100
3/4 in	0.112 in	0.312 in	FT	26KZ03	100
1 in	0.112 in	0.312 in	PT	26KZ05	100
#10-24 Thread Size, 1/8 in Drive					
1/2 in	0.127 in	0.411 in	FT	26KZ15	100
3/8 in	0.127 in	0.411 in	FT	26KZ16	100
3/4 in	0.127 in	0.411 in	FT	26KZ17	100
1 in	0.127 in	0.411 in	FT	26KZ19	100
1 1/4 in	0.127 in	0.411 in	PT	26KZ20	100
1 1/2 in	0.127 in	0.411 in	PT	26KZ21	100
#10-32 Thread Size, 1/8 in Drive					
1/2 in	0.127 in	0.411 in	FT	4XY110	100
3/8 in	0.127 in	0.411 in	FT	26LD37	100
3/4 in	0.125 in	0.375 in	FT	4XY112	100
1 in	0.127 in	0.411 in	FT	26LD38	100