

1-800-GRAINGER (472-4643)



Wall-Mount Speaker

- 93±3 dB sensitivity
- 70V
- 8 ohm impedance

Installation requires no cutting into ceiling or wall. Brown, walnut-grained wood construction has black cloth grille. Paper woofer.



Watt (RMS)	Max. Wattage	Frequency Response	Woofer Dia.	Overall H	Overall W	Overall Length	Item No.
10 W	16 W	85Hz to 20kHz	8 in	10 in	10 in	10 in	23Y702



5KZG3



2KJX9



45MK48



36H467



36H468



2KJP1



45MK49



In-Ceiling and In-Wall Speakers

- 8 ohm impedance

For music or paging. Mounting brackets are required and are sold separately.

5KZG3—Includes fire-retardant metal back can, quick-snap terminal connections, 70V transformer dial, mounting brackets, metal safety loop, and ported bass.

2KJX9—Plastic and flame-retardant back-box enclosure offers extra protection. Features up to 9 full-range wattage tap settings.

45MK48 and **45MK50** include a volume control knob.

30 and 10 W Speakers—Feature 5 built-in wattage tap settings, except 36H467 to 36H470 have 6 built-in wattage tap settings.

Watt (RMS)	Max. Wattage	Sensitivity	Frequency Response	Woofer Dia.	Woofer Composition	Tweeter Dia.	Tweeter Composition	Overall H	Overall W	Overall Length	Item No.	Pkg. Qty.
Speakers												
40 W	80 W	8 dB	60Hz to 20,000Hz	6 ½ in	Polypropylene Woofer	¾ in	Silk	7 ¾ in	10 ¼ in	10 ¼ in	5KZG3	2
40 W	80 W	88 dB	34Hz to 20,000Hz	6 ½ in	Polypropylene	1 in	Mylar	7 ½ in	11 in	11 in	2KJX9	1
30 W	60 W	87 dB	57Hz to 20,000Hz	5 ¼ in	Polypropylene	1 in	Mylar	6 in	9 ½ in	9 ½ in	2KJX8	1
30 W	60 W	—	63Hz to 21,000Hz	6 ½ in	Mineral Polymer	½ in	Titanium	7 ½ in	9 in	9 in	2KJW8	2
10 W	15 W	90 dB	85Hz to 20kHz	8 in	Paper	8 in	Paper	3 ½ in	12 in	24 in	45MK46	1
10 W	15 W	90 dB	85Hz to 20kHz	8 in	Paper	8 in	Paper	3 ½ in	24 in	24 in	45MK47	1
10 W	15 W	90 dB	85Hz to 20kHz	8 in	Paper	8 in	Paper	3 ½ in	24 in	24 in	45MK48	1
Speakers w/Transformer												
10 W	15 W	91±3 dB	90Hz-20kHz	8 in	Treated Paper	—	—	3 ½ in	10 ¾ in	10 ¾ in	36H467	1
10 W	15 W	91±3 dB	120Hz-20kHz	6 in	Treated Paper	—	—	3 in	9 in	9 in	36H469	1
Speakers w/Transformer & Volume Control												
10 W	15 W	91±3 dB	90Hz-20kHz	8 in	Treated Paper	—	—	3 ½ in	10 ¾ in	10 ¾ in	36H468	1
10 W	15 W	91±3 dB	120Hz-20kHz	6 in	Treated Paper	—	—	3 in	9 in	9 in	36H470	1
Speaker Grill Combination												
10 W	15 W	—	85Hz to 20,000Hz	8 in	Polypropylene	—	—	3 ½ in	13 in	13 in	2KJP1	1
Speaker Kits												
10 W	15 W	90 dB	85Hz to 20kHz	8 in	Paper	8 in	Paper	3 ½ in	13 in	13 in	45MK49	1
10 W	15 W	90 dB	85Hz to 20kHz	8 in	Paper	8 in	Paper	3 ½ in	13 in	13 in	45MK50	1
				Overall H				Overall W			Overall Length	Item No.
Speaker Ceiling Supports												
								23 ¾ in			14 ¾ in	36A981
Speaker Ceiling Back Boxes, Pkg. of 1												
				4 ½ in				11 ¾ in			11 ¾ in	2KJP2



Quick-Install Speaker Assembly

- 90 dB sensitivity
- 70/25V pigtail leads
- 8 ohm impedance

Lay-in ceiling mount system replaces a standard 24" x 24" ceiling tile. Polypropylene woofer, mylar tweeter. Includes a 2-ft L drop ceiling crossbar rail.



Watt (RMS)	Max. Wattage	Frequency Response	Woofer Dia.	Tweeter Dia.	Overall H	Overall W	Overall Length	Item No.
30 W	60 W	50Hz to 20,000Hz	8 in	¾ in	23 in	23 in	6 in	2KJY1

Sign in to **Grainger.com**® to see **YOUR Pricing** and **MORE**