



**ABS Plastic
3CWU8**



**ABS Plastic
3CWX2**



**Aluminum
2KJW2**



**Aluminum
2KJW3**



Horn Speakers

Designed for telephone and micro-
phone paging in loud environments,
both indoors and out. Mounting bracket
sets and hardware included.

Explosionproof Audible Signal

Multitone Horn—Has a 55-tone
capability and internal volume control.

Hazardous Location Multitone

Horn—Includes a 55-tone capability.
For use in dusty and hazardous areas

where a distinctive alert is required.
For Division 2 locations.

36H458—An amplified weatherproof
PA speaker; designed for applications
that can benefit by not having a dedi-
cated amplifier.

Additional Transformer—Works
with most brands of horn speakers.
Flange mount.

Impedance	Sensitivity	Max. Wattage	Watt (RMS)	Frequency Response	Overall H	Overall W	Overall Length	Encl. Material	Brand	Item No.	
Multi-Tone Horn - Explosionproof Audible Signal											
—	90 dB	—	—	—	11 1/4 in	11 1/4 in	18 1/2 in	Cast Aluminum	Edwards Signaling	13T112	
Multi-Tone Horn - Hazardous Location, 24VDC											
—	110 dB	—	—	—	15 in	8 7/8 in	8 in	Cast Zinc	Edwards Signaling	13T111	
Paging Speakers											
8 ohm	107 dB	40 W	30 W	400Hz to 6kHz	9 1/16 in	6 3/16 in	11 in	ABS Plastic	—	3AXC9	
8 ohm	107 dB	25 W	15 W	400Hz to 6kHz	9 1/16 in	6 3/16 in	11 in	ABS Plastic	—	3AXC8	
PA Horns											
8 ohm	105 dB	15 W	10 W	250 to 15,000Hz	6 in	6 in	6 in	Aluminum	Speco Technologies	3CWU7	
3-16 ohm	—	20 W	—	500Hz-5kHz	—	—	—	—	Speco Technologies	36H458	
8 ohm	110 dB	30 W	15 W	200 to 15,000Hz	4 in	6 in	8 in	ABS Plastic	Speco Technologies	3CWX1	
8 ohm	105 dB	15 W	10 W	300 to 15,000Hz	5 in	5 in	5 in	ABS Plastic	Speco Technologies	3CWU8	
8 ohm	120 dB	32 W	15 W	250 to 15,000Hz	11 in	6 1/2 in	13 in	ABS Plastic	Speco Technologies	3CWX2	
PA Weatherproof Speakers											
8 ohm	110 dB	25 W	15 W	200Hz to 15,000Hz	8 in	8 in	8 in	Aluminum	Speco Technologies	2KJW2	
8 ohm	110 dB	25 W	15 W	200Hz to 15kHz	5 in	8 in	8 in	Aluminum	Speco Technologies	2KJW3	
8 ohm	105 dB	15 W	6 W	300Hz to 15kHz	5 1/4 in	5 1/4 in	6 in	ABS Plastic	Speco Technologies	2KJW6	
8 ohm	105 dB	30 W	15 W	450Hz to 15,000Hz	8 in	8 in	9 in	Aluminum	Speco Technologies	2KJW4	
8 ohm	120 dB	30 W	20 W	250Hz to 16,000Hz	8 in	11 in	10 1/4 in	ABS Plastic	Speco Technologies	2KJW5	
Speaker											
8 ohm	—	—	80 W	—	—	—	—	—	Speco Technologies	49N875	
										Item No.	
Additional Transformer											
Multiple Tap Transformer, 70V										10 W/5 W/2.5 W/1.25 W/0.625 W	2KJP4



3CWU8



3CWU5

Projection Horn Casing and Driver

Combine casing with universal
driver to create custom projection
horns. Sold separately.

PROJECTION HORN CASING

Weatherproof, for indoor or
outdoor use. Includes mounting
brackets and hardware.

UNIVERSAL RMS DRIVER

Features built-in line
transformers.

Overall H	Overall W	Overall Length	Item No.			
20 in	20 in	20 1/4 in	3CWT8			
Watt (RMS)	Max. Wattage	Sensitivity	Frequency Response	Overall H	Overall W	Item No.
80 W	100 W	112 dB	300 to 5000Hz	7 in	3 1/4 in	3CWU5



2KJU4



49CA21



2KJT7

Amplifiers and Tuner

PA Amplifiers—Provide power to paging and
music address systems. **2KJU4**—On-hold feature
assures customers hear supplied music or dialogue.

PA Amplifiers with Multiple Zones—Allow differ-
ent or same audio sources to be played in different
rooms simultaneously.

Digital AM/FM Tuner—Works with most amplifiers
to play radio broadcasts. Includes 30 presets.

Output Watts	Inputs	Output	Includes	Item No.
PA Amplifiers				
30 W	(2) Mics, Auxiliary, Telephone Paging	70/25V	Music On Hold Feature with Separate Level Control	2KJU4
15 W	(1) Auxiliary, (2) Mics	4/8/16 Ohms, 70/25V	—	36H471
30 W	2 Mics and 1 Auxiliary	4/8/16 Ohms, 70/25V	—	36H472
120 W	—	25/70V	AC Power Cord, IR Remote Control, Rack Mounting Brackets	49CA18
120 W	—	25/70V	AC Power Cord, AM Antenna, IR Remote Control, Rack Mounting Brackets	49CA19
120 W	—	25/70V	AC Power Cord, AM Antenna, CD, IR Remote Control, Rack Mounting Brackets, USB	49CA20
60 W	(3) Auxiliary Stereo RCA, (3) Mic XLR, 1-RS-232, Telephone	25/70V	AC Power Cord, IR Remote Control, Rack Mounting Brackets	49CA21
60 W	—	25/70V	AC Power Cord, AM Antenna, IR Remote Control, Rack Mounting Brackets	49CA22
60 W	—	25/70V	AC Power Cord, AM Antenna, CD, FM Antenna, IR Remote Control, Rack Mounting Brackets, USB	49CA23
240 W	(3) Auxiliary Stereo RCA, (3) Mic XLR,	70V	AC Power Cord, IR Remote Control, Module Bay, Rack Mounting Brackets	49AH98
240 W	1-RS-232, AM Antenna Press Terminal, FM Antenna BNC, Telephone Terminal	70V	AC Power Cord, IR Remote Control, Rack Mounting Brackets, Tuner Module	49AH99
240 W	(1) AM Antenna (Press Terminal), (1) FM Antenna (BNC), (1) Telephone (Terminal), (3) Auxiliary (Stereo RCA), (3) Mics (XLR)	4/8 Ohms (Non-Zoned), 70V (Zoned)	AC Power Cord, AM Antenna, FM Antenna, IR Remote Control, Rack-Mountable Brackets	49NU92
PA Amplifiers with Multiple Zones				
260 W	(1) EQ/Mix, (1) Telephone Paging, (3) Auxiliary, (5) XLR Mics	4/8/16 Ohms, 70/25V	Music On Hold Feature with Separate Level Control	2KJU6
40W	(2) RCA, (3) XLR 7/8 in, Combination	160 W	—	3CWR5
PA Amplifier with AM/FM Tuner				
30 W	(1) Auxiliary, (1) Telephone, 2 XLR Connections	25/70V	30 Presets	2KJT7