

**1-800-GRAINGER (472-4643)**



**Digital Video Recorders (DVRs)**

- 100 to 240VAC
- USB export function

Recorders are for use with IP video cameras. They can help law enforcement and security agencies identify suspected lawbreakers on the highway, in a convenience store, in your business and anywhere else CCTV cameras are installed. They can also help deter crime. RAID-5 protected (standard configuration), all-in-one recording solution for up to 128 channels. Rack mount units have 6 USB ports.



**52YP57**



**52YP58**

Storage Capacity	H	W	D	Item No.
8 x 3 TB	3 1/2 in	25 1/2 in	25 1/2 in	52YP57
None	3 1/2 in	25 1/2 in	25 1/2 in	52YP58
4 x 4 TB	3 1/2 in	25 1/2 in	25 1/2 in	52YP59



**53UK32**



**53UK33**



**61KR70**



**61KR74**

**Hybrid Video Recorders**

These recorders allow you to have both analog and IP systems running at the same time on the same system. This technology is a great addition to an already established security system for your business or facility. This enables you to upgrade your surveillance system to IP equipment at your own pace, according to your budget.

**53UK32 and 53UK33**—Include central management software disk and power supply. Resolution: 1024x768P @60Hz, 1280x1024P @60Hz, 1280x720P @60Hz, 1920x1080P @60Hz.

**61KR70 to 61KR86**—Include central management software disk, mouse, power cord, power supply, remote, remote control, and SATA cables. Resolution: Analog Channel: 5MP Lite@10 fps, 4MP Lite/1080P@ 15 fps (NTSC) 1080P Lite/720P/WD1/D1@/30 fps (NTSC). IP Channel: 30 fps (NTSC)

No. of Analog Camera Inputs	No. of IP Camera Inputs	Included Hard Drive Size	Max. Frames per Second	Power Req.	Video Compression Format	Video Export Function	Recording Modes	H	W	D	Item No.
<b>LTS</b>											
4	4	1 TB	30 fps	12V DC	H.264	Network, USB	Continuous, Motion, Schedule	4 in	20 in	4 in	53UK32
8	8	1 TB	30 fps	12V DC	H.264			4 in	20 in	4 in	53UK33
<b>Invid Tech</b>											
4	2	2 TB	120 fps	12V DC @ 2 A	H265/H264	External HDD, Internal HDD, Network, USB	Continuous, Motion, Schedule, Smart Recording	45 mm	249 mm	249 mm	61KR73
4	2	4 TB	120 fps	12V DC @ 2 A	H265/H264			45 mm	249 mm	249 mm	61KR77
4	2	6 TB	120 fps	12V DC @ 2 A	H265/H264			45 mm	249 mm	249 mm	61KR80
4	2	8 TB	120 fps	12V DC @ 2 A	H265/H264			45 mm	249 mm	249 mm	61KR82
4	2	500 GB	120 fps	12V DC @ 2 A	H265/H264			45 mm	249 mm	249 mm	61KR72
4	2	—	120 fps	12V DC @ 2 A	H265/H264			45 mm	249 mm	249 mm	61KR70
8	4	2 TB	240 fps	12V DC @ 2 A	H265/H264			45 mm	249 mm	249 mm	61KR75
8	4	4 TB	120 fps	12V DC @ 2 A	H265/H264			45 mm	249 mm	249 mm	61KR78
8	4	8 TB	240 fps	12V DC @ 2 A	H265/H264			45 mm	249 mm	249 mm	61KR83
8	4	—	240 fps	12V DC @ 2 A	H265/H264			45 mm	249 mm	249 mm	61KR71
16	8	2 TB	480 fps	12V DC @ 4 A	H265/H264			45 mm	268 mm	268 mm	61KR76
16	8	4 TB	480 fps	12V DC @ 4 A	H265/H264			45 mm	268 mm	268 mm	61KR79
16	8	6 TB	480 fps	12V DC @ 4 A	H265/H264			45 mm	268 mm	268 mm	61KR81
16	8	8 TB	480 fps	12V DC @ 4 A	H265/H264			45 mm	268 mm	268 mm	61KR84
16	8	12 TB	480 fps	12V DC @ 4 A	H265/H264			45 mm	268 mm	268 mm	61KR85
16	8	16 TB	480 fps	12V DC @ 4 A	H265/H264			45 mm	268 mm	268 mm	61KR86
16	8	—	480 fps	12V DC @ 4 A	H265/H264	45 mm	268 mm	249 mm	61KR74		



**Video Surveillance Pan-Tilt-Zoom Controllers**

Security camera controllers allow you to manage a number of surveillance cameras. They're compatible with many video management systems and designed to control pan-tilt-zoom cameras (also known as PTZ cameras) capable of remote directional and zoom control.



**36K084**



**45LA11**



**48ZV55**



**404N51**

Description	Camera Inputs	Display Type	Power Supply	Brand	Item No.
Keyboard Controller	32	Speed Dome	Included	Speco Technologies	36K084
Digital Keyboard	—	—	350 mA	Bosch	45LA11
PTZ Keyboard	Variable	LCD	12V DC	LTS	48ZV55
PTZ Joystick/Keyboard	Variable	LCD	12V DC @ 0.5A	LTS	404N51

Sign in to **Grainger.com**® to see **YOUR Pricing** and **MORE**