

Standard Clevis Pins

Flat-headed pins have a hole drilled in the opposite end. All pins meet ASME B18.8.1 standards.

Note: 316 stainless steel and plain finish steel clevis pins are also available: on Grainger.com, search for “clevis pins.”



		Steel, Zinc-Plated		18-8				Steel, Zinc-Plated		18-8				Steel, Zinc-Plated		18-8	
Overall Length	Usable Length	Steel, Zinc-Plated Item No.	Plated Pkg. Qty.	Stainless Steel Item No.	Plated Pkg. Qty.	Overall Length	Usable Length	Steel, Zinc-Plated Item No.	Plated Pkg. Qty.	Stainless Steel Item No.	Plated Pkg. Qty.	Overall Length	Usable Length	Steel, Zinc-Plated Item No.	Plated Pkg. Qty.	Stainless Steel Item No.	Plated Pkg. Qty.
3% in Pin Dia.						3% in Pin Dia.						3% in Pin Dia.					
1/2"	23/64 in	3HKT4	25	—	—	1"	49/64 in	2MUJ1	25	2XAY4	5	1 1/2"	1 1/64 in	2MUP7	10	—	—
3/4"	39/64 in	2MUC5	25	2XAV2	10	1 1/8"	57/64 in	2MUJ2	25	2XAY5	5	1 3/4"	1 3/64 in	2MUP8	10	2MTZ7	1
7/8"	47/64 in	1BAF9	25	—	—	1 1/4"	1 1/64 in	2MUJ3	25	2XAY6	5	2"	1 1/4 in	2MUP9	10	2MTZ8	1
1"	55/64 in	2MUC6	25	2XAV3	10	1 3/8"	1 3/64 in	2MUJ4	25	—	—	2 1/4"	2 1/64 in	2MUR1	5	2MTZ9	1
1 1/4"	1 1/64 in	2MUC7	25	2XAV4	10	1 1/2"	1 1/64 in	2MUJ5	25	—	—	2 3/8"	2 1/64 in	2MUR2	5	2MUA1	1
1 1/2"	1 2/64 in	2MUC8	25	3HKR3	10	1 5/8"	1 2/64 in	3HKT7	25	—	—	3"	2 3/64 in	2MUR3	5	2MUA2	1
1 3/4"	1 3/64 in	1BAU8	25	2XAV5	10	1 3/4"	1 3/64 in	2MUJ6	25	2XAZ1	5	3 1/2"	3 1/64 in	2MUR4	5	—	—
2"	1 5/64 in	2MUC9	25	2XAV6	10	2"	1 4/64 in	2MUJ7	25	2XAZ2	5	3% in Pin Dia.					
3"	2 5/64 in	3HKT5	25	—	—	2 1/4"	2 1/64 in	2MUJ8	25	2XAZ4	1	2 3/4"	2 3/64 in	3HKU1	5	—	—
3% in Pin Dia.						2 1/2"	2 1/64 in	2MUJ9	10	—	—	3"	2 4/64 in	2MUR5	5	—	—
1/2"	23/64 in	—	—	2XAV8	10	2 3/4"	2 3/64 in	2MUL1	10	—	—	3 1/2"	3 1/64 in	2MUR6	5	—	—
3/4"	39/64 in	2MUE3	25	3HKR4	10	3"	2 4/64 in	2MUL2	10	2XAZ6	1	3 3/4"	3 3/64 in	1WFF7	5	—	—
7/8"	47/64 in	2MUE5	25	—	—	3 1/2"	3 1/64 in	2MUL3	10	2XAZ7	1	4"	3 4/64 in	3HKU2	1	—	—
1"	55/64 in	2MUE6	25	3HKR5	10	4"	3 4/64 in	2MUL4	10	2XAZ8	1	4 1/2"	4 1/64 in	3HKU3	1	—	—
1 1/4"	1 1/64 in	2MUE8	25	3HKR7	10	3% in Pin Dia.						5"	4 4/64 in	2MUR7	1	—	—
1 1/2"	1 1/64 in	2MUE9	25	3HKR8	10	1 1/2"	1 1/64 in	2MUL5	10	—	—	6"	5 4/64 in	1WFF6	1	—	—
1 3/4"	1 3/64 in	1BAX7	25	3HKR9	10	1 3/4"	1 1/64 in	2MUL6	10	2XAZ9	1	6 1/2"	6 1/64 in	2MUR8	1	—	—
1 5/8"	1 3/64 in	2MUE1	25	3HKR9	10	1 5/8"	1 3/64 in	2MUL7	10	2MTX5	1	3% in Pin Dia.					
1 7/8"	1 1/64 in	1BAV2	25	2XAW2	5	2"	1 4/64 in	2MUL8	10	2MTX6	1	3"	2 5/64 in	1WFF1	1	—	—
2"	1 5/64 in	2MUF2	25	2XAW3	5	2 1/4"	2 1/64 in	3PLV6	10	—	—	4"	3 4/64 in	1WFF3	1	—	—
2 1/4"	2 1/64 in	2MUF3	25	2XAW4	5	2 1/2"	2 1/64 in	2MUL9	10	2MTX7	1	1 in Pin Dia.					
2 1/2"	2 2/64 in	2MUF4	25	2XAW6	5	3"	2 4/64 in	1PVT2	10	2MTX8	1	2"	1 4/64 in	2MUR9	1	—	—
2 3/4"	2 3/64 in	1BAZ1	25	—	—	3 1/2"	3 1/64 in	1PVU4	10	2MTX9	1	2 1/2"	2 1/64 in	2MUJ2	1	—	—
3"	2 5/64 in	2MUF5	25	2XAW7	5	4"	3 4/64 in	1PVX6	10	2MTY1	1	2 3/4"	2 2/64 in	2MUJ3	1	—	—
3 1/2"	3 3/64 in	1BAZ5	25	—	—	3% in Pin Dia.						3"	2 5/64 in	2MUJ4	1	—	—
3% in Pin Dia.						1"	49/64 in	2MUN2	10	—	—	3 1/4"	2 6/64 in	2MUJ5	1	—	—
3/4"	1/32 in	2MUF8	25	2XAW9	5	1 1/4"	1 1/64 in	2MUN3	10	2MTY3	1	3 1/2"	3 1/64 in	2MUJ6	1	—	—
1"	29/32 in	2MUH1	25	2XAW1	5	1 1/8"	1 3/64 in	1WEW8	10	—	—	4"	3 4/64 in	2MUJ7	1	—	—
1 1/8"	29/32 in	2MUH2	25	—	—	1 1/2"	1 1/64 in	2MUN5	10	2MTY4	1	4 1/2"	4 1/64 in	2MUJ8	1	—	—
1 1/4"	1 1/32 in	2MUH3	25	2XAX3	5	1 3/4"	1 3/64 in	2MUN6	10	2MTY5	1	5"	4 4/64 in	1WFF5	1	—	—
1 1/2"	1 1/32 in	2MUH4	25	2XAX5	5	2"	1 4/64 in	2MUN7	10	2MTY6	1	6"	5 4/64 in	2MUJ9	1	—	—
1 5/8"	1 1/32 in	1BBB9	25	—	—	2 1/4"	2 1/64 in	2MUN8	10	2MTY7	1	1 1/2 in Pin Dia.					
1 3/4"	1 1/32 in	2MUH5	25	2XAX7	5	2 1/2"	2 1/64 in	2MUN9	10	2MTY8	1	4"	3 3/64 in	1WFF9	1	—	—
2"	1 2/32 in	2MUH6	25	—	—	2 5/8"	2 5/64 in	1WEY4	10	—	—	5"	4 4/64 in	1WFFJ2	1	—	—
2 1/8"	1 2/32 in	1BBG8	25	—	—	2 3/4"	2 3/64 in	2MUP1	10	2MTY9	1	6"	5 5/64 in	1WFFJ4	1	—	—
2 1/4"	2 1/32 in	2MUH7	25	3HKT1	5	3"	2 4/64 in	2MUP2	10	2MTZ1	1	1 1/4 in Pin Dia.					
2 1/2"	2 2/32 in	1BUC9	25	2XAX9	5	3 1/2"	3 1/64 in	2MUP3	10	2MTZ2	1	4"	3 3/64 in	1WFFJ6	1	—	—
2 3/4"	2 2/32 in	3HKT6	25	—	—	4"	3 4/64 in	2MUP4	10	2MTZ3	1	5"	4 4/64 in	1WFFJ8	1	—	—
2 5/8"	2 1/32 in	1BUC2	25	—	—	4 1/2"	4 1/64 in	2MUP5	10	2MTZ4	1	6"	5 5/64 in	1WFFK1	1	—	—
3"	2 3/32 in	2MUH8	25	3HKT2	5	5"	4 4/64 in	2MUP6	5	2MTZ5	1	1 1/2 in Pin Dia.					
3 1/2"	3 3/32 in	1BUE4	25	2XAY1	5	6"	5 4/64 in	1WEZ9	5	—	—	4"	3 3/64 in	1WFFK3	1	—	—
4"	3 5/32 in	1BUE5	25	—	—	3% in Pin Dia.						5"	4 4/64 in	1WFFK5	1	—	—
						2"	1 49/64 in	1WFA2	10	—	—	6"	5 5/64 in	1WFFK7	1	—	—
						2 1/2"	2 1/64 in	1WFA4	5	—	—						
						3"	2 49/64 in	1WFA6	5	—	—						



Cotter Pin

Cotter Pins


Meet ANSI/ASME 18.8 standards.

Note: 316 stainless steel and brass pins and bulk packaging also available on Grainger.com, search for "bulk cotter pins."


		18-8 Stainless Steel		Low Carbon Steel, Zinc-Plated				18-8 Stainless Steel		Low Carbon Steel, Zinc-Plated	
Pin Dia.	Length	Item No.	Pkg. Qty.	Item No.	Pkg. Qty.	Pin Dia.	Length	Item No.	Pkg. Qty.	Item No.	Pkg. Qty.
3/64 in	1/2"	2UHX6	100	50U54	100	3/16 in	1"	2WZT5	100	2WZK6	100
	3/8"	2WZP6	100	2UHK2	100		1 1/4"	2WZT6	100	—	—
	1/2"	2WZP7	100	—	—		1 1/2"	2WZT7	100	2WZK7	50
	5/8"	2WZP8	100	—	—		1 3/4"	2WZT8	50	—	—
1/8 in	1"	2WZP9	100	—	—	1/2 in	2"	2WZT9	50	2WZK8	50
	1 1/4"	2WZR1	100	2UHL1	100		2 1/2"	2WZT10	50	2WZK9	50
	1 1/2"	2WZR2	100	2UHL5	100		3"	2WZU2	50	2WZL1	50
	1 3/4"	2WZR3	100	—	—		3 1/2"	2WZU3	25	2WZL2	50
3/32 in	2"	2WZR4	100	—	—	3/8 in	4"	2WZU4	25	2WZL3	50
	2 1/2"	—	—	—	—		4 1/2"	2WZU5	25	2WZL6	50
	3"	—	—	—	—		5"	2WZU6	25	2WZL8	50
	3 1/2"	—	—	—	—		—	—	—	2WZN1	25
7/64 in	4"	—	—	2UHN5	100	1/4 in	6"	—	—	2WZN3	50
	4 1/2"	—	—	2UHN9	100		8"	—	—	2WZN5	25
	5"	2WZR5	100	—	—		—	—	—	—	—
	5 1/2"	2WZR6	100	—	—		—	—	—	—	—
1/16 in	6"	2WZR7	100	2WZG6	100	5/16 in	10"	—	—	—	—
	6 1/2"	2WZR8	100	2WZG8	100		12"	3DZK6	10	—	—
	7"	—	—	2WZH1	100		—	—	—	2WZN7	25
	7 1/2"	—	—	2WZH3	100		—	—	—	2WZN9	25
3/32 in	8"	2WZT9	100	2WZHS	100	3/8 in	14"	—	—	2WZP2	25
	8 1/2"	2WZT1	100	2UHR1	100		16"	—	—	2WZP4	25
	9"	—	—	2WZH7	100		—	—	—	—	—
	9 1/2"	2WZT2	100	2WZH9	100		—	—	—	—	—
1/8 in	10"	2WZT3	100	2WZJ2	100	1/2 in	18"	2UHY9	5	—	—
	11"	—	—	2WZJ4	100		2"	2UHZ1	2	2UHV6	5
	11 1/2"	2WZT4	100	2WZJ6	100		4"	2UHZ2	2	2UHV8	5
	12"	—	—	2WZJ8	50		6"	2UHZ3	2	2UHW1	5
3/16 in	14"	—	—	—	—	5/8 in	8"	3DZL3	2	2UHW3	5
	15"	—	—	—	—		10"	—	—	—	—
	16"	—	—	—	—		12"	—	—	—	—
	17"	—	—	—	—		14"	—	—	—	—

Grooved Head and Headless Clevis Pins

- Stainless steel pins have stainless steel E rings
- Zinc-plated steel pins have a phosphate finish Meet ASME B18.8 standards.



Grooved



Grooved Headless

Pin Dia.	Overall Length	Usable Length	Item No.	
Grooved				
18-8 Stainless Steel				
3/8 in	1/2"	13/32 in	2XAA3	
	3/4"	21/32 in	3HKP6	
	1"	29/32 in	2XAA4	
	1 1/4"	1 3/32 in	2XAA5	
	1 1/2"	1 19/32 in	2XAA6	
	2"	2 29/32 in	2XAA7	
1/2 in	2 1/2"	2 1/32 in	2XAA8	
	3"	2 19/32 in	2XAC1	
	3 1/4"	2 21/32 in	2XAC2	
	3 1/2"	2 29/32 in	2XAC3	
	4"	2 31/32 in	2XAC4	
	4 1/4"	2 31/32 in	2XAC5	
5/8 in	4 1/2"	2 31/32 in	2XAC6	
	5"	2 19/32 in	2XAC8	
	5 1/4"	2 29/32 in	2XAC9	
	5 3/4"	3 9/64 in	2XAD1	
	6"	3 55/64 in	2XAD2	
	6 1/4"	3 1/64 in	2XAD3	
3/4 in	6 1/2"	3 29/64 in	2XAD4	
	7"	3 59/64 in	2XAD5	
	7 1/4"	3 27/32 in	2XAD8	
	7 1/2"	3 31/32 in	2XAD9	
	8"	3 11/32 in	2XAE1	
	8 1/2"	3 21/32 in	2XAE2	
7/8 in	9"	3 23/32 in	2XAE3	
	9 1/2"	3 11/32 in	2XAE4	
	10"	3 27/32 in	2XAE5	
	Grooved Headless			
	Pin Dia.	Overall Length	Usable Length	Item No.
	1/2 in	1 1/2"	1 11/32 in	2XAE6
2"		2 17/32 in	2XAE7	
2 1/2"		2 11/32 in	2XAE8	
3/4 in	3"	2 27/32 in	2XAE9	
	Grooved Headless Zinc Plated Steel			
3/8 in	1 1/2"	1 1/4 in	2XAF2	
	1 3/4"	3/4 in	2XAF3	
1/2 in	1 3/4"	1 in	2XAF4	
	1 3/2"	3/4 in	2XAF7	
5/8 in	1 11/2"	1 in	2XAF8	
	1 19/32"	1 1/4 in	2XAF9	
	2 1/2"	1 1/2 in	2XAG1	
3/4 in	1 11/2"	1 in	2XAG2	
	1 19/32"	1 1/4 in	2XAG3	
	2 1/2"	1 1/2 in	2XAG4	
	2 11/2"	2 in	2XAG5	
7/8 in	2 1/2"	1 1/4 in	2XAG9	
	2 3/4"	1 1/2 in	2XAH1	
	2 13/8"	2 in	2XAH2	
	2 5/8"	2 1/2 in	2XAH3	
1 in	3 3/4"	3 in	2XAH4	