



Hollow-Wall Anchor



Hollow-Wall Anchor,
Self Setting



Caulking
Anchor

Hollow-Wall and Caulking Anchors

For light-duty applications.

Hollow-Wall Anchors—Easy-to-install anchors expand behind the wallboard.

Hollow-Wall Anchors, Self Setting—11K362 and 11K363 require no predrilling; with pointed tip, anchor drives into wall.

Caulking Anchors—Zamac Cone with 3% to 5% Antimonial Lead Expander. For use with hollow-walls, brick, and block.

Screw Size	Screw Length	Wall Thickness	Drill Size	Item No.	Pkg. Qty.
Wall Anchors					
3/16"	2 1/16 in	1/2 in to 5/8 in	3/8 in	11K358	50
M4(6#-32)	1 3/4 in	3/8 in to 1/2 in	5/16 in	11K355	100
M4(6#-32)	1 in	1/2 in to 1/2 in	5/16 in	11K356	100
M4(6#-32)	1 1/4 in	1/2 in to 1/2 in	5/16 in	11K362	100
M4(6#-32)	2 in	5/8 in to 1 1/4 in	5/16 in	11K357	100
M4(6#-32)	2 3/8 in	5/8 in to 1 1/4 in	5/16 in	11K363	100
Caulking Anchors					
1/4 in	3/8 in	—	1/2 in	11K364	50
5/16 in	1 in	—	5/8 in	11K365	25
3/8 in	1 1/4 in	—	3/4 in	11K366	25



Conical Screw Anchor



Flanged Anchor



Plug Anchor

Conical and Plug Anchors

■ Plastic

Corrosion-resistant anchors are for light-duty applications in hollow walls, brick, and block.

Anchor Size	Drill Bit Size	Includes	Brand	Item No.	Pkg. Qty.
Plastic Plug Anchors					
#4 to #10 x 1 in	3/16 in	—	DeWalt	54TV25	100
#6 to #12 x 1 1/8 in	1/4 in	—	DeWalt	54TV26	100
#8 to #14 x 1 1/2 in	5/8 in	—	DeWalt	54TV27	100
Conical Plug Anchors					
#6 to #8 x 3/4 in	3/16 in	—	—	11K367	100
#8 to #10 x 7/8 in	3/16 in	—	—	11K368	100
#10 to #14 x 1 in	1/4 in	—	—	11K369	100
#14 to #16 x 1 1/2 in	5/8 in	—	—	11K370	50
#6 x 3/4 in	3/16 in	(100) Combo Slotted/Phillips Pan Head Sheet Metal Screws #6 x 3/4 in, (100) Plastic Anchors, (1) Carbide Tipped Masonry Drill, Number 11K367	—	40L970	100
#8 x 7/8 in	3/16 in	(100) Combo Slotted/Phillips Pan Head Sheet Metal Screws #10 x 1 in, (100) Plastic Anchors, (1) Carbide Tipped Masonry Drill, Number 11K368	—	40L971	100
#10 x 1 in	1/4 in	(100) Combo Slotted/Phillips Pan Head Sheet Metal Screws #10 x 1 in, (100) Plastic Anchors, (1) Carbide Tipped Masonry Drill	—	40L969	100
#14 x 1 1/2 in	5/8 in	Carbide Tipped Masonry Drill, (50) Combo Slotted/Phillips Pan Head Sheet Metal Screws #14 x 1 1/2 in, (50) Plastic Anchors	—	40L972	50



12F257



11K317



6UTC4



38VC32



WallClaw
Anchors

WingIts®
The Solutions Company

Hollow-Wall and Drywall Anchors

Hammer-In Drywall Anchors—Install with no drilling necessary. Easy to remove, leaving only a tiny slit of a hole. Include anchors and screws. Meet ASTM E488 standard.

Hollow-Wall Anchors—Heavy-duty hollow-wall plastic anchors are designed for use in plaster, wallboard, concrete block or hollow tile. Feature 5/16" drill size and easily adjust to accommodate wall thickness up to 2 1/2" when using a short bolt.

MASTER Anchor Hollow Wall Anchors—Structural plastic and stainless steel anchors secure objects up to 300 lb. in drywall and will work in holes created by other anchors' failure. Objects can be easily repositioned without loss of anchor integrity. Each includes faceplate, tape, and wings.

8-32 Thread Size supports most bathroom accessories. Can also be used for guest room window dressings, heavy drapery rods, shelving, cabinets, pedestal sinks, dispensers, coat hooks, railings, and most wall-mount accessories with 1" base or larger.

10-32 Thread Size supports low-profile or tilting-mount flatscreen TVs, bathroom partitions, commercial products, and electrical panel boxes.

Self-Drilling Drywall Anchors—Preserve drywall integrity at installation and when screws are removed. Deep thread provides strong engagement in 3/8", 1/2", and 5/8" drywall. No predrilling or hole preparation necessary. Can be easily backed out.

■ For plastic use #8 sheet metal screws

Screw Thread Dia.	Grip Range	Includes	Anchor Material	Brand	Item No.	Pkg. Qty.
Hammer-In Drywall Anchors						
#8	½ in to ¾ in	Anchors, Screws	Engineered Plastic	WallClaw	12F254	4
	½ in to ¾ in		Engineered Plastic	WallClaw	12F255	10
	½ in to ¾ in		Engineered Plastic	WallClaw	12F256	25
	½ in to ¾ in		Engineered Plastic	WallClaw	12F257	50
	½ in to ¾ in		Engineered Plastic	WallClaw	12F258	100
Hollow-Wall Anchors						
#6 to #8	⅝ to ¾ in	Plastic Setting Key	Plastic	—	11K317	100
	¾ to ⅞ in		Plastic	—	11K319	100
	¾ to ¾ in		Plastic	—	11K321	100
	1 in		Plastic	—	11K323	50
MASTER Anchor Hollow Wall Anchors						
#8	1 ⅝ in	Anchor, Faceplate, Stainless Steel Screw, Tape	Fire Retardant Structural Plastic	WingIt	6UEU5	6
	1 ⅝ in	Faceplate, Stainless Steel Screw, Tape and Wings	Fire Retardant Structural Plastic	WingIt	6UTC1	2
	1 ⅝ in		Fire Retardant Structural Plastic	WingIt	6UTC2	24
	1 ⅝ in		Fire Retardant Structural Plastic	WingIt	6UTC3	100
#10	1 ⅝ in		Anchor, Faceplate, Stainless Steel Screw, Tape	Fire Retardant Structural Plastic	WingIt	6UEU6
	1 ⅝ in	Faceplate, Stainless Steel Screw, Tape and Wings	Fire Retardant Structural Plastic	WingIt	6UTC4	2
	1 ⅝ in		Fire Retardant Structural Plastic	WingIt	6UTC5	24
	1 ⅝ in		Fire Retardant Structural Plastic	WingIt	6UTC6	100
	Self-Drilling Drywall Anchors					
#6 to #10	⅝ to ½ in	—	Plastic	—	11K352	100
	⅝ to ¾ in	Anchors	Zamac	—	38VC32	100
	¾ to 1 in	Anchors, Screws	Zamac	—	38VC33	25