

## **0-Ring Assortments**

Sizes	No. of Pieces	Duro.	Sizes Incl.	Item No.
Buna N	1.050	70 Shore A	AS568A Dash No. (100) Each of 006 to 012, 110 to 112, (25) Each of 113, 210	1RGZ5
27	216	90 Shore A	Flange Seals (8) Each of 210, 214, 219, 222, 225, 228, Flat Face Seals (8) Each of 011, 012, 014, 016, 018, 021,	5JJT9
30	382	70 Shore A	025, 029, Boss Seals (8) Each of 902, 903, 904, 905, 906, 908, 910, 912, 914, 916, 920, 924, 932 AS568A Dash No. (20) Each of 006 to 012, (13) Each of 110 to 116, (10) Each of 210 to 222, (7) Each of 325 to 327	1RGX6
30	385	70 Shore A	2mm C/S (16) Fach of 3mm, 4mm, 5mm, 6mm, 7mm, 8mm, 10mm; 2.5mm C/S (13) Fach of 10mm, 11mm, 12mm, 14mm, 16mm, 17mm, 19mm; 3mm C/S	1RGY1
30	385	90 Shore A	(12) Each of 20mm, 22mm, 24mm, 25mm, 27mm, 28mm, 30mm, 32mm, 33mm, 35mm, 36mm, 38mm, (11) 9mm, 4mm C/S (9) Each of 38mm, 41mm, 44mm	1RGY2
36	226	70 Shore A	AS568A Dash No. (10) Each of 005 to 012, (6) Each of 013 to 016, 110 to 116, (5) Each of 017 to 018, 210 to 219, (4) Each of 117 to 121 (12) P12 11.8 mm x 2.4 mm C/S, (12) P15 14.8 mm x 2.4 mm C/S, (12) P16	1RGZ8
36	380	70 Shore A	12.8 mm x 2.4 mm C/S, (15) P10 9.8 mm x 1.9 mm C/S, (15) P10 9.8 mm x 1.9 mm C/S, (16) P10 10.8 mm x 2.4 mm C/S, (15) P10 10.8 mm x 1.9 mm C/S, (15) P10 9.8 mm x 1.9 mm C/S, (15) P10 9.8 mm x 1.9 mm C/S, (15) P10 9.8 mm x 1.9 mm C/S, (15) P1 10.8 mm x 2.4 mm C/S, (15) P1 10.8 mm x 1.9 mm C/S, (15) P1 2.1 mm x 2.4 mm C/S, (15) P1 2.1 mm x 3.5 mm C/S, (15) P1 2.1	1RGX9
36	436	70 Shore A	AS568A Dash No. (25) Each of 005 to 011, (15) Each of 012, 110, (10) Each of 013 to 018, 111 to 116, 210, 211, (7) Each of 117 to 121, 212 to 219	3CWA4
36	436	90 Shore A	1.5mm C/S (20) 5mm, (15) 13mm, (10) 16mm; 1.6mm C/S (20) Each of 2.2mm, 3.1mm, 4.1mm, 7.1mm, (15) 9.1mm, 10.1mm,	3CWA5
36	500	70 Shore A	1.3.1mii 6/3 (20) 3iniii, (13) 7iniiii, (13) 7iniii, 13) 7iniii, 13,1mii, 1	1RGY3
37	485	70 Shore A	AS568A Dash No. (32) Each of 006 to 012. (12) Each of 110 to 116. (9) Each of 210 to 222. (6) Each of 325 to 334	1RGZ3
81	1,415	90 Shore A	AS568A Dash No. ¼s in C/S (25) Each of 006 to 018, (20) Each of 019 to 021, (15) Each of 022 to 026, 028, (10) Each of 029, 030, ½z in C/S (25) Each of 109 to 118, (20) Each of 119, 120, (15) Each of 121 to 127, (10) Each of 128, 129, 131, 133, (5) 135, ½s in C/S (20) Each of 210 to 214, (15) Each of 215 to 222, (10) Each of 223, 224, 226, 228, 232, 236, Boss (25) Each of 904, 907, 908, 910, (15) Each of 903, 906, 912, (10) 916, Flange Fitting O-Rings (10) Each of Flange Numbers 8, 12, 16, (5) Each of Flange Numbers 20, 24, 32	5JJT8
150	1,110	70 Shore A	AS588A Dash No. (20) Each of 001 to 016, (15) Each of 110 to 116, (10) Each of 017 to 024, 117 to 124, 210 to 216, (7) Each of 025 to 031, (5) Each of 032 to 043, 125 to 142, 217 to 229, 325 to 328, 901 to 914, 916, 918, 920, 924, 928, 932, (4) Each of 032 to 034, 025 to 143 to 146, 230 to 232, (2) Each of 044 to 046, 147 to 151, 233 to 237, 331 to 338	1RGX7
Buna N	and Vito			
19	1,168	70 Shore A and 75 Shore A	AS568A Dash No. (65) Each of 006 to 012, (12) Each of 110 to 116, (9) Each of 210 to 214	1RGY9
24	610	70 Shore A	AS568A Dash No. Buna N (40) Each of 012, 013, 110, 112, 113, (30) Each of 007, 014, 016, 115, 214, (25) Each of 010, 011, 111, 116, 210, 211, (20) Each of 120, 212, 216, (10) Each of 218, 220, 222, 326, Viton (10) 120	2NRY7
PTFE			5 11, 111, 115, 215, 211, (25) 2451 51 125, 215, (15) 2451 51 215, (25) 225, (16) (17) 125	
36 36	325 325	55 Shore D	AS568A Dash No. (15) Each of 005 to 012, (10) Each of 013 to 018, 110 to 116, (5) Each of 117 to 121, 210 to 219	1RHA1
Silicon		55 Shore D		1RGZ7
36	436	70 Shore A	AS568A Dash No. (25) Each of 005 to 011, (15) Each of 012, 110, (10) Each of 013 to 018, 111 to 116, 210, 211, (7) Each of 117 to 121, 212 to 219	3CVZ8
Viton				
20	212	90 Shore A	ASS68A Dash No. (12) Each of 905 to 910, (10) Each of 901 to 904, 911 to 914, 916, 918, 920, 924, 928, 932	1RGY6
30 33	180 461	75 Shore A 75 Shore A	ASS68A DASH NO. (10) EAGH OF UOU 10 U12, 110 U0 114, 13) EAGH OF 115 U1 10, 210 U0 215, (2) EAGH OF 216 U0 222, 325 U0 327	1RGY4 1RGZ2
36	436	75 Shore A	AS568A Dash No. (10) Each of 006 to 012, 110 to 114, (5) Each of 115 to 116, 210 to 215, (2) Each of 216 to 222, 325 to 327 AS568A Dash No. (32) Each of 006 to 012, (12) Each of 110 to 116, (9) Each of 210 to 222, (6) Each of 325 to 330 AS568A Dash No. (25) Each of 005 to 011, (15) Each of 012, 110, (10) Each of 013 to 018, 111 to 116, 210, 211, (7) Each of 117 to 121, 212 to 219	3CWA3
36	500	75 Shore A	1.5mm C/S (20) Each of 5mm, (15) 13mm, (10) 16mm; 1.6mm C/S (20) Each of 2.2mm, 3.1mm, 4.1mm, 7.1mm, (15) Each of 9.1mm, 10.1mm, 13.1mm; 2.0mm c/S (20) Each of 4mm, 6mm, (15) Each of 8mm, 9mm, 10mm, 12mm, (10) Each of 14mm, 16mm, 19mm, 20mm; 2.4 mm c/S (16) Each of 4.3mm, 5.3mm, 5.6mm, 7.6mm, 8.3mm, 8.6mm; 2.5mm C/S (10) Each of 4.3mm, 14mm, 15mm, 17mm, 18mm, 19mm	1RGY7
150	1,110	75 Shore A	AS568A Dash No. (10) Each of 210 to 216, (7) Each of 025 to 031, (5) Each of 032 to 043, 125 to 142, 217 to 229, 325 to 328, 901 to 914, 916, 918, 920, 924, 928, 932, (4) Each of 339, 329 (3) Each of 143 to 146, 230 to 232, (2) Each of 044 to 046, 147 to 151, 233 to 237, 331 to 338	1RGY5

No.	Dia.	Outside Dia.	Item No.	ITE ORE D IETER Pkg. Qty.	NEOPF - BLA 70 SHO DUROM Item No.	CK IRE A	No.	Dia.	Outside Dia.	PTF - WH 55 SHO DUROM Item No.	ITE RE D IETER Pkg. Qty.	Item No.	CK RE A ETER Pkg. Qty.
		ractiona					111	7/16"	0.630"	1RGD9	25	1BUV1	100
004	5/64"	0.210"	1RFZ1	25	1BUK8	100	112	1/2"	0.693"	1RGE1	25	1BUV2	100
005	3/32"	0.241"	1RFZ2	25			113	9/16"	0.755"	1RGE2	25	1BUV3	100
006	1/8"	0.254"	1RFZ3	50	1BUL1	100	114	5/8"	0.818"	1RGE3	25	1BUV4	100
007	5/32"	0.285"	1RFZ4	50	1BUL2	100	115	11/16"	0.880"	1RGE4	25	1BUV5	100
800	3/16"	0.316"	1RFZ5	50	1BUL3	100	116	3/4"	0.943"	1RGE5	25	1BUV6	100
009	7/32"	0.348"	1RFZ6	50	1BUL4	100	117	13/16"	1.000"	1RGE6	10		_
010	1/4"	0.379"	1RFZ7	50	1BUL5	100	118	7/8"	1.068"	1RGE7	10	_	_
011	5/16"	0.441"	1RFZ8	50	1BUL6	100	119	15/16"	1.130"	1RGE8	10	_	_
012	3/8"	0.504"	1RFZ9	50	1BUL7	100	120	1"	1.193"	1RGE9	10	1BUV9	100
013	7/16"	0.566"	1RGB1	50	1BUL8	100	121	11/16"	1.255"	1RGF1	10	_	_
014	1/2"	0.629"	1RGB2	50	1BUL9	100	122	11/8"	1.318"	1RGF2	10		_
015	9/16"	0.691"	1RGB3	50	1BUP1	100	124	11/4"	1.443"	1RGF4	5	1BUW2	100
016	5/8"	0.754"	1RGB4	50	1BUP2	100	125	15/16"	1.505"	1RGF5	5		
017	11/16"	0.816"	1RGB5	25	1BUP3	100	126	13/8"	1.568"	1RGF6	5		_
018	3/4"	0.879"	1RGB6	25	1BUP4	100	128	11/2"	1.693"	1RGF8	5	1BUW3	100
019	13/16"	0.941"	1RGB7	25	_		129	19/16"	1.755"	1RGF9	5	_	_
020	7/8"	1.004"	1RGB8	10	1BUP6	100	131	111/16"	1.880"	1RGG2	5	_	
021	15/16"	1.066"	_		1BUP7	100	133	113/16"	2.005"	1RGG3	5	_	
022	1"	1.129"	1RGC1	10	1BUP8	100	137	21/16"	2.256"	1RGG5	5		
023	11/16"	1.191"	1RGC2	10	1BUP9	100	139	23/16"	2.381"	1RGG6	5	_	_
024	11/8"	1.254"	1RGC3	10	1BUR1	100	148	23/4"	2.943"	1RGG9	5		
028	13/8"	1.504"	1RGC5	10	1BUR3	50	Widt	h: 1/8" Fı	ractional	(0.139 i	n Acti	ıal)	
029	11/2"	1.629"	1RGC6	10	_		208	5/8"	0.887"	1RGH4	10		
030	15/8"	1.754"	1RGC7	10	_		210	3/4"	1.012"	1RGH5	10	1BUW6	100
031	13/4"	1.879"	1RGC8	10	_		211	13/16"	1.074"	1RGH6	10	1BUW7	100
032	17/8"	2.004"	1RGC9	5	_		212	7/8"	1.137"	_	_	1BUW8	100
033	2"	2.129"	1RGD1	5	_		213	15/16"	1.199"		_	1BUW9	100
034	21/8"	2.254"	1RGD2	5	_		214	1"	1.262"	1RGH9	10	1BUX1	100
		ractiona			tual)		216	11/8"	1.387"	1RGJ2	10	_	
108	1/4"	0.443"	1RGD6	50	1BUR7	100	217	13/16"	1.449"	1RGJ3	10	_	
109	5/16"	0.505"	1RGD7	50	1BUR8	100	218	11/4"	1.512"	1RGJ4	10	1BUX5	100
110	3/8"	0.568"	1RGD8	25	1BUR9	100	219	15/16"	1.574"	1RGJ5	10	1BUX6	100
					, ,,,,,							, ,,,,,	

			PTF	E	NEOPRENE		
			- WH		- BLA		
			55 SHO	RE D	70 SHO		
			DURON		DUROM	ETER	
Dash	Inside	Outside	Item	Pkg.	Item	Pkg.	
No.	Dia.	Dia.	No.	Qtv.	No.	Qtý.	
220	13/8"	1.637"	1RGJ6	10			
222	11/2"	1.762" 1.887"	1RGJ8	10	1BUX9	50	
223	15/8"	1.887"	1RGJ9	10	1BUZ1	50	
224	1½" 15/8" 13/4"	2.012"	1RGK1	10	1BUZ2	50	
225	17/8"	2.137"	1RGK2	5 5 5 5 5 5 5	1BUZ3	50	
226	2"	2.262"	1RGK3	5	1BUZ4	50	
227	21/8"	2.387"	1RGK4	- 5	1BUZ5	50	
228	21/4"	2.512"	1RGK5	5	1BUZ6	50	
229	21/4" 23/8"	2.512" 2.637" 2.762" 2.887" 3.012"	1RGK6	5	1BUZ7	50	
230	2½" 25/8" 23/4"	2.762"	1RGK7	- 5	1BUZ8	25	
231	25/8"	2.887"	1RGK8	5	_		_
232	23/4"	3.012"	1RGK9	5		_	
233	27/8"	3.13/	1RGL1	5			
234	3"	3 262"	1RGL2	5 5 5			
235	31/8"	3 387"	1RGL3	5		_	
236	31/4"	3.512" 3.762" 3.887"	1RGL4	- 5	1BUZ9	25	-
238 239	3½" 35/8" 4"	3.762"	1RGL6	2 2 2 2 2	1BVG5	25	
239	35/8"	3.887"	1RGL7	2			•
242	4"	4.262"	1RGL8	2		_	
243	41/8"	4.387"	1RGL9	2			-
250	5"	4.262" 4.387" 5.262"	1RGN2	2	1BVL2	25	
Widt	h: ¾16" F	ractiona	I (0.21 i	n Actu	ial)		
326	15/8"	2.020"	1RGN5	2 2 2 2 2 2	1BVL5	25	_
327	13/4"	2.145"	1RGN6	2		_	
328	17/8"	2.270"	1RGN7	2		_	_
329 330	17/8"	2.395"	1RGN8	2	1BVL7	25	F
330	21/8"	2.270" 2.395" 2.520"	1RGN9	2		_	(
333	21/2"	2.895"	1RGP1	2	1BVL9	25	A
337	3"	3.395"		_	1BWL2	10	F
338	31/8"	3.520"	1RGP4	2		_	N
340	33/8"	3.770"		_	1BWL4	10	
342 343	35/8"	4.020"	1RGP6	2 2 2		_	е
343	33/4"	4.145"	1RGP7	2		_	٧
348	43/8"	4.770"	1RGP8	2		_	



## PTFE and Neoprene O-Rings

- PTFE operating temp.: -300° to 500°F
- Neoprene operating temp.: -40° to 225°F

Round cross-section. Neoprene O-rings meet SAE J200 and ASTM D2000 standards.

Note: Polyurethane and FEP encapsulated O-rings with silicone or Viton are also available on Grainger.com.