Turned Wire Eyebolts

Supplied with UNC rolled machine threads and one hex nut.



Size	Overall Length	Length		Eye I.D.	Eye O.D.	Item No.	Pkg. Qty.	Thread Size	Overall Length			Eye I.D.	Eye O.D.	Item No.	Pkg. Qty.
	ainless S	teel						5/8"-11	8.31 in	2 ½ in	7 in	3/4 in	1 % in	5ZU56	1
#6-32	1.25 in	5/8 in	3/4 in	1/4 in	31/64 in	5ZU60	10	0/11 / 0 -	9 in	3 in	6 15/16 in	7⁄8 in	2 % in	5ZU57	
#8-32	1.69 in	1 in	1 1/8 in	1/4 in	17/32 in	5ZU61	10	3/4"-10		3 in	8 15/16 in	7/8 in	2 3/8 in	5ZU58	1
#0-32	1.69 in	7/8 in	1 in	3/8 in	11/16 in	5ZU62	10	7ine Di	14.0 in	3 in	11 ¹⁵ / ₁₆ in	⅓ in	2 ¾ in	5ZU59	_1_
#40 O4	2.0 in	70 111	1 3/8 in	5/16 in	11/ ₁₆ in	5ZU63	10	#6 22	ated Fini	\$11 5% in	3/4 in	1/4 in	31/64 in	5ZE79	10
#10-24	2.69 in	1 in	2 in	3/8 in	11/ ₁₆ in	5ZU64	10	#6-32 #8-32	1.25 in 1.69 in	1 in	1 1/8 in	1/4 in	17/32 in	5ZE80	10
	3.69 in	1 ½ in	3 in	3⁄8 in	11/16 in	5ZU65	10	#0 02	1.69 in	7/8 in	1 in	3/8 in	11/16 in	5ZE81	10
	2.0 in 2.5 in	7∕8 in	1 in	½ in	¹⁵ / ₁₆ in	5ZU66	10	"40 04	2.0 in	1 1/4 in	1 3/8 in	5/16 in	11/16 in	5ZE82	10
	2.5 in	1 1/4 in	1 ½ in	1/2 in	15/ ₁₆ in	5ZU67	10	#10-24	2.69 in	1 in	2 in	3/8 in	11/16 in	5ZE83	10
	3.0 in	1 1/4 in	2 in	½ in	15/16 in	5ZU68	10		3.69 in	1 ½ in	3 in	3⁄8 in	11/16 in	5ZE84	10
1/4"-20 -	3.5 in	1 ½ in	2 ½ in	½ in	15/16 in	5ZU69	10		2 ½ in	1 1/4 in	1 ½ in	½ in	15/16 in	35Z523	10
	4.0 in 5.0 in	1 ½ in 2 ½ in	3 in 4 in	½ in ½ in	15/16 in 15/16 in	5ZU70 5ZU71	10		2 in	7∕8 in	1 in	½ in	15/16 in	35Z487	10
-	6.0 in	3 in	5 in	½ in	15/16 in	5ZU71	5		2.0 in	7/8 in	1 in	½ in	15/16 in	4P802	10
	7.0 in	4 in	6 in	½ in	15/ ₁₆ in	5ZU73	5	-	2.5 in	1 1/4 in	1 ½ in	1/2 in	15/16 in	5ZE85	10
	2.13 in	7∕8 in	1 in	5/8 in	1 11/64 in		5		3 in	1 1/4 in 1 1/4 in	2 in 2 in	1/2 in	15/16 in		10
-	3.13 in	1 ½ in	2 in	5/8 in	1 11/64 in	5ZU75	5	-	3.0 in 3.5 in	1 1/4 in	2 ½ in	½ in ½ in	15/16 in 15/16 in	4P803 5ZE86	10
5/16"-18	4.13 in	1 ½ in	3 in	5/8 in	1 11/64 in	5ZU76	5	1/4"-20 -	4 in	1 ½ in	3 in	½ in	15/16 in	35Z534	10
	5.13 in	2 ½ in	4 in	5⁄8 in	1 11/64 in		5		4.0 in	1 ½ in	3 in	½ in	15/16 in	4P804	10
	2.5 in 3.5 in	7∕8 in	1 in	3/4 in	1 13/32 in	5ZU78	1	-	5 in	2 ½ in	4 in	1/2 in	15/16 in		10
	3.5 in	1 1/4 in	2 in	3/4 in	1 13/32 in		1	-	5.0 in	2 ½ in	4 in	½ in	15/16 in	5ZE87	10
	4.0 in	1 ½ in	2 ½ in	3/4 in	1 13/32 in		_1_		6 in	3 in	5 in	1/2 in	15/16 in	35Z551	10
3/8"-16	4.5 in	1 ½ in 2 ½ in	3 in	3/4 in 3/4 in	1 13/32 in		1		6.0 in	3 in	5 in	½ in	15/16 in	4P805	10
	5.5 in 6.5 in	3 in	4 in 5 in	3/4 in	1 13/32 in 1 13/32 in		-		7.0 in	4 in	6 in	½ in	15/16 in	5ZE88	10
	7.5 in	3 ¾ in	6 in	3/4 in	1 13/32 in	5ZU84	+		2 1/8 in	7/8 in	1 in	5/8 in		35Z454	10
	4.0 in	1 ½ in	2 in	1 in	1 1/8 in	5ZU85	+	-	2.13 in 3 1/8 in	7/8 in 1 1/4 in	1 in 2 in	5/8 in 5/8 in	1 11/64 in	35Z530	10 10
1/2"-13	6.0 in	2 ½ in	4 in	1 in	1 % in	5ZU86 1	i	-	3.13 in	1 ½ in	2 in		1 11/64 in		10
72 10	8.0 in	4 in	6 in	1 in	1 % in	5ZU87	主	5/16" -18 -	4 1/8 in	1 ½ in	3 in			35Z549	10
Steel								-	4.13 in	1 ½ in	3 in	5% in	1 11/64 in	57F91	10
	Oxide Fin								5 1/8 in	2 ½ in	4 in		1 11/64 in	35Z553	10
#6-32 #8-32	1.25 in 1.69 in	5⁄8 in	3/4 in	1/4 in	31/64 in	5ZU22 5ZU23	10	-	5.13 in	2 ½ in	4 in	5/8 in	1 11/64 in		10
#8-32	1.69 in	1 in	1 1/8 in	1/4 in	17/32 in	52023	10	0 -	2 ½ in	7∕8 in	1 in	3/4 in	1 13/32 in	35Z514	10
-	1.69 in	7/8 in	1 in	3/8 in	11/16 in	5ZU24	10		2.5 in	7∕8 in	1 in		1 ¹¾32 in		10
#10-24	2.0 in 2.69 in	1 ½ in 1 in	1 % in 2 in	5∕16 in 3∕8 in	11/ ₁₆ in	5ZU25 5ZU26	10 10		3 ½ in	1 1/4 in	2 in	3/4 in		35Z543	10
	3.69 in	1 ½ in	3 in	3/8 in	11/16 in	5ZU27	10		3.5 in	1 ½ in	2 in 3 in	3/4 in	1 ¹³ / ₃₂ in	4P806	10
	2.0 in	7/8 in	1 in	½ in	15/ ₁₆ in	5ZU28	10	- - - - - 3%"-16	4 ½ in 4 in	1 ½ in 1 ½ in	2 ½ in			35Z556 35Z529	10
	2.5 in	1 1/4 in	1 ½ in	½ in	15/ ₁₆ in	5ZU29	10		4.0 in	1 ½ in	2 ½ in		1 13/32 in		10
	3.0 in	1 1/4 in	2 in	½ in	15/16 in	5ZU30	10		4.5 in	1 ½ in	3 in		1 13/32 in		10
1/4"-20	3.5 in	1 1/4 in	2 ½ in	½ in	¹⁵ / ₁₆ in	5ZU31	10		5 ½ in	2 1/2 in	4 in	3/4 in	1 13/32 in	35Z559	10
74 20	4.0 in	1 ½ in	3 in	1/2 in	15/ ₁₆ in	5ZU32	10		5.5 in	2 ½ in 3 in	4 in	3/4 in	1 13/32 in	4P807	10
	5.0 in	2 ½ in	4 in	½ in	15/16 in	5ZU33	10	-	6 ½ in	3 in	5 in	3∕4 in	1 13/32 in	35Z535	10
	6.0 in	3 in 4 in	5 in 6 in	½ in	15/16 in 15/16 in	5ZU34	10 10		6.5 in	3 in	5 in	3/4 in	1 ¹3⁄32 in	5ZU10	10
	7.0 in 2.13 in	7/8 in	1 in	½ in % in	1 11/64 in	5ZU35 5ZU36	10		7 ½ in 7.5 in	3 ¾ in	6 in	3/4 in	1 ¹³ / ₃₂ in	35Z561	10
	3.13 in	1 ½ in	2 in	5% in	1 11/64 in		10		7.5 IN	4 in	6 in		1 13/32 in		10
5/16" -18	4.13 in	1 ½ in	3 in	5/8 in	1 11/64 in	5ZU38	10		8.56 in	2 ½ in	7 3/8 in	½ in	1 5/32 in		1
	5.13 in	2 ½ in	4 in	5/8 in	1 11/64 in	5ZU39	10	-	10.69 in 12.56 in	2 ½ in 2 ½ in	9 % in 11 % in	½ in ½ in	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		+
	2.5 in	7∕8 in	1 in	3/4 in	1 13/32 in	5ZU40	10		4 in	1 ½ in	2 in	1 in	1 7/8 in		10
	3.5 in	1 1/4 in	2 in	3/4 in	1 13/32 in	5ZU41	10	-	4.0 in	1 ½ in	2 in	1 in	1 % in	5ZU12	10
	4.0 in	1 ½ in	2 ½ in	3/4 in	1 13/32 in		10		6 in	2 ½ in	4 in	1 in		35Z443	1
	4.5 in	1 ½ in	3 in	3/4 in	1 13/32 in	5ZU46	10	-	6.0 in	2 ½ in	4 in	1 in	1 1/8 in	5ZU16	1
3/8"-16 -	5.5 in	2 ½ in	4 in	3/4 in	1 13/32 in	5ZU47	10	1/2"-13	8 in	4 in	6 in	1 in	1 % in		1
	6.5 in	3 in	5 in	3/4 in	1 ¹³ / ₃₂ in 1 ¹³ / ₃₂ in		10		8.0 in	4 in	6 in	1 in		5ZU17	1
	7.5 in 8.56 in	3 ¾ in 2 ½ in	6 in 7 % in	3/4 in 1/2 in	1 19/32 IN 1 5/32 In	5ZU49 5ZU43	10		8.81 in	2 ½ in	7 3/16 in		1 33/64 in		1
	10.69 in	2 ½ in	9 % in	½ in	1 5/32 in	5ZU43	+		10.81 in	2 ½ in	9 3/16 in		1 33/64 in		1
-	12.56 in	2 ½ in	11 % in	½ in	1 5/32 in	5ZU45	+	5/11 4 4	12 ¹³ / ₁₆ in	2 ½ IN	11 ¾16 in			35Z455	1
	4.0 in	1 ½ in	2 in	1 in	1 1/8 in	5ZU50	Ť	5/8"-11	8.31 in 9 in	2 ½ in 3 in	7 in 6 ¹⁵ / ₁₆ in	3/4 in 7/8 in	1 % in 2 % in	5ZU18 5ZU19	1
	6.0 in	2 ½ in	4 in	1 in	1 % in	5ZU54	1	3/4"-10		3 in	8 15/16 in	7/8 in	2 3/8 in	5ZU20	+
1/2"-13	8.0 in	4 in	6 in	1 in	1 % in	5ZU55	1	/4 10	14.0 in		11 ¹⁵ / ₁₆ in		2 3/8 in		÷
	8.81 in	2 ½ in	7 3/16 in	5⁄8 in	1 33/64 in	5ZU51	1		. 1.0 111	0 111	/ 10 111	70 111	- 70 ml	JEULI	



Wood Screw Eyebolts

Wood screw thread and gimlet point.

Thread Size			Shank Length	Eye I.D.	Eye O.D.	Item No.	Pkg. Qty.
Steel							
Zinc Pla	ated Finis	sh					
1/4"-20	3 11/16 in	2 in	2 3/4 in	1/2 in	15/ ₁₆ in	35Z533	10
94 -20	4 % in	2 in	4 in	½ in	15/16 in	35Z558	10
5/16"-18	3 % in	2 in	2 ¾ in	5% in	1 11/64 in	35Z557	10
916 - 10	5.81 in	2 in	4 3/4 in	5⁄8 in	1 11/64 in	5ZU97	10
3/8"-16	4 3/8 in	2 ½ in	3 in	3/4 in	1 13/32 in	35Z541	10
98 - 10	7 5/16 in	2 ½ in	6 in	3/4 in	1 13/32 in	35Z537	10



Welded Eyebolts

Include UNC nut and 2 washers.

Thread	Overall	Thread	Shank		Eye	Item	Pkg.
Size		Length	Length	Eye I.D.	0.D.	No.	Qty.
	inless St	eel					
Plain F	inish						
#10-24	3 in	1 ½ in	2 in	13/32 in	²³ / ₃₂ in	5LAD3	1
#10-24	4 in	2 in	3 in	13/32 in	²³ / ₃₂ in	5LAD4	1
	3 ¾16 in	1 ½ in	2 in	15/32 in	²⁹ / ₃₂ in	5LAD5	1
	4 1/4 in	2 in	3 in	15/32 in	²⁹ / ₃₂ in	5LAD6	1
1/4"-20	5 ¾16 in	2 in	4 in	15/32 in	²⁹ / ₃₂ in	5LAD7	1
	6 5/16 in	2 in	5 in	15/32 in	²⁹ / ₃₂ in	5LAD8	1
	7 in	2 in	6 in	15/32 in	²⁹ / ₃₂ in	5LAD9	1
	4 3/8 in	2 in	3 in	½ in	1 1/16 in	5LAE0	1
5/16"-18	5 21/64 in	2 in	4 in	½ in	1 1/16 in	5LAE1	1
916 - 10	6 % in	2 in	5 in	½ in	1 1/16 in	5LAE2	1
	7 3/8 in	2 in	6 in	½ in	1 1/16 in	5LAE3	1
	4 ½ in	2 in	3 in	21/32 in	1 11/32 in	5LAE4	1
3/8"-16	5 ½ in	2 in	4 in	²¹ / ₃₂ in	1 11/32 in	5LAE5	1
78 - 10	6 5/8 in	2 in	5 in	21/32 in	1 11/32 in		1
	7 5/g in	2 in	6 in	21/22 in	1 11/22 in	51 AF7	1

FIND MORE ONLINE

Can't find it here?

Go to **Grainger.com**® today to see our full selection of over **1.5 million products** and the **services** and **solutions** to help you get it done!

Forged Machined Rod Ends - 304 stainless - Alloy steel and - Fully

• 304 Stai		ilion Siee		= rully		() Secure and a s			
steel ha		teel have xide finis		thread	ded	19L383		L383	
pium im	1011	Aldo IIIII			Boss	304 SS	Alloy Steel	Steel	
Thread Size	Shank Dia.	Hole I.D.		Boss Dia.		Item No.	Item No.	Item No.	
			1 ½ in	39/64 in	1/4 in	19L383	19L354	19L325	
1/4"-20	1/4 in	1/4 in	3 ½ in	39/64 in	1/4 in	19L384	19L355	19L326	
	74 111	74 III	6 in	39/64 in	1/4 in	19L385	19L356	19L327	
1/4"-28	1/4"-28		3 ½ in	³⁹ ⁄64 in	1/4 in	19L409	19L379	19L350	
			1 ½ in	39/64 in	5/16 in	19L386	19L357	19L328	
5/16" -18	5∕16 in	5/16 in	3 ½ in	43/64 in	5∕16 in	19L387	19L358	19L329	
			6 in	43/64 in	5∕16 in	19L388	19L359	19L330	
		3⁄8 in	1 15/16 in	13/16 in	3⁄8 in	19L389	19L360	19L331	
3/8"-16			3 ½ in	13/16 in	3⁄8 in	19L390	19L361	19L332	
98 - 10	3/8 in		5 in	13/16 in	¾ in	19L391	19L362	19L333	
			6 in	13/16 in	3⁄8 in	19L392	19L363	19L334	
3/8"-24			3 ½ in	13/ ₁₆ in	3⁄8 in	19L410	19L380	19L351	
	½ in	½ in	2 7/16 in	1 1/32 in	½ in	19L393	19L364	19L335	
1/2"-13			3 ½ in	1 1/32 in	½ in	19L394	19L365	19L336	
72 - 13			5 in	1 1/32 in	½ in	19L395	19L366	19L337	
			6 in	1 1/32 in	½ in	19L396	19L367	19L338	
1/2"-20			3 ½ in	1 1/32 in	½ in	19L411	19L381	19L352	
			3 ½ in	1 5/16 in	5⁄8 in	19L397	19L368	19L339	
5/8"-11	5⁄8 in	5∕8 in	5 in	1 5/16 in	5∕8 in	19L398	19L369	19L340	
			6 in	1 5/16 in	5⁄8 in	19L399	19L370	19L341	
			3 ½ in	1 % in	3/4 in	19L401	19L371	19L342	
3/4"-10		3⁄4 in	5 in	1 % in	3/4 in	19L402	19L372	19L343	
	3/4 in		6 in	1 9/16 in	3/4 in	19L403	19L373	19L344	
3/4"-16	_		6 in	1 % in	3/4 in	_	19L382	19L353	
74 - 10			6 in	1 9/16 in	3/4 in	19L412	_	_	
7/8"-9	7∕8 in	7⁄8 in	5 in	1 1/8 in	⅓ in	19L404	19L374	19L345	
76 -9	78 III	½8 III -	6 in	1 1/8 in	7⁄8 in	19L405	19L375	19L346	



Black Oxide Coated Steel Rod Ends

■ Partially threaded

Thread Size	Shank Dia.	Hole I.D.	Length	Boss Dia.	Boss Thickness	ltem No.	Pkg. Qty.
1/4"-20	1/4 in	3∕16 in	2 in	1/2 in	9∕32 in	4YVH7	10
5/16"-18	5/16 in	5∕16 in	3 in	5⁄8 in	11/32 in	4YVH8	10
		3⁄8 in	3 ¾ in	3/4 in	7∕16 in	4YVJ2	10
3/8"-16	3/8 in	5/16 in	3 in	3/4 in	7∕16 in	4YVH9	10
98 - 10	78 III	3/8 in	4 in	3/4 in	7∕16 in	4YVJ3	10
		3/8 in	5 in	3/4 in	7∕16 in	4YVJ4	10
		3/8 in	3 ¾ in	1 in	9/16 in	4YVJ5	10
1/2"-13	1/2 in	3/8 in	4 in	1 in	9/16 in	4YVJ6	10
		3/8 in	5 in	1 in	9/16 in	4YVJ8	10
		5/8 in	4 ½ in	1 1/4 in	11/16 in	4YVJ9	10
5/8"-11	5∕8 in	5% in	5 in	1 1/4 in	11/16 in	4YVK1	10
		5% in	6 in	1 1/4 in	11/16 in	4YVK2	10
3/11 40	3/ :	3/4 in	4 ½ in	1 ½ in	13/16 in	4YVK3	10
3/4"-10	3∕4 in	3/4 in	6 in	1 1/2 in	13/4c in	AVVKA	10

KEN FORGING