

With

KEN FORGING

Drop-Forged Eyebolts

Loads are based on a safety factor of 5-to-1. Heat-treated, forged carbon steel eyebolts are available with zinc plated or hot galvanized finish. Stainless steel eyebolts have plain finish.

| Thread Size | Shank Length | Eye I.D. | Eye O.D. | Working Load Limit | Finish | WITH SHOULDER Item No. | WITHOUT SHOULDER Item No. |
|----------------|------------------|-----------|------------|--------------------------|--------|---------------------------------|------------------------------------|
| 1/4"-20 | 2 in | ½ in | 1 in | 500 lb | Plain | 19L190 | |
| | 2 ½ in | 3/4 in | 1 ½ in | 1.200 lb | Plain | 19L190 | |
| 3/8"-16 | 4 ½ in | 3/4 in | 1 ½ in | 1,200 lb | Plain | 19L195 | |
| 9/8 - 10 | 10 in | 3/4 in | 1 ½ in | 1,200 lb | Plain | 19L190 | |
| | 4 ½ in | 1 in | 2 in | 2,200 lb | Plain | 191190 | 19L175 |
| | 4 72 III 4 in | 1 3/16 in | 2 ½ iii | 2,400 lb | Plain | 19L165 | ISLITS |
| 1/2"-13 | 6 in | 1 in | 2 in | 2,400 lb | Plain | 19L103 | 19L176 |
| | 12 in | 1 in | 2 in | 2,200 lb | Plain | 19L201 | ISL170 |
| | 6 in | 1 3/8 in | 2 ½ in | 3,500 lb | Plain | 19L202 | |
| 5/8"-11 | 12 in | 1 3% in | 2 ½ in | 3,500 lb | Plain | 19L203 | |
| 3/4"-10 | 6 in | 1 ½ in | 2 13/16 in | 5,200 lb | Plain | 19L204 19L205 | 19L180 |
| | 6 in | 1 3/4 in | 3 ½ in | 7,200 lb | Plain | 19L203 | 191100 |
| 7/8"-9 | 12 in | 1 3/4 in | 3 ½ in | 7,200 lb | Plain | ISLZUI | 19L183 |
| 1"-8 | 6 in | 2 in | 4 in | 10.000 lb | Plain | 19L209 | 19L103 |
| Steel | O III | 2 111 | 4 111 | 10,000 10 | FIdIII | 191209 | 191104 |
| 31661 | 2 in | ½ in | 1 in | 500 lb | Zinc | | 3XRZ2 |
| | 2 in | ½ in | 1 in | 500 lb | Galv | 3XTE3 | 35Z457 |
| | 3 in | ½ in | 1 in | 500 lb | Zinc | SVIES | 33Z437 3XRZ3 |
| | 3 in | ½ in | 1 in | 500 lb | Galv | | 35Z477 |
| 1/4"-20 | 4 in | ½ in | 1 in | 500 lb | Zinc | | 33Z477 3XRZ4 |
| 74 - 20 | 4 in | ½ in | 1 in | 500 lb | Galv | 3XTE4 | 35Z459 |
| | 5 in | ½ in | 1 in | 500 lb | Zinc | 3/154 | 33Z439 3XRZ5 |
| | 6 in | ½ in | 1 in | 500 lb | Zinc | | 3XRZ6 |
| | 6 in | ½ in | 1 in | 500 lb | Galv | | 35Z493 |
| | 2 ½ in | 5/8 in | 1 1/4 in | 800 lb | Galv | 3ZGV2 | 35Z495 3ZHG6 |
| | 3 1/4 in | 5/8 in | 1 1/4 in | 800 lb | Galv | 32012 | 3ZHG7 |
| 5/16"-18 | 4 1/4 in | 5/8 in | 1 1/4 in | 800 lb | Galv | 3ZGV3 | 3ZHG8 |
| 710-10 | 5 in | 5% in | 1 1/4 in | 800 lb | Galv | 32013 | 3ZHG9 |
| | 6 in | 5/8 in | 1 1/4 in | 800 lb | Galv | | 3ZHH1 |
| | 2 ½ in | 3/4 in | 1 ½ in | 1.200 lb | Galv | 3ZGV4 | 35Z440 |
| | 3 in | 3/4 in | 1 ½ in | 1,200 lb | Galv | 32014 | 35Z489 |
| | 4 ½ in | 3/4 in | 1 ½ in | 1,200 lb | Galv | 3ZGV5 | 35Z442 |
| | 4 in | 3/4 in | 1 ½ in | 1,200 lb | Galv | 02010 | 35Z474 |
| 3/8"-16 | 5 in | 3/4 in | 1 ½ in | 1,200 lb | Galv | -= | 32HH5 |
| | 6 in | 3/4 in | 1 ½ in | 1,200 lb | Galv | 3LVX9 | 35Z447 |
| | 8 in | 3/4 in | 1 ½ in | 1,200 lb | Galv | OLVAS | 35Z447 35Z496 |
| | 10 in | 3/4 in | 1 ½ in | 1,200 lb | Galv | | 3JWY2 |
| | 10 111 | 74 111 | 1 72 111 | 1,200 10 | udiv | | JJWIZ |

| Thread Size | Shank Length | Eye I.D. | | Working Load Limit | Finish | WITH SHOULDER Item No. | Item No. |
|----------------|-----------------|------------------|--|--------------------------|--------------|---------------------------------|----------------|
| | 2 in | 1 in | 2 in | 2,200 lb | Galv | 3ZGV6 | 35Z503 |
| | 3 1/4 in | 1 in | 2 in | 2,200 lb | Galv | 3ZGV7 | 35Z464 |
| | 4 ½ in | 1 in | 2 in | 2,200 lb | Galv | | 35Z463 |
| 1/2"-13 | 4 in | 1 in | 2 in | 2,200 lb | Galv | 3LVY1 | 3JWY3 |
| | 6 in | 1 in | 2 in | 2,200 lb | Galv | 3ZGV8 | 35Z461 |
| | 8 in | 1 in | 2 in | 2,200 lb | Galv | | 35Z475 |
| | 10 in | 1 in | 2 in | 2,200 lb | Galv | 011//0 | 35Z476 |
| | 12 in | 1 in | 2 in | 2,200 lb | Galv | 3LVY2 | 35Z467 |
| | 4 ½ in | 1 3/s in | 2 ½ in | 3,500 lb | Galv | 3ZGV9 | 3ZHJ6 |
| | 4 in | 1 % in | 2 ½ in | 3,500 lb | Galv | 3LVY3 3ZGW1 | 3JWY4 |
| | 6 in | 1 3/8 in | 2 ½ in | 3,500 lb | Galv | | 3ZHJ7 |
| 5/11 4 4 | 8 in | 1 3/8 in | 2 ½ in | 3,500 lb | Galv | 3LVY4 | 3ZHJ8 |
| 5⁄8"-11 | 10 in 12 in | 1 3/8 in | 2 ½ in 2 ½ in | 3,500 lb | Galv | 3LVY5 | 3ZHJ9 |
| | 15 in | 1 3/8 in | | 3,500 lb | Galv | 3LVY6 | 3ZHK1 |
| | | 1 3/8 in | 2 ½ in | 3,500 lb | Galv | 3LVY7 | 3ZHK2 |
| | 18 in | 1 3/8 in | 2 ½ in 2 ½ in | 3,500 lb 3,500 lb | Galv | 3LVY8 | 3ZHK3 |
| | 24 in 4 ½ in | 1 % in 1 ½ in | 2 ½ III 2 ¼ in | 5,200 lb | Galv | 3LVY9 3ZGW2 | 3ZHK4 3ZHK5 |
| | | | 2 ¹³ / ₁₆ in | 5,200 lb | Galv | | |
| | 4 in 6 in | 1 ½ in 1 ½ in | 2 ¹³ / ₁₆ in | 5,200 lb | Galv Galv | 3LVZ1 3ZGW3 | 3JWY5 3ZHK6 |
| | 8 in | | 2 ¹³ / ₁₆ in | | | | 3ZHK7 |
| 3/4"-10 | 10 in | 1 ½ in 1 ½ in | 2 ¹³ / ₁₆ in | 5,200 lb 5,200 lb | Galv Galv | 3LVZ2 3LVZ3 | 3ZHK8 |
| 94 - 10 | 10 in 12 in | | 2 ¹³ / ₁₆ in | 5,200 lb | | 3LVZ3 3LVZ4 | |
| | 15 in | 1 ½ in | | 5,200 lb | Galv | 3LVZ4 | 3ZHK9 3ZHL1 |
| | 18 in | 1 ½ in 1 ½ in | 2 ¹³ / ₁₆ in 2 ¹³ / ₁₆ in | 5,200 lb | Galv | 3LVZ5 | 3ZHL2 |
| | 24 in | | 2 ¹³ / ₁₆ in | 5,200 lb | Galv | 3LVZ0 | 3JWY6 |
| | 5 in | 1 ½ in 1 ¾ in | 3 ½ in | 7,200 lb | Galv Galv | 3ZGW4 | 3ZHL3 |
| | | 1 3/4 in | 3 ½ in | 7,200 lb | Galv | 3LVZ8 | эгпгэ |
| | 6 in 8 in | 1 3/4 in | 3 ½ in | 7,200 lb | Galv | 3ZGW5 | 3ZHL4 |
| 7/8"-9 | 10 in | 1 3/4 in | 3 ½ in | 7,200 lb | Galv | 3ZGW3 | 3JWY8 |
| 78 -9 | 12 in | 1 3/4 in | 3 ½ in | 7,200 lb | | 3LVZ9 | SJWTO |
| | 18 in | 1 3/4 in | 3 ½ in | 7,200 lb | Galv Galv | SLVZ9 | 3XRY5 |
| | 24 in | 1 3/4 in | 3 ½ in | 7,200 lb | Galv | 3LWA1 | JANIJ |
| | 6 in | 2 in | 4 in | 10.000 lb | Galv | 3ZGW6 | 3XRY6 |
| | 8 in | 2 in | 4 in | 10,000 lb | Galv | 32000 | 3JWZ1 |
| | 9 in | 2 in | 4 in | 10,000 lb | Galv | 3ZGW7 | 33 W Z I |
| | 10 in | 2 in | 4 in | 10,000 lb | Galv | JZUW1 | 3XRY7 |
| 1"-8 | 12 in | 2 in | 4 in | 10,000 lb | Galv | 3LWA2 | 3XRY8 |
| | 15 in | 2 in | 4 in | 10,000 lb | Galv | OLWAZ | 3JWZ2 |
| | 18 in | 2 in | 4 in | 10,000 lb | Galv | | 3XRY9 |
| | 24 in | 2 in | 4 in | 10,000 lb | Galv | 3LWA3 | 3XRZ1 |
| | 6 in | 2 ¾16 in | 4 7/16 in | 13,500 lb | Galv | 3LWA4 | UAILLI |
| | 8 in | 2 3/16 in | 4 7/16 in | 13,500 lb | Galv | 3LWA5 | |
| 1 1/4"-7 | 12 in | 2 3/16 in | 4 7/16 III | 13,500 lb | Galv | 3LWA5 | 3JWZ5 |
| | 18 in | 2 3/16 in | 4 7/16 in | 13,500 lb | Galv | OLWAU - | 3JWZ6 |
| | 6 in | 2 ½ in | 5 3/16 in | 20.000 lb | Galv | 3LWA8 | 3JWZ8 |
| 1 1/2"-6 | 12 in | 2 ½ in | 5 3/16 in | 20,000 lb | Galv | 3LWA9 | 33 11 20 |
| 1 /2 0 | 18 in | 2 ½ in | 5 3/16 in | 20,000 lb | Galv | - OLWAS | 3JXA1 |
| | 10 111 | £ /4 III | J 7 10 III | 20,000 ID | uaiv | | UUAAI |



Half Clip

Without Shoulder



Half Clip w/Vinyl



Loop Strap







Loop Strap w/Vinyl Loop Strap w/Extruded Plastisol Cushion EDPM Cushion

Wire/Cable Clamps

■ Temp range: -50° to 350°F (Rubber); -30° to 180°F (Vinyl)

Vinyl Plastisol cushioned clamps are chem-treated for corrosion resistance.

| | - | nion | | _ | | |
|------------------|-------------|-----------------------|---------------|--------|-------------|--------------|
| Clamping Dia. | Thickness | Mounting Hole Dia. | Material | Width | Item No. | Pkg. Qty. |
| Clamp | | | | | | |
| Half Clip | | | | | | |
| 3/16" | 0.032 in | 0.2188 in | Steel | ½ in | 6RNA8 | 50 |
| 1/4" | 0.032 in | 0.2813 in | Steel | ½ in | 6RNA9 | 50 |
| 5/16" | 0.048 in | 0.2813 in | Steel | ½ in | 6RNC0 | 50 |
| 3/8" | 0.048 in | 0.2813 in | Steel | ½ in | 6RNC1 | 50 |
| 1/2" | 0.06 in | 0.2813 in | Steel | ½ in | 6RNC2 | 50 |
| 5/8" | 0.06 in | 0.2813 in | Steel | ½ in | 6RNC3 | 50 |
| 3/4" | 0.06 in | 0.2813 in | Steel | ½ in | 6RNC4 | 50 |
| | with Cushi | | | | | |
| 3/16" | 0.032 in | 0.2188 in | Steel | ½ in | 6YDR3 | 50 |
| 1/4" | 0.048 in | 0.2813 in | Steel | ½ in | 6YDR4 | 50 |
| 5/16" | 0.048 in | 0.2813 in | Steel | ½ in | 6YDR5 | 50 |
| 3/8" | 0.048 in | 0.2813 in | Steel | ½ in | 6YDR6 | 50 |
| 1/2" | 0.06 in | 0.2813 in | Steel | ½ in | 6RNA5 | 50 |
| 5/8" | 0.06 in | 0.2813 in | Steel | ½ in | 6RNA6 | 50 |
| 3/4" | 0.06 in | 0.2813 in | Steel | ½ in | 6RNA7 | 50 |
| | y with Cust | iion | | | | |
| 1/4" | 0.032 in | 0.2031 in | Steel | ½ in | 6YDP6 | 50 |
| 5/16" | 0.032 in | 0.2031 in | Steel | ½ in | 6YDP7 | 50 |
| 3/8" | 0.032 in | 0.2031 in | Steel | ½ in | 6YDP8 | 50 |
| 1/2" | 0.032 in | 0.2031 in | Steel | ½ in | 6YDP9 | 50 |
| 5/8" | 0.032 in | 0.2031 in | Steel | ½ in | 6YDR0 | 50 |
| 3/4" | 0.032 in | 0.2031 in | Steel | ½ in | 6YDR1 | 50 |
| 7/8" | 0.032 in | 0.2031 in | Steel | ½ in | 6YDR2 | 50 |
| Loop Stra | | | | | | |
| 1/4" | 0.032 in | 0.2813 in | Aluminum | ½ in | 6RNC6 | 50 |
| 5/16" | 0.032 in | 0.2813 in | Aluminum | ½ in | 6RNC7 | 50 |
| 3/8" | 0.032 in | 0.2813 in | Aluminum | ½ in | 6RNC8 | 50 |
| 1/2" | 0.048 in | 0.2813 in | Aluminum | ½ in | 6RNC9 | 50 |
| 5/8" | 0.048 in | 0.2813 in | Aluminum | ½ in | 6RND0 | 50 |
| 3/4" | 0.048 in | 0.2813 in | Aluminum | ½ in | 6RND1 | 50 |
| 7/8" | 0.048 in | 0.2813 in | Aluminum | ½ in | 6RND2 | 25 |
| 1" | 0.048 in | 0.2813 in | Aluminum | ½ in | 6RND3 | 25 |
| Loop Stra | p, Center t | o Center L | ength 15/32 i | in | | |
| 3/16" | 0.032 in | 0.2813 in | Aluminum | ½ in | 6RNC5 | 50 |
| Rubber C | | | | | | |
| 1/4" | 0.032 in | 0.2813 in | Steel | ½ in | 1BAB1 | 50 |
| 74 | 0.032 in | 0.4063 in | Steel | 3/4 in | 1BAB2 | 50 |
| | | | | | | |

| Clamping | | Mounting | | | Item | |
|-----------|------------|-----------|----------|--------|-------|------|
| Dià. ~ | Thickness | Hole Dia. | Material | Width | No. | |
| 3/8" | 0.032 in | 0.2813 in | Steel | ½ in | 1BAB3 | |
| 78 | 0.032 in | 0.4063 in | Steel | 3/4 in | 1BAB4 | |
| 1/2" | 0.032 in | 0.2813 in | Steel | ½ in | 1BAB5 | |
| 72 | 0.048 in | 0.4063 in | Steel | 3/4 in | 1BAB6 | |
| 5/8" | 0.032 in | 0.2813 in | Steel | ½ in | 1BAB7 | |
| 70 | 0.048 in | 0.4063 in | Steel | 3∕4 in | 1BAB8 | |
| 3/4" | 0.032 in | 0.2813 in | Steel | ½ in | 1BAB9 | |
| 74 | 0.048 in | 0.4063 in | Steel | 3/4 in | 1BAC1 | |
| 7/8" | 0.032 in | 0.2813 in | Steel | ½ in | 1BAC2 | 50 |
| 78 | 0.048 in | 0.4063 in | Steel | 3/4 in | 1BAC3 | 50 |
| 1" | 0.032 in | 0.2813 in | Steel | ½ in | 1BAC4 | Oty. |
| | 0.048 in | 0.4063 in | Steel | 3/4 in | 1BAC5 | 25 |
| 11/8" | 0.048 in | 0.2813 in | Steel | ½ in | 4DZZ5 | 25 |
| 11/4" | 0.048 in | 0.2813 in | Steel | ½ in | 1BAC6 | 25 |
| | 0.048 in | 0.4063 in | Steel | 3/4 in | 1BAC7 | |
| 13/8" | 0.048 in | 0.2813 in | Steel | 1/2 in | 4DZZ6 | 25 |
| 11/2" | 0.048 in | 0.2813 in | Steel | ½ in | 1BAC8 | 25 |
| | 0.048 in | 0.4063 in | Steel | 3/4 in | 1BAC9 | 25 |
| 15/8" | 0.048 in | 0.2813 in | Steel | ½ in | 4DZZ7 | |
| 13/4" | 0.048 in | 0.2813 in | Steel | ½ in | 1BAE1 | |
| 194 | 0.048 in | 0.4063 in | Steel | 3/4 in | 1BAE2 | |
| 2" | 0.048 in | 0.2813 in | Steel | ½ in | 1BAE3 | |
| _ | 0.048 in | 0.4063 in | Steel | 3/4 in | 1BAE4 | 10 |
| Vinyl Coa | ited | | | | | |
| 3/16" | 0.032 in | 0.2813 in | Steel | ½ in | 1AYZ2 | |
| 716 | 0.032 in | 0.4063 in | Steel | 3/4 in | 1AYZ3 | |
| 1/4" | 0.032 in | 0.2813 in | Steel | ½ in | 1AYZ4 | |
| 74 | 0.032 in | 0.4063 in | Steel | 3/4 in | 1AYZ5 | 50 |
| 5/16" | 0.032 in | 0.2813 in | Steel | ½ in | 1AYZ6 | |
| 9/16 | 0.032 in | 0.4063 in | Steel | 3/4 in | 1AYZ7 | 50 |
| 3/8" | 0.032 in | 0.2813 in | Steel | ½ in | 1AYZ8 | |
| 9/8 | 0.032 in | 0.4063 in | Steel | 3/4 in | 1AYZ9 | 50 |
| 1/2" | 0.048 in | 0.2813 in | Steel | 1/2 in | 1AZG2 | |
| 1/2 | 0.048 in | 0.4063 in | Steel | 3/4 in | 1AZK3 | 50 |
| 5.41 | 0.048 in | 0.2813 in | Steel | ½ in | 1AZL1 | |
| 5/8" | 0.048 in | 0.4063 in | Steel | 3/4 in | 1AZL2 | |
| 2/1 | 0.048 in | 0.2813 in | Steel | 1/2 in | 1AZL3 | 50 |
| 3/4" | 0.048 in | 0.4063 in | Steel | 3/4 in | 1AZL4 | 50 |
| | 2.2 10 111 | | 2.001 | | | |

| Clamping Dia. | Thickness | | Material | Width | Item No. | Pkg. Qty. |
|------------------|-----------|-----------|------------------|--------|-------------|--------------|
| 7/8" | 0.048 in | 0.2813 in | Steel | ½ in | 1AZL5 | 50 |
| | 0.048 in | 0.4063 in | Steel | 3⁄4 in | 1AZL6 | 50 |
| 1" | 0.048 in | 0.2813 in | Steel | ½ in | 1AZL7 | 25 |
| 1 | 0.048 in | 0.4063 in | Steel | 3∕4 in | 1AZL8 | 25 |
| 11/4" | 0.048 in | 0.2813 in | Steel | ½ in | 1AZL9 | 25 25 |
| 1 74 | 0.048 in | 0.4063 in | Steel | 3∕4 in | 1BAA1 | 25 |
| 11/2" | 0.048 in | 0.2813 in | Steel | ½ in | 1BAA2 | 25 |
| 1 72 | 0.048 in | 0.4063 in | Steel | 3⁄4 in | 1BAA3 | 25 |
| 13/4" | 0.048 in | 0.2813 in | Steel | ½ in | 1BAA4 | 25 |
| 194 | 0.048 in | 0.4063 in | Steel | 3/4 in | 1BAA5 | 10 |
| 2" | 0.048 in | 0.2813 in | Steel | ½ in | 1BAA6 | 10 |
| _ | 0.048 in | 0.4063 in | Steel | 3/4 in | 1BAA7 | 10 |
| 21/2" | 0.048 in | 0.4063 in | Steel | 3/4 in | 1BAA8 | 5 |
| 3" | 0.048 in | 0.4063 in | Steel | 3/4 in | 1BAA9 | 5 |
| Clamp, Lo | oop Strap | | | | | |
| Cushione | | | | | | |
| 1/4" | 0.032 in | 0.2813 in | 304 SS | ½ in | 2UTF1 | 25 |
| 3/8" | 0.032 in | 0.2813 in | 304 SS 304 SS | ½ in | 2UTF2 | 25 25 |
| 1/2" | 0.032 in | 0.2813 in | 304 SS | ½ in | 2UTF3 | 25 |
| 5/8" | 0.032 in | 0.2813 in | 304 SS | ½ in | 2UTF4 | 25 |
| 3/4" | 0.032 in | 0.2813 in | 304 SS | ½ in | 2UTF5 | 25 |
| 7/8" | 0.032 in | 0.2813 in | 304 SS | ½ in | 2UTF6 | 25 |
| 1" | 0.032 in | 0.2813 in | 304 SS | ½ in | 2UTF7 | 25 |
| 11/4" | 0.048 in | 0.2813 in | 304 SS 304 SS | ½ in | 2UTF8 | 10 |
| 11/2" | 0.048 in | 0.2813 in | 304 SS | ½ in | 2UTF9 | 10 |
| 13/4" | 0.048 in | 0.2813 in | 304 SS | ½ in | 2UTG1 | 10 |
| 2" | 0.048 in | 0.2813 in | 304 SS | ½ in | 2UTG2 | 10 |
| Without (| Cushion | | | | | |
| 1/4" | 0.032 in | 0.2813 in | Steel | ½ in | 2UTD8 | 50 |
| 3/8" | 0.032 in | 0.2813 in | Steel | ½ in | 2UTD9 | 50 |
| 1/2" | 0.048 in | 0.2813 in | Steel | ½ in | 2UTE1 | 50 |
| 5/8" | 0.048 in | 0.2813 in | Steel | ½ in | 2UTE2 | 50 |
| 3/4" | 0.048 in | 0.2813 in | Steel | ½ in | 2UTE3 | 50 |
| 7/8" | 0.048 in | 0.2813 in | Steel | ½ in | 2UTE4 | 50 |
| 1" | 0.048 in | 0.2813 in | Steel | ½ in | 2UTE5 | 25 |
| 11/4" | 0.048 in | 0.2813 in | Steel | ½ in | 2UTE6 | 25 |
| 11/2" | 0.048 in | 0.2813 in | Steel | ½ in | 2UTE7 | 25 |
| 13/4" | 0.048 in | 0.2813 in | Steel | ½ in | 2UTE8 | 25 |
| 2" | 0.048 in | 0.2813 in | Steel | 1/2 in | 2UTE9 | 10 |