

With Tooth Washer



## Hex Locknuts with Washer

Captive washers eliminate need for a separate washer component and make installation easy.

Dia./Thread Size	Flange Dia.	Item No.	Pkg. Qty.	Dia./Thread Size	Flange Dia.	Item No.	Pkg. Qty.
<b>Nylon Insert Lock Nut</b>							
<b>18-8 Stainless Steel Plain</b>							
1/2"-13	—	4EFX6	1	5/16"-18	0.5781 in	4EFZ1	25
<b>Grade 2 Steel Zinc Plated</b>							
1/4"-20	—	4EFX7	100	5/16"-24	0.5781 in	4EFA6	25
5/16"-18	—	4EFX8	100	3/8"-16	0.6563 in	4EFZ2	25
3/8"-16	—	4EFX9	50	3/8"-24	0.6563 in	4CAJ7	25
1/2"-13	—	4EFY1	25	3/8"-24	0.6563 in	4CAJ8	20
5/8"-11	—	4EFY2	10	<b>A2 Stainless Steel Plain</b>			
<b>Self Locking Flange Nut - Serrated</b>							
<b>18-8 Stainless Steel Plain</b>							
1/2"-13	1.0313 in	4CAN2	10	M3-0.50	6.5 mm	4EFZ9	50
<b>Grade 2 Steel Zinc Plated</b>							
1/4"-28	0.5781 in	4CAN3	100	M4-0.70	8.2 mm	4CAK5	50
5/16"-24	0.6563 in	4CAN4	100	M5-0.80	9.5 mm	4CAK6	50
3/8"-24	0.7344 in	4CAN5	100	M6-1.00	11.5 mm	4EGA1	50
7/16"-20	0.9375 in	4CAN6	50	M8-1.25	15.0 mm	4CAK7	50
1/2"-20	1.0313 in	4CAN7	25	<b>Class 5 Steel Zinc Plated</b>			
<b>Serrated Lock Nut</b>							
<b>18-8 Stainless Steel Plain</b>							
3/8"-16	0.7344 in	4EGA7	25	M6-1.00	11.5 mm	4CAK8	100
<b>Tooth Washer Lock Nut</b>							
#4-40	0.2813 in	4EFY4	100	M8-1.25	15.0 mm	4CAK9	50
#6-32	0.3438 in	4EFY5	100	<b>Class 8 Steel Zinc Plated</b>			
#8-32	0.375 in	4EFY6	100	M3-0.50	6.5 mm	4EGA2	100
#10-24	0.4063 in	4EFY7	100	M4-0.70	8.2 mm	4EGA3	100
#10-32	0.4063 in	4EFY8	100	M5-0.80	9.5 mm	4EGA4	100
1/4"-20	0.5 in	4EFY9	50	<b>Grade 2 Steel Zinc Plated</b>			
1/4"-20	0.5781 in	4EGA5	50	#4-40	0.0938 in	4EFZ3	100
1/4"-28	0.5 in	4CAJ6	50	#6-32	0.0938 in	4EFZ4	100

## Hex Flange Locknuts

Provide vibration resistance and increased load over a wider bearing surface.



Dia./Thread Size	Item No.	Pkg. Qty.	Dia./Thread Size	Item No.	Pkg. Qty.	
<b>Nylon Insert Lock Nut - Flanged</b>						
<b>Grade 2 Steel Zinc Plated</b>						
#10-24	4CAN8	100	#12-24	15D981	50	
#10-32	4CAN9	100	1/4"-20	3HDX2	100	
1/4"-20	4CAP1	100	5/16"-18	3HDX3	100	
5/16"-18	4CAP2	100	3/8"-16	3HDX4	100	
3/8"-16	4CAP3	50	7/16"-14	3HDX5	50	
1/2"-13	4CAP4	25	3/8"-11	3HDX6	25	
3/4"-10	4CAP6	5	<b>Grade 8 Steel Black Oxide</b>			
<b>Grade 8 Steel Zinc Plated</b>						
1/4"-20	4CAP7	100	1/4"-20	41MG42	100	
3/8"-16	4CAP9	50	5/16"-18	41MG43	100	
1/2"-13	4CAR1	25	3/8"-16	41MG44	100	
5/8"-11	4CAR2	10	1/2"-13	41MG45	50	
3/4"-10	4CAR3	5	5/8"-11	41MG46	25	
<b>Grade 8 Steel Zinc Yellow</b>						
3/4"-10	4CAR3	5	3/4"-10	41MG47	10	
<b>Self Locking Flange Nut - Serrated</b>						
<b>18-8 Stainless Steel Plain</b>						
#6-32	41MG57	50	<b>Grade A Steel Zinc Plated</b>			
#8-32	41MG58	50	#6-32	41MG28	100	
#10-24	41MG59	50	#8-32	41MG29	100	
#10-32	41MG64	25	#10-24	41MG30	100	
1/4"-20	41MG60	50	#12-24	41MG31	100	
5/16"-18	41MG61	50	1/4"-20	41MG32	100	
3/8"-16	41MG62	25	1/4"-28	41MG50	100	
1/2"-13	41MG63	25	5/16"-18	41MG33	100	
3/8"-24	41MG66	10	5/16"-24	41MG51	100	
1/2"-13	41MG63	25	3/8"-16	41MG34	100	
<b>316 Stainless Steel Plain</b>						
#10-24	41MG67	10	3/8"-24	41MG52	100	
1/4"-20	41MG68	10	7/16"-14	41MG35	50	
5/16"-18	41MG69	10	1/8"-20	41MG53	50	
3/8"-16	41MG70	5	1/2"-13	41MG36	50	
			1/2"-20	41MG54	50	
			5/8"-12	41MG37	25	
			5/8"-11	41MG38	25	
			5/8"-18	41MG55	25	
			3/4"-10	41MG39	10	
			3/4"-16	41MG56	10	
			7/8"-9	41MG40	10	



Top Lock



Deformed Thread Lock Nut

## Steel Deformed Thread Locknuts

Feature irregular internal threads that lock onto mating threads of a bolt or rod and prevent rotation or loosening.

Dia./Thread Size	Item No.	Pkg. Qty.	Dia./Thread Size	Item No.	Pkg. Qty.
<b>Top Lock Flange Nut</b>					
<b>Grade C Steel Phosphate and Oil</b>					
3/8"-16	4CAL7	50	5/16"-24	4FAW5	100
1/2"-13	4CAL8	25	3/8"-16	4FAW6	100
5/8"-11	22RV38	10	3/8"-24	4FAW7	100
3/4"-10	4CAN1	10	7/16"-14	4FAW8	50
<b>Top Lock</b>					
<b>Class 8 Steel Zinc Plated</b>					
M8-1.25	4CAL1	50	7/16"-20	4FAW9	50
M10-1.50	4CAL2	25	1/2"-13	4FAK1	50
M12-1.75	4CAL3	25	1/2"-20	4FAK2	50
M14-2.00	4CAL4	10	3/8"-12	4FAK3	25
M16-2.00	4CAL5	20	5/8"-11	3XTN9	25
M20-2.50	4CAL6	10	5/8"-18	4FAK5	25
<b>Grade C Steel Zinc Plated</b>					
3/8"-16	26LH07	50	3/8"-10	3XTP1	20
3/8"-24	26LH29	50	3/8"-16	4FAK6	20
7/16"-14	26LH08	25	7/8"-9	3XTP2	10
7/16"-20	26LH30	25	7/8"-14	4FAK7	10
1/2"-20	26LH31	25	1"-8	3XTP3	10
5/16"-12	12P601	25	1"-14	3XTP4	10
5/16"-18	12P602	25	<b>Reversible Lock Nut</b>		
5/16"-11	26LH11	10	<b>Grade A Steel Zinc Plated</b>		
5/8"-18	26LH33	10	1/4"-20	4FAP1	100
3/4"-10	26LH12	10	1/4"-28	4FAP2	100
3/4"-16	26LH34	10	5/16"-18	4FAP3	100
7/8"-9	26LH13	5	5/16"-24	4FAP4	100
7/8"-14	26LH35	5	3/8"-16	4FAP5	100
1"-8	12P603	5	3/8"-24	4FAP6	100
1"-14	12P604	5	7/16"-14	4FAP7	100
<b>Grade C Steel Zinc Yellow</b>					
1/4"-20	4FAR9	100	7/16"-20	4FAP8	100
1/4"-28	4FAU1	100	1/2"-13	4FAP9	50
5/16"-18	4FAW3	100	1/2"-20	4FAR1	50
			3/4"-10	4FAR2	50
			5/8"-11	4FAR3	25
			5/8"-18	4FAR4	25
			3/4"-10	4FAR5	25
			3/4"-16	4FAR6	25
			7/8"-9	4FAR7	25
			1"-8	4FAR8	10



## Hex Locknuts and Safety Wheel Nuts

■ Carbon steel

Interlocking cams form a vibration- and shock-proof, free-spinning 1-pc. locking nut assembly that holds tight under forces that cause other locknuts to come loose. Can be used with Grade 5 (Class 8.8), Grade 8 (Class 10.9), and stronger bolts.

Dia./Thread Size	Washer O.D.	Item No.	Pkg. Qty.	Dia./Thread Size	Washer O.D.	Item No.	Pkg. Qty.
<b>Heavy Hex Lock Nut</b>							
1/2"-13	1.045"	36RM15	50	<b>Wedge Lock Nut</b>			
5/8"-11	1.265"	36RM16	50	3/8"-16	0.787"	36RM07	50
3/4"-10	1.495"	36RM17	20	3/8"-24	0.787"	36RM08	50
7/8"-9	1.735"	36RM18	20	7/16"-20	1.000"	36RM09	50
<b>Safety Wheel Lock Nut</b>							
3/4"-16	1.880"	36RM19	10	1/2"-13	1.000"	36RM11	50
7/8"-14	2.000"	36RM20	10	1/2"-20	1.000"	36RM10	50
M18-1.50	47.5mm	36RM21	10	5/8"-18	1.230"	36RM12	50
M20-2.50	47.5mm	36RM23	10	5/8"-11	1.230"	36RM13	50
M20-1.50	47.5mm	36RM22	10	5/8"-18	1.230"	36RM14	50
M22-1.50	52mm	36RM24	10	M10-1.50	20mm	36RM02	50
				M12-1.75	25mm	36RM03	50
				M14-1.50	32mm	36RM04	50
				M16-2.00	32mm	36RM06	50
				M16-1.50	32mm	36RM05	50