



For more information on Rubber, see page 2101.

Rubber Sheets and Rolls

Ideal for use in sealing, cushioning, and can be formed into custom gaskets.



| L | W | ►CHOOSE: Backing Type | ►CHOOSE: Durometer | ►CHOOSE: Overall Thickness | ►CHOOSE: Texture | Color | Item No. |
|---------------------------------------|----------|--------------------------|------------------------------|---|---------------------|-------|----------|
| General Purpose Buna-N | | | | | | | |
| 12 in | 12 in | Acrylic, Plain Backing | 40A, 50A, 60A, 70A | 0.03125 in, 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in | Smooth | Black | D4973 |
| 24 in | 12 in | Acrylic, Plain Backing | 40A, 50A, 60A, 70A | 0.03125 in, 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in | Smooth | Black | D4976 |
| 36 in | 12 in | Acrylic, Plain Backing | 40A, 50A, 60A, 70A | 0.03125 in, 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in | Smooth | Black | D4977 |
| 36 in | 24 in | Plain Backing | 40A, 50A, 60A, 70A | 0.03125 in, 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in | Smooth | Black | D4979 |
| 36 in | 36 in | Plain Backing, Acrylic | 40A, 50A, 60A, 70A | 0.03125 in, 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in | Smooth | Black | D4981 |
| 48 in | 36 in | Plain Backing | 40A, 50A, 60A, 70A | 0.03125 in, 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in | Smooth | Black | D4982 |
| High-Strength Buna-N | | | | | | | |
| 12 in | 12 in | Plain Backing, Acrylic | 40A, 50A, 60A, 70A, 80A, 90A | 0.03125 in, 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in | Smooth | Black | D5021 |
| 36 in | 12 in | Plain Backing, Acrylic | 40A, 50A, 60A, 70A, 80A, 90A | 0.03125 in, 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in | Smooth | Black | D5026 |
| 60 in | 36 in | Plain Backing, Acrylic | 40A, 50A, 60A, 70A, 80A, 90A | 0.03125 in, 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in | Smooth | Black | D5034 |
| General Purpose Butyl | | | | | | | |
| 12 in | 12 in | Plain Backing, Acrylic | 60A | 0.0625 in, 0.125 in, 0.25 in | Smooth | Black | K295 |
| 36 in | 12 in | Plain Backing, Acrylic | 60A | 0.0625 in, 0.125 in, 0.25 in | Smooth | Black | K297 |
| 120 in | 36 in | Plain Backing | 60A | 0.0625 in, 0.125 in, 0.25 in | Smooth | Black | K299 |
| General Purpose EPDM | | | | | | | |
| 1 ft | 12 in | Plain Backing, Acrylic | 60A | 0.03125 in, 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in | Smooth | Black | K5180 |
| 3 ft | 12 in | Plain Backing, Acrylic | 60A | 0.03125 in, 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in | Smooth | Black | K5184 |
| 10 ft | 36 in | Plain Backing, Acrylic | 60A | 0.03125 in, 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in | Smooth | Black | K5191 |
| 15 ft | 36 in | Plain Backing | 60A | 0.03125 in, 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in | Smooth | Black | K5192 |
| 20 ft | 36 in | Plain Backing, Acrylic | 60A | 0.03125 in, 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in | Smooth | Black | K5193 |
| 25 ft | 36 in | Plain Backing | 60A | 0.03125 in, 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in | Smooth | Black | K7328 |
| 40 ft | 36 in | Plain Backing, Acrylic | 60A | 0.03125 in, 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in | Smooth | Black | K5195 |
| 50 ft | 36 in | Plain Backing, Acrylic | 60A | 0.03125 in, 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in | Smooth | Black | K5198 |
| High-Strength EPDM | | | | | | | |
| 10 ft | 36 in | Plain Backing | 60A | 0.03125 in, 0.0625 in, 0.125 in, 0.1875 in, 0.25 in | Smooth | Black | K5219 |
| General Purpose Fluorosilicone | | | | | | | |
| 1 ft | 12 in | Plain Backing | 60A | 0.03125 in, 0.0625 in, 0.125 in, 0.1875 in, 0.25 in | Smooth | Blue | K5287 |
| 2 ft | 12 in | Plain Backing | 60A | 0.03125 in, 0.0625 in, 0.125 in, 0.1875 in, 0.25 in | Smooth | Blue | K5288 |
| 3 ft | 36 in | Plain Backing | 60A | 0.03125 in, 0.0625 in, 0.125 in, 0.1875 in, 0.25 in | Smooth | Blue | K5289 |
| General Purpose Hypalon | | | | | | | |
| 1 ft | 12 in | Plain Backing, Acrylic | 60A | 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in | Smooth | Black | K5132 |
| 5 ft | 36 in | Plain Backing | 60A | 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in | Smooth | Black | K5135 |
| 10 ft | 36 in | Plain Backing | 60A | 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in | Smooth | Black | K5136 |
| 15 ft | 36 in | Plain Backing | 60A | 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in | Smooth | Black | K5137 |
| 24 in | 12 in | Plain Backing, Acrylic | 60A | 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in | Smooth | Black | K5133 |
| 36 in | 12 in | Plain Backing, Acrylic | 60A | 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in | Smooth | Black | K5134 |
| General Purpose Natural | | | | | | | |
| 2 ft | 12 in | Plain Backing | 40A, 60A | 0.0625 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in, 0.008 in, 0.01 in, 0.012 in, 0.014 in, 0.02 in, 0.025 in, 0.03 in | Smooth | Tan | K5268 |
| 3 ft | 12 in | Plain Backing | 40A | 0.0625 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in, 0.008 in, 0.01 in, 0.012 in, 0.014 in, 0.02 in, 0.025 in, 0.03 in | Smooth | Tan | K5269 |
| 3 ft | 36 in | Plain Backing | 60A | 0.008 in, 0.01 in, 0.012 in, 0.014 in, 0.02 in, 0.025 in, 0.03 in | Smooth | Tan | K5270 |
| 10 ft | 36 in | Plain Backing, Acrylic | 40A, 60A | 0.0625 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in, 0.008 in, 0.01 in, 0.012 in, 0.014 in, 0.02 in, 0.025 in, 0.03 in | Smooth | Tan | K5271 |
| Fabric-Reinforced Neoprene | | | | | | | |
| 2 ft | 12 in | Plain Backing | 60A | 0.0625 in, 0.125 in, 0.1875 in, 0.25 in | Smooth | Black | D5054 |
| 2 ft | 12 in | Plain Backing | 60A, 70A | 0.0625 in, 0.125 in, 0.1875 in, 0.25 in | Smooth | Black | D5055 |
| 3 ft | 12 in | Plain Backing | 60A | 0.0625 in, 0.125 in, 0.1875 in, 0.25 in | Smooth | Black | D5056 |
| 5 ft | 4 1/2 ft | Plain Backing | 70A | 0.0625 in, 0.125 in, 0.1875 in | Smooth | Black | D5062 |
| 5 ft | 4 ft | Plain Backing | 60A | 0.0625 in, 0.125 in, 0.1875 in | Smooth | Black | D5061 |
| 5 ft | 36 in | Plain Backing | 60A | 0.0625 in, 0.125 in, 0.1875 in | Smooth | Black | D5059 |
| Food-Grade (FDA) Neoprene | | | | | | | |
| 2 ft | 12 in | Plain Backing | 60A | 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in | Smooth | White | D5083 |
| 3 ft | 12 in | Plain Backing | 60A | 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in | Smooth | White | D5084 |
| 3 ft | 24 in | Plain Backing | 60A | 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in | Smooth | White | D5085 |
| 3 ft | 36 in | Plain Backing, Acrylic | 60A | 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in | Smooth | White | D5086 |
| 12 in | 12 in | Plain Backing, Acrylic | 60A | 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in | Smooth | White | D5082 |
| High-Strength Neoprene | | | | | | | |
| 2 ft | 12 in | Plain Backing, Acrylic | 40A, 50A, 60A, 70A | 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in, 0.03125 in | Smooth | Black | D5212 |
| 2 ft | 12 in | Plain Backing, Acrylic | 30A | 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in | Smooth | Black | D5214 |
| 3 ft | 12 in | Plain Backing, Acrylic | 40A, 50A, 60A, 70A, 80A, 90A | 0.0625 in, 0.09375 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in, 0.03125 in | Smooth | Black | D5215 |
| 3 ft | 12 in | Plain Backing, Acrylic | 30A | 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in | Smooth | Black | D5216 |
| 3 ft | 18 in | Plain Backing, Acrylic | 40A, 50A, 60A, 70A | 1 in, 0.0625 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in, 0.03125 in | Smooth | Black | D5217 |
| 3 ft | 36 in | Plain Backing, Acrylic | 40A, 50A, 60A, 70A, 80A, 90A | 0.09375 in, 0.1875 in, 0.375 in, 0.5 in, 0.75 in, 1 in, 0.03125 in | Smooth | Black | D5219 |
| 3 ft | 36 in | Plain Backing | 30A | 1 in, 0.0625 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in | Smooth | Black | D5222 |
| 5 ft | 36 in | Plain Backing, Acrylic | 40A, 50A, 60A, 70A, 80A, 90A | 0.0625 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in | Smooth | Black | D5224 |
| 12 in | 12 in | Plain Backing, Acrylic | 40A, 50A, 60A, 70A, 80A, 90A | 0.0625 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in | Smooth | Black | D5206 |
| 12 in | 12 in | Plain Backing, Acrylic | 30A | 0.0625 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in | Smooth | Black | D5208 |
| 18 in | 18 in | Plain Backing, Acrylic | 40A, 50A, 60A, 70A | 1 in, 0.0625 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in | Smooth | Black | D5211 |
| Ultra-Strength Neoprene | | | | | | | |
| 2 ft | 12 in | Plain Backing, Acrylic | 50A, 60A, 70A | 0.0625 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in, 0.03125 in | Smooth | Black | D7154 |

CONTINUED ▶