CONTINUED

Rubber Sheets and Rolls

1 1 1 2 1 2 1 1 2 1 1 2 1	L Gene	W ral Pui	CHOOSE: Backing Type rpose Neoprene	Durometer	: r ▶CHOOSE: Overall Thickness	CHOOSE: Texture	Color	ltem No.	L Gener	W ral Purj	CHOOSE: Backing Type		CHOOSE: Overall Thickness	CHOOSE: Texture	Color	ltem No.
2 ft 12 in	1 ft	12 in		50A, 60A, 70A	in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in, 0.03125 in		Black	D5096	12 in	12 in	Plain Backing	75A	in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in	Smooth	Black	K5048
31f 12 in Pain Backing 936, 60A, in 0.157 in 0.25 in 0.375 in 0.156 in 0.375 in 0.375 in 0.316 in 0.325 in 0.325 in 0.316 in 0.316 in 0.325 in 0.325 in 0.325 in 0.	2 ft	12 in		50A, 60A, 70A	in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in, 0.03125 in		Black	D5099	24 in	12 in	Plain Backing	75A	in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in	Smooth	Black	K5050
31ft 16 in	3 ft	12 in		50A, 60A,	in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 1 in, 0.75 in, 0.03125 in	Smooth, Textured	Black	D5101	36 in	12 in	Plain Backing	75A	in, 0.1875 in, 0.25 in, 0.375	Smooth	Black	K5052
3ft 24 in Plain Backing, 40A, 50A, 00325 in 0.0525 in 0.0555 in 0	3 ft	18 in		60A, 70A	in, 0.25 in, 0.125 in, 0.1875 in, 0.09375 in, 0.75 in, 0.375 in	Smooth	Black	D5102			Plain Backing,	10A, 20A, 40A, 50A,		n. Smo	oth Re	ed D5309
31 35 Plain Backing, Acrylic 40A, 50A, Box 0.0375 in, 0.058 in, 0.025 in, 0.0375 in, 0.058 in, 0.0375 in, 0.158 in, 0.0375 in, 0.251 in, 0.0375 in, 0.251 in, 0.0375 in, 0.158 in, 0.03	3 ft	24 in	Plain Backing	60A, 70A, 30A	in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in		Black	D5103			Plain Backing,	60A, 70A 40A, 50A,	0.09375 in, 0.375 in, 0.5 i 0.03125 in, 0.0625 in,	in		
4 ft 36 in Plain Backing 0.375 in .0.25 in .	3 ft	36 in	Plain Backing, Acrylic	60A, 70A,	in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in	Smooth, Textured	Black	D5137					in, 0.25 in, 0.375 in, 0.5 in 0.03125 in, 0.0625 in, 0.12	n 25		
5 ft 36 in Plain Backing, 60A, 70A, in, 0.125 in, 0.1875 in, 0.0375 in, 0.025 in, 0.575 in, 0.0625 in, 0.58 in, 0.0625 in, 0.058 in, 0.	4 ft	36 in	Plain Backing	60A, 70A	in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 0.75 in, 1 in	Smooth	Black	D5138	36 in	36 in		40A, 50A, 60A, 70A	in, 0.375 in, 0.5 in, 0.5-mr 1-mm, 1.5-mm, 2-mm,	n, Smoo	oth Re	ed D7232
18 In 12 in Plain Backing 400, 200, 10, 25 in, 0.125 in, 0.1375 in, 0.500 (0.03975 in, 0.725 in, 0.2375 in, 0.500 (0.03975 in, 0.125 in, 0.1375 in, 0.1375 in, 0.1375 in, 0.250 in, 0.375 in, 0.500 (0.03975 in, 0.125 in, 0.1375 in,	5 ft	36 in		60A, 70A,	in, 0.125 in, 0.1875 in, 0.375 in, 0.5 in, 0.75 in, 1 in, 0.25 in	Smooth, Textured	Black	D5139	60 in	36 in			0.09375 in, 0.125 in, 0.18 in, 0.25 in, 0.375 in, 0.5 i	75 Smoo	oth Re	ed D7234
18 In 18 in Paint Backing, Acrylic 404, 504, bit 0, 25 in, 0.25 in, 0.125 in, 0.1875 in, 704, 700, 704, 705, 704, 705, 705, 705, 705, 706, 705, 706, 705, 706, 705, 706, 705, 7	18 in	12 in	Plain Backing		in, 0.25 in, 0.125 in, 0.1875 in, 0.09375 in, 0.75 in, 0.375 in	Smooth	Black	D5097	120 in	12 in	Plain Backing		0.09375 in, 0.125 in, 0.18 in, 0.25 in, 0.375 in, 0.5 i		oth Re	ed D5309
12 in 12 in Plain Backing, Acrylic 40A, 60A, 00A, 95D, 0075 in, 125 in, 0.5 i			Acrylic	60Å, 70Å	in, 0.25 in, 0.125 in, 0.1875 in,	Smooth	Black	D5098	120 in	36 in	High-Temp, Plain Backing	60A, 70A	0.09375 in, 0.125 in, 0.18 in, 0.25 in, 0.375 in, 0.5 i	n	oth Re	ed D5313
12 in 12 in Pain Backing, Acrylic Backing, Acrylic MA, 90A, 99A, 99A, 99A, 99A, 99A, 99A, 99	Gene	ral Pu			0.0625 in 0.125 in 0.1876				720 in	36 in	Plain Backing	40A, 50A, 60A, 70A	0.03125 in, 0.0625 in, 0.093 in 0.125 in 0.1875 in 0.25	375 Smor	oth Re	ed D7246
24 in 12 in Plain Backing, Acrylic 20, 60, 60, 00, 60, 60, 60, 60, 60, 60, 60, 60, 60,	12 in	12 in		70A, 75D	D, in, 0.25 in, 0.375 in, 0.5 in,	Smooth	Black	< K5096	Gene	ral Pur	oose Silicone	0011, 1011	in, 0.120 in, 0.1070 in, 0.20	,		
24 in 24 in Plain Backing, Acrylic 40A, 60A, 70A, 75D, 80A, 90A, 95A 0.0625 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.25 in Smooth Black K5102 36 in 12 in Plain Backing, Acrylic 60A 0.0625 in, 0.125 in, 0.1875 in, 0.25 in Smooth Amber K5103 36 in 24 in Plain Backing, 36 in 36 in Plain Backing, Acrylic 60A 0.0625 in, 0.125 in, 0.1875 in, 0.25 in Smooth Amber K5103 36 in 36 in Plain Backing, Acrylic 60A 0.0625 in, 0.125 in, 0.1875 in, 0.25 in Smooth Amber K5105 36 in 36 in Plain Backing, Acrylic 60A 0.0625 in, 0.125 in, 0.1875 in, 0.25 in Smooth Amber K5106 36 in 36 in Plain Backing, Acrylic 40A, 60A, 70A, 75D, ROA, 50D, Acrylic 0.0625 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in Smooth Black K5101 36 in 12 in Plain Backing, Acrylic 40A, 60A, 70A, 75D, ROA, 50D, 0.25 in, 0.25 in, 1.25 in, 1.15 in, 1.15 in, 0.25 in, 0.375 in, 0.25 in Smooth Black K5101 36 in 12 in Plain Backing, Acrylic 60A 0.0625 in, 0.125 in, 0.25 in, 0.375 in, 0.25 in <td>24 in</td> <td>12 in</td> <td>Plain Backing,</td> <td>40A, 60A 70A, 75D</td> <td> 0.0625 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, </td> <td>Smooth</td> <td>Black</td> <td>< K5099</td> <td>12 in</td> <td>12 in</td> <td>Plain Backing, High-Temp</td> <td>30A</td> <td>0.09375 in, 0.125 in, 0.18 in, 0.25 in, 0.375 in, 0.5 i</td> <td></td> <td>oth Re</td> <td>ed J4592</td>	24 in	12 in	Plain Backing,	40A, 60A 70A, 75D	 0.0625 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 	Smooth	Black	< K5099	12 in	12 in	Plain Backing, High-Temp	30A	0.09375 in, 0.125 in, 0.18 in, 0.25 in, 0.375 in, 0.5 i		oth Re	ed J4592
36 in 12 in Plain Backing, Acrylic 60A 0.0625 in, 0.125 in, 0.25 in, 0.375 in,	24 in	24 in		40A, 60A 70A, 75D	 0.0625 in, 0.125 in, 0.1875 in, 0.25 in, 0.375 in, 0.5 in, 	Smooth	Black	< K5102	36 in	12 in	Plain Backing, High-Temp	30A	0.09375 in, 0.125 in, 0.18 in, 0.25 in, 0.375 in, 0.5 i		oth Re	ed J4595
Job III 24 III Plain Backling Bod M 0.1875 in, 0.25 in Smooth Andrer K104 36 in 36 in Plain Backling, Acrylic 60A 0.0625 in, 0.125 in, 0.1875 in, 0.25 in Smooth Amber K5105 36 in 36 in Plain Backling, Acrylic 80A 1.5-mm, 1-mm, 2.5- m, 0.75 in, 0.25 in Smooth Amber K5105 48 in 24 in Plain Backling, Acrylic 80A 0.0625 in, 0.125 in, 0.175 Smooth Black K5010 60 in 36 in Plain Backling, Acrylic 60A 0.0625 in, 0.125 in, 0.175 Smooth Black K5010 10 ft 36 in Plain Backling 60A 0.0625 in, 0.125 in, 0.175 Smooth Black K5010 60 in 36 in Plain Backling 60A 0.0625 in, 0.125 in, 0.125 in, 0.125 Smooth Black K5011 11 ft 11 ft Plain Backling 60A 0.0625 in, 0.3125 in, 0.125 in, 0.125 in, 0.125 in, 0.3125 in, 0.125 in, 0.125 in, 0.3125 in	36 in	12 in	Plain Backing, Acrylic		0.0625 in, 0.125 in, 0.1875 in, 0.25 in		Ambe	er K5103	36 in	24 in	Plain Backing	30A	0.09375 in, 0.125 in, 0.18 in, 0.25 in, 0.375 in, 0.5 i	75 Smoo n	oth Re	ed J4596
Base in 36 in Acrylic BodA in, 0.25 in, 0.5 in Smooth Andrek K103 36 in 36 in Plain Backing, Acrylic 80.4 1.5-mm, 1-mm, 2.5- mm, 2-mm, 3-mm Smooth Amber K5106 48 in 24 in Plain Backing, Acrylic 40.4, 60.4, 0.0625 in, 0.125 in, 0.51 in, 0.51 in, 30.4, 90.4, 95.4 0.0625 in, 0.125 in, 0.51 in, 30.4, 90.4, 95.4 0.0625 in, 0.125 in, 0.51 in, 30.4, 90.4, 95.4 Smooth Black K5101 60 in 36 in Plain Backing, Acrylic 60.4 0.0625 in, 0.125 in, 0.51 in, 30.625 in, 0.125 in, 0.51 in Smooth Black K5041 10 ft 36 in Plain Backing 70.4 0.1875 in, 0.25 in Smooth Black K5041 25 ft 26 in 0.1875 in, 0.25 in Smooth Amber K5111 Smooth Black K5041 11 ft 11 ft Plain Backing 60.4 0.0625 in, 0.3125 in, 0.125 in, 0.25 in Smooth Black-Speckled K5261 2.5 ft 24 in Plain Backing 60.4 0.0625 in, 0.3125 in, 0.125 in, 0.375 in, 0.25 in Smooth Black-Speckled K5262 4 ft 1 ft Plain Backing 60.4 0.0625 in, 0.3125 in, 0.125 in, 0.125 in, 0.375 in					0.1875 in, 0.25 in				120 in	36 in	Plain Backing, High-Temp	30A	0.09375 in, 0.125 in, 0.187		oth Re	ed J4594
36 in 36 in Acrylic 300, mm, 2-mm, 3-mm 300, 01 Ander K100 48 in 24 in Plain Backing, Acrylic 40A, 60A, 0.0625 in, 0.125 in, 0.1875 5, 0.025 in, 0.1875 5, 0.025 in, 0.1875 5, 0.025 in, 0.125 in, 0.1875 60 in 36 in Plain Backing 60A 0.0625 in, 0.125 in, 0.1875 5, 0.025 in, 0.1875 5, 0.025 in, 0.1875 5, 0.025 in, 0.1875 60 in 36 in Plain Backing 60A 0.0625 in, 0.125 in, 0.25 in 5, 0.015 in, 0.025 in, 0.015 in, 0.025 in, 0.015 in, 0.025 in, 0.015 in, 0.025 in, 0.015 in, 0.0375 in, 0.25 in 5, 0.016 Black-Speckled K5261 3 ft 3 ft Plain Backing 60A 0.0625 in, 0.0125 in, 0.125 in, 0.125 in, 0.125 in, 0.0125 in, 0.0125 in, 0.0125 in, 0.025 in 5, 0.05 in 0.03125 in, 0.125 in, 0.157 in, 0.25 in 5, 0.05 in 3 ft 1 ft 1 ft 1 ft<	36 10	36 10	Acrylic	60A	in, 0.25 in, 0.5 in	Smooth	Ambe	IND IND	Gener	ral Purj						
48 in 24 in Plain Backing, Acrylic 40A, 60A, 70A, 75D, in, 0.25 in, 0.1875, in, 0.51n, 70A, 75D, in, 0.25 in, 0.1875, in, 0.51n, 70A, 75D, in, 0.25 in, 0.1875, in, 0.25 in Smooth Black K5040 60 in 36 in Plain Backing 60A 0.0625 in, 0.125 in, 0.1875, in Smooth Amber K5111 60 in 36 in Plain Backing 60A 0.0625 in, 0.125 in, 0.1875, in Smooth Amber K5111 60 in 36 in Plain Backing 60A 0.0625 in, 0.125 in, 0.1875, in Smooth Black K5041 70A 0.025 in, 0.1875 in Smooth Amber K5111 60 in 36 in Plain Backing 70A 0.025 in, 0.1875 in Smooth Black K5041 11 ft 1 ft Plain Backing 60A 0.0625 in, 0.3125 in, 0.125 in, 0.375 in, 0.25 in Smooth Black-Speckled K5261 2.5 ft 24 in Plain Backing 60A 0.0625 in, 0.3125 in, 0.125 in, 0.375 in, 0.25 in Smooth Black-Speckled K5262 4 ft 1 ft Plain Backing 60A 0.0625 in, 0.3125 in, 0.125 in, 0.375 in, 0.25 in Smooth Black-Speckled K5263 4 ft 4 ft Plain Backing 60A 0.0625 in, 0.3125 in, 0.125 in, 0.375 in, 0.25 in Smooth	36 in	36 in		80A		Smooth	Ambe	er K5106	3 ft	12 in		70A		Smoo	oth Bla	.ck K5038
60 in 36 in Plain Backing 60A 0.0625 in, 0.125 in, 0.125 in, 0.25 in Smooth AmberK5111 General Purpose Recycled 1ft 1 ft	48 in	24 in		70A, 75D	D, in, 0.25 in, 0.375 in, 0.5 in,	Smooth	Black	K5110			-		0.25 in, 0.1875 in			
Odd 0.1875 in, 0.25 in 3modul Ander KST1 General Purpose Recycled 0.1875 in, 0.25 in 3modul Ander KST1 1 ft 0.375 in, 0.25 in 5mooth Black-Speckled K5261 3 ft 3 ft 9 ft 0.0625 in, 0.3125 in, 0.125 5mooth Black-Speckled K5262 0.0375 in, 0.25 in 5mooth Black-Speckled K5263 4 ft 1 ft Plain Backing 60A 0.0625 in, 0.3125 in, 0.125 in 5mooth Black-Speckled K5264	60 in	96 in	Diain Baaking				Amba	-VE111								
1 ft 1 ft Plain Backing 60A 0.0625 in, 0.3125 in, 0.125 in, 0.125 in, 0.125 in, 0.125 in, 0.25 in Smooth Black-Speckled K5261 3 ft 3 ft 9 lain Backing 60A 0.0625 in, 0.3125 in, 0.125 in, 0.125 in, 0.125 in, 0.375 in, 0.25 in Smooth Black-Speckled K5261 3 ft 3 ft 9 lain Backing 60A 0.0625 in, 0.3125 in, 0.125 in, 0.125 in, 0.125 in, 0.375 in, 0.25 in Smooth Black-Speckled K5261 4 ft 1 ft Plain Backing 60A 0.0625 in, 0.3125 in, 0.125 in, 0.125 in, 0.125 in, 0.375 in, 0.25 in Smooth Black-Speckled K5262 4 ft 1 ft Plain Backing 60A 0.0625 in, 0.3125 in, 0.125 in, 0.125 in, 0.125 in, 0.3125 in, 0.025 in Smooth Black-Speckled K5263 4 ft 4 ft Plain Backing 60A 0.0625 in, 0.3125 in, 0.125 in, 0.15			-			5110001	AIIIDE	TROTT	50 ft	36 in	Plain Backing					
Int Int <thint< th=""> <thint< th=""> <thint< th=""></thint<></thint<></thint<>				0).0625 in. 0.3125 in. 0.125			145000	Gener				0.03125 in .0.0625 in			
3 ft 3 ft 9 lain Backing 604 0.0625 in, 0.3125 in, 0.125 in, 0.125 in, 0.125 in, 0.375 in, 0.25 in Smooth Black-Speckled K5262 4 ft 1 ft Plain Backing 60A 0.0625 in, 0.3125 in, 0.125 in, 0.125 in, 0.125 in, 0.375 in, 0.25 in Smooth Black-Speckled K5263 4 ft 1 ft Plain Backing 60A 0.0625 in, 0.3125 in, 0.125 in, 0.125 in, 0.375 in, 0.25 in Smooth Black-Speckled K5263 4 ft 4 ft Plain Backing 60A 0.0625 in, 0.3125 in, 0.125 in, 0.125 in, 0.125 in, 0.375 in, 0.25 in Smooth Black-Speckled K5263 4 ft 4 ft Plain Backing 60A 0.0625 in, 0.3125 in, 0.125 in, 0.135 in, 0.25 in Smooth Black-Speckled K5263 4 ft 24 in Plain Backing 75A 0.09375 in, 0.25 in, 0.315 in, 0.25 in Smooth Black K5021 10 ft 4 ft Plain Backing 60A 0.0625 in, 0.3125 in, 0.125 in, 0.125 in, 0.1375 in, 0.25 in Smooth Black-Speckled K5264 10 ft 4 ft Plain Backing 60A 0.0625 in, 0.3125 in, 0.125 in, 0.1375 in, 0.25 in Smooth Black-Speckled K5264 10 ft				004	in, 0.375 in, 0.25 in 0.0625 in, 0.3125 in, 0.125		-		12 in	12 in		75A	0.09375 in, 0.125 in, 0.187 in, 0.25 in, 0.375 in, 0.5 ir	75 Smoo	oth Bla	.ck K5019
4 ft 1 ft Plain Backing 60A in, 0.375 in, 0.25 in Smooth Black-Speckled K3263 4 ft 4 ft 4 ft Plain Backing 60A 0.0625 in, 0.3125 in, 0.125 Smooth Black-Speckled K5264 4 ft 24 in Plain Backing 60A 0.0625 in, 0.3125 in, 0.125 Smooth Black-Speckled K5264 10 ft 4 ft Plain Backing 60A 0.0625 in, 0.125 in, 0.125 Smooth Black-Speckled K5264 10 ft 4 ft Plain Backing 60A 0.0625 in, 0.0125 in, 0.125 in Smooth Black-Speckled K5264 10 ft 4 ft Plain Backing 60A 0.025 in, 0.0125 in, 0.025 in Smooth Black-Speckled K5264 10 ft 4 ft Plain Backing 60A 0.025 in, 0.0125 in, 0.01875 in, 0.25 in Smooth Black-K5022 72 in, 26 in Plain Backing 75A 0.03125 in, 0.025 in Smooth Black-K5022				60A ⁰	0.0625 in, 0.3125 in, 0.125 in in, 0.375 in, 0.25 in Smo		-		24 in	12 in	Plain Backing	75A	0.09375 in, 0.125 in,		oth Bla	.ck K5020
4 ft 24 in Plain Backing 60A 0.0375 in, 0.25 in Onicol black-Speckled K5264 4 ft 24 in Plain Backing 60A 0.0625 in, 0.3125 in, 0.125 in 5mooth Black-Speckled K5264 10 ft 4 ft Plain Backing 60A 0.0625 in, 0.3125 in, 0.125 in Smooth Black-Speckled K5264 10 ft 4 ft Plain Backing 60A 0.0625 in, 0.3125 in, 0.125 in Smooth Black-Speckled K5264 70 in 9 in 0.03125 in, 0.0375 in, 0.25 in Smooth Black-Speckled K5264				OUA	in, 0.375 in, 0.25 in		-		36 in	12 in	Plain Backing	75A	0.09375 in, 0.125 in, 0.187		oth Bla	ıck K5021
4 ft 24 in Plain Backing 60A 0.0625 in, 0.125 in, 0.125 in, 0.125 in Smooth Black-Speckled K5264 10 ft 4 ft Plain Backing 60A 0.0625 in, 0.125 in, 0.125 in Smooth Black-Speckled K5266 10 ft 4 ft Plain Backing 60A 0.0625 in, 0.125 in, 0.125 in Smooth Black-Speckled K5266 72 in 28 in Plain Backing 75A 0.03125 in, 0.0625 in, 0.09375 in, 0.25 in Smooth Black-K5022	4 TT	4 Π		004	in, 0.375 in, 0.25 in				36 in	24 in	Plain Backing	75A	0.03125 in, 0.0625 in, 0.093	375 smoo	oth Bla	ick K7353
10 it 4 it Hain Backing 00H in, 0.375 in, 0.25 in 0100 in Diack Operation Rock 01 2 in 26 in Plain Backing 75A 0.03125 in, 0.0625 in, 0.09375 Smooth Plack K5025			-	00A 0	in, 0.375 in, 0.25 in						High-Temp,	-	0.03125 in, 0.0625 in, 0.093	375 Smor		
	10 ft	4 ft	Plain Backing	60A 0		oth Black-S	speckle	d K5266	72 in	36 in		75A	0.03125 in, 0.0625 in, 0.093	375 Smoo	oth Bla	ıck K5025

Polyurethane Rubber Tubes These abrasion-resistant tubes are polyurethane

These abrasion-resistant tubes are polyurethane construction and offer the shock-absorbing characteristics of rubber with the durability and tear resistance of plastic.



	Inside Dia.	Outside Dia.	Wall	CHOOSE: Duro.	CHOOSE: Overall Length	CHOOSE:	CHOOSE: Clarity	ltem No.
	⅔ in	1 in	5∕16 in	40A, 60A, 75D, 80A, 95A	6 in, 12 in	Black	Opaque	K4763
	1⁄2 in	2 in	3⁄4 in	60A, 75D, 80A, 95A	6 in, 12 in, 36 in	Black, Amber	Opaque, Semi-Clear	K4756
	3⁄4 in	21/2 in	7∕s in	40A	6 in, 12 in, 36 in	Black	Opaque	K4762
		1¾ in	⅔ in	40A, 60A, 75D, 80A, 95A	6 in, 12 in, 36 in	Black, Amber	Opaque, Semi-Clear	K4752
	1 in	2 in	1⁄2 in	40A, 60A, 75D, 80A, 95A	6 in, 12 in, 36 in	Black, Amber	Opaque, Semi-Clear	K4754
1 111	21/2 in	3⁄4 in	40A, 60A, 75D, 80A, 95A	6 in, 12 in, 36 in	Black, Amber	Opaque, Semi-Clear	K4753	
		3 in	1 in	40A, 60A, 75D, 80A, 95A	6 in, 12 in, 36 in	Black, Amber	Opaque, Semi-Clear	K4755

				CHOOSE:			
Inside Dia.	Outside Dia.	Wall	CHOOSE: Duro.	Overall Length	CHOOSE: Color	CHOOSE: Clarity	ltem No.
1¼ in	2 in	⅔ in	40A, 60A, 75D, 80A, 95A	6 in, 12 in, 36 in	Black, Amber	Opaque, Semi-Clear	K4750
	21/2 in	1⁄2 in	80A, 95A	6 in, 12 in, 36 in	Amber	Semi-Clear	K4749
	2 in	1⁄4 in	40A, 60A, 75D, 80A, 95A	6 in, 12 in, 36 in	Black, Amber	Opaque, Semi-Clear	K4747
1½ in	21/2 in	1⁄2 in	40A, 60A, 75D, 80A, 95A	6 in, 12 in, 36 in	Black	Opaque	K4745
1 72 111	2¾ in	5∕s in	40A, 60A, 75D, 80A, 95A	6 in, 12 in, 36 in	Black, Amber	Opaque, Semi-Clear	K4746
	3 in	3⁄4 in	40A, 60A, 75D, 80A, 95A	6 in, 12 in, 36 in	Black, Amber	Opaque, Semi-Clear	K4748
1¾ in	2¾ in	1⁄2 in	40A, 60A, 75D, 80A, 95A	6 in, 12 in, 36 in	Black, Amber	Opaque, Semi-Clear	K4751
2 in	3 in	1⁄2 in	40A, 60A, 75D, 80A, 95A	6 in, 12 in, 36 in	AIIIDei	Opaque, Semi-Clear	K4760
2 111	31⁄2 in	3⁄4 in	40A, 60A, 75D, 80A, 95A	6 in, 12 in, 36 in	Black, Amber	Opaque, Semi-Clear	K4759
2¼ in	3 in	⅔ in	40A, 60A, 75D, 80A, 95A	6 in, 12 in, 36 in	Black, Amber	Opaque, Semi-Clear	K4758
3 in	4 in	1⁄2 in	40A, 60A, 75D, 80A, 95A	6 in, 12 in, 36 in	Black, Amber	Opaque, Semi-Clear	K4761

•

Sign in to Grainger.com® to see YOUR Pricing and MORE