



## Gorilla Glue

- Full cure: 24 hr.

### General Purpose Instant Adhesive—

Bonds to most common building materials. Anticlog cap with a metal pin inside ensures an airtight seal for maximum reusability.

- Temp. range: -65° to 220°F

### General Purpose Liquid Glues—Bonds

wood, stone, metal, ceramic, and more. White dries faster. Waterproof.

- Temp. range: -40° to 212°F

### General Purpose Wood Glue—Bonds wood-

to-wood without leaving an orange afterglow. FDA approved for indirect food contact.

- Temp. range: 0° to 150°F

Characteristics	Color	Clamp Time	Size	Item No.
General Purpose Instant Adhesives				
Anti-Clog Cap, Easy to Use, Impact Resistant, Multipurpose, No Run		10 to 45 sec.	0.53 oz.	30WM02
Anti-Clog Tip, Impact Resistant, Polyurethane Adhesive, Rubber Toughened	Clear	10 to 45 sec.	(2) 3g Tubes	4GZK5
Rubber Toughened for Impact Strength		10 to 45 sec.	15g	4GZK6
		10 to 45 sec.	1 lb.	16V096
General Purpose Liquid Glues				
and Dries White, Paintable, Sandable, Stainable, Waterproof, Weatherproof	White	30 to 60 min	0.75 oz.	2KKF3
		30 to 60 min	2 oz.	2KKF2
Dries Clear, Non Foaming, Strong	Clear	2 hr	1.75 oz.	453U44
		2 hr	3.75 oz.	453U45
Extremely Strong Bonding Power	Brown	1 to 2 hr	2 oz.	1TLZ9
		1 to 2 hr	4 oz.	1TMA1
		1 to 2 hr	8 oz.	1TMA2
		1 to 2 hr	18 oz.	1TMA3
		1 to 2 hr	36 oz.	1TMA4
General Purpose Wood Glues				
Dries Natural Color, FDA Approved For Direct Food Contact, Non-Toxic, PVA, Solvent Resistant, Water Clean-Up, Water-Resistant	Cream	20 to 30 min	8 oz.	4GZK3
20 to 30 min		18 oz.	4GZK4	



## Wood Glues



Weldwood®



### DAP WELDWOOD

**Carpenter's Glue**—Sets fast, grips tight, and sands easily. Solvent resistant. Nontoxic.

### TITEBOND III ULTIMATE WOOD GLUE

Waterproof formula meets ANSI/HPVA Type I water-resistance specification. Has longer open assembly time and lower application temperature. Sands easily. Interior/exterior.

### TITEBOND II

**Premium and Extended Wood Glue**—Meet ANSI Type II water-resistance specification. 3KRU6 and 3KRU7 have a longer set time. Interior/exterior.

**Wood Glue**—Great for general woodworking with porous and semiporous materials. ANSI Type II.

### TITEBOND ORIGINAL WOOD GLUE

Aliphatic-resin glue sets quickly to reduce clamp time. Resists heat, solvents, and mildew. 3KRU4 and 4EML7 have a longer set time.

### TITEBOND

**Quick & Thick, No Run/No Drip**—Glue dries twice as fast and three times as thick as traditional PVAs. Bonds to multiple surfaces.

Type	Color	Begins to Harden	Size	Item No.
DAP Weldwood Carpenter's Wood Glue				
Aliphatic Resin	Yellow	10 min.	1 qt.	5UFR4
			1 gal.	5E104
Titebond III Ultimate Wood Glue				
Water-Resistant	Tan	10 Min.	4 oz.	3KZJ4 *
		10 min.	8 oz.	1FCC1 *
		10 min.	16 oz.	1FCC2 *
		10 min.	1 gal.	1FCC3 *
Titebond II Premium Wood Glue				
Exterior	Honey Cream	5 Min.	4 oz.	3KZJ6 *
		5 min.	8 oz.	3KRU5 *
		5 min.	16 oz.	1FCC4 *
		5 min.	1 gal.	1FCC5 *
Titebond II Extended Wood Glue				
Slow Set	Cream	15 min.	16 oz.	3KRU6
		15 min.	1 gal.	3KRU7
Titebond II Wood Glue				
Dark	Brown	5 min.	8 oz.	4EMP2
		5 min.	16 oz.	3KRU8
		5 min.	1 gal.	4EMP3
Titebond II Original Wood Glue				
Heat- and Solvent-Resistant	Yellow	5 min.	4 oz.	4EML7
		5 min.	8 oz.	3KRU3
		5 min.	16 oz.	1FCC6
		5 min.	1 gal.	1FCC7
Titebond II Original Extended Wood Glue				
Slow Set	Yellow	15 min.	16 oz.	3KRU4
		15 min.	1 gal.	4EML8
Titebond Quick & Thick, No Run/No Drip				
No Run, No Drip	Beige	3 to 5 min.	16 oz.	4EMP4

\* FDA approved for indirect food contact (cutting board).



5E104



1FCC1



1FCC4

## Asphalt Patch Paving Material

**Sakrete**—21HC47 is a liquid formula used to fill cracks up to 1/2" wide. Accepts traffic after 5 days. 39UV47 has a full cure time of 2 days.

**Perma-Patch**—Patches potholes, utility cuts, and cracks. Bonds permanently to asphalt, concrete, steel, and wood. Apply in any weather condition. No mixing. Dries immediately; cures faster under greater volumes of traffic. Compaction can be accomplished by hand tamping.



**GreenPatch**—Ready-to-use VOC-compliant formula contains recycled asphalt and permanently repairs potholes and cracks in pavement. Workable in all weather and can be installed in standing water. Accepts traffic immediately after application.

**Rust-Oleum**—Concrete Patch and Repair is a 2-part, industrial-strength epoxy that permanently bonds concrete, won't shrink or crack, and creates a surface stronger than concrete. For indoor/outdoor use. Fast curing; paintable in 8 hours. Easy mixing, low odor, no solvents.


 Perma-Patch  
32C17

 GreenPatch  
39F847

Description	Coverage	Container Size	Mr. Model	Item No.
<b>Sakrete</b>				
Crack Filler	160 ft @ 1/4 in x 1/4 in	128 oz	120039	21HC47
	40 ft @ 1/4 in x 1/4 in	32 oz	120041	39UV47
<b>Perma-Patch</b>				
Cold Patch	3 sq ft @ 1 in	30 lb	PP-30-CP	13R450
Black Asphalt Paving Compound	6 sq ft @ 1 in	60 lb	PP-60-C	32C17
<b>GreenPatch</b>				
Cold Patch	3 sq ft @ 21 in x 21 in x 1 in	40 lb	GP40P	39F847
	4 sq ft @ 2 ft x 2 ft x 1 in	50 lb	GP50	39F846
<b>Rust-Oleum</b>				
Concrete Repair Compound	14 Linear ft @ 1/2 in x 1/2 in	24 oz	301012	52JU46