

## ADHESIVES

### Asphalt/Concrete Patch & Repair

Scan. Order. Done.  
Details on page A1.



40P317



**Henry**  
#1 CHOICE OF PROFESSIONALS

## Driveway Asphalt and Coating

**Asphalt Resurfacer**—Fills and seals rough surfaces and cracks in asphalt driveways. Features a 7x rubberized formulation for long life and durability. Stir gel formula applies easily, dries quickly, and reduces tracking.

### E-Z Stir Asphalt Filler/Sealer

—Do-it-yourself, easy-to-use formula stirs and applies easily. Reinforced for improved traction and durability.

**Asphalt Pothole Patch**—Use this solvent-based asphalt and aggregate compound to fill larger cracks and potholes. All-weather formula requires no mixing.

**Asphalt Coating**—Brush-applied sealcoat is ideal for home use. Stirs and applies easily.

Description	Container Size	Flash Point	Dry Time Recoat	Coverage	Item No.
Asphalt Resurfacer	5 gal	Greater than 212 °F	4 hr	250 to 500 sq ft	40P317
E-Z Stir Asphalt Filler/Sealer	5 gal	Greater than 212 °F	4 hr	250 to 500 sq ft	40P318
Asphalt Pothole Patch	11 lb	170 °F	Immediately After Compacting	2 sq ft x 1 in	40P320
Asphalt Coating	55 gal	Greater than 212 °F	4 hr	2200 to 4400 sq ft	35LR68



21HC54

## Concrete Mixes



### ■ 50 lb. pail

Formulated with sand, gravel, and cement for repair and building jobs where concrete is more than 2" thick.

21HC53 sets posts and poles easily without blending. Sets in 30 min.

21HC52 includes fibers that help resist cracking due to shrinkage.

21HC54 achieves 5000 psi strength. Also good for use in concrete countertops.

21HC55 is a general purpose concrete mix with a strength of 4000 psi.

Description	Meets	Mfr. Model	Item No.
Fast Setting Concrete Mix	ASTM C-387 and ASTM C-270	120019	21HC53
Crack Resistant Concrete Mix	ASTM C-387	120018	21HC52
5000 Plus High Strength Concrete Mix	ASTM C-387	120020	21HC54
High Strength Concrete Mix	ASTM C-387	120021	21HC55



39H820



39H819

**CRACK-STIX**

## Permanent Concrete & Asphalt Joint & Crack Filler

Easy to use with no mixing: Cut pliable cord to length, hand-pack, and heat with a propane torch. It melts instantly and cures quickly, accepting traffic in less than 20 min. Creates a permanent watertight bond.

Container Size	Coverage	Color	Mfr. Model	Item No.
<b>Concrete</b>				
10 lb	125 ft @ 1/2 in x 1/2 in	Gray	2051	39H820
10 lb	225 ft @ 1/4 in x 1/4 in	Gray	2061	30WM10
<b>Asphalt</b>				
8 lb	125 ft @ 1/2 in x 1/2 in	Black	2050	39H819
10 lb	250 ft @ 1/4 in x 1/4 in	Black	2060	30WM09

2134 **GRAINGER**

Find even **MORE** on **Grainger.com**



21HC50



52VY64



## Concrete Cleaner and Dissolver

**Concrete and Asphalt Cleaner**—Mild, acidic liquid used to clean concrete, masonry, and asphalt surfaces. Use to clean existing surfaces prior to making repairs.

**Concrete Mortar Dissolver**—A safe, environmentally-friendly liquid alternative to aggressive acid concrete removers. Used to remove dried on cement, concrete, mortar, or stucco from most surfaces.

Description	Container Size	Item No.
Concrete and Asphalt Cleaner	0.3 gal	21HC50
Concrete Mortar Dissolver	0.2 gal	52VY64



15F516



## Tinted Concrete Mixes

### TintCrete Resurfacer

Resurface or patch concrete with this colored resurfacing material. Trowel, broom, or brush onto existing concrete.

Color	Starts to Harden	Mfr. Model	Item No.
<b>TintCrete Resurfacer, 50 lb</b>			
Almond	30 min to 1 hr	GRA-DLC-21	15F511
Gray	30 min to 1 hr	GRA-DLC-16	15F520
<b>TintCrete Concrete, 50 lb</b>			
Red	45 min to 1.5 hr	GRA-P38-1310	15F516

**TintCrete Concrete**—Repair horizontal or formed areas with pourable colored concrete. Use to patch and repair concrete from 1" to full depth.



62173



## Expansion Cement

Develops a compression strength of 4500 lb./sq.-in. within 1 hr. For applications such as anchoring bolts, buildings, partitions, machines, appliances, tools, railings, hardware, and posts to concrete and other masonry floors and walls.

Starts to Harden	Container Size	Mfr. Model	Item No.
	5 lb	10005	62173
15 min	10 lb	10010	62174
	50 lb	10051	62175



62FY3

## Polymeric Jointing Sand



For use with concrete pavers, cast stone, and natural stone products in patio, walkway, and driveway applications. Material fills the joints between pavers, to help prevent weed growth and sand erosion due to rain or water run off.

Color	Container Size	Container Style	Item No.	Pkg. Qty.
Tan	50 lb	Bag	62FY3	8
Gray	50 lb	Bag	62FY4	8

1-800-GRAINGER (472-4643)