ELECTRICAL Logic Relays



Schneider Gelectric





Accessories			
PC Connection Cable, RS-32 Connector	SR2CBL01	1CNL7	
PC Connection Cable, PC USB to 1CNL7	SR2CBL06	2GNW5	
PC Connection Cable, PC USB to Relay	SR2USB01	2GNW8	
Memory Cartridge, EEPROM	SR2MEM02	2GNX2	
Add-In Memory, EEPROM	SR2MEM01	1CNL8	

Logic Relays and Extension Modules

- 16 counters and timers

Integral display

Expandable design allows users to manage a simple automation system with multiple inputs and outputs, without the need for a complex programmable controller. 6-button navigation allows direct programming in any of several computer languages. Compact, space-saving

design. Extension modules add inputs and outputs to customize systems for specific needs. Programming software 1CNL6 and PC connection cable 1CNL7 permit uploading programs from a PC, directly to multiple relays. Use for small machinery and supplemental large machinery automation systems, lighting management, security systems management, and HVAC management.

						24V AC	24V DC	100 to 240V AC			
No. of	No. of			_	Mfr.	Item	Item	Item			
Inputs	Outputs	W	H	D	Model	No.	No.	No.			
	Relay Output with Display and Clock										
6	4	2.8 in	4.24 in	2.34 in	SR3B101	2GNR1	2GNN5	2GNR8			
8	4	2.8 in	4.24 in	2.34 in	SR2B121	2GNJ3	1CNL1	1CNL3			
12	8	4.91 in	4.24 in	2.34 in	SR2B201	2GNJ5	2GNH6	2GNK1			
16	10	4.91 in	4.24 in	2.34 in	SR3B261	2GNR4	2GNP4	2GNT2			
Discrete Input	Discrete Inputs/Outputs Extension Modules, For Use With SR3B Series Above										
4	2	_	—	—	SR3XT61	2GNU2	2GNT8	2GNU5			
6	4	—	—	—	SR3XT101	2GNU8	1CNL4	2GNV2			
Relay Output											
6	4	2.8 in	4.24 in	2.34 in	SR2D101	—	2GNK4	2GNL4			
12	8	4.91 in	4.24 in	2.34 in	SR2E201	—	2GNL1	-			
Relay Output v	vith Clock										
8	4	2.8 in	4.24 in	2.34 in	SR2E121	—	2GNK7	2GNL7			
Relay Output v	vith Display										
12	8	4.91 in	4.24 in	2.34 in	SR2A201	_	2GNH3	2GNJ7			
Transistor Out	put with Display	and Clock									
6	4	2.8 in	4.24 in	2.34 in	SR3B102	—	2GNN9				
8	4	2.8 in	4.24 in	2.34 in	SR2B122	_	2GNG9	_			
12	8	4.91 in	4.24 in	2.34 in	SR2B202	_	2GNH9	_			
16	10	4.91 in	4.24 in	2.34 in	SR3B262	_	2GNP7	_			
Discrete Input	s/Outputs Exten	sion Modules, H	For Use With SR	3B Series Abov	e						
8	6	_	—	—	SR3XT141	—	2GNV5	1CNL5			
Analog Inputs/	Outputs Extensi	ion Module, For	Use With SR3B	Series Above							
2	2	_ `	_	_	SR3XT43	_	2GNW2	_			
Communications Extension Module, For Use With SR3B Series Above											
0	0	_	_	_	SR3MBU01	_	2GNT5	_			
Relay Output v	Relay Output with Clock										
12	8	4.91 in	4.24 in	2.34 in	SR2E201	_	_	2GNN1			
Relay Output v	vith Display										
6	4	2.5 in	3.5 in	3.9 in	SR2A101	—	-	1CNL2			
		2.0	2.2	2.2	2						

+24V OV 11 12 13 E.T.N POW / RUN easy-E4 B 0 01 02

Programmable Relays Easy to use Programmable Relays feature expandable design that allows you to manage a simple automation system with multiple inputs and outputs, without the need for a complex programmable controller. Compact, space-saving design with extension modules that add inputs and outputs to customize systems for specific needs. They are also easy to connect via Ethernet or Profibus to other PLC's or automation systems. Use for small machinery and supplemental large machinery automation systems,

lighting management, security systems management, and HVAC systems.									
For Use With	Includes	No. of Inputs	No. of Outputs	Power Reg.	Features	ltem No.			
Input/Output Module		· · · · · · · · · · · · · · · · · · ·							
Easy E4 Control Relays	Screw Terminals	4	4 Relav	100 to 240V AC	Easy E4 Expansion I/O	55PK26			
Easy E4 Control Relays	Screw Terminals	4	0	24V DC	Easy E4 Expansion I/O	55PK28			
Easy E4 Control Relays	Screw Terminals	4	2	24V DC	Easy E4 Expansion I/O	55PK29			
Easy E4 Control Relays	Screw Terminals	4	4	24V DC	Easy E4 Expansion I/O	55PK30			
Easy E4 Control Relays	Screw Terminals	4	4	12 to 24V DC	Easy E4 Expansion I/O	55PK32			
Easy E4 Control Relays	Screw Terminals	8	8 Relay	100 to 240V AC	Easy E4 Expansion I/O	55PK25			
Easy E4 Control Relays	Screw Terminals	8	8	24V DC	Easy E4 Expansion I/O	55PK27			
Easy E4 Control Relays	Screw Terminals	8	8	12 to 24V DC	Easy E4 Expansion I/O	55PK31			
LCD									
EasySoft PLC Software	Screw Terminals	4 Digital, 4 Digital or Analog	4	24V DC	Diagnostic LED Display, Easy E4 Nano PLC	55PK35			
EasySoft PLC Software	Screw Terminals	4 Digital, 4 Digital or Analog	4	12 to 24V DC	Diagnostic LED Display, Easy E4 Nano PLC	55PK37			
EasySoft PLC Software	Screw Terminals	8 Digital	4	100 to 240V AC	Diagnostic LED Display, Easy E4 Nano PLC	55PK33			
No Display		0							
EasySoft PLC Software	Screw Terminals	4 Digital, 4 Digital or Analog	4	100 to 240V AC	Easy E4 Nano PLC	55PK34			
EasySoft PLC Software	Screw Terminals	4 Digital, 4 Digital or Analog	4	24V DC	Easy E4 Nano PLC	55PK36			
EasySoft PLC Software	Screw Terminals	4 Digital, 4 Digital or Analog	4	12 to 24V DC	Easy E4 Nano PLC	55PK38			





2REP7



OMRON. **Programmable** Relays

56 timers and 17 counters LCD with calendar and clock

Provide relay, timer, counter, and time switch functions; easily programmable in ladder-view format. With weekly and calendar timers, flexible mounting expansion via 8-point I/O units, twintimer operation, and multilanguage display. DC models have analog inputs. For use in time-controlled and smallscale applications such as lighting and air conditioning.

	Input	Output			No. of			_	Mfr.	Item
	Voltage	Type	Amps	Inputs	Outputs	W	Н	D	Model	No.
	Expandable									
	100 to 240V AC	Relay	4.5 A	6	4		3.54 in		ZEN-10C1AR-A-V2	2REN9
	100 to 240V AC	Relay	4.5 A	12	8		3.54 in	2.2 in	ZEN-20C1AR-A-V2	2REP7
	12 to 24V AC/DC	Relay	30 A	6	4	2.75 in	3.54 in	2.2 in	ZEN-10C1DR-D-V2	2REP1
	12 to 24V AC/DC	Transistor	30 A	6	4	2.75 in	3.54 in	2.2 in	ZEN-10C1DT-D-V2	2REP2
	12 to 24V AC/DC	Transistor	30 A	12	8	4.82 in	3.54 in	2.2 in	ZEN-20C1DT-D-V2	2REP8
	Nonexpandable									
	100 to 240V AC	Relay	4.5 A	6	4	2.75 in	3.54 in	2.2 in	ZEN-10C3AR-A-V2	2REP3
	100 to 240V AC	Relay	4.5 A	12	8	4.82 in	3.54 in	2.2 in	ZEN-20C3AR-A-V2	2REP9
	12 to 24V AC/DC	Relay	30 A	6	4	2.75 in	3.54 in	2.2 in	ZEN-10C3DR-D-V2	2REP4
	12 to 24V AC/DC	Relay	30 A	12	8	4.82 in	3.54 in	2.2 in	ZEN-20C3DR-D-V2	2RER1
;	With RS-485 Com	municatio	1							
	100 to 240V AC	Relay	4.5 A	6	3	2.75 in	3.54 in	2.2 in	ZEN-10C4AR-A-V2	2REP5
	12 to 24V AC/DC	Relay	30 A	6	3	2.75 in	3.54 in	2.2 in	ZEN-10C4DR-D-V2	2REP6
	Extension Module	es								
	100-240VAC	Relay	_	4	4	_	_	_	ZEN-8E1AR	2RER2
	12-24VDC	Relay	_	4	4	_	_	_	ZEN-8E1DR	2RER3
	12-24VDC	Transistor	_	4	4	_	_	_	ZEN-8E1DT	2RER4
	Accessories									
	Support Software								ZEN-SOFT01V4	2RER5
	Connecting Cable								ZEN-CIF01	2RER6
1	Memory Cassette								ZEN-ME01	2RER7
	Battery Unit								ZEN-BAT01	2RER8

Find even MORE on Grainger.com®

1-800-GRAINGER (472-4643)



EasySoft PLC Software Screw Terminals 4 Digital, 4 Digital of Analog 4

GRAINGER

216