



## Powder-Actuated Tool

For fast, secure fastening into steel, concrete, and masonry. Ergonomically designed for operator comfort and safety. Trigger-operated tool uses 10-load powder strips for efficient operation and has automatic powder load ejection and steel construction.

Description	Caliber	Tool Length (In)	Tool Weight (lb.)	Mfr. Model	Item No.
<b>Power-Actuated Tools</b>					
<b>Capacity 2 -1/2 in Pins and 3 in Pin with Washer</b>					
Semi-Automatic, 10 Load Strip	0.27	13 1/4 in	4.5 lb	COBRA	2HNW6

Description	Mfr. Model	Item No.	Pkg. Qty.
<b>Knurled Pins</b>			
1/2 in* Length, 0.3 in00 Head Dia./0.145 in Shank Diameter	1503K	2HNX8	* 100
<b>Straight Pins</b>			
3/4 in* Length, 0.3 in00 Head Dia./0.145 in Shank Diameter	1506	2HNX9	* 100
1 in* Length, 0.3 in00 Head Dia./0.145 in Shank Diameter	1508	2HNY1	* 100
1 1/4 in* Length, 0.3 in00 Head Dia./0.145 in Shank Diameter	1510	2HNY2	* 100
1 1/2 in* Length, 0.3 in00 Head Dia./0.145 in Shank Diameter	1512	2HNY3	* 100
2 in* Length, 0.3 in00 Head Dia./0.145 in Shank Diameter	1514	2HNY4	* 100
2 1/2 in* Length, 0.3 in00 Head Dia./0.145 in Shank Diameter	1516	2HNY5	* 100
3 in* Length, 0.3 in00 Head Dia./0.145 in Shank Diameter	1524	2HNY6	* 100
<b>Fastening Pins With 1" Washer</b>			
3/4 in* Length, 0.3 in00 Head Dia./0.145 in Shank Diameter	1506SD	2HNY8	* 100
1 in* Length, 0.3 in00 Head Dia./0.145 in Shank Diameter	1508SD	2HNY7	* 100
1 1/4 in* Length, 0.3 in00 Head Dia./0.145 in Shank Diameter	1510SD	2HNY9	* 100
1 1/2 in* Length, 0.3 in00 Head Dia./0.145 in Shank Diameter	1512SD	2HNZ1	* 100
2 in* Length, 0.3 in00 Head Dia./0.145 in Shank Diameter	1514SD	2HNZ2	* 100
2 1/2 in* Length, 0.3 in00 Head Dia./0.145 in Shank Diameter	1516SDC	2HNZ3	* 100
3 in* Length, 0.3 in00 Head Dia./0.145 in Shank Diameter	1524SDP	2HNZ4	* 100
<b>Powder Loads</b>			
0.27, Green, Fastening	3RS27	2HPA1	100
0.27, Yellow, Fastening	4RS27	2HPA2	100
0.27, Red, Fastening	5RS27	2HPA3	100

\* All pins are 1060-1065 steel with core hardness of 52-56 Rc.



## Shower and Grab Bar Anchors

**Shower Rod Anchor**—Use with crescent and oval curved shower rods when there is insufficient structural blocking. Installs quickly into any hollow wall substrate up to 1 1/4" thick. Made of fire-retardant plastic material. Includes 4 stainless steel screws, 4 wings, and water-proof adhesive tape.

**Grab Bar Anchors**—Watertight installation eliminates blocking, even over grout lines in drywall with tile. 6UTC8 is rated up to 600 lb. and 6UTC7 is rated up to 800 lb. Each includes stainless steel screws. Meet ADA guidelines and commercial building codes. Installation into bare 1/2" drywall is not compliant with commercial building codes.

**Wall and Tile Drill Bits and Sets**—Precision bits cut fast, clean holes to install anchors in ceramic wall tile, wallboard, glass, steel, marble, and plaster. Made of industrial carbide.



Material	Item No.	Pkg. Qty.
<b>Shower Rod Anchor</b>		
Fire Retardant Structural Plastic	6UTD3	2
<b>Grab Bar Anchors</b>		
Stainless Steel	6UTC7	2
Fire Retardant Structural Plastic	6UTC8	2
<b>Wall and Tile Drill Bits and Sets</b>		
3/4"	6UTC9	1
1/4 in, 3/4 in, 1 1/4 in	6UTD1	3
1/4 in, 1/2 in, 3/4 in, 1 in, 1 1/4 in	6UTD2	1
1 1/4"	6UTD0	1