



## Wire Mesh—PVC Coated Galvanized

Coated welded wire can handle intensive use without stripping or peeling in industrial, cage, and marine applications.

Mesh Size	Color	Wire Dia.	Opening Size	4 ftW x 48 inL Item No.	4 ftW x 96 inL Item No.
<b>Wire Mesh PVC Coated Galvanized</b>					
<b>Fine</b>					
½ in x ½ in	Black	0.063 in	0.437 in	49N578	49N580
	Yellow	0.063 in	0.437 in	49N588	49N590
<b>Medium</b>					
1 in x 1 in	Black	0.08 in	0.92 in	49N598	49N601
	Black	0.105 in	0.895 in	49N609	49N611
	Yellow	0.105 in	0.895 in	49N619	49N621
<b>Coarse</b>					
1½ in	Yellow	0.105 in	1.395 in	—	49N641
	Black	0.105 in	1.395 in	49N629	49N631
2 in	Yellow	0.105 in	1.895 in	49N659	49N661
	Black	0.105 in	1.895 in	49N649	49N651



Raised

## Expanded Metal Sheets

Strong, rigid sheets allow air and light to pass through. Mesh construction is easily shaped, welded, and cut. Flat sheets provide a smooth surface. Raised sheets are used in applications that require surface traction.

Overall Thickness	Trade Size	Opening Size	4 FT X 4 FT Item No.	4 FT X 8 FT Item No.
<b>1008 Carbon Steel - Cold Rolled Temper (Mill)</b>				
<b>Flat</b>				
0.03 in	¼ in -#20	0.094 x 0.688 in	—	5PAV5
0.04 in	¼ in -#18	0.094 x 0.688 in	5PCJ3	5PAV3
0.05 in	½ in -#16	0.250 x 1.000 in	—	5PAX9
	½ in -#13	0.250 x 1.000 in	—	5PAX4
0.07 in	¾ in -#13	0.688 x 1.782 in	—	5PAX6
	1½ in -#13	1.063 x 2.750 in	—	5PAX5
0.11 in	1½ in -#9	1.000 x 2.563 in	—	5PAV6
0.12 in	¾ in -#9	0.563 x 1.688 in	—	5PAV7
<b>Raised</b>				
0.125 in	¼ in -#18	0.172 x 0.719 in	5PCN3	5PAZ8
0.157 in	½ in -#16	0.375 x 0.938 in	5PCL7	5PAZ4
0.182 in	½ in -#13	0.313 x 0.938 in	—	5PAZ0
0.195 in	¾ in -#13	0.750 x 1.688 in	—	5PAZ2
0.215 in	1½ in -#13	1.188 x 2.500 in	—	5PAZ1
0.295 in	1½ in -#9	1.125 x 2.375 in	—	5PCA1
0.3 in	¾ in -#9	0.688 x 1.562 in	5PCR3	5PCA3

Overall Thickness	Trade Size	Opening Size	4 FT X 4 FT Item No.	4 FT X 8 FT Item No.
<b>3003 Aluminum - H14 Temper (Mill)</b>				
<b>Flat</b>				
0.055 in	1½ in -#0.081	1.063 x 2.750 in	—	5PAW1
0.06 in	½ in -#0.081	0.313 x 1.000 in	5PCD9	5PAW0
0.07 in	¾ in -#0.081L	0.688 x 1.750 in	5PCE3	5PAW3
	¾ in -#0.081	0.688 x 1.750 in	5PCE1	5PAW2
0.08 in	1½ in -#0.125	1.000 x 2.750 in	5PCE6	5PAW4
0.095 in	¾ in -#0.125	0.625 x 1.750 in	5PCE7	5PAW5
<b>Raised</b>				
0.186 in	½ in -#0.081	0.375 x 0.938 in	5PCF5	5PAW8
0.2 in	¾ in -#0.081L	0.750 x 1.688 in	5PCF9	5PAW1
0.24 in	1½ in -#0.081	1.188 x 2.500 in	—	5PAW9
0.3 in	1½ in -#0.125	1.188 x 2.500 in	5PCG2	5PAW2
0.305 in	¾ in -#0.125	0.688 x 1.688 in	5PCG3	5PAW3
<b>304 Stainless Steel - 2B Temper (Mill)</b>				
<b>Flat</b>				
0.04 in	½ in -#18	0.313 x 1.000 in	5PCU4	5PC22
	½ in -#16	0.313 x 1.000 in	5PCU0	5PCA9
0.05 in	¾ in -#16	0.750 x 1.813 in	5PCU2	5PC21
	1½ in -#16	1.063 x 2.750 in	5PCU1	5PC20
0.07 in	¾ in -#13	0.625 x 1.750 in	5PC16	5PCA8
0.08 in	1½ in -#13	1.000 x 2.625 in	5PC15	5PCA7
0.12 in	¾ in -#9	0.563 x 1.688 in	5PC16	5PC33
<b>Raised</b>				
0.164 in	½ in -#18	0.438 x 0.938 in	5PCV9	5PC29
	½ in -#16	0.438 x 0.938 in	5PCV5	5PC26
0.2 in	¾ in -#13	0.750 x 1.688 in	5PCV1	5PC25
	¾ in -#16	0.813 x 1.750 in	5PCV7	5PC28
0.22 in	1½ in -#13	1.250 x 2.625 in	5PCV0	5PC24
<b>316 Stainless Steel - (Annealed)</b>				
<b>Flat</b>				
0.05 in	½ in -#16	0.313 x 1.000 in	5PCT3	5PCD1
0.07 in	¾ in -#13	0.625 x 1.750 in	5PCT1	5PCD0
<b>Zinc Galvanized Carbon Steel - Hot Rolled</b>				
0.05 in	½ in -#16	0.250 x 1.000 in	5PCR7	5PCA5
0.07 in	½ in -#13	0.250 x 1.000 in	5PCR5	5PCA4
0.12 in	¾ in -#9	0.563 x 1.688 in	5PCR9	—
<b>Zinc Galvanized Galvanized Steel - Hot Rolled</b>				
0.12 in	¾ in -#9	0.563 x 1.688 in	—	5PCA6

## Perforated Sheets

Used in multiple applications, these sheets are available in staggered or straight patterns, with various hole diameters and open area percentages.

Width	Length	Thickness	Gauge	Hole Dia.	Center Spacing	Open Area	Item No.
<b>3003 Aluminum - H14 Temper (Mill)</b>							
<b>Round Staggered Pattern</b>							
36 in	40 in	0.032 in	20	0.062 in	¼ in	30 %	SPDC8
		0.032 in	20	0.062 in	½ in	23 %	SPDC7
		0.032 in	20	0.125 in	¾ in	40 %	SPDC6
		0.032 in	20	0.188 in	1¼ in	51 %	SPDC9
		0.032 in	20	0.25 in	¾ in	58 %	SPDC4
		0.05 in	16	0.062 in	¼ in	23 %	SPDC0
		0.05 in	16	0.125 in	¾ in	40 %	SPDA9
		0.05 in	16	0.188 in	1¼ in	51 %	SPDC2
		0.05 in	16	0.25 in	¾ in	40 %	SPDA8
		0.063 in	14	0.125 in	¾ in	40 %	SPDA6
		0.063 in	14	0.188 in	1¼ in	51 %	SPDA7
		0.063 in	14	0.25 in	¾ in	40 %	SPDA5
<b>Hex Staggered Pattern</b>							
36 in	40 in	0.032 in	20	0.25 in	¾ in	77 %	SPDC5



Staggered Hex  
5PDC5

Width	Length	Thickness	Gauge	Hole Dia.	Center Spacing	Open Area	Item No.
<b>1008 Carbon Steel - Cold Rolled Temper (Mill)</b>							
<b>Round Staggered Pattern</b>							
36 in	40 in	0.036 in	20	0.063 in	¼ in	23 %	SPDH0
		0.048 in	18	0.063 in	½ in	23 %	SPDF7
		0.048 in	18	0.078 in	½ in	35 %	SPDF4
		0.048 in	18	0.094 in	¾ in	35 %	SPDG2
		0.048 in	18	0.125 in	¾ in	40 %	SPDF6
		0.048 in	18	0.156 in	¾ in	46 %	SPDG0
		0.048 in	18	0.188 in	1¼ in	40 %	SPDG1
		0.048 in	18	0.25 in	¾ in	58 %	SPDF5
		0.06 in	16	0.063 in	¼ in	30 %	SPDE3
		0.06 in	16	0.063 in	½ in	23 %	SPDE2
		0.06 in	16	0.078 in	½ in	35 %	SPDD6
		0.06 in	16	0.094 in	¾ in	33 %	SPDF1
0.06 in	16	0.125 in	¾ in	40 %	SPDE1		
0.06 in	16	0.156 in	¾ in	63 %	SPDE5		
0.06 in	16	0.156 in	¾ in	46 %	SPDE6		
0.06 in	16	0.188 in	1¼ in	50 %	SPDF0		
0.06 in	16	0.188 in	¾ in	32 %	SPDE9		
0.06 in	16	0.25 in	¾ in	58 %	SPDE0		
0.06 in	16	0.25 in	¾ in	40 %	SPDD9		
0.06 in	16	0.313 in	¾ in	46 %	SPDF2		
0.06 in	16	0.375 in	¾ in	40 %	SPDE8		
0.06 in	16	0.5 in	1½ in	48 %	SPDD7		
0.075 in	14	0.25 in	¾ in	40 %	SPDD3		
0.075 in	14	0.375 in	¾ in	40 %	SPDD4		
0.075 in	14	0.5 in	1½ in	48 %	SPDD2		
0.25 in	0.25 in	¾ in	40 %	SPDJ7			
<b>Square Straight Pattern</b>							
36 in	40 in	0.06 in	16	0.5 in	1½ in	53 %	SPDD8

Width	Length	Thickness	Gauge	Hole Dia.	Center Spacing	Open Area	Item No.
<b>304 Stainless Steel - Annealed Temper (2B)</b>							
<b>Round Staggered Pattern</b>							
36 in	40 in	0.048 in	18	0.094 in	¾ in	33 %	SPDL0
		0.048 in	18	0.125 in	¾ in	40 %	SPDK8
		0.048 in	18	0.188 in	1¼ in	51 %	SPDK9
		0.048 in	18	0.25 in	¾ in	58 %	SPDK7
		0.048 in	18	0.25 in	¾ in	40 %	SPDK0
		0.06 in	16	0.125 in	¾ in	40 %	SPDK5
		0.06 in	16	0.188 in	1¼ in	51 %	SPDK6
		0.06 in	16	0.25 in	¾ in	58 %	SPDK4
		0.06 in	16	0.25 in	¾ in	40 %	SPDJ8
		0.075 in	14	0.125 in	¾ in	40 %	SPDK3
		0.075 in	14	0.25 in	¾ in	40 %	SPDK2
		0.12 in	11	0.25 in	¾ in	40 %	SPDK1
<b>Polypropylene - White</b>							
<b>Round Staggered Pattern</b>							
48 in	32 in	0.063 in	0.125 in	¾ in	40 %	5PCY1	
		0.125 in	0.125 in	¾ in	40 %	5PCX3	
		0.125 in	0.188 in	¾ in	32 %	5PCX2	
		0.063 in	0.125 in	¾ in	40 %	5PCY4	
96 in	12 in	0.125 in	0.125 in	¾ in	40 %	5PCX9	
		0.125 in	0.188 in	¾ in	32 %	5PCX8	
<b>Round Straight Pattern</b>							
48 in	32 in	0.25 in	0.25 in	½ in	20 %	5PCW9	
		0.25 in	0.25 in	½ in	20 %	5PCW5	
		0.25 in	0.25 in	½ in	20 %	5PCW7	
<b>PVC - Gray</b>							
<b>Round Staggered Pattern</b>							
48 in	96 in	0.25 in	0.5 in	1½ in	48 %	5PCY9	
		0.063 in	0.125 in	¾ in	40 %	5PDA2	
		0.125 in	0.125 in	¾ in	40 %	5PCZ8	