



1TDX3



49CE92



1FBH5



2PAC7



2GXZ1



5E220



48LR95



## Gasket Sealants

Sealants indicated as Low-VOC are low-solvent formulations that release significantly fewer harmful vapors than standard adhesives. 1TDX3 is an odorless, solvent-free adhesive for rigid or flexible flanges. Solvent-based, paste-like sealant 2EMY3 sets slowly to a pliable film and is best suited for nonrigid, vibrating assemblies. Resistant to gasoline and other solvents. General purpose Superflex RTV Silicone Sealants 3KMY7, 3KNK3, and 3KMY8 cure at room temperature to form a tough rubber seal. Will not slump in overhead or vertical applications. Withstand extreme temperature cycling, UV light, and ozone. Cannot be painted.

Description	Type	Color	Size	Temp. Range	Full Cure	Brand	Mfr. Model	Item No.
Form-A-Gasket #2 Gasket Maker	Slow Dry Flexible Cure	Black	11 oz	-65 to 400°F	24 hr	Permatex	80011	2GXY1
	Instant Sealing Oil-Resistant	Black	190 mL	-75 to 500°F	24 hr	Loctite	743913	1TDX3
Gasket Sealant	Silicone	Copper	300 mL	700°F	24 hr	Vibra-Tite	99330	49CJ43
		Gray	300 mL	500°F	24 hr	Vibra-Tite	99330	49CE92
Gasket Sealant, Low-VOC	Oil-Resistant	Black	2.8 oz	-40 to 400°F	24 hr	DAP	00754	3WEZ5
Gasket Sealant, Solvent-Based	Slow Dry Flexible Cure	Black	7 oz	-65F to 400°F	Remains Tacky	Loctite	198819	2EMY3
		Red	3 oz	-70 to 650°F	24 hr	Pro Seal	80726	1FBH5
	High Temp. Sensor-Safe	Red	8 oz	-70 to 650°F	24 hr	Pro Seal	80729	3HHH6
		Red	11.1 oz	-80 to 700°F	24 hr	Pro Seal	80728	1FBH9
RTV Silicone Gasket Maker, Low-VOC	Oil and Water-Resistant Noncorrosive	Gray	70 mL	-75 to 625°F	24 hr	Loctite	135275	2PAC7
		Black	8 oz	-75 to 500°F	24 hr	Pro Seal	80049	3HHH5
RTV Silicone Sealant	Oil-Resistant	Black	11.1 oz	-75 to 500°F	24 hr	Pro Seal	80047	1FBH8
		Red	11 oz	-65 to 650°F	24 hr	Permatex	81409	2GXZ1
	High Temp. Increased Oil Resistance Multipurpose	Black	3.35 oz	-65 to 400°F	24 hr	Permatex	82180	2GXZ4
		Black	10 oz	400°F	24 hr	White Lightning	W11125010	48XW77
RTV Silicone Sealant, Low-VOC	Waterproof	Clear	3 oz	-75 to 500°F	24 hr	Pro Seal	80066	1FBH7
		Clear	11.1 oz	-75 to 500°F	24 hr	Pro Seal	80067	1FBJ1
RTV Silicone Sealant, Superflex®, Low-VOC	Shrink-Resistant for Precut Gaskets	Blue	80 mL	-65 to 500°F	24 hr	Loctite	270642	5E220
		Blue	300 mL	-65 to 500°F	24 hr	Loctite	270639	5E221
RTV Silicone Sealant, Superflex RTV	General Purpose	Clear	80 mL	-65 to 450°F	24 hr	Loctite	160809	3KMY7
		Clear	190 mL	-65 to 450°F	24 hr	Loctite	743915	3KNK3
RTV Silicone Sealant, Superflex RTV, 595	General Purpose	Clear	300 mL	-65 to 450°F	24 hr	Loctite	193999	3KMY8
		Black	10.3 oz	-62 to -350°F	24 hr	Surebond	SB-160 T BL	48LR95
RTV Silicone Sealant, Thread & Gasket, Low-VOC	Acetoxy Cure	Clear	5 gal	-62 to -350°F	24 hr	Surebond	SB-160 P CL	48LR96
		Gray	10.3 oz	-62 to -350°F	24 hr	Surebond	SB-160 T AL	48LR93
RTV Silicone Sealant, Ultra Black®, Low-VOC	Oil-Resistant	Black	3 oz	-75 to 500°F	24 hr	Pro Seal	80046	1FBH4



## Gasket/Paint Remover

Solvent-based cleaner 5YK56 removes baked-on fiber gaskets, gasket adhesives, and sealants. Excellent on paint and varnish. Contains no methylene chloride. Blistered paint can be scraped off or flushed away with water. Use on brick, tile, steel, brass, chrome, porcelain, and other surfaces.



Description	Mfr. Model	Item No.
Gasket Remover	03017	5YK56