



**A.**  
**Weldwood Nonflammable**  
2NJ92



**I.**  
**Pliobond 25**  
40P231



**J.**  
**3M Fastbond 30-NF**  
3XH48



**L.**  
**Loctite MR 5414**  
12Z248



**P.**  
**Weldwood Multipurpose**  
2PE38



Weldwood®



**PLIOBOND® 25**  
VOC COMPLIANT  
Special Purpose Contact Adhesive



## Contact Construction Adhesives

### CONTACT CEMENTS

**A. Weldwood Nonflammable**—High solids polychloroprene-based, waterborne contact adhesive.

**B. Weldwood Original**—A neoprene rubber that forms a permanent bond. For use with all laminate products. Adheres to wood, masonry, and most metals with no clamping required. High heat resistance.

**C. Weldwood Bottled**—Strong cement bonds on contact.

**D. Weldwood Gel**—Easy-to-use gel does not drip. No-mess formula is ideal for vertical and overhead surfaces. Easy spread for excellent coverage.

**E. DAP Landau Top & Trim High Heat-Resistant**—Automotive interior cement adheres headliners, fabric, and other materials during refurbishment. Apply with hot or cold spray equipment.

**F. Acrylic Contact Cement**—Solvent-based single-component adhesive remains flexible after cure. Dries clear to light yellow in 30 min. Full cure in 24 hr. Use on tile, rubber, wood, metal, laminates, and most plastics.

**G. 3M Neoprene Contact Adhesive 10**—Air-drying neoprene adhesive bonds immediately and permanently upon contact pressure without clamping or texturizing.

**H. 3M Neoprene High-Performance Contact Adhesive 1357**—Neoprene-based brush- or spray-coat adhesive bonds metal, wood, rubber (except EPDM), urethane foam, acrylic, and ABS. Meet Fed. Spec. MMM-A-121. 5E127 and 5E130 also meet MIL-A-21366A.

**I. Pliobond 25/35 Nitrile Special Purpose Adhesive**—All-purpose thermosetting contact adhesives have pigment-reinforced synthetic rubber and synthetic plastic resin solids; provide a permanent bond that won't get brittle with age.

**J. 3M Fastbond Contact Adhesive 30-NF**—High water-dispersed sprayable contact adhesive for high immediate bond strength and long bonding range. Green adhesive dries to green. Neutral dries to clear. Nonflammable in wet state. Post-formable and heat resistant.

### K. 3M Fastbond Pressure Sensitive Adhesive 4224NF

Water-based carpet adhesive is plasticizer resistant and has an aggressive tack. Repositionable for adhering carpet matting tiles to the floor. For use with glass, paper, steel, galvanized steel, bare and clad aluminum, fabric, and foam.

**L. Loctite MR 5414 Black Contact Adhesive**—Professional, solvent-based adhesive with neoprene blends in with black-colored fabric, rubber, weatherstripping, and other porous materials. Withstands temperature extremes and is resistant to gasoline, kerosene, and other solvents. Fast drying and waterproof. Allows repositioning of the parts after initial contact.

### FLOORING ADHESIVES

**M. DAP 4000 Subfloor VOC, Subfloor and Deck**—Bonds wet, frozen, and treated lumber.

**N. DAP 7000 Subfloor and Deck**—Solvent-based formula reduces nailing requirements, floor squeaks, and nail pops. Easy gunning.

**O. DAP 4000 Subfloor and Deck**—Forms a permanent bond on wet, frozen, and treated lumber. Reduces nailing requirements.

**P. Weldwood Multipurpose**—Trowel-grade adhesive bonds many types of floor coverings. Formula provides greater shrink resistance and allows for easy repositioning during installation. Water-resistant, low-odor adhesive is nonflammable and cleans up easily with water. Ideal for Interior use.

**Q. Weldwood Sheet Floor**—Trowel-grade, latex-based formula is for installing synthetic, felt-backed resilient sheet goods.

**R. Weldwood Ceramic Tile**—Trowel-grade, latex-based adhesive for installing ceramic and mosaic tile on floors, walls, and countertops.

**S. Weldwood Wood Floor**—High solids, trowel-grade synthetic adhesive for installation of prefinished wood flooring.

Key	Description	VOC Levels Meet SCAQMD Requirements	Size	Brand	Item No.
<b>Contact Cements</b>					
A	Weldwood Nonflammable	Meets SCAQMD Requirements	1 qt.	DAP	2NJ92
		Meets SCAQMD Requirements	1 gal.	DAP	4UK99
B	Weldwood Original	No	1 qt.	DAP	5E094
C	Weldwood Bottled	No	1 gal.	DAP	5E095
D	Weldwood Gel	No	3 oz.	DAP	5E096
		No	1 qt.	DAP	10L520
E	DAP Landau Top & Trim High Heat Resistant	No	1 gal.	DAP	29RU98
		No	5 gal.	DAP	29RU99
		No	5 gal.	DAP	29RV01
F	Acrylic Contact Cement	No	1 oz.	Super Glue	3EHR7
G	3M Neoprene 10	Does Not Contain Methylene Chloride	1 qt.	3M	2RU2F
		Does Not Contain Methylene Chloride	5 oz.	3M	5E127
H	3M Neoprene High Performance 1357	Does Not Contain Methylene Chloride	1 pt. Can	3M	2RU3F
		Does Not Contain Methylene Chloride	1 qt.	3M	5E130
		No	1 qt.	Pliobond	40P231
		No	1 gal.	Pliobond	40P232
I	Pliobond 25, Special Purpose Adhesive, 25LV	No	1/2 pt.	Pliobond	40P233
		No	3 oz.	Pliobond	40P234
		No	1 qt.	Pliobond	40P235
		No	1 gal.	Pliobond	40P236
		No	1/2 pt.	Pliobond	40P237
		Does Not Contain Methylene Chloride, Meets SCAQMD Requirements	1 qt.	3M	3XH48 †
J	3M Fastbond 30-NF, Green	Does Not Contain Methylene Chloride, Meets SCAQMD Requirements	5 gal.	3M	2JBJ3 †
		Does Not Contain Methylene Chloride, Meets SCAQMD Requirements	1 qt.	3M	3XH47 †
		Does Not Contain Methylene Chloride, Meets SCAQMD Requirements	1 gal.	3M	2JBR1 †
		Does Not Contain Methylene Chloride, Meets SCAQMD Requirements	5 gal.	3M	2JBL8 †
K	3M Fastbond Contact Cement 85780	Does Not Contain Methylene Chloride	5 gal.	3M	2JCC8
L	Loctite MR 5414 Contact Cement	No	5 fl. oz.	Loctite	12Z248
<b>Flooring Adhesives</b>					
M	DAP 4000 Subfloor VOC, Subfloor and Deck	Meets SCAQMD Requirements	10.3 oz	DAP	2PE27
		Meets SCAQMD Requirements	28 oz	DAP	2PE28
N	DAP 7000 Subfloor and Deck	No	28 oz	DAP	2KVJ3
O	DAP 4000 Construction Adhesive	No	10.3 oz	DAP	2KVJ7
		No	28 oz	DAP	2KVJ8
P	Weldwood Multipurpose	No	1 gal	DAP	2PE38 † ‡
		No	1 qt.	DAP	48TR38
Q	Weldwood Sheet Floor	Meets SCAQMD Requirements	1 gal	DAP	2PE45 † ‡
R	Weldwood Ceramic Tile	No	1 gal	DAP	2PE47 † ‡
S	Weldwood Wood Floor	No	1 gal	DAP	2PE43 † ‡

† Nonflammable. ‡ Water-resistant.