





Mitering 446N88



Mitering 42W923



Non-Mitering 55KM81



Semi-Automatic Horizontal Band Saws

A tool head on these saws automatically cuts metal after the operator manually positions and clamps the workpiece in place. Semi-automatic saws help prevent fatigue and speed operations when the same cut is made repeatedly. These saws are used in small production facilities where similar materials are cut and settings don't need to be changed regularly.

Rectangular Cutting Capacity Mitering Band Saws	Round Cutting Capacity	SFPM Range	Miter Angle Range	Current	Phase	Brand	ltem No.
110V AC, 120V AC							
7 in x 12 in	7 in	85 to 235	45° Right	13.8 A	1	Dake Corporation	40F055
9 in x 12 in	9 in	98 to 328	45° Right	16.0 A	1	Dake Corporation	40F056
115/230V AC	5 111	30 10 320	40 Hight	10.0 A			401 000
2 in x 6 ³ / ₄ in, 5 in x 6 in	5 in	80 to 200	45°, 90°	_	1	Jet	42W915
10 in x 14 in. 2 in x 16 in	10 in	100 to 350	45°, 90°	18.0/9.0 A	1	Jet	3WRN8
120/240V AC	TUTI	100 10 330	45,50	10.0/3.0 A		JEL	3 111110
7 in x 12 in	7 in	86 to 260	0°	12/6	1	Dayton	21C004
7 in x 8 in	7 in	150 to 255	0°	14.0/7.0 A	1	Dayton	21UM99
8 in x 12 in	8 in	150 to 255	0° to 45°	14.0/7.0 A	1	Dayton	48WE31
120V AC	0 111	100 10 200	0 10 45	14.0/1.0 A	1	Dayton	4011231
5 in x 6 in	6 in	114 to 262	0° to 45°	20.0 A	1	Dake Corporation	480Z97
7 ¾ in x 3 in	6 ½ in	114 to 262	0° to 60° Right	20.0 A	1	Dake Corporation	400257
220V AC	0 72 111	114 10 202	0 to 00 might	20.0 A		Dake Guipulation	457230
10 %16 in x 4 5/16 in	8 % in	66 to 280	45° Left to 60° Right		1	Baileigh Industrial	31XU48
10 %16 in x 11 13/16 in	10 1/4 in	66 to 328	45 LEILLOOU RIGHT	17.0 A	3	Sharp	446N88
10 1/2 in x 7 3/4 in	10 % III	115 to 230	45° Left to 60° Right		3	Dake Corporation	4401000
13 ¹³ / ₁₆ in x 8 ¹¹ / ₁₆ in	10 % in	66 to 280	45° Left to 60° Right		1	Baileigh Industrial	31XU53
13 % in x 12 in	12 in	66 to 328	AS LEILIUOU RIGIIL	17.0 A	3		446N89
	12 in 13 in				3	Sharp Bailaigh Industrial	31XU42
13 in x 18 in		60 to 306	45° Left to 60° Right			Baileigh Industrial	
13 in x 18 % in	13 in	82 to 270	0° to 45°	_	3	Baileigh Industrial	31XU52
14 3/16 in x 22 in	18 ½ in	66 to 279	0°	17.0 4	3	Baileigh Industrial	31XU54
15 in x 12 %16 in	12 % in	66 to 328		17.0 A	3	Sharp	446N90
15 in x 24 in	18 ¼ in	106 to 317	65° Left to 65° Right	—	3	Baileigh Industrial	31XU45
230/460V AC							
10 in x 17 in	10 in	50 to 275	60° Left to 45° Right		3	Jet	53ZC52
10 in x 17 in	10 in	53 to 275	45° Left to 60° Right		3	Jet Elite	20UT89
10 in x 17 in	10 in	53 to 275	45° Left to 60° Right	_	3	Jet Elite	20UT90
10 in x 14 in	10 in	82 to 330	45°, 90°		3	Jet	42W934
10 in x 14 in, 2 in x 16 in	10 in	100 to 350	45°, 90°	15.0 A	3	Jet	3WRN2
10 in x 21 in, 13 in x 19 ir	ı 13 in	80 to 260	45°, 90°	—	3	Jet	42W914
230V AC							
7 ¹³ / ₁₆ in x 6 in	7 in	157 to 314	45° ,60° ,90°	_	3	Jet	42W929
7 ¾ in x 15 ¾ in	12 in	125 to 252	45° Left to 60° Right		3	Dayton	499F62
8 ¾ in x 7 in	8 ¾ in	137 to 275	45° ,60° ,90°	_	3	Jet	42W930
8 ½ in x 13 in	10 ¼ in	125 to 255	0° to 60°	7.0	3	Dayton	499F60
9 in x 16 in	9 in	80 to 250	0° to 45°	4.7	1	Dayton	499F31
10 in x 17 in	10 in	50 to 275	45°, 90°	13.5 A	3	Jet	53ZC54
10 in x 18 in	10 in	50 to 275	60° Left to 45° Right	13.5 A	1	Jet	53ZC53
10 in x 14 in	10 in	82 to 330	45°, 90°	_	1	Jet	42W933
10 in x 16 in	10 in	95 to 350	0° to 60°	6.2	3	Dayton	499F33
10 in x 16 in	10 in	95 to 350	0° to 60°	12.0	1	Dayton	499F32
12 in x 20 in	12 in	82 to 262	45°, 90°	_	3	Jet	42W924
12 in x 18 ½ in	12 in	85 to 370	0° to 45°	8.6	3	Dayton	499F36
460V AC							
7 % in x 15 ¾ in	12 in	125 to 252	45° Left to 60° Right	4.0	3	Dayton	499F63
8 1/2 in x 13 in	10 ¼ in	125 to 255	45° Left to 60° Right		3	Dayton	499F61
10 in x 14 in, 2 in x 16 in	10 in	100 to 350	45°.90°	_	3	Jet	42W923
12 in x 20 in	12 in	82 to 262	45°, 90°	_	3	Jet	42W925
12 in x 18 ½ in	12 in	85 to 370	0° to 45°	4.3	3	Dayton	499F37
Non-Mitering Band Saw					· · · ·	.,	
220V AC							
29 ¾ in x 27 ½ in	27 ½ in	65 to 279	0°	_	3	Baileigh Industrial	55KM81
43.3 in x 43.3 in	43 1/8 in	66 to 279	0°		3	Baileigh Industrial	31XU37



Mitering 446N85



Automatic Horizontal Band Saws

SFPM

Range

89 to 256

85 to 330 65 to 330

50 to 330 66 to 279

70 to 330

Miter Angle Range

0° to 45°

45° Left to 60° Right 0° to 45° Right

0°

3-phase

Cutting Capacity Mitering Band Saws 220V AC

 2200 AC
 13 in x 18 in
 13 ii

 13 in x 18 in
 13 ii
 14

 460V AC
 12 in x 17 ¾ in
 13 ii

 15 in x 24 in
 13 ii
 15 in x 24 in
 18 ii

 Non-Mittering Band Saws
 220V AC
 11 in y 40 in
 14 in

Programmable, automatic saws feed and cut material based on settings determined by the operator. This speeds

13 in

13 in 18 in

10 in 31 ½ in

10 in

Rectangular Round Cutting utting Capacity Capacity

processing and helps alleviate operator fatigue. Automatic band saws are used in production applications when cuts are repeated.

Brand

Marve Marve

Marvel

Baileigh Industrial 31XU40

Sharp 446N85 Baileigh Industrial 31XU58

Current

6.4 A 10.2 A

10.0 A

19.6A

Item

No.

53RU29 419J31

55EM59

0	
i I	BAILEGOT
Non-Mitering 31XU58	



8 in x 11 1/4 Find even MORE on Grainger.com®

11 in x 10 in 31 ½ in x 31 ½ in 230V AC

1-800-GRAINGER (472-4643)