

1-800-GRAINGER (472-4643)



Gorilla Glue

▪ Full cure: 24 hr.

Dries White and All-Purpose Glue—Bonds wood, stone, metal, ceramic, and more. White dries faster. Waterproof.

▪ Temp. range: -40° to 212°F

Super Glue—Bonds to most common building materials. Anticlog cap with a metal pin inside ensures an airtight seal for maximum reusability.

▪ Temp. range: -65° to 220°F

Wood Glue—Bonds wood-to-wood without leaving an orange afterglow. FDA approved for indirect food contact.

▪ Temp. range: 0° to 150°F



Item	Characteristics	Color	Clamp Time	Size	Mfr. Model	Item No.
All Purpose Glue	Extremely Strong Bonding Power	Brown	1 to 2 hr	2 oz.	5000201	1TLZ9
		Brown	1 to 2 hr	4 oz.	5000413	1TMA1
		Brown	1 to 2 hr	8 oz.	5000802	1TMA2
		Brown	1 to 2 hr	18 oz.	5001803	1TMA3
		Brown	1 to 2 hr	36 oz.	5003601	1TMA4
Dries White Glue	and Dries White, Paintable, Sandable, Stainable, Waterproof, Weatherproof	White	30 to 60 min	2 oz.	5201208	2KKF2
Dries White Glue Pen		White	30 to 60 min	0.75 oz.	5201111	2KKF3
Glue	Dries Clear, Non Foaming, Strong	Clear	1 to 2 hr	1.75 oz.	4500102	453U44
		Clear	1 to 2 hr	3.75 oz.	4537502	453U45
Super Glue	Anti-Clog Tip, Impact Resistant, Polyurethane Adhesive, Rubber Toughened	Clear	10 to 45 sec.	(2) 3g Tubes	7800102	4GZK5
	Anti-Clog Cap, Easy to Use, Impact Resistant, Multipurpose, No Run	Clear	10 to 45 sec.	0.53 oz.	7600101	30WM02
	Rubber Toughened for Impact Strength	Clear	10 to 45 sec.	1 lb.	78007	16V096
Wood Glue	Anti-Clog Tip, Impact Resistant, Polyurethane Adhesive, Rubber Toughened	Clear	10 to 45 sec.	15g	7805002	4GZK6
	Dries Natural Color, FDA Approved For Direct Food Contact, Non-Toxic, PVA, Solvent Resistant, Water Clean-Up, Water-Resistant	Cream	20 to 30 min	8 oz.	6200002	4GZK3
		Cream	20 to 30 min	18 oz.	6205001	4GZK4



Wood Glues

DAP WELDWOOD

Carpenter's Glue—Sets fast, grips tight, and sands easily. Solvent resistant. Nontoxic.

TITEBOND III ULTIMATE WOOD GLUE

Waterproof formula meets ANSI/HPVA Type I water-resistance specification. Has longer open assembly time and lower application temperature. Sands easily. Interior/exterior.

TITEBOND II

Premium and Extend Wood Glue—Meet ANSI Type II water-resistance specification. 3KRU6 and 3KRU7 have a longer set time. Interior/exterior.

Wood Glue—Great for general woodworking with porous and semiporous materials. ANSI Type II.

TITEBOND ORIGINAL WOOD GLUE

Aliphatic-resin glue sets quickly to reduce clamp time. Resists heat, solvents, and mildew. 3KRU4 and 4EML7 have a longer set time.

TITEBOND

Quick & Thick, No Run/No Drip—Glue dries twice as fast and three times as thick as traditional PVAs. Bonds to multiple surfaces.

Polyurethane Wood Glue—Combines a long 20-min. working time with a short 45-min. clamping time.

Waterproof formula is excellent for wood to wood, metals, ceramics, most plastics—porous and nonporous materials. ANSI Type I and Type II.

Type	Color	Begins to Harden	Size	Item No.
DAP® Weldwood Carpenter's Wood Glue				
Aliphatic Resin	Yellow	10 min.	1 qt.	5UFR4
		—	1 gal.	5E104
Titebond® III Ultimate Wood Glue				
Water-Resistant	Tan	10 Min.	4 oz.	3KZJ4 *
		10 min.	8 oz.	1FCC1 *
		10 min.	16 oz.	1FCC2 *
		10 min.	1 gal.	1FCC3 *
Titebond® II Premium Wood Glue				
Exterior	Honey Cream	5 Min.	4 oz.	3KZJ6 *
		5 min.	8 oz.	3KRU5 *
		5 min.	16 oz.	1FCC4 *
		5 min.	1 gal.	1FCC5 *
Titebond® II Extended Wood Glue				
Slow Set	Cream	15 min.	16 oz.	3KRU6
		15 min.	1 gal.	3KRU7
Titebond® II Wood Glue				
Dark	Brown	5 min.	8 oz.	4EMP2
		5 min.	16 oz.	3KRU8
		5 min.	1 gal.	4EMP3
		5 min.	1 gal.	1FCC8
Interior	White	5 min.	5 gal.	3KRU2
		Titebond® II Original Wood Glue		
Heat- and Solvent-Resistant	Yellow	5 min.	4 oz.	4EML7
		5 min.	8 oz.	3KRU3
		5 min.	16 oz.	1FCC6
		5 min.	1 gal.	1FCC7
Titebond® II Original Extended Wood Glue				
Slow Set	Yellow	15 min.	16 oz.	3KRU4
		15 min.	1 gal.	4EML8
Titebond® Quick & Thick, No Run/No Drip				
Quick & Thick No Run, No Drip	Beige	3 to 5 min.	8 oz.	3KRU9
		3 to 5 min.	16 oz.	4EMP4
Titebond® Polyurethane Wood Glue				
Polyurethane	Brown	3 to 25 min.	4 oz.	4EML9
		3 to 25 min.	8 oz.	3KRV1
		3 to 25 min.	12 oz.	4EMN1

* FDA approved for indirect food contact (cutting board).

