

Color-coded hand pads combine the durability and aggressiveness of diamond on a high-strength, flexible backing. Single-sided; conform to shapes and contours. Well-suited for quick finishing of ceramic tile to get a smooth edge before grouting. Can be used on many other surfaces to smooth edge chips, reface edges, or polish dies and molds. 1RDJ5 is an assortment that contains 1 of

Color

White

Blue Yellow

Black Red

Green

Black, Blue, Green, Red, White, Yellow



Item

Nn

1RDJ3 1RDJ4 1RDJ2 1RDH9 1RDJ1

Mfr. Model

66260306363 66260306364 66260305852 66260306361 66260306362

66260306360 1RDH8

66260307720 1RDJ5



1RDJ5




General Purpose

1RDV8



Sealer Sanding 3WK97





Corner Drywall 1PW39



Diamond Hand Pads

each type of pad.

Hand Pads

Grade

Ultra Fine Ultra Fine Super Fine

Medium

Coarse

Assortment Coarse, Fine, Medium,

Super Fine, Ultra Fine

Durable coated foam lasts up to 5 times longer than sandpaper and resists tearing. Can be used wet or dry, and can be washed and reused multiple times.

Grit

800

1500 400

120

120, 1500, 200, 400, 60, 800


General Purpose—Small, flexible sponges are coated on 2 sides and can be used on most materials. Silicon carbide abrasive.

Sealer Sanding—Designed for hand sanding primers and sealers between coats on furniture and cabinets. Premium silicon carbide abrasive. Coated on 2 sides.

Profile—Designed for flat surfaces and corners on metal, wood, plastic, or paint. Aluminum oxide abrasive. Coated on 3 sides.

Small Area—The ultra sharp aluminum oxide grain offers faster cut and longer life for small area paint and drywall repair. Coated on 2 sides.

Dual-Angle and Angled—Extra-firm sponges are coated with aluminum oxide abrasive on 4 sides for sanding inside corners and crevices of drvwall compound.



w

2 1/8 in 2 1/8 in

2 1⁄8 in

NORTON

3 1/2 in 3 1/2 in

3 1/2 in

3 ½ in

Soft Touch-Superior flexibility for hand sanding or finishing flat, curved, contoured, and hard-to-reach areas. Aluminum oxide abrasive. Coated on 1 side.

Corner Drywall-2 sides have aluminum oxide abrasive, providing dual sanding action for near-perfect inside corners on drywall. Extrafirm sponges are designed for sanding drywall corners, but can also be used on a variety of other materials.

Softback-Coated on one side with an aluminum oxide grit that is excellent for automotive applications, this flexible sponge is effective for hard-to-reach areas like headlight openings and door jambs. The soft foam backing allows comfortable hand sanding.

Description	L	w	Thickness	Grit	Grade	Mfr. Model	ltem No.	Pkg. Qty.
Norton								
General	4 in	2.75 in	1 in	36,80	Medium/Coarse	07660749503	1RDV8	1
Purpose	4 in	2.75 in	1 in	120,80	Fine/Medium	07660749502	1RDW1	1
Sealer Sanding	4.75 in	3.75 in	0.5 in	36	Extra Coarse	63642502538	2KNA7	1
	4.75 in	3.75 in	0.5 in	60	Coarse	63642552870	3WK98	1
	4.75 in	3.75 in	0.5 in	100	Medium	63642552869	3WK97	1
	4.75 in	3.75 in	0.5 in	220	Very Fine	63642552868	3WK96	1
Profile	4 in	2.75 in	0.5 in	100	Medium	63642536313	2KNA9	1
Small Area	4.5 in	2.687 in	1 in	60	Coarse	07660782071	45GF45	1
	4.5 in	2.687 in	1 in	180	Fine	07660782073	45GF46	1
Dual-Angle	4.875 in	2.875 in	1 in	_	Medium/Coarse	07660700936	1PW28	1
	4.875 in	2.875 in	1 in	_	Fine/Medium	07660700935	1PW27	1
Angled	4.875 in	2.875 in	1 in	120	Fine	07660702284	33GN50	24
	4.875 in	2.875 in	1 in	80	Medium	07660702285	33GN51	24
Contour	5.5 in	4.5 in	0.187 in	150	Fine	07660700938	2DZY1	2
	5.5 in	4.5 in	0.187 in	100	Medium	07660700939	2DZY2	2
	5.5 in	4.5 in	0.187 in	220	Extra Fine	07660700937	2DZY3	2
Soft Touch	5.5 in	4.5 in	0.187 in	60	Medium	07660703074	1RDW7	20
	5.5 in	4.5 in	0.187 in	100	Fine	07660703075	1RDW8	20
	5.5 in	4.5 in	0.187 in	180	Super Fine	07660703076	1RDW9	20
	5.5 in	4.5 in	0.187 in	220	Ultra Fine	07660703077	1RDX1	20
	5.5 in	4.5 in	0.187 in	280	Micro Fine	07660703078	1RDX2	20
Corner Drywall	7 in	4.5 in	3.75 in	80	Medium	07660701715	1PW39	1
3M								
Softback	5.5 in	4.5 in	0.25 in	500, 600	Super Fine	02602	2BAE1	120




Soft Touch **1RDW8**

2254

Foam Sanding Pads

- A275 aluminum oxide grain with No-Fil coating
- = 41/2" W x 82' L roll
- 178 (5½" L) sheets per roll

Water-resistant sheets are excellent for fine sanding water-based primers, topcoats, wood, metal and composite, especially on rounded edges, contours, and curves. Can be used moist to provide a uniform finish that minimizes scratching.



Find even MORE on Grainger.com®

1-800-GRAINGER (472-4643)

