



22mm Illuminated Push Buttons—Complete Units

■ NEMA rated 1, 2, 3,

■ No-notch mounting

►CHOOSE:

Momentary operation 4, 4X, 12, and 13



installation. UL Listed, CSA Certified, and CE Certified. Meet IEC standards. ► CHOOSE: Basic

Type of Operator	Lamp Module Voltage	Color
Round Button; Round Guarded Button	24V AC/DC; 120V AC	Red; Green; Blue; Yellow; White
22mm Nonillumir Ruttons—Comple		

►CHOOSE:

Schneider Electric

Material Metal



- No-notch mounting

■ NEMA rated 1, 2, 3, 4, 4X, 12, and 13

Come complete with contact block, ready for easy installation. UL Listed, CSA Certified, and CE Certified. Meet IEC standards.

► CHOOSE:	►CHOOSE:	►CHOOSE:	Contact		Item
Type of Operator	Head Material	Color	Form	Legend	No.
Flush Button	Plastic, Metal	Black, Green, Yellow, Blue	1NO	No Legend	H7077
Flush Button	Plastic, Metal	Black, Green, Red, Yellow	1NO/1NC	No Legend	H7079
Flush Button	Plastic, Metal	Green	1NO	1	H7075
Flush Button	Plastic, Metal	Red	1NC	0	H7075
Flush Button, Extended Button	Plastic, Metal	Red	1NC	No Legend	H7076
40mm Mushroom Head	Plastic	Black	1NO	No Legend	6HL41
40mm Mushroom Head	Metal	Black	1NO	No Legend	6HK58





Chrome/Full Guard

Plastic/Full Guard

22mm Selector Switches—Complete Units No-notch mounting

Complete with contact block for fast, easy installation. UL Listed,

■ NEMA rated 1, 2, 3, 4, 4X, 12, and 13 CSA Certified, and CE Certified. Meet IEC standards.

PLASTIC | METAL Item

	Type of	ney	GUIIIaGI	SWILLII	SWILLII	SWILLII		III	III
Position	Operator	Removal	Form	@ Pos. A	@ Pos. B	@ Pos. C	IP Rating	No.	No.
Maintained	/ Momentary								
2	Keyed	Left	1NO	0	X	_	65	_	6HK66
Maintained	/ Maintained								
2	Keyed	Left	1NO	0	Х	_	65	2UZC7	6HK63
2	Keyed	Left/Right	1NO	0	X		65	6HL48	6HK65
2	Lever	No Key	1NO	0	X	_	65	6HL42	6HK59
2	Extended Lever	No Key	1NO	0	Х	_	65	2UZC8	6HK67
Momentary /	/ Maintained / Mor	nentary							
3	Lever	No Key	2N0	X0	00	OX	65	2UZD1	6HK61
3	Extended Lever	No Key	2N0	X0	00	OX	65	2UZD2	6HK69
Maintained,	/ Maintained / Mai	ntained							
3	Keyed	Any Position	2NO	X0	00	OX	65	6HL45	6HK62
3	Keyed	Center	2NO	X0	00	0X	65	6HL47	6HK64
3	Lever	No Key	2NO	X0	00	OX	65	2UZD3	6HK60
3	Extended Lever	No Key	2NO	X0	00	OX	65	6HL51	6HK68
Selector Sw									
	For Use	With Schneider	XB4 and XB	5 Series Sele	ctor Switches	S			6HZ23

Standard

Keyed



Schneider Electric

22mm Chrome Joystick

Controllers—Complete Units ■ No-notch mounting 1-step, 1NO contact per direction. Complete with ■ NEMA rated 1, 2, 3, contact block for fast, easy installation. UL Listed, 4, 4X, 12, and 13 CSA Certified, and CE Certified. Meet IEC standards.

6HM22

Action	No. of Directions	Bezel	ltem No.	
	2	Chromium Plated Metal	6HM17	
Momentary	4	Plastic	6HM22	
,	4	Chromium Plated Metal	6HM18	
	2	Plastic	6HM19	
Maintained	2	Chromium Plated Metal	6HM15	
	4	Chromium Plated Metal	6HM16	

Schneider Blectric

22mm LED Pilot **Lights—Complete Units**

■ No-notch mounting

■ NEMA rated 1, 2, 3, 4, 4X, 12, and 13

Come complete with lamp module, ready for easy installation. UL Listed, CSA Certified, and CE Certified. Meet IEC standards.

		PLA	SIIC		WEIAL				
	White	Green	Red	Yellow	White	Green	Red	Yellow	
	Item	Item	Item	Item	Item	Item	Item	Item	
Voltage	No.	No.	No.	No.	No.	No.	No.	No.	
24V AC	2UZC1	2UZC3	2UZC4	2UZC5	6HK91	6HK92	6HK93	6HK94	
110 to 120V AC	2UZC2	6HL81	6HL82	2UZC6	6HK96	6HK97	6HK98	6HK99	
110 to 120 / A0	LULUL	UIILUI	UIILUL	20200	UIIKSU	UIIKJI	UIIKJU	UIIKJJ	

6HK93



Flush



Rase **6HR01**

22mm Illuminated Push Buttons and Incandescent BA9s Modules

■ NEMA rated 1, 2, 3, A complete push button requires an operator, mounting base, contact block, and incandescent 4. 4X. 12. and 13 module. Some lamps sold separately, see page 228. UL Listed, CSA Certified, and CE Certified. DI ACTIC ZDE CEDIFO

		PLASTIC, ZB5 SERIES					CHRUWE, ZB4 SERIES						
Type of		White	Green	Red	Yellow	Blue	White	Green	Red	Yellov	v Blue		
Operator	Action	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item No.	Item N	o. Item No.		
Illuminated Push Button Operators													
Flush Button	Momentary	6HW94	6HW96	6HW98	6HX01	6HX03	6HR55	6HR57	6HR59	6HR6	1 6HR63		
Extended Button	Momentary	6HW84	6HW86	6HW88	_		6HR45	6HR47	6HR48	6HR5	0 6HR52		
	•					1	1NO	1NC	2N	n	1NO/1NC		
	Descriptio	n			Voltage		Item No.	Item N			tem No.		
Mounting Base, C			lescent Mo	dule, For U		stic, ZB5	Series Opera						
Lamp Module and	d Contact Block	, Includes (SV Lamp		120VAC						6HW38		
Lamp Module and	Contact Block	. Includes	SV Lamp		240VAC		_				6HW39		
Lamp Module and	Contact Block	(Lamp Red	quired)		Max. 250V		6HW40	6HW4	1 6HW	42	6HW43		
Mounting Base, Contact Block, and Incandescent Module, For Use with Chrome, ZB4 Series Operators													
Lamp Module and				•	120VAC		6HP98				6HP99		
Lamp Module and	Contact Block	(Lamp Red	mired)		Max 250V		6HR01	6HRO	2 6HR	N3	6HR04		

Schneider **Electric**

Item

No. H6941

Schneider









Rase 6HW41