



Looking for additional Dayton components? See Grainger.com for even more Illuminated and Nonilluminated Push Buttons, Selector Switches, LED Modules, and Contact Blocks.



30G082

H7743

30G154

30G294



22mm Illuminated Push Buttons—Complete Units



- LED
- 1NO/1NC contact
- NEMA 1, 2, 3, 4, 4X, 12, and 13 rated

Feature flush head and momentary action. Chrome construction. UL Listed. CSA and CE Certified.

►CHOOSE: Lamp Module Voltage
24V AC/DC, 125V AC/DC

►CHOOSE: Color
Green, Red, Yellow

Item No.
H6943

22mm Nonilluminated Push Buttons—Complete Units



- Momentary action
- NEMA 1, 2, 3, 4, 4X, 12, and 13 rated

Round shape. UL Listed. CSA and CE Certified.



30G234

Type of Operator	Contact Form	Legend	PLASTIC			CHROME DIE CAST ALUMINUM			
			Black Item No.	Green Item No.	Red Item No.	Black Item No.	Green Item No.	Red Item No.	Yellow Item No.
Flush Button	1NO/1NC	No Legend	30G232	30G233	30G234	30G236	30G237	30G238	—
Flush Button	1NO	No Legend	30G224	30G225	—	30G227	30G228	—	—
Flush Button	1NO	—	—	—	—	—	30G240	—	—
Flush Button	1NC	No Legend	—	—	30G230	—	—	—	—
Flush Booted Button	1NO	No Legend	32UK43	—	—	30G242	30G243	—	30G244
Extended Button 40mm	1NC	No Legend	—	—	32UK48	—	—	30G246	—
Mushroom Head	1NO	No Legend	—	32UK29	—	30G247	32UK32	32UK34	—

22mm Selector Switches—Complete Units



- 10A
- NEMA 1, 2, 3, 4 and 4X rated

Chrome construction. Black Lever. UL Listed. CSA and CE Certified.



30G262

Position	Action	Type of Operator	Key Removal	Contact Form	PLASTIC Item No.	METAL Item No.
2	Maintained / Momentary	Keved	Left	1NO	—	30G259
2	Maintained / Maintained	Keved	Left	1NO	—	30G259
2	Maintained / Maintained	Keved	Left/Right	1NO	30G270	30G271
2	Maintained / Maintained	Lever	No Key	1NO	30G264	30G265
2	Maintained / Maintained	Lever	No Key	1NO	30G266	30G267
3	Momentary / Maintained / Momentary	Extended Lever	No Key	2NO	30G260	30G261
3	Momentary / Maintained / Momentary	Extended Lever	No Key	2NO	30G262	—
3	Maintained / Maintained / Maintained	Keved	Any Position	2NO	—	30G277
3	Maintained / Maintained / Maintained	Keved	Center	2NO	30G278	30G279
3	Maintained / Maintained / Maintained	Lever	No Key	2NO	30G272	30G273
3	Maintained / Maintained / Maintained	Extended Lever	No Key	2NO	30G274	30G275

22mm LED Pilot Lights—Complete Units



- NEMA 1, 2, 3, 4, 4X, 12, and 13 rated

Designed with screw-clamp terminal connection. Round shape. LED lamps provide 10,000 hr. of average life. UL Listed. CSA and CE Certified.



30G209

Voltage	PLASTIC				METAL	
	Green Item No.	Red Item No.	White Item No.	Yellow Item No.	Green Item No.	Red Item No.
24V AC/DC	30G209	30G210	30G208	30G211	30G213	30G214
120V AC	30G217	30G218	30G216	30G219	30G221	30G222

22mm Push-Button Control Stations—Complete Units



- ABS NEMA 4X enclosures
- 600VAC
- Station contact rating: 3A at 240VAC, 6A at 120VAC, 0.27A at 250VDC, 0.55A at 125VDC

Surface-mount stations are 600VAC/DC. Gray enclosures. UL Listed, IEC, CSA and CE Certified. 32W279 is UL Listed, IEC and CSA Certified.



32W267



32W274



32W275



32W278

Action	No. of Operators	Legend	Contact Form	Operator Color	Encl. Material	H	W	D	Item No.
Push Button Control Stations									
Momentary	1	Start	1NO	Black	ABS	1.98 in	2.92 in	2.69 in	32W265
Momentary	1	Stop	1NC	Red	ABS	1.98 in	2.92 in	2.69 in	32W266
Momentary	2	Start/Stop	1NO/1NC	Black/Red	ABS	1.98 in	4.09 in	2.69 in	32W267
Momentary	2	For/Rev	2NO	Black	ABS	1.98 in	4.09 in	2.69 in	32W268
Momentary	3	Open/Stop/Close	2NO/1NC	Black/Red	ABS	1.98 in	5.27 in	2.69 in	32W271
Momentary	3	Forward/Stop/Reverse	2NO/1NC	Black/Red	ABS	1.98 in	5.27 in	2.69 in	32W272
Momentary	3	Up/Stop/Down	2NO/1NC	Black/Red	ABS	1.98 in	5.27 in	2.69 in	32W273
Momentary	1	Stop	1NC	Red	ABS	1.98 in	2.92 in	2.69 in	32W274
Twist-to-Release	1	Twist to Release Arrows	1NC	Red	ABS	1.98 in	2.92 in	2.69 in	32W275
Key Release	1	Emergency Stop	1NC	Red	ABS	1.98 in	2.92 in	2.69 in	32W276
Push / Pull	1	No Legend	1NC	Red	ABS	1.98 in	2.92 in	2.69 in	32W277
Pushbutton Enclosures									
—	1	—	—	—	Plastic	1.98 in	2.68 in	2.91 in	32W279
—	1	—	—	—	Die-Cast Aluminum	2.91 in	2.68 in	2.1 in	32W278
Contact Block									
1NO. For Use With 32W267, 32W268, 32W271, 32W272, 32W273, 32W278, 32W279, Mfr. No. 32W265									32W280
1NC. For Use With 32W267, 32W271, 32W272, 32W273, 32W274, 32W275, 32W276, 32W277, 32W278, 32W279, Mfr. No. 32W266									35V483