



Hand Crank  
3VE31



Hand Crank  
3VE30



Spring Drive  
4NB19



## Arc Welding Cable Reels

Corrosion-resistant powder-coated finish. Hand crank reels include lead wire. Spring drive reels have vibrationproof, self-locking latch and permanently lubricated bearings.

Description	Max. Amps	Overall Length	Overall Width	Overall Height	Mfr. Model	Item No.
<b>Hand Crank Crank, Truck Mount</b>						
Single Reel	300 A	18 in	16.25 in	38 in	T-1460-0	2CAJ6
Double Reel	300 A	18 in	16.25 in	38 in	T-2464-0	3VE31
	300 A	18 in	29 in	19 in	T-2462-0	3VE30
<b>Spring, Bench, Ceiling, Floor, Truck, Wall Mount</b>						
Single Reel	400 A	19 in	14 in	20.25 in	WC7000	4NB19
	400 A	24 in	15.63 in	25.75 in	WC80001	4NB20



## Twin-Line Welding Hose Coupled Assemblies

Welding hose assemblies come with fittings installed on both ends of the hoses and have two hoses: a green hose for carrying oxygen to welding equipment, and a red hose for carrying acetylene to welding equipment. The hoses have oil-resistant covers. The hoses' cover resists flames and oils.

Hose I.D.	Fitting Type	25 ft			Hose Length 50 ft			100 ft		
		Brand	Item No.	Fitting Type	Brand	Item No.	Fitting Type	Brand	Item No.	Fitting Type
3/16 in	UNF x UNF	Continental	22704	UNF x UNF	Continental	62C11	BB x BB	Radnor	31UT33	3/16 in
1/4 in	UNF x UNF	Continental	22705	UNF x UNF	Continental	62C12	BB x BB	Radnor	31UT06	1/4 in
3/8 in	BB x BB	Radnor	31UT52	BB x BB	Radnor	31UT54	BB x BB	Radnor	31UT42	3/8 in
1/2 in	BB x BB	Radnor	31UT44	BB x BB	Radnor	31UT46	BB x BB	Radnor	31UT42	1/2 in
3/4 in	BB x BB	Radnor	31UT28	BB x BB	Radnor	31UT30	BB x BB	Radnor	31UT21	3/4 in
1 in	BB x BB	Radnor	31UT13	UNF x UNF	Continental	4LG87	UNF x UNF	Continental	4LG88	1 in
1 1/2 in	BB x BB	Radnor	31UT45	BB x BB	Radnor	31UT47	BB x BB	Radnor	31UT43	1 1/2 in



33N139



41GR96



## Welding Hand-Crank Reels

■ Max. operating pressure: 200 psi

Reinforced steel construction includes powder-coated finish for corrosion resistance. These low-pressure reels mount on the floor, wall, bench, or on trucks. Reels use Grade R (oxygen and acetylene gas) or Grade T (oxygen and fuels) hoses. They are used with oxygen and acetylene welding hoses in applications where space, weight, and flexibility are important.

Hose Cap.	Swivel Material	Reel Color	Overall Dim.	Brand	Item No.
100 ft (1/4 in I.D.)	Brass	Blue	12 in L x 14 1/2 in W x 13 in H	Coxreels	33N139
150 ft (1/4 in I.D.)	Aluminum	Black	18 in L x 16 1/4 in W x 19 in H	Reelcraft	4NB18
250 ft (1/4 in I.D.)	Aluminum	Red	28 3/8 in L x 21 3/8 in W x 20 1/4 in H	Reelcraft	41GR96



## Welding Spring-Return Hose Reels

■ Max. operating pressure: 200 psi

Reels have an independent dual-swivel design that allows a positive separation of gases with double sealed O-rings to prevent leaks. The dual-swivels are made from aluminum that's hard-coated for wear resistance, and the swivel body and inlet are permanently identified with machined grooves on the gas side to assure proper installation. Reinforced steel construction includes powder-coated finish for corrosion resistance. These low-pressure reels mount on the floor, wall, ceiling, bench, or on trucks, and include an adjustable guide arm.

Hose Cap.	Hose End Configuration	Includes Hose	Swivel Material	Reel Color	Brand	Item No.
<b>Standard Spring-Return Hose Reels</b>						
<b>Hose Grade R</b>						
25 ft (1/4 in ID)	3/16 in F UNF	Yes	Aluminum	Red	Reelcraft	38EE86
50 ft (1/4 in ID)	3/16 in F UNF	Yes	Aluminum	Red	Reelcraft	38EE87
60 ft (1/4 in ID)	3/16 in F UNF	Yes	Brass	Blue	Coxreels	271F18
75 ft (3/8 in ID)	3/16 in F UNF	Yes	Aluminum	Red	Reelcraft	38EE88
<b>Hose Grade T</b>						
50 ft (1/4 in ID)	3/16 in F UNF	Yes	Aluminum	Red	Reelcraft	5PR84
60 ft (1/4 in ID)	3/16 in F UNF	Yes	Aluminum	Red	Reelcraft	38EE89
75 ft (3/8 in ID)	3/16 in F UNF	No	Aluminum	Red	Reelcraft	38L565
100 ft (1/4 in ID)	3/16 in F UNF	Yes	Aluminum	Red	Reelcraft	4NB17
150 ft (1/4 in ID)	3/16 in F UNF	No	Aluminum	Red	Reelcraft	5PG12
200 ft (1/4 in ID)	1/4 in MNPT x 3/16 in F UNF, 3/16 in F UNF x 3/16 in F UNF	Yes	—	Blue	Coxreels	16X587
250 ft (1/4 in ID)	3/16 in F UNF	Yes	Aluminum	Red	Reelcraft	4NB16
<b>Controlled-Retraction Spring-Return Hose Reels</b>						
<b>Hose Grade R</b>						
50 ft (1/4 in ID)	3/16 in F UNF	Yes	Aluminum Black, Red	Reelcraft	56MW57	
<b>Hose Grade T</b>						
50 ft (1/4 in ID)	3/16 in F UNF	Yes	Aluminum Black, Red	Reelcraft	56MW58	



38EE87



16X587



## Torch Kits and Accessories

Kits feature quick-disconnect handles and tips. O-rings are color-coded for quick gas identification. Tips feature swirl combustion for higher target temperatures.

Description	Series	Mfr. Model	Item No.
<b>TurboTorch Torch Tips</b>			
1/8" Tip, 1/2" Soft Solder, 1/4" Silver Braz	A-2	0386-0100	4PU28
3/8" Tip, 1" Soft Solder, 1/2" Silver Braz	A-3	0386-0101	5UX12
1/4" Tip, 1 1/2" Soft Solder, 3/4" Silver Braz	A-5	0386-0102	5UX13
3/16" Tip, 2" Soft Solder, 1" Silver Braz	A-8	0386-0103	5UX14
1/2" Tip, 3" Soft Solder, 1 1/2" Silver Braz	A-11	0386-0104	5UX15
1/2" Tip, 3 1/2" Soft Solder, 2" Silver Braz	A-14	0386-0105	4PU32
3/4" Tip, 6" Soft Solder, 4" Silver Braz	A-32	0386-0106	5GEJ2
<b>Self-Lighting Torch Tips</b>			
1/4" Tip, 1" Soft Solder, 1/2" Silver Solder	PL-3A	0386-0874	5GEJ1
3/8" Tip, 2" Soft Solder, 1" Silver Solder	PL-8A	0386-0819	4PU18
3/8" Tip, 4" Soft Solder, 2" Silver Solder	PL-12A	0386-0820	5GEJ6



5GE90



5UX29

Description	Includes	Mfr Model	Brand	Item No.
<b>Acetylene Torch Kits</b>				
<b>For B Tanks</b>				
Hobbyist, HVAC, Light Fabrication	AH-12 Hose, Gauge Guard	0386-0090	TurboTorch	4PU19
1 1/2 in Soft Solder, 3/4 in Silver Braz	AH-12 Hose	0386-0386	TurboTorch	5UX20
3 in Soft Solder, 1 1/2 in Silver Braz	A-11 Tip, AH-12 Hose	0386-0335	TurboTorch	5UX19
3 1/2" Soft Solder, 2" Silver Braz	AH-12 Hose, Tank Key	0386-0336	TurboTorch	5GEG3
<b>For B Tanks, Self-Lighting</b>				
Hobbyist, HVAC, Light Fabrication	AH-12 Hose	0386-0835	TurboTorch	5GEG1
2 in Soft Solder, 1 in Silver Braz	AH-12 Hose, B Tank Connections, Cylinder Wrench, Gauge Guards	0386-0833	TurboTorch	5UX29
<b>For MC Tanks</b>				
1 1/2" Soft Solder, 3/4" Silver Braz	AH-12 Hose, Tank Key	0386-0384	TurboTorch	5GEG2
2 in Soft Solder, 1 in Silver Braz	AH-12 Hose	0386-0339	TurboTorch	5UX21
<b>For MC Tanks, Self-Lighting</b>				
Hobbyist, HVAC, Light Fabrication	AH-12 Hose	0386-0834	TurboTorch	5GEG0
<b>MAP-Pro Torch Kits</b>				
2 1/2 in Soft Solder, 1 1/4 in Silver Braz	H-12 Hose, H-4 Handle, RL-P (CGA-510) Regulator, T-4 Tips	0386-0006	TurboTorch	5UX08
4 in Soft Solder, 2 in Silver Braz	H-12 Hose, H-4 Handle, RL-P (CGA-510) Regulator, T-3 Tips, T-5 Tips	0386-0007	TurboTorch	5UX09
1/4 to 4 in Soft Solder	Flexible Hose, Fuel Holster	384401	Bernzomatic	5JPK0