




39F945





2YKK6



1MUC1



52YA13











Multipurpose Greases

CRC®

General Purpose—For bearings and on cables, chains, latches, machinery, open gears, and overhead door tracks.

CITGO

Premium Lithium EP-Lubricates journal and antifriction bearings.

Lithoplex® MP—Helps minimize wear in heavily loaded components. Offers corrosion and oxidation resistance.

Lithoplex® CM and HM—Provide wear protection in construction and mining applications. Polymer-fortified for improved adhesion and water resistance. Lithoplex CM has 3% MoS2 Lithoplex HM has 5% Mos₂.

Lithoplex® RT-Tacky, moly-free formula provides good adhesion and water resistance.

JET-LUBE

MP-50 Moly Paste-Lead-free, water-resistant low-friction grease helps prevent corrosion.

Temp-Guard—Contains graphite and molybdenum disulfide for low friction and extreme pressure capabilities.

Mobilith SHC 220—Lubricates at temperature extremes: rust-, corrosion-, and oxidation-resistant.

Mobillith SHC-4ZF48 is for extreme pressure applications. 4ZF49 is for grease-lubricated rolling-element bearings in electric motors.

Mobilgrease XHP 222—Provides lubrication and oxidation stability plus rust, corrosion, and water resistance. Use for automotive, construction, marine applications and farm equipment.

Mobilgrease XTC-Resists oil separation in high-speed flexible gear and grid coupling applications.

Mobilux EP 1 and 2—EP 1 can be pumped at low temperatures. EP 2 is recommended for antifriction and plain bearings, bushings, and pins under normal operating conditions.

WD-40® SPECIALIST®

High Temperature—For high-speed bearing in high-temperature applications with heavy mechanical loads. Extreme Pressure—Offers protection against wear and high loads in heavy-duty applications

Marine Grade Water

Resistant—For moisture and corrosion protection for equipent that's exposed to the damp weather conditions

Waterproof Marine Grease—

Provides protection, even with extended exposure to saltwater and saltwater mist.

Heavy-Duty Grease—Protects and lubricates in temperatures up to 500°F. Great for automotive, construction, mining, and farm equipment.

Extra-Tacky Red Grease—

Provides anti-wear and extreme pressure protection, in temperatures up to 550°. Rust- and -corrosion resistant.

Pro-Grade Multipurpose

Grease—Water-resistant formula provides lubrication under moderate loads. Protects against rust and corrosion.

SUPER LUBE

Max. Min.

O-Ring Silicone Grease—For

lubricating, sealing, and conditioning 0-rings and other regulator and valve system components.

| | Grease | Lubricant | Base | | Container | | | | | | ltem |
|------------------------------------|-------------------|--------------------------|-----------|-------|-----------|---------|---------------|--------|-------------------|--------------|-----------------|
| Description | Thickener | Additives | Oil | Grade | Type | Size | Color | Temp. | Temp. | Model | No. |
| Blaster | | | | | | | | | | | |
| Extra Tacky Red Grease | Lithium Complex | Lithium | Petroleum | 2 | Cartridge | 14 oz | Red | 500 °F | 97 °F | GR-14C-HTR | 443V02 |
| Heavy-Duty Grease | Calcium Sulfonate | Calcium Sulfonate | Petroleum | 2 | Cartridge | 14 oz | Green | 500 °F | 97 °F | GR-14C-HDG | 443U99 |
| Penetrating Grease | Polymer | Distillates | Synthetic | _ | Cartridge | 14 oz | Orange | 500 °F | 97 °F | GR-14C-PB | 443U98 |
| Pro-Grade Multi- Purpose Grease | Lithium Complex | Lithium | Petroleum | 2 | Cartridge | 14 oz | Amber | 550 °F | -20 °F | GR-14C-MP | 443V03 |
| Waterproof Marine Grease | Calcium Sulfonate | Calcium Sulfonate | Petroleum | 2 | Cartridge | 14 oz | Blue | 500 °F | 97 °F | GR-14C-WP | 443V01 |
| Citgo | | | | | | | | | | | |
| Lithoplex CM | Lithium Complex | Zinc | Mineral | 1 | Tube | 14 oz | Gray | 350 °F | -5 °F | 655351001080 | |
| Lithoplex HM | Lithium Complex | | Mineral | 2 | Cartridge | 14 oz | Gray | 325 °F | -10 °F | 655357001080 | |
| Lithoplex MP | Lithium Complex | Zinc | Mineral | 2 | Tube | 14 oz | Gray | 350 °F | 0 °F | 655340001080 | |
| Lithoplex RT | Lithium Complex | Zinc | Mineral | 1 | Tube | 14 oz | Red | 350 °F | 0 °F | 655343001080 | |
| Lithoplex RT | Lithium Complex | | Mineral | 2 | Pail | 35 lb | Red | 325 °F | -10 °F | 655344001044 | |
| Premium Lithium Ef | | | Mineral | 2 | Pail | 35 lb | Amber | 250 °F | 5 °F | 655212001022 | |
| Premium Lithium EF | P Lithium | | Mineral | 2 | Drum | 120 lb | Amber | 250 °F | 5 °F | 655212001072 | 33ME/1 |
| CRC | 1.91.1 | | D | _ | D 11 | 05.11 | A 1 | 050.05 | 0.05 | 010045 | 005045 |
| General Purpose | Lithium | | Petroleum | 2 | Pail | 35 lb | Amber | 250 °F | 0 °F | SL3315 | 39F945 |
| Jet-Lube | | Mark de de accessor | | | | 2 lb | | 750 °F | -300 °F | 00007 | 5CHT5 |
| MP-50 Moly Paste | | Molybdenum | Minand | 3.5 | Can | 1 lb | Blue | 750 °F | | 28007 | |
| MP-50 Moly Paste | Clay | Molybdenum | Mineral | | | | | 600 °F | -300 °F -10 °F | 28003 | 2YKK6 26W739 |
| Temp-Guard Mobil | | | Synthetic | 1.5 | Cartridge | 14 oz | Black | 600 F | -10 -F | 31850 | 20W/39 |
| Mobilgrease | | | | | | | | | | | |
| SHC 220 | Lithium Complex | | Synthetic | 2 | Cartridge | 13.4 oz | Red | 300 °F | -40 °F | 121952 | 5ZN11 |
| Mobilgrease XHP 222 | Lithium Complex | | Mineral | 2 | Cartridge | 13.7 oz | Blue | 284 °F | 0 °F | 121929 | 1MUC1 |
| Mobilgrease XHP 222 | Lithium Complex | | Mineral | 2 | Pail | 5 gal | Blue | 284 °F | 0 °F | 105842 | 1MUC2 |
| Mobilgrease XTC | Lithium | | Mineral | 1 | Cartridge | 14 oz | Dark Brown | 120 °F | -30 °F | 105804 | 2RV27 |
| Mobillith SHC | Lithium Complex | | Synthetic | 1.5 | Cartridge | 13.7 oz | White | 350 °F | -40 °F | 122129 | 4ZF48 |
| Mobillith SHC | Lithium Complex | | Synthetic | 2 | Cartridge | 13.4 oz | Red | 350 °F | -40 °F | 122112 | 4ZF49 |
| Mobilux EP 1 | Lithium | | Mineral | 1 | Cartridge | 13.7 oz | Brown | 120 °F | -20 °F | 121093 | 2RV29 |
| Mobilux EP 2 | Lithium | | Mineral | 2 | Cartridge | 13.7 oz | Brown | 266 °F | -4 °F | 122136 | 2RV31 |
| Mobilux EP 2 | Lithium | | Mineral | 2 | Pail | 5 gal | Tan | 130 °F | -20 °F | 105763 | 5NJT9 |
| Super Lube | | | | | | | | | | | |
| O-Ring Silicone Grease | Silicone | No Additives | Silicone | 2 | Tube | 3 oz | White | 500 °F | -40 °F | 93003 | 436P94 |
| O-Ring Silicone Grease | Silicone | No Additives | Silicone | 2 | Can | 14.1 oz | White | 500 °F | -40 °F | 93016 | 436P95 |
| WD-40 Specialist | | | | | | | | | | | |
| Extreme Pressure | Lithium Complex | Distillates | Mineral | 2 | Cartridge | 14 oz | Red | 325 °F | -40 °F | 300400 | 52YA12 |
| High Temperature | Lithium Complex | Distillates | Mineral | 2 | Cartridge | 14 oz | Green | 325 °F | -40 °F | 300394 | 52YA11 |
| Marine Grade Water Resistant | Lithium Complex | Petroleum Distillates | Mineral | 2 | Cartridge | 14 oz | Blue | 325 °F | -40 °F | 300417 | 52YA13 |
| | | | | | | | | | | | |