



**CRC**  
4JB56



**Jet-Lube**  
5CHP4



**Mobil**  
2RV34



**Petrochem**  
Foodsafe  
3NLK4



**Sta-Lube**  
13P453



**Super Lube**  
44N732



**Tri-Flow**  
4TA91



## Food Grade Multipurpose Greases

### CRC

**Greases**—4JB56 is formulated on a premium aluminum complex base. 12G584 has a smooth, buttery texture and is a premium-grade aluminum complex grease. 12G587 is plastic-safe and particularly useful in high-temperature applications. Extreme Duty 12G591 is a plastic-safe grease with excellent water-washout resistance.

### JET-LUBE

**FMG**—Food Machine Grease is formulated for a wide variety of operating conditions, with extreme water resistance to stay in place even after frequent washdowns. Polymer additives provide adhesive and cohesive strength to resist pound-out under shock loads. It is recommended to lubricate all types of bearings in food processing machinery.

### MOBIL

**Mobilgrease FM 222**—High-performance multipurpose formula is designed to lubricate food processing machinery in varied environments, from oven to freezer operations, and over a wide range of speeds and loads. The grease withstands periodic washdown and cleaning operations, with excellent water resistance and rust inhibition and good protection against wear and shock loads.

### PETROCHEM FOODSAFE

**PETRO-GARD FMG-2**—Formulated with special additives selected to provide excellent water, oxidation, and corrosion resistance, plus corrosion prevention and excellent antiwear and extreme-pressure (EP) properties. The product stays in place between washdown cycles to help boost equipment and lubricant life in wet conditions.

**SYN GEL FG-750**—High-temperature gel grease seals bearings against water and other contaminants and provides corrosion protection. It remains stable

under high shear and high temperatures, and will not melt, drip, carbonize, or emulsify. The lubricant is highly water-resistant and performs exceptionally well in wet applications.

### STA-LUBE

**Super White Multipurpose**—High-purity greases provide superior performance in any weather and most temperatures. Bright white color is great where appearance is important.

### SUPER-LUBE

**Multipurpose Grease with Syncolon PTFE**—Heavy-duty lubricant is made with proprietary Syncolon PTFE micropowders combined with synthetic base fluids for longer lasting protection against friction, wear, rust, and corrosion. Designed to help reduce downtime, increase productivity, and extend machinery life. The formula has good mechanical stability, won't melt or separate, and does not evaporate or form gummy deposits.

**Silicone Lubricating Compound with Syncolon PTFE**—Synthetic grease offers excellent water protection and moisture barrier over a wider operating range than petroleum-based lubes. It's good for plastic gears and threads and as a damping medium for dash pots. Also lubricates O-rings, electrical motor and slow-speed bearings, brake parts, weather stripping, trunk seals, speedometer cables, window channels, hood strips, pads, rubber gaskets, and other rubber components.

### TRI-FLOW

**Synthetic Grease with PTFE**—Compatible with most rubbers and plastics; excellent for O-rings. Nonstaining and waterproof. Pure synthetic provides added durability and performance.

Description	Grease Thickener	Base Oil	NLGI Grade	Container Type	Container Size	NSF Rating	Grease Color	Max. Operating Temp.	Min. Operating Temp.	Mfr. Model	Item No.
<b>CRC</b>											
Multipurpose Food Grade Grease	Aluminum Complex	Mineral	2	Cartridge	14 oz	H1	White	300 °F	-30 °F	SL35600	4JB56
Synthetic Food Grade Grease	Aluminum Complex	Mineral	2	Pail	35 lb	H1	White	300 °F	-30 °F	SL35605	12G584
Extreme Duty Food Grade Grease	Silica	Synthetic	2	Cartridge	14 oz	H1	Clear	350 °F	-20 °F	SL35610	12G587
Jet-Lube FMG	Calcium Sulfonate	Mineral	2	Cartridge	14 oz	H1	Tan	400 °F	-20 °F	SL35615	12G591
<b>Jet-Lube</b>											
FMG	Aluminum Complex	Mineral	2	Cartridge	14 oz	H1	White	400 °F	0 °F	30150	5CHP4
<b>Mobil</b>											
Mobilgrease FM 222	Aluminum Complex	Mineral	2	Cartridge	13.7 oz	H1	White	500 °F	0 °F	121956	2RV34
<b>Petrochem Foodsafe</b>											
PETRO-GARD FMG-2	Aluminum Complex	Semi-Synthetic	2	Cartridge	14 oz	H1	White	300 °F	-22 °F	PETRO-GARD FMG-2	3NLK5
SYN GEL FG-750	—	Synthetic	2	Cartridge	14 oz	H1	White	500 °F	-4 °F	SYNGEL FG-750	3NLK4
<b>Sta-Lube</b>											
Super White Multipurpose	Lithium	Mineral	2	Tube	10 oz	H2 No Food Contact	White	300 °F	0 °F	SL3360	39F946
	Lithium	Mineral	1.5	Cartridge	14 oz	H2 No Food Contact	White	300 °F	0 °F	SL3150	13P453
	Lithium	Mineral	1.5	Pail	35 lb	H2 No Food Contact	White	300 °F	0 °F	SL3155	39F944
<b>Super-Lube</b>											
Multipurpose Grease With Syncolon (PTFE)	PTFE	Synthetic	2	Pail	30 lb	H1	White	450 °F	-45 °F	41030	44N724
Silicone Lubricating Grease With Syncolon (PTFE)	—	Synthetic	2	Cartridge	14.1 oz	H1	White	500 °F	-40 °F	92150	44N732
<b>Tri-Flow</b>											
Synthetic Grease with PTFE	PTFE	Synthetic	2	Cartridge	14 oz	—	White	400 °F	-10 °F	TF220211	4TA91