



**ThermaPlex**  
**Multi-Purpose**  
**4UJ42**



**Jet-Lube EP**  
**6HAL9**

Description	Container Size	NSF Rating	Grease Thickener	Grease Color	Max. Operating Temp.	Min. Operating Temp.	Mfr. Model	Item No.
<b>Mobil</b>								
Polyrex EM	13.7 oz	Not Rated	Polyurea	Blue	320 °F	-4 °F	124050	5XB54
<b>LPS ThermaPlex</b>								
Multipurpose	14.1 oz	Not Rated	Lithium Complex	Blue	350 °F	-22 °F	70614	4UJ42
Hi-Temp	14.1 oz	Not Rated	Lithium Complex	Tan	392 °F	-15 °F	70214	4UJ38
Hi-Load	14.1 oz	Not Rated	Lithium Complex	Black	350 °F	-22 °F	70414	4UJ40
Aqua	14.1 oz	Not Rated	Aluminum Complex	Amber	300 °F	-4 °F	70514	4UJ41
FoodLube	14.1 oz	H1 Food Grade	Aluminum Complex	White	302 °F	-4 °F	70114	38F843
CS Moly	14.1 oz	H2 No Food Contact	Calcium Sulfonate	Gray	425 °F	0 °F	70814	4FPW8
<b>Jet-Lube</b>								
EP	14 oz	Not Rated	Lithium	Purple	325 °F	0 °F	30350	6HAL9
<b>Sta-Lube</b>								
Sta-Plex Extreme Pressure Grease	14 oz	H2 No Food Contact	Lithium Complex	Red	325 °F	-20 °F	SL3190	5EV20



## Bearing Grease

- Grease container: Cartridge

### Mobil

**Polyrex EM**—Super-premium grease is formulated for electric-motor bearings, particularly vertically mounted bearings or very large motors that may require stiffer grease consistency.

### LPS THERMAPLEX

**Multipurpose**—For use as a high-performance, multifunctional bearing grease in general purpose applications.

**Hi-Temp**—Resists carbonization, vibration, and bearing failure. Extends relubrication intervals. Excellent resistance.

**Hi-Load**—Provides long-lasting lubrication for bearings subjected to shock loading and vibration. Offers antiwear properties and corrosion resistance.

**Aqua**—Provides long-lasting lubrication even when fully submerged in fresh or salt water.

**FoodLube**—Nonstaining, nonemulsifying formula for use in food processing and other clean industries.

**CS Moly**—Calcium sulfonate formula with molybdenum disulfide for high load carrying capacity. Reduces wear from vibration. Water- and corrosion-resistant.

### JET-LUBE

**EP**—Bearing grease contains an extreme-pressure additive that enhances shear stability in high temperatures.

### STA-LUBE

**Sta-Plex Extreme Pressure Grease**—Multipurpose, lithium complex formula contains extreme pressure, anti-oxidation, and anti-wear additives. For high temperature applications and for use in ball and roller bearings and in assembly/machining equipment.




**CRC**  
**1HBK3**



**Jet-Lube**  
**2YKK4**



**Loctite**  
**5E201**



**Super-Lube**  
**44N728**



## Dielectric Grease

**CRC Dielectric Grease**—Food-grade noncuring silicone compound waterproofs electrical connections and components to protect against arcing. 2F136 features Perma-Lock integrated actuator that will not detach.

**Jet-Lube Silicone Compound DM**—Moisture-proofing sealant and lubricant's low volatility, inert properties, and high dielectric strength are good for use on a wide range of elastomers and plastics. It can serve as a lubricant, sealant, or chemical barrier coating for valves, O-rings, stuffing boxes, and vacuum and pressure systems; great to insulate electrical connectors against the elements.

**Jet-Lube MP (Moisture-Proofing) Silicone Grease**—Nonconductive premium moistureproofing lubricant is useful in a wide variety of applications, and a great insulator to protect electrical connectors against the elements. It is excellent on marine, automotive, and aircraft ignition systems, as well as electrical assemblies, cable and spark plug connections, and battery terminals. The formula is designed for compatibility with O-ring materials including Buna-N, Viton FKM, HSN (hydrogenated nitrile), Teflon PTFE, and nylon.

**Loctite LB 8801 Silicone Lubricant**—Noncuring. Seals, waterproofs, and electrically insulates metal, rubber, and plastic parts. Can also be used as a mold release agent.

**Super-Lube H1 Food Grade Dielectric Grease**—Noncuring synthetic compound lubricates, seals, and protects electrical components and connectors including battery cables, spark plugs, distributor caps, terminal strips and disconnects, and cable connections. Compatible with most plastics and rubber, it helps moistureproof and insulate electrical connections, offers corrosion prevention, and helps keep contaminants out.

**Super-Lube H1 Food Grade Multipurpose Grease**—PTFE-based formula provides friction, wear, rust, and corrosion protection. This grease will not run, drip, melt or separate.

NLGI Grade	Container Type	Container Size	NSF Rating	Grease Color	Base	Max. Operating Temp.	Min. Operating Temp.	Mfr. Model	Item No.
<b>CRC Dielectric Grease</b>									
2	Tube	3.3 oz	H1	White	Silicone	400 °F	-70 °F	02085	1HBK3
<b>CRC</b>									
2	Aerosol Can	10 oz	H1	Clear	Silicone	400 °F	-70 °F	03082	2F136
<b>Jet-Lube Silicone Compound DM</b>									
3	—	—	—	—	Silicone	—	—	73560	2YKJ9
3	Cartridge	14 oz	H1	Clear	Silicone	400 °F	-70 °F	73550	2YKK4
<b>Jet-Lube MP Silicone Grease</b>									
1.5	Tube	5.3 oz	H1	Clear	Silicone	400 °F	-70 °F	32460	2YKK1
<b>Loctite LB 8801 Dielectric Grease</b>									
—	Tube	5.3 oz	Not Rated	Clear	Silicone	400 °F	—	234317	5E201
<b>Super-Lube H1 Food Grade Dielectric Grease</b>									
2	Cartridge	14.1 oz	H1	White	PAO/Mineral Oil/Silicone	500 °F	-40 °F	91015	44N728
<b>Super-Lube H1 Food Grade Multipurpose Grease</b>									
2	Cartridge	14.1 oz	H1	White	PAO/Mineral Oil	450 °F	-45 °F	41150	44N721