

lachine Oi

2F132



## **Food Grade Machinery Oils**

NSF H1 Rated

**CRC**—General-purpose lubricant is silicone-free, virtually odorless, and colorless. Will not harm metal, wood, plastic, or painted surfaces. Zero VOC. The Perma-Lock integrated actuator will not detach.

LPS with DETEX—Features metal-detectable plastic components with DETEX. Colorless, odorless, nonstaining oil loosens nuts and bolts and lubricates to reduce sticking, binding, and squeaking on bottling equipment, conveyors, food service racks, slicers, and other equipment. Safe on most surfaces. Silicone- free and VOC-free. No chlorinated solvents.

Sprayon LU700 Oil—Silicone-free lubricant loosens corrosion.

Tri-Flow Synthetic Oil with PTFE—Nonstaining oil does not emulsify in water.

Description	Container Size	Temp. Range	Mfr. Model	ltem No.
CRC	16 oz	32° to 300°F	03081	2F132
LPS with DETEX	11 oz	0° to 385°F	01316	19C659
Sprayon LU700 Food Grade Machinery Oil	10 oz	-20° to 450°F	SC0700000	6KHE5
Tri-Flow Synthetic Oil with PTFE	12 oz	-10° to 400°F	TF230101	4TA90



WESTWARD

## **Reusable Sprayer**

Refillable sprayer uses compressed air to deliver a uniform, controlled mist spray of bulk lubricants, penetrants, degreasers, solvents, and cleaners. 80 to 150 psi operating pressure. Top-fill carbon steel canister with blue enamel coating. Not for use with paint.

punt.	Dia.	н	Item
Cap. (oz.)	(in.)	(in.)	No.
32	4 in	7 1 in	31ER19



**Tapmatic Edge Lube**—Biodegradable bar is packaged in a cylinder for rotating or stationary cutting tools. Excellent for sawing applications, eliminating heat buildup and belt loading. Low toxicity. Compatible with oil and water systems. Safe on all metals.

**Tapmatic Edge Creme**—Biodegradable paste cutting fluid can be applied to tools before tapping or reaming. Use when drilling, tapping blind holes, forming, bending, precoating fasteners, and lubricating rubber seals.

**Gel Paste**—Vegetable-based gel lubricant with workable texture for taps, drills, and cutting tools. Safe for ferrous and nonferrous metals. A1 and T1.

**Stick Lubricants**—Designed to reduce heat buildup in belt, disc, or wheel grinding operations.



6KHE5

4**TA**90

Container Size	Container Style	Physical Form	Color	Brand	Mfr. Model	ltem No.			
Tapmatic Edge Lube									
13 oz	Tube	Solid	White	LPS	43200	4KK73			
Tapmatic Edge Cream									
10 oz	Tube	Paste	White	LPS	43100	4KK72			
Gel Paste									
8 oz	Jar	Paste	Dark Blue	Accu-Lube	79030	1MKN8			
Stick Lubricants									
2.2 oz	Jar	Solid	Light Blue	Accu-Lube	79042	1MKN6			
13 oz	Tube	Solid	Light Blue	Accu-Lube	79045	1MKN7			

Sign in to Grainger.com<sup>®</sup> to see YOUR Pricing and MORE