



Schneider
Electric

30mm Selector Switch
Combinations—Complete Units

- Metal units: NEMA 3, 3R, 4, 12, and 13 rated
 - Plastic units: NEMA 3, 3R, 4, 4X, 12, and 13 rated
- Oiltight, watertight, and dust-tight. Include operator and contact block. UL Listed, CSA and CE Certified. RoHS compliant and ABS Certified.

Position	Action*	Contact Form	Cam	Switch @ Pos. A	Switch @ Pos. B	Switch @ Pos. C	Switch @ Pos. D	METAL Item No.	PLASTIC Item No.
2	M / M	1NO/1NC	E	OX	XO	—	—	2EN52	5GEV1
2	M / M	1NO/1NC	E	OX	XO	—	—	2EN53	45J160
2	M / M	1NO/1NC	E	OX	XO	—	—	7A161 †	—
2	M / M	2NO/2NC	E	OXOX	XOXO	—	—	2EN54	45J161
2	M / S	1NO/1NC	D	XO	OX	—	—	5GET0	—
2	S / M	1NO/1NC	E	OX	XO	—	—	5GER8	5EAV7
3	M / M / M	1NO/1NC	B	OX	XO	XO	—	45C539	—
3	M / M / M	1NO/1NC	B	XO	XO	OX	—	5GET3	45J168
3	M / M / M	2NO/2NC	B	XOXO	XOXO	OXOX	—	45C540	45J169
3	M / M / M	1NO/1NC	C	OX	OX	XO	—	5GET5	5CFJ3
3	M / M / M	1NO/1NC	C	OX	OX	XO	—	2EN61	45J170
3	M / M / M	2NO/2NC	C	OXOX	OXOX	XOXO	—	—	45J171
3	M / M / M	1NO/1NC	D	OX	XO	OX	—	5GET8	—

Note: X=Closed/On, O=Open/Off. * M=maintained contact, S=spring return momentary contact. † Unassembled versions.

Position	Action*	Contact Form	Cam	Switch @ Pos. A	Switch @ Pos. B	Switch @ Pos. C	Switch @ Pos. D	METAL Item No.	PLASTIC Item No.
3	M / M / M	1NO/1NC	D	OX	XO	OX	—	7A163 †	—
3	M / M / M	2NO/2NC	F	OXOX	OXOX	XOXO	—	45C542	45J174
3	M / M / M	1NO/2NC	F	OXOX or OOX	XOXO or OXO	XOXO or XOXO	—	7A164 †	—
3	M / M / M	1NO/1NC	F	OX	OX	XO	—	—	45J173
3	M / M / M	1NO/1NC	F	OX or OX	OX or OX	XO or XO	—	7A162 †	—
3	M / M / M	2NO/2NC	J	OXOX	XOXO	OXOX	—	45C544	45J175
3	M / M / S	1NO/1NC	C	OX	OX	XO	—	5GEU6	5CFJ5
3	S / M / M	1NO/1NC	C	OX	OX	XO	—	5GEU3	—
3	S / M / S	1NO/1NC	C	OX	OX	XO	—	45C545	—
3	S / M / S	1NO/1NC	C	OX	OX	XO	—	5GEU0	5GEP8
3	S / M / S	2NO/2NC	C	OXOX	OXOX	XOXO	—	45C546	—
4	M / M / M / M	1NO/1NC	H	OXOX or OOX	XOXO or OOX	OXOX or OOX	OXOX or OOX	7A165 †	—
4	M / M / M / M	1NO/1NC	H	OX or OX	XO or XO	OX or OX	OX or OX	7A166 †	—
4	M / M / M / M	2NO/2NC	H	OXOX	XOXO	OXOX	OXOX	5GEU8	5CFJ6
Extended Lever									
2	M / M	1NO/1NC	E	OX	XO	—	—	5GER3	45J164
2	M / M	1NO/1NC	E	OX	XO	—	—	5GER2	45J163
2	M / M	2NO/2NC	E	OXOX	XOXO	—	—	5GER4	45J165
2	M / S	1NO/1NC	D	XO	OX	—	—	5GET1	—
2	S / M	1NO/1NC	E	OX	XO	—	—	5GER9	—
3	M / M / M	1NO/1NC	B	XO	XO	OX	—	5GET4	—
3	M / M / M	1NO/1NC	C	OX	OX	XO	—	5GET6	5CFJ4
3	M / M / M	1NO/1NC	C	OX	OX	XO	—	45C541	—
3	M / M / S	1NO/1NC	C	OX	OX	XO	—	5GEU7	—
3	S / M / M	1NO/1NC	C	OX	OX	XO	—	5GEU4	5GER1
3	S / M / S	1NO/1NC	C	OX	OX	XO	—	5GEU1	5GEP9
3	S / M / S	1NO/1NC	C	OX	OX	XO	—	45C547	45J178
3	S / M / S	2NO/2NC	C	OXOX	OXOX	XOXO	—	45C548	—
4	M / M / M / M	1NO/1NC	H	OXOX	XOXO	OXOX	OXOX	5GEU9	—

Position	Action	Contact Form	Cam	Key Removal	Switch @ Pos. A	Switch @ Pos. B	Switch @ Pos. C	Switch @ Pos. D	METAL Item No.
Keyed									
2	M / M	1NO/1NC	E	Left	OX	XO	—	—	5GER5
2	M / M	1NO/1NC	E	Right	OX	XO	—	—	5GER6
2	M / M	1NO/1NC	E	Left/Right	OX	XO	—	—	5GER7
2	M / M	2NO/2NC	E	Left and Right	OXOX	XOXO	—	—	45C538
2	M / S	1NO/1NC	D	Left	XO	OX	—	—	5GET2
3	M / M / M	1NO/1NC	C	Any Position	OX	OX	XO	—	5GET7
3	S / M / M	1NO/1NC	C	Center and Right	OX	OX	XO	—	5GEU5
3	S / M / S	1NO/1NC	C	Center	OX	OX	XO	—	5GEU2
4	M / M / M / M	1NO/1NC	H	Any Position	OXOX	XOXO	OXOX	OXOX	5GEV0



30mm Illuminated Operators

- Momentary operators
- Caps not included
- NEMA rated 4 and 13 without boots
- Plastic operators are NEMA 4X rated (corrosion-resistant)

Oiltight, watertight, and dust-tight. Ring nuts are interchangeable. Premium long-life, incandescent lamp included. A complete push button requires a contact block (see page 237) and cap, sold separately. UL Listed, CE and CSA Certified.

	►CHOOSE: Lamp Module Voltage	►CHOOSE: Type of Operator	►CHOOSE: Bezel	Item No.
Full Voltage	24V AC/DC; 120V AC	No Guard; Full Guarded Button	Plastic; Metal	H4484
Transformer	120V AC; 240V AC	No Guard; Full Guarded Button	Plastic; Metal	H4530
Push Button Cap	For Use With Schneider Illuminated Push Buttons K1L, K2L, K3L, SK1L and SK2L Series	Yellow; White; Red; Green; Clear; Blue; Amber		H7108



Schneider
Electric

30mm Nonilluminated Operators

- Notch-mount with contact blocks, sold separately
 - NEMA rated 4 and 13 without boots
 - Plastic models are NEMA 4X rated (corrosion-resistant)
- Oiltight, watertight, and dust-tight operators with interchangeable ring nuts and color inserts make design changes easy. A complete push button requires a contact block, sold separately, see page 237

EMERGENCY BREAK GLASS OPERATOR

Glass disc holds operator in depressed position. When disc is broken, button returns to normal extended position. Includes hammer and 5 discs.

	►CHOOSE: Type of Operator	►CHOOSE: Color	►CHOOSE: Basic Material	Item No.
Momentary Push / Maintained Intermediate / Momentary Pull				
40mm Mushroom Head		Black; Green; Red; Yellow	Metal; Plastic	H4522
40mm Mushroom Head		No Cap	Metal; Plastic	H4528
Momentary Push				
40mm Mushroom Head; 60mm Mushroom Head		Black; Green; Red	Metal	H4527
Extended Button; Flush Button		Black; Green; Red	Metal; Plastic	H4518
Extended Button; Flush Button		Multi	Metal; Plastic	H4517
Maintained Push / Turn To Release				
30mm dia Mushroom Head; 40mm Mushroom Head		Red	Plastic; Metal	H7010
Maintained Push / Maintained Pull				
40mm Mushroom Head; 60mm Mushroom Head		Black; Green; Red; Amber; Blue; White; Yellow	Metal; Plastic	H4526
40mm Mushroom Head		Black; Green; Red	Metal	H4539 *
40mm Mushroom Head		No Cap	Metal; Plastic	H4533
60mm Mushroom Head		Red	Metal	H4540
Maintained Push / Maintained Intermediate / Maintained Extended Key Lockable				
Flush Button		No Cap	Metal	2EN06
Maintained Push				
Emergency Break Glass Operator		Black	Metal	2EL29
Interlocked, Maintained 2 Position				
Full Guard		Black/Red; Green/Red	Metal	H4531

* Metal head.