



Pneumatic Framing Nailers

Clipped Head—Drives ring, screw, and smooth-shank 34° paper taped strip nails. High-efficient internal design reduces less wear and tear. Eliminates jams and mis-feeds and fits easily between studs and joints.


Full Round Head—35JG54 features a TrueDrive magazine to help reduce misfeeds and jams. Low-profile design allows use in tight spaces. 5KNH5 has a magnesium body with a 130:1 power-to-weight ratio and 1050 in.-lb. of driving power. Use in engineered lumber. Features tool-free push-button drive depth control, adjustable exhaust, and steel backer plate.

Offset Round Head—Features tool-free adjustable exhaust and push-button depth of drive.

Collation Angle	Collation Type	Fastener Range	Shank Dia.	Magazine Cap.	Tool Weight	Brand	Mfr. Model	Item No.
Clipped Head Nail Gun								
34°	Paper	2 in to 3 1/4 in	0.113 in to 0.148 in	83	7.1 lb	Senco	FRAMEPRO 325XP	48LR49
Full Round Head Nail Gun								
20°	Plastic	2 in to 3 1/4 in	0.113 in to 0.148 in	64	7.9 lb	Senco	FRAMEPRO 325FRHXP	35JG54
	Plastic	2 in to 3 1/2 in	0.113 in to 0.162 in	60	8.1 lb	Bostitch	F21PL	2UV89
21°	Plastic	2 in to 3 1/2 in	0.113 in to 0.162 in	60	8.1 lb	Bostitch	F21PL2	5KNH5
	Plastic	2 in to 3 1/4 in	0.113 in to 0.131 in	64	7.7 lb	Bostitch	BTF83PL	410X70
Offset Round Head Nail Gun								
28°	Wire	2 in to 3 1/2 in	0.113 in to 0.131 in	100	7.7 lb	Bostitch	F28WW	2UV87




Clipped Head



Round Head



21U144



4X922

Collation Angle	Collation Type	L	Shank	Shank Dia.	Finish	Item No.	Pkg. Qty.
Clipped Head Senco							
34°	Tape	2 1/2 in	Ring	0.113 in	Bright	21U144	2500
34°	Tape	3 in	Smooth	0.12 in	Bright	21U143	2500
34°	Tape	3 in	Smooth	0.131 in	Bright	21U142	2500
Full Round Head Bostitch							
21°	Plastic	2 1/2 in	Smooth	0.113 in	Coated	4WL05	5000
21°	Plastic	2 1/2 in	Ring	0.113 in	Coated	3HZG9	5000
21°	Plastic	3 in	Ring	0.12 in	Hot Dipped Galvanized	3HZG6	4000
21°	Plastic	3 in	Ring	0.131 in	Hot Dipped Galvanized	400F90	4000
21°	Plastic	3 in	Smooth	0.131 in	Coated	4WL03	4000
21°	Plastic	3 1/4 in	Smooth	0.131 in	Coated	4WL04	4000
21°	Plastic	3 1/4 in	Smooth	0.131 in	Hot Dipped Galvanized	5LB33	4000
Paslode							
30°	Tape	2 in	Ring	0.113 in	Hot Dipped Galvanized	3FRP6	2000
30°	Tape	2 1/2 in	Ring	0.113 in	Hot Dipped Galvanized	5LB31	2000
30°	Tape	3 in	Ring	0.12 in	Hot Dipped Galvanized	3FRP7	2000
30°	Tape	3 in	Ring	0.131 in	Hot Dipped Galvanized	3FRP9	2000
30°	Tape	3 in	Smooth	0.131 in	Brite US32	31EE20	2500
30°	Tape	3 in	Smooth	0.12 in	Brite US32	31EE21	2500
30°	Tape	3 1/4 in	Smooth	0.131 in	Hot Dipped Galvanized	5LB33	2000
30°	Tape	3 1/4 in	Smooth	0.131 in	Brite US32	31EE22	2500



Fuel Actuated Cordless Framing Nailer

Operate on a fuel cell and cordless battery. Both include a rechargeable Li-Ion battery and charger. Features a nose that allows toe nailing at any angle, keyless adjustable depth of drive, and a heavy-duty utility hook.

Head Style	Collation Angle	Collation Type	Fastener Range	Shank Dia.	Magazine Cap.	Tool Weight	Brand	Mfr. Model	Item No.
Nail Gun									
Round	30°	Paper	2 in to 3 1/4 in	0.113 in to 0.131 in	30	7.2 lb	Paslode	906300	48PD34
Includes									
Paslode Fuel/Fastener Pack for 48PD34									
(1000) 2 1/2 in x 0.113 in, Tape Collated, Smooth Bright, (1) Fuel Cartidge & Adapter									650522 3FRR7
(1000) 2 1/2 in x 0.113 in, Tape Collated, Ring Bright, (1) Fuel Cartidge & Adapter									650523 3FRR8
(1000) 3 in x 0.12 in, Tape Collated, Smooth Bright, (1) Fuel Cartidge & Adapter									650524 3FRR9
(1000) 3 in x 0.131 in, Tape Collated, Smooth Bright, (1) Fuel Cartidge & Adapter									650525 3FRT1
(1000) 2 1/2 in x 0.113 in, Tape Collated, Ring HDG+, (1) Fuel Cartidge & Adapter									650526 3FRT2
(1000) 3 in x 0.12 in, Tape Collated, Ring HDG+, (1) Fuel Cartidge & Adapter									650527 3FRT3
(1000) 3 1/4 in x 0.131 in, Tape Collated, Smooth Bright, (1) Fuel Cartidge & Adapter									650535 3FRT4
(1000) 2 in x 0.113 in Tape Collated Ring HDG+, (1) Fuel Cartidge & Adapter									650564 3FRT6
Description									
Accessories for Paslode Cordless Tools									
(2) Fuel Cartidge For 19L844, 18PD34									31EE19
6.0V Ni-Cd Battery Charger									4WL47
6V DCV Ni-Cd Battery									4WL38
7.4V Li-Ion Battery									19L845
Cordless Lubricating Oil									4WL31
Li-Ion Battery Charger Kit, Cordless Nailers									19L846



Collated Framing Nails

For use with both cordless and pneumatic framing nailers.

Collation Angle	Collation Type	L	Shank	Shank Dia.	Finish	Item No.	Pkg. Qty.
Senco							
15°	Wire	2 1/2 in	Ring	0.113 in	Bright	48LR13	6000
15°	Plastic	3 in	Smooth	0.12 in	Bright	48LR14	4000
15°	Wire	3 in	Ring	0.12 in	Hot Dipped Galvanized	48LR15	2400
20°	Plastic	2 1/2 in	Ring	0.113 in	Bright	21U146	5000
20°	Plastic	2 1/2 in	Smooth	0.131 in	Bright	48LR16	4000
20°	Plastic	3 in	Smooth	0.113 in	Bright	21U145	4000
20°	Plastic	3 1/4 in	Smooth	0.131 in	Hot Dipped Galvanized	48LR17	2500
20°	Plastic	3 1/4 in	Smooth	0.131 in	Bright	48LR18	4000
20°	Plastic	3 1/2 in	Smooth	0.131 in	Bright	48LR19	4000
34°	Tape	2 in	Ring	0.113 in	Hot Dipped Galvanized	48LR50	2500
34°	Tape	2 1/2 in	Ring	0.113 in	Bright	48LR51	2500
34°	Tape	2 1/2 in	Ring	0.113 in	Hot Dipped Galvanized	48LR52	2500
34°	Tape	3 in	Smooth	0.12 in	Bright	48LR53	2500
34°	Tape	3 in	Ring	0.12 in	Hot Dipped Galvanized	48LR55	2500
34°	Tape	3 in	Smooth	0.131 in	Bright	48LR56	2500
34°	Tape	3 in	Smooth	0.131 in	Hot Dipped Galvanized	48LR57	2500
34°	Tape	3 in	Ring	0.131 in	Hot Dipped Galvanized	48LR61	2500
34°	Tape	3 1/4 in	Smooth	0.131 in	Bright	48LR58	2500
34°	Tape	3 1/4 in	Smooth	0.131 in	Hot Dipped Galvanized	48LR59	2500
34°	Tape	3 1/2 in	Smooth	0.131 in	Bright	48LR60	2500
Offset Round Head Bostitch							
28°	Wire	2 in	Smooth	0.113 in	Coated	5X386	2000
28°	Wire	2 1/2 in	Smooth	0.12 in	Coated	5W231	2000
28°	Wire	2 1/2 in	Smooth	0.12 in	Thickcoat Galvanized	4X953	2000
28°	Wire	2 1/2 in	Ring	0.12 in	Coated	3HZH5	2000
28°	Wire	3 in	Smooth	0.12 in	Coated	4X922	2000
28°	Wire	3 in	Smooth	0.12 in	Thickcoat Galvanized	4X954	2000
28°	Wire	3 in	Ring	0.12 in	Thickcoat Galvanized	3HZH4	2000
28°	Wire	3 1/4 in	Smooth	0.12 in	Coated	5X389	2000
28°	Wire	3 1/4 in	Smooth	0.12 in	Thickcoat Galvanized	4X955	2000
28°	Wire	3 1/2 in	Smooth	0.131 in	Coated	5X390	2000
28°	Wire	3 1/2 in	Smooth	0.131 in	Thickcoat Galvanized	4X956	2000