

Mandrel-Mounted Mini Grind-O-Flex Kit—Includes 10 wheels, 1" to 3" dia., with various grit sizes. Each wheel has ½" mandrel.

Mini Grind-O-Flex Test Kit—Includes 10 wheels, 1" to 3" dia., and $\frac{1}{4}$ " quick-change adapter. Each wheel has $\frac{1}{4}$ -20 thread.

	Mfr.	Item
Description	Model	No.
Mandrel Mounted Mini Grind-O-Flex Test Kit "CMM"	08834138006	3RB87
Mini Grind-O-Flex Test Kit "CQ"	08834138003	3RB86



3RB91

ue know abrasives

Interleaf Mounted Flap Wheels

- Flexible and conformable
- 1/4" dia. shank

Premium aluminum oxide abrasive and nonwoven cloth provide excellent performance and long wheel life for material finishing and surface preparation applications.

11	ia.	Abrasive Grit	Abrasive Grade	Max. RPM	Item No.	
Merit						
1	in	240	Very Fine	30,000 RPM	464P81	
		60	Coarse	25,000 RPM	464P82	
		80	Coarse	25,000 RPM	464P83	
-	2 in	120	Medium	12,000 RPM	3RB91	
_	. 1111		Medium	25,000 RPM	464P84	
		180	Fine	12,000 RPM	3RB92	
		320	Very Fine	12,000 RPM	3RB93	
		60	Coarse	20,000 RPM	464P85	
			Coarse	20,000 RPM	464P92	
9	in 3	120	Medium	12,000 RPM	3RB94	
ď)		Medium	20,000 RPM	464P86	
		180	Fine	12,000 RPM	3RB95	
	240	Very Fine	20,000 RPM	464P87		
	l in	120	Very Fine	12,000 RPM	464P80	
DeWalt®						
2 in	60	Coarse	12,000 RPM	6TMT9		
	100	Medium	12,000 RPM	6TMU0		
		150	Medium	12,000 RPM	6TMU1	
3	3 in	130	Medium	8,000 RPM	6TMU4	



Spiral Rolls and Cartridge Rolls

■ 1/8" arbor hole
Use spiral rolls for grinding and polishing channels, fillets, and radii and deburring small holes. Use cartridge rolls for flash removal, polishing, or removing machine tool marks and edge breaking.

Dia.	L	CHOOSE: Grit	Item No.		
Spiral Rolls					
3/8 in	1 in	60, 80, 120	H6018		
½ in -	1 in	60, 80, 120	H6020		
	1 ½ in	60, 80, 120	H6022		
Cartridge Rolls					
3/8 in	1 in	60, 80, 120	H6024		
1/2 in	1 ½ in	60, 80, 120	H6026		
3/4 in	1 ½ in	60, 80, 120	H6028		
Accessory					
Threaded Ma	andrel ¼ in		3RB82		




Alo Resin Bond Bore Polishers

- · As flaps wear, fresh abrasive is constantly exposed
- Finish a range of interior diameter sizes without changing polisher

Self-centering polishers apply equal pressure to full wall of interior diameter. Spring-action design provides fast cleaning, deburring, and polishing of interior diameter of cylinders, deep tubes, and hydraulic fittings. Flaps adjust automatically to interior diameter, polishing the entire surface area with each pass. Equal spacing between packs of abrasive flaps eliminates heat buildup.

			FUNUUSE.		ILEIII
Series	Min. Inner Dia.	Max. Inner Dia.	Grit	Max. RPM	No.
Bore Polishers					
B-305	5⁄8 in	1 in	60, 80, 120, 180	25,000 RPM	H6015
B-405	1 in	1 ½ in	60, 80, 120, 180	22,000 RPM	H6016
B-410	1 ½ in	2 in	60, 80, 120, 180	20,000 RPM	H6017
B-8	5 1/4 in	5 % in	60	8,000 RPM	464P72
B-8	5 1/4 in	5 % in	180	8,000 RPM	464P73
B-8	5 ¼ in	5 % in	240	8,000 RPM	464P74
	Pilot Length		Mfr. Model		ltem No.
Extension Man	idrels, ¼ in Shank				
	4 in		0883415446		3RB59
	6 in		0883415418		3RB60
	8 in		0883415446	35	3RB61
Thre	ad			Mfr.	Item







MERIT

Spiral Bands

Spiral Bands and Expanding Rubber Drums

Fast-cutting spiral bands remove tough material. Achieve close tolerances when finishing curved, contoured, or hard-to-reach areas. Maximum rpm is determined by rpm rating of expanding rubber drum. Use rubber drums to provide backing support for spiral bands. Steel shank enables use of straight shaft and right-angle grinders.

Drum Sanding Kit includes 6 sizes of drums: $\frac{1}{2}$ " x $\frac{1}{2}$ ", $\frac{3}{4}$ " x 1", 1" x 1", $\frac{1}{2}$ " x $\frac{1}{2}$ ", $\frac{2}{3}$ " x 3", with 1 medium 80 grit and 1 fine 120 grit aluminum oxide abrasive sleeve to fit each drum size.

Dia.	w	CHOOSE:	Max. RPM	Item No.
Spira	I Band:	S		
½ in	½ in	120, 80, 50	30,000 RPM	H6030
3/4 in	1 in	80, 120, 50	17,000 RPM	H6031
1 in	1 in	36, 80, 120, 50	18,000 RPM	H6033
1½ in	1 ½ in	60, 36, 80	10,000 RPM	H6035
2 in	1 in	80, 120	11,000 RPM	H6037
3 in	3 in	36	3,000 RPM	3DV68
		Shank I	Max.	Item

Dia.	W	Size	RPM	No.
Expand	ding Rul	bber Dru		
3/4 in	1 in	1⁄4 in	17,000 RPM	3X040
1 in	1 in	1⁄4 in	18,000 RPM	3X042
1 ½ in	1 ½ in	1⁄4 in	10,000 RPM	3X044
2 in	1 in	1⁄4 in	11,000 RPM	3X046
3 in	3 in	3∕8 in	3,000 RPM	3X048
Drum Sand Rubbering Kit				
18-Pc	. Drum	Sanding	Kit	3DV67