

BOSTITCH Pneumatic Coil Roofing Nailer and Nails

Features depth-of-drive adjustment for added versatility. Has contact trip trigger and magnesium housing for durability. Features fixed exhaust, single-action canister, rubber housing pads that prevent sliding, and tool-free shingle gauge. Hardened nose with carbide inserts resists wear.



4Z782

Collation Angle	Collation Type	For Nail Length Range	For Nail Shank Diameter	Nail Cap.	Tool Weight	Brand	Mfr. Model	Item No.
Air-Powered Roofing Nailers								
15°	Wire	¾ in to 1 ¾ in	0.120 in	120	4.9 lb	Bostitch	RN46-1	4Z782
L	Mfr. Model	Item No.	Pkg. Qty.					
Roofing, Siding and Framing Nails				Senco Smooth, 0", 0.12 in Shank Dia.				
Bostitch Smooth, 15°, 0.12 in Shank Dia.								
1 ¼ in	CR2DGAL	5W012	7200	1 ¼ in	M003104	21U158	7200	
Senco Smooth, 15°, 0.12 in Shank Dia.								
1 ¼ in	CR3DGAL	2W762	7200	¾ in	M003101	48LR63	7200	
1 ½ in	CR4DGAL	2W763	7200	1 in	M003103	48LR65	7200	
1 ¾ in	CR5DGAL	2W764	7200	1 ½ in	M003105	48LR66	7200	
				1 ¾ in	M003106	48LR67	7200	



31CC52



48LR62



4Z931

BOSTITCH Pneumatic Coil Framing Nailers and Nails

■ Aluminum housing

Quick-driving nailers are easy to handle. 31CC52 includes 5mm and 6mm hex wrenches. 4Z931 has adjustable exhaust.

Collation Angle	Collation Type	For Nail Length Range	For Nail Shank Diameter	Nail Cap.	Tool Weight	Brand	Mfr. Model	Item No.
Air-Powered Framing Nailers								
15°	Wire	½ in to ¾ in	0.099 in to 0.130 in	300	8.2 lb	Speedaire	31CC52	31CC52
15°	Wire	¾ in to 1 ¼ in	0.120 in	120	5.2 lb	Senco	ROOFPRO 445XP	48LR62
15°	Wire	1 ½ in to 3 ¼ in	0.099 in to 0.120 in	300	8.4 lb	Bostitch	N80CB-1	4Z931
15°	Wire	2 in to 3 ½ in	0.099 in to 0.131 in	225 to 275	8 lb	Senco	SCN65XP	48LR11
L	Shank Dia.	Shank	Finish	Point Type	Mfr. Model	Item No.	Pkg. Qty.	
Bostitch, Wire Collation Type, 15° Collation Angle, Framing Nails								
2 in	0.099 in	Smooth	Coated	Diamond	C6P99D	5W014	3600	
2 ½ in	0.12 in	Smooth	Coated	Diamond	C8P120D	5W016	2700	
3 in	0.12 in	Smooth	Coated	Diamond	C10P120D	5W017	2700	
3 in	0.12 in	Smooth	Thickcoat Galvanized	Diamond	C10P120DG	3HZH6	2700	
3 ¼ in	0.12 in	Smooth	Coated	Diamond	C12P120D	5W018	2700	
3 ¼ in	0.12 in	Smooth	Thickcoat Galvanized	Diamond	C12P120DG	3HZH7	2700	
Bostitch, Wire Collation Type, 15° Collation Angle, Siding Nails								
2 ½ in	0.099 in	Ring	Coated	Blunt Diamond	C8R99BD	3HZJ3	3600	
2 ½ in	0.099 in	Ring	Thickcoat Galvanized	Blunt Diamond	C8R99BCG	3HZJ2	3600	



3HZF8



792UV8

BOSTITCH Pneumatic Coil Siding/Utility Nailers and Nails

Nailers drive wire and plastic-sheet collated nails and have adjustable depth of drive. 3HZF8 features tool-free adjustable exhaust and soft rubber foot.

Collation Angle	Collation Type	For Nail Length Range	For Nail Shank Diameter	Nail Cap.	Tool Weight	Brand	Mr. Model	Item No.
Air-Powered Siding Nailers								
15°	Wire	1 ¼ in to 2 ½ in	0.080 in to 0.092 in	300	4.7 lb	Bostitch	N66C-1	3HZF8
15°	Plastic, Wire	1 ¼ in to 2 1/2 in	0.082 in to 0.092 in	250 to 375	5.58 lb	Senco	SN71P1	792UV8
Length	Shank Dia.	Shank	Finish			Mr. Model	Item No.	Pkg. Qty.
Bostitch, Wire Collation, 15° Coil Siding/Utility Nails								
2 in	0.092 in	Ring	Thickcoat Galvanized			C6R90BDG	3HZH8	3600
2 ¾ in	0.09 in	Ring	Thickcoat Galvanized			C7R90BDG	3HZH9	3600
2 ½ in	0.09 in	Ring	Thickcoat Galvanized			C8R90BDG	3HZJ1	3600
Duo-Fast, Plastic Collation, 0° Coil Siding/Utility Nails								
1 ½ in	0.086 in	Ring	Hot Dipped Galvanized			650392	6KVX2	3600
2 ¼ in	0.092 in	Ring	Hot Dipped Galvanized			650394	6KVX3	3600
Senco 15° Full Round Shank Coil Siding/Utility Nails								
2 ¼ in	0.092 in	Smooth	Electro Galvanized			ED23AABH	48LP97	3600
2 ¼ in	0.092 in	Smooth	Hot Dipped Galvanized			EJ23ASBC	48LP98	3600
Senco 15° Ring Shank Coil Siding/Utility Nails								
1 ¾ in	0.092 in	Ring	Hot Dipped Galvanized			EL19ASBH	21U147	3600
2 in	0.092 in	Ring	Hot Dipped Galvanized			EL21ASBH	21U148	3600



48LP96

Pneumatic Pallet Nailer and Nails

Features high load capacity and an adjustable nail canister that accepts nails up to 2 ¼". Has a rugged driver and piston bumper for long life, and side steel wear plates for added housing protection. Ideal for boxes, crates, and pallet applications.

Collation Angle	Collation Type	For Nail Length Range	For Nail Shank Diameter	Nail Cap.	Tool Weight	Mfr. Model	Item No.
Air-Powered Pallet Nailer							
15°	Wire	1 ¼ in to 2 ¼ in	0.082 in to 0.092 in	300 to 350	5.9 lb	PALLETPRO57FXP	48LP96
Length	Shank Dia.	Shank	Finish	Point Type	Mfr. Model	Item No.	Pkg. Qty.
Wire Collation Type, 15° Collation Angle Framing Nails							
2 ¼ in	0.092 in	Ring	Hot Dipped Galvanized	Diamond	EL23ASBH	48LP99	3600