

Pneumatic Carton

Closing Stapler

and Staples





Powerful tool can handle hard and dense material, and provides added strength for larger butt joints. Suitable for joint fasten-

ing in box, crate, pallet, truss, and wood assembly.

For Staple Leg Length	Crown	Staple Cap.	Tool Weight	Mfr. Model	ltem No.
Corrugated Stap	ler				
1⁄4 in to 1⁄2 in	1 in	80	6.9 lb	SC2 SENCOR	48LR01
Leg Length	Crown	Gauge	Mfr. Mode	lten I No	
Staples					
1/4 in	1 in	25 ga	X04NR	A 48LR	03 8000
1/2 in	1 in	25 ga	X08NR	A 48LR	02 4000
3⁄8 in	1 in	25 ga	X06NR	A 48LR	04 5000

<u>Senco</u>

Crown

Crown Bostitc

7/32 in

Senco®

1⁄4 in

SENCO


16-Ga. Construction Staples

Chisel point staples can be used with a variety of stapler brands and models.

L



Pkg. Qty.



	1 ½ in	Bright	N17BRB	21U152 10000
	1 ½ in	Class 1 Galvanized	N17BAB	21U153 10000
7⁄16 in	1 1/4 in	Electro Galvanized	N15BAB	48LR28 10000
	2 in	Class 1 Galvanized	N21BAB	21U154 10000
	2 in	Bright	N21BRB	21U155 10000
	5⁄8 in	Class 1 Galvanized	P10BAB	21U156 10000
	3⁄4 in	Electro Galvanized	P11BAB	48LR24 10000
1 in	1 1/4 in	Class 1 Galvanized	P15BAB	21U157 10000
	1 1/2 in	Electro Galvanized	P17BAB	48LR26 10000
	1 in	Galvanized	P13BAB	485W37 10000
	2 in	Electro Galvanized	P21BAB	48LR27 5000

BOSTITCH SENCO

18-Ga. Finish Staples

Staples can be used with a variety of stapler brands and models.

Air Tapping Arms



n	L	Finish	Point Type	Mfr. Model	ltem No.	Pkg. Qty.
:h®						
	1⁄2 in	Coated	Chisel	SX50351/2G-7M	3RCY7	7000
	3⁄4 in	Coated	Chisel	SX5035 3/4G	4WL11	5000
1	1 in	Coated	Chisel	SX50351G	4YF10	5000
	1 1/4 in	Coated	Chisel	SX5035 1-1/4G	4YF08	3000
	1 ¾ in	Coated	Chisel	SX50351-3/8G	4WL09	3000
9						
	1 in	Galvanized	Chisel	L13BABN	21U149	5000
	1 ¼ in	Galvanized	Chisel	L15BAB	21U150	5000
	1 ½ in	Galvanized	Chisel	L17BAB	210151	5000

Arms support the weight of their tapping tool and absorb torque to reduce user fatigue and injuries, especially when performing repetitive actions. They position the tool at the end of the arm and balance it for a weightless effect when swiveling the tool or moving it up, down, back, and forth. The tool holds a range of tap sizes to cut different thread sizes. These arms mount to a worktable, cart, or other flat surface.

Re Max.	ach Min.	Max. Tap Steel	ping Capacity Aluminum	Included Tap Holder Sizes	Tool Holder Size	Free Speed	Air Consumption	ltem No.
Baileigh		SIEEI	Aluminum	Included Tap Holder Sizes	noiuer Size	Sheen	Consumption	NU.
33.3 in	3.9 in	1 in	1 in	1/4 in, 3/8 in, 1/2 in, 5/8 in, 3/4 in, 7/8 in	_	220 RPM	16 cfm	36HZ21
75 in	7.8 in	1 in	1 in	1/4 in, 3/8 in, 1/2 in, 5/8 in, 3/4 in, 7/8 in	_	220 RPM	16 cfm	36HZ22
Flexarm								
34 in	11 in	1/2 in	9⁄16 in	_	Size 1	400 RPM	24 cfm	33NY36
51 in	14 in	1/2 in	9⁄16 in	_	Size 1	400 RPM	24 cfm	33NY37
Palmgren								
37 in	4 in	1/2 in	9⁄16 in	_	Size 1	400 RPM	24 cfm	4WXT8
43 in	4 in	3% in	1/2 in	_	Size 1	700 RPM	24 cfm	4WXT9
57 in	22.5 in	3% in	1/2 in	_	Size 1	700 RPM	24 cfm	4WXU2
57 in	22.5 in	1/2 in	9⁄16 in	<u> </u>	Size 1	400 RPM	24 cfm	4WXU1



Pneumatic 16-Ga. **Construction Staplers** Staples are sold separately, this page.

SPEEDAIRE

SENCO

Senco-allows fast multidirectional stitching and has EZ-Clear feature that reduces downtime due to fastener jams.

Speedaire—Features a top-loading magazine for fast loading and adjustable depth control. Tool has a 360° adjustable exhaust port and a comfortable rubber handle.

%i 1 in 12 in 160 4.6 lb Senco SNS41 48LR68 1 in ½ in 160 5.5 Ib Speedaire 31CC54 31CC54	Crown Staple Gun	For Staple Leg Length	Staple Cap.	Tool Weight	Brand	Mfr. Model	ltem No.
1 in ½ in to 1 ½ in 160 5.5 lb Speedaire 31CC54 31CC54		1 in to 2 in	160	4.6 lb	Senco	SNS41	48LR68
	1 in	½ in to 1 ½ in	160	5.5 lb	Speedaire	31CC54	31CC54

BOSTITCH PORTER 🔂 CABLE

Pneumatic 18-Ga. **Finish Staplers**

Bostitch—Tool-free access to drive channel, over-molded grip, dry-fire lockout, and rear exhaust. Oil-free. Fastener is sequential-trip release.



Porter Cable-Features toolless depth-of-drive adjustment and split nose design, helps removal of jammed staples. Convenient low staple reload indicator alerts you when to reload magazine. Magnesium body.

Crown	For Staple Leg Length	Staple Cap.	Tool Weight	Brand	Mfr. Model	ltem No.	
7/32 in	1/2 in to 11/2 in	100	3 lb	Bostitch	SX1838K	3FWY4	
1⁄4 in	1/2 in to 1 1/2 in	100	2.6 lb	Porter Cable	NS150C	45YJ65	

Fuel Actuated @ Ramset Cordless Pin Na

Cordless Tool Kit Contents: Bare Tool, (1) Battery, (1) C

Powered by a compatible Ramset 6V battery and fuel cell. Fuel cells contain combustible gas that the nailers use to generate force for driving nails. They provide driving power that is comparable to air-powered nailers. Nail guns hold nail strips or coils that feed nails one after the other to speed installation in framing. roofing, cabinetry, and flooring applications. Magnetic Pin Guide

ailer (1) Charger			787	MF8
For Nail Shank Diameter	For Nail Length Range	Includes	Mfr. Model	ltem No.
Pin Nailers, 6 V				
0.104 in to 0.125 in	1⁄4 in to 1 1⁄2 in	Safety Glasses	T4SS	787MF8
0.125 in	1 in	Safety Glasses	T4MAG	787MF9
Description	Fo	or Use With	ltem No.	ı Pkg. Qty.
Accessories				
Cup		Extension Po		
Fuel Cell	<u>T4 I-F</u>	, T4MAG, T4S	S 787M	
Battery		T4MAG, T4S	S 787M	
Magnetic Pin Gu	ide Ra	amset T4SS	787M	Li4 1



Sign in to Grainger.com[®] to see YOUR Pricing and MORE