



Mounted Points

- Use on die or in-line/straight shaft grinders
- Max. RPM based on 1/2" overhang

Quantum® Vitrified—Best for high-volume operation.
Ceramic alumina abrasive.

Gemini® Vitrified—Aluminum oxide abrasive 38A in a vitrified bond.

No. of Pieces	Spindle Dia.	Includes	Brand	Item No.
Vitrified Mounted Point Kits				
50	1/8 in	(5) B42, B52, B97, B131, B122, W154, W164, W185, W215, and W163	Norton	2LRJ9
	1/4 in	(5) A1, A5, A11, A23, A21, A26, A36, A39, W242, and W220	Norton	2LRJ8
	3/4 in	(5) B42, B52, B97, B122, B131, W154, W164, W185, W215, W163 A80-HBF3	Norton	4DDV6

Shape	Dia.	Thick-ness	Spindle Dia.	Max. RPM	Grit	Item No.
Quantum® Vitrified Mounted Points						
A1	3/4 in	2 1/2 in	1/4 in	20	80	15K091
A11	7/8 in	2 in	1/4 in	20	80	15K092
A12	1 1/4 in	1 1/4 in	1/4 in	48	60	15K075
A21	1 in	1 in	1/4 in	35	80	15K094
A23	3/4 in	1 in	1/4 in	39	80	15K093
A25	1 in	—	1/4 in	36	80	15K076
A26	3/8 in	—	1/4 in	61	80	15K095
A36	1 3/8 in	3/8 in	1/4 in	24	80	15K096
A38	1 in	1 in	1/4 in	35	80	15K077
A39	3/4 in	3/4 in	1/4 in	47	80	15K097
B42	1/2 in	3/4 in	1/8 in	34	80	15K082
B52	3/8 in	3/4 in	1/8 in	45	80	15K083
B97	3/8 in	3/8 in	1/8 in	105	80	15K084
B122	3/8 in	—	1/8 in	62	80	15K086
B131	3/8 in	—	1/8 in	35	80	15K085
W154	3/16 in	3/2 in	1/8 in	71	80	15K087
W164	1/2 in	3/4 in	1/8 in	46	80	15K088
W185	1/2 in	1/2 in	1/8 in	35	80	15K089
W189	1/8 in	2 in	1/4 in	24	80	15K078
W208	3/4 in	2 in	1/4 in	23	80	15K079
W215	1 in	1/8 in	1/8 in	38	80	15K090
W220	1 in	1 in	1/4 in	26	80	15K080
W236	1 1/2 in	1/2 in	1/4 in	25	80	15K081
Gemini® Vitrified Mounted Points						
Norton						
A1	3/4 in	2 1/2 in	1/4 in	20	36	4F758
A1	3/4 in	2 1/2 in	1/4 in	20	60	4F759
A3	1 in	2 3/4 in	1/4 in	16	36	4F760
A3	1 in	2 3/4 in	1/4 in	16	60	4F761
A4	1 1/4 in	1 1/4 in	1/4 in	31	60	2D821
A5	3/4 in	1 1/8 in	1/4 in	45	60	2D822
A5	3/4 in	1 1/8 in	1/4 in	45	36	4F762
A11	7/8 in	2 in	1/4 in	20	60	2D823
A11	7/8 in	2 in	1/4 in	20	36	4F763
A12	1 1/4 in	1 1/4 in	1/4 in	48	36	4F764
A12	1 1/4 in	1 1/4 in	1/4 in	48	60	4F765
A13	1 3/8 in	1 1/4 in	1/4 in	34	60	4F766
A14	1 1/4 in	7/8 in	1/4 in	56	60	4F767
A15	3/4 in	1 1/8 in	1/4 in	73	60	2D824
A21	1 in	1 in	1/4 in	35	60	2D825
A23	3/4 in	1 in	1/4 in	39	60	2D826
A24	1/2 in	3/4 in	1/4 in	77	60	2D827

Shape	Dia.	Thick-ness	Spindle Dia.	Max. RPM	Grit	Item No.
Quantum® Vitrified Mounted Points						
A25	1 in	Ball	1/4 in	36	60	4F769
A26	3/8 in	Ball	1/4 in	61	60	2D828
A31	1 3/8 in	1 in	1/4 in	28	60	4F771
A34	1 1/2 in	3/8 in	1/4 in	25	60	2D830
A36	1 1/2 in	3/8 in	1/4 in	24	60	2D831
A37	1 1/4 in	1/4 in	1/4 in	31	60	2D832
A38	1 in	1 in	1/4 in	35	60	4F773
A39	3/4 in	3/4 in	1/4 in	47	60	2D833
B41	3/8 in	3/8 in	1/8 in	34	60	2D835
B42	1/2 in	3/4 in	1/8 in	34	60	2D836
B43	1/4 in	3/8 in	1/8 in	81	60	2D837
B44	3/8 in	3/8 in	1/8 in	68	60	2D838
B45	3/8 in	3/8 in	1/8 in	104	60	2D839
B46	1/2 in	3/8 in	1/8 in	105	60	2D840
B51	3/8 in	3/4 in	1/8 in	45	60	15K114
B52	3/8 in	3/4 in	1/8 in	45	60	2LRK2
B52	3/8 in	3/4 in	1/4 in	45	60	4F774
B52	3/8 in	3/4 in	1/8 in	45	90	15K115
B53	3/8 in	3/8 in	1/8 in	60	60	2D841
B54	1/2 in	1/2 in	1/8 in	60	60	2D842
B55	1/2 in	1/4 in	1/8 in	105	60	2D843
B81	3/4 in	3/8 in	1/8 in	51	60	2D846
B91	1/2 in	3/8 in	1/8 in	35	60	2D848
B96	1/8 in	1/4 in	1/8 in	105	60	2D852
B96	1/8 in	1/4 in	1/8 in	105	90	15K116
B97	1/8 in	3/8 in	1/8 in	105	60	2D850
B98	3/8 in	1/4 in	1/8 in	105	60	2D853
B121	1/2 in	Ball	1/8 in	45	60	15K117
B122	3/8 in	Ball	1/8 in	62	60	2D856
B122	3/8 in	Ball	1/8 in	62	90	15K118
A71	3/8 in	Ball	1/8 in	104	60	2D857
B124	1/2 in	Ball	1/8 in	105	90	15K119
B131	1/2 in	1/2 in	1/8 in	35	60	2D859
B132	3/8 in	1/2 in	1/8 in	45	60	2D860
B133	3/8 in	3/8 in	1/8 in	54	60	2D861
B134	3/8 in	3/8 in	1/8 in	62	60	4F779
B135	1/4 in	1/2 in	1/8 in	60	60	2D862
W144	1/8 in	1/4 in	1/8 in	105	60	2D865
W145	1/8 in	3/8 in	1/8 in	105	60	2D866
W146	1/8 in	1/2 in	1/8 in	105	60	2D867
W152	3/8 in	1/4 in	1/8 in	105	60	2D868
W153	3/8 in	3/8 in	1/8 in	81	60	2D869
W154	3/8 in	1/2 in	1/8 in	71	60	2D870
W160	1/2 in	1/4 in	1/8 in	81	60	4F780

Cotton Fiber—Ideal for blending and finishing parts without changing part geometry. Aluminum oxide abrasive.

Charger® Resin—Made of self-sharpening zirconia alumina abrasive.



Shape	Dia.	Thick-ness	Spindle Dia.	Max. RPM	Grit	Item No.
W162	1/4 in	3/8 in	1/8 in	68	60	2D871
W163	1/4 in	1/2 in	1/8 in	60	60	2D872
W164	1/4 in	3/4 in	1/8 in	46	60	2D873
W170	3/4 in	1/2 in	1/8 in	53	60	2D875
W175	3/8 in	3/8 in	1/8 in	54	60	2D876
W176	3/8 in	1/2 in	1/8 in	45	60	4F781
W177	3/8 in	3/4 in	1/8 in	34	60	2D877
W178	3/8 in	1 in	1/8 in	26	60	2D878
W185	1/2 in	1/2 in	1/8 in	35	60	2LRK3
W185	1/2 in	1/2 in	1/4 in	35	60	4F782
W186	1/2 in	3/4 in	1/4 in	51	60	2D880
W188	1/2 in	1 1/2 in	1/4 in	30	60	2D882
W189	1/2 in	2 in	1/4 in	24	60	2D883
W196	3/8 in	1 in	1/4 in	35	60	2D885
W200	3/4 in	1/8 in	1/8 in	51	60	2D887
W200	3/4 in	1/8 in	1/8 in	51	90	15K120
W204	3/4 in	3/4 in	1/4 in	43	60	2D888
W205	3/4 in	1 in	1/4 in	35	60	2D889
W208	3/4 in	2 in	1/4 in	23	60	2D892
W215	1 in	1/8 in	1/8 in	38	60	2D893
W216	1 in	1/4 in	1/4 in	38	60	15K121
W218	1 in	1/2 in	1/4 in	38	60	2D896
W220	1 in	1 in	1/4 in	26	60	4F785
W221	1 in	1 1/2 in	1/4 in	19	60	2D897
W222	1 in	2 in	1/4 in	16	60	2D898
W230	1 1/4 in	1 1/4 in	1/2 in	20	60	2D902
W235	1 1/2 in	3/4 in	1/4 in	25	60	2D903
W236	1 1/2 in	1/2 in	1/4 in	25	60	4F787
W237	1 1/2 in	1 in	1/4 in	23	60	2D904
W238	1 1/2 in	1 1/2 in	1/4 in	16	60	2D905
W242	2 in	1 in	1/4 in	19	60	2D906
Cotton Fiber Mounted Points						
Norton						
W163	1/4 in	1/2 in	1/8 in	60	80	2LRK4
W220	1 in	1 in	1/4 in	26	80	2LRK1
Charger® Resin Mounted Points						
Norton						
A1	3/4 in	2 1/2 in	1/4 in	20	30	3UN58
A3	1 in	2 3/4 in	1/4 in	16	30	3UN59
A5	3/4 in	1 1/4 in	1/4 in	45	30	3UN60
A11	7/8 in	2 in	1/4 in	20	30	3UN61
W189	1/2 in	2 in	1/4 in	24	30	3UN62
W207	3/4 in	1 1/2 in	1/4 in	24	30	3UN64
W220	1 in	1 in	1/4 in	26	30	6PC06
W221	1 in	1 1/2 in	1/4 in	19	30	3UN66
W222	1 in	2 in	1/4 in	16	30	3UN67
Aluminum Oxide Mounted Points						
Approved Vendor						
A3	1 in	2 3/4 in	1/4 in	11	60	447T13
A12	1 1/4 in	1 1/4 in	1/4 in	27	60	447T12
B52	3/8 in	3/4 in	1/8 in	21	60	447T14
B53	3/8 in	3/8 in	1/8 in	26	60	447T09
B121	1/2 in	1/2 in	1/8 in	21	60	447T15
B122	3/8 in	3/8 in	1/8 in	27	60	447T11