



Dual-Pedestal Air or Water Spring-Return Hose Reels

- Hose Included
- Max. operating pressure: 300 psi
- Red reel color
- Nickel-plated steel swivel

Include a reinforced dual-pedestal base and guide arm to reduce vibration during use. Feature an all-steel construction with a baked-on powder-coated finish for corrosion resistance. Low-pressure, compact reels mount on a wall or on the ceiling. Dual-pedestal hose reels and air or water hoses are commonly used in manufacturing facilities, auto or fleet service centers, and food and chemical processing.



5KPA6



2CAG5

Hose Cap.	Hose End Configuration	Overall Dim.	Item No.
35 ft (3/4 in I.D.)	1/4 in MNPT	14 3/4 in L x 8 in W x 16 3/4 in H	5KPA6
35 ft (1/2 in I.D.)	3/8 in MNPT x 1/4 in MNPT	14 3/4 in L x 9 in W x 16 3/4 in H	5KPA8
50 ft (1/4 in I.D.)	1/4 in MNPT	14 3/4 in L x 8 in W x 16 3/4 in H	5KPA5
50 ft (3/8 in I.D.)	1/4 in MNPT	16 1/2 in L x 8 in W x 17 in H	2CAG5
50 ft (1/2 in I.D.)	3/8 in MNPT	16 1/2 in L x 9 in W x 17 in H	2CAG6



Air or Water Combination Spring-Return Hose Reels

- Max. operating pressure: 300 psi
- Blue reel color
- Brass swivel

Items combine two hose reels in one unit where each reel and hose operates independently and can carry air in one hose, water in the other hose. Combination hose reels are used where two hoses are needed to complete a job and where space is limited. The heavy-duty steel, single-mount base provides stability and is powder-coated for corrosion resistance. Two external fluid paths include 90° full-flow NPT swivel inlets and nitrile seals. Low-pressure reels mount on a wall, floor, or overhead with one mounting pattern to save installation time, and include adjustable guide arms. Reels connect air or water hoses to pneumatic tools, with air/water services, and in washdown applications.



5FZW5



29PX34

Hose Cap.	Hose End Configuration	Overall Dim.	Item No.
Hose Included			
25 ft (1/2 in ID)	1/2 in MNPT x 1/2 in MNPT	17 in L x 10 1/2 in W x 18 3/4 in H	5FZW8
25 ft (3/8 in ID)	3/8 in MNPT x 3/8 in MNPT		5FZW6
50 ft (1/4 in ID)	1/4 in MNPT x 1/4 in MNPT		5FZW5
50 ft (3/8 in ID)	3/8 in MNPT x 3/8 in MNPT		5FZW7
Hose Not Included			
25 ft (3/8 in ID)		17 in L x 10 1/2 in W x 18 3/4 in H	29PX32
25 ft (1/2 in ID)			29PX35
50 ft (1/4 in ID)			29PX31
50 ft (3/8 in ID)			29PX34



Base Frame Air or Water Spring-Return Hose Reels

- Nickel plated steel swivel

Reels include full-width frames for stable mounting on portable surfaces, for permanent service, or in plant work areas. Low-pressure, powder-coated steel reels resist corrosion and hold shorter lengths of larger diameter hose. Base frame spring-return hose reels and air or water hoses are commonly used for bulk handling, fuel delivery, and construction operations.



4NA94



29RD69

Hose Cap.	Hose End Configuration	Max. Operating Pressure	Overall Dim.	Reel Color	Brand	Item No.
Hose Included						
50 ft (3/4 in I.D.)	3/4 in MNPT	250 psi	26 1/4 in L x 16 3/4 in W x 26 3/4 in H	Red	Reelcraft	184V93
50 ft (1 in I.D.)	3/4 in MNPT	250 psi	26 1/4 in L x 12 in W x 26 3/4 in H	Red	Reelcraft	2CAH7
75 ft (3/4 in I.D.)	3/4 in MNPT	250 psi	26 1/4 in L x 12 in W x 26 3/4 in H	Red	Reelcraft	4NA94
100 ft (3/4 in I.D.)	3/4 in MNPT	250 psi	26 1/4 in L x 12 in W x 26 3/4 in H	Red	Reelcraft	2CAH6
100 ft (1 in I.D.)	3/4 in MNPT	300 psi	26 3/4 in L x 19 3/4 in W x 24 1/2 in H	Blue	Coxreels	29RD56
Hose Not Included						
50 ft (1 in I.D.)	—	300 psi	26 3/4 in L x 19 3/4 in W x 24 1/2 in H	Blue	Coxreels	29RD69