

**BAND-IT®**

**Light-Duty Buckle-On Band Clamps**

■ Center-punch band clamp type

Installed and tightened with a clamping tool that has a built-in conical punch. The integrated buckle is locked by striking the punch with a hammer. They are suitable for hoses in non-pressurized applications and are not recommended for use with plastic fittings that could crack.

Clamping Diameter	Band Width	Band Thickness	Item No.	Pkg. Qty.
<b>Galvanized Steel Band</b>				
<b>201 Stainless Steel Closure</b>				
3/4 in	3/8 in	0.025 in	2LPD2	10
3/4 in - 1 in	3/8 in	0.025 in	2LPD3	10
<b>316 Stainless Steel Closure</b>				
3/8 in - 1 1/8 in	3/8 in	0.025 in	2LPF3	10
3/4 in - 1 1/4 in	3/8 in	0.025 in	2LPD5	10
3/4 in - 1 3/4 in	3/8 in	0.025 in	2LPD6	10
3/4 in - 2 in	3/8 in	0.025 in	2LPD7	10
3/4 in - 2 1/2 in	3/8 in	0.025 in	2LPD9	10
3/4 in - 2 3/4 in	3/8 in	0.025 in	2LPF1	10
3/4 in - 3 3/4 in	3/8 in	0.025 in	2LPF2	10
1 in - 3 3/4 in	3/8 in	0.025 in	6YP24	10
1 in - 4 1/4 in	3/8 in	0.025 in	6YP26	10
1 in - 4 3/4 in	3/8 in	0.025 in	5DLG2	10
1 in - 5 3/4 in	3/8 in	0.025 in	5DLG4	10
1 in - 6 3/4 in	3/8 in	0.025 in	5DLG6	10
1 in - 7 3/4 in	3/8 in	0.025 in	5DLG8	10

<b>201 Stainless Steel Band</b>				
<b>316 Stainless Steel Closure</b>				
3/8 in	3/8 in	0.025 in	2LPF4	10
3/4 in	3/8 in	0.025 in	2LPF5	10
3/8 in - 1 1/8 in	3/8 in	0.025 in	2LPG6	10
3/4 in - 1 in	3/8 in	0.025 in	2LPF6	10
3/4 in - 1 1/2 in	3/8 in	0.025 in	2LPF8	10
3/4 in - 2 1/2 in	3/8 in	0.025 in	2LPG3	10
1 in - 3 3/4 in	3/8 in	0.025 in	6YP25	10
1 in - 4 1/4 in	3/8 in	0.025 in	6YP27	10
1 in - 5 3/4 in	3/8 in	0.025 in	5DLG5	10
1 in - 6 3/4 in	3/8 in	0.025 in	5DLG7	10
1 in - 7 3/4 in	3/8 in	0.025 in	5DLG9	10

**BAND-IT®**

**Medium-Duty Buckle-On Band Clamps**

■ Lip-lock band clamp type

Has a lip-lock buckle and a smooth inside surface that reduces the risk of leaks on thin-walled hose. They are installed with a clamping tool that pushes levers down on the clamp to lock it without hammering or crimping.

Clamping Diameter	Band Width	Band Thickness	Item No.	Pkg. Qty.
<b>Galvanized Steel Band</b>				
<b>201 Stainless Steel Closure</b>				
1 1/8 in - 1 3/8 in	3/8 in	0.03 in	5DLH9	24
1 1/8 in - 1 7/8 in	3/8 in	0.03 in	5DLJ0	24
1 1/8 in - 2 1/8 in	3/8 in	0.03 in	6YRA3	24
1 1/8 in - 2 3/8 in	3/8 in	0.03 in	6YRA4	24
1 1/4 in - 1 1/2 in	3/8 in	0.03 in	2PLA2	24
1 3/4 in - 4 3/4 in	3/4 in	0.03 in	2PLJ7	16
<b>316 Stainless Steel Closure</b>				
3/8 in	3/8 in	0.025 in	2LPH9	24
7/8 in	1/2 in	0.03 in	5DLH7	24
3/8 in - 1 1/8 in	3/8 in	0.025 in	2LPJ1	24

<b>201 Stainless Steel Band</b>				
<b>316 Stainless Steel Closure</b>				
1 1/8 in - 2 1/8 in	3/8 in	0.03 in	6YRA0	24
1 1/8 in - 2 3/8 in	3/8 in	0.03 in	6YRA1	24
1 1/8 in - 4 1/4 in	3/4 in	0.03 in	6YRA2	16
1 3/4 in - 3 3/4 in	3/4 in	0.03 in	2LPH4	24
1 3/4 in - 3 3/4 in	3/4 in	0.03 in	2LPH5	16
1 3/4 in - 5 3/4 in	3/4 in	0.03 in	2LPH7	16

<b>316 Stainless Steel Closure</b>				
3/8 in	3/8 in	0.025 in	2LPG8	24
3/8 in - 1 1/8 in	3/8 in	0.025 in	2LPG9	24
3/8 in - 1 3/8 in	1/4 in	0.02 in	5DLH6	50
1 in - 1 1/8 in	1/2 in	0.03 in	5DLH1	24
1 in - 1 1/2 in	1/2 in	0.03 in	5DLH2	24
1 1/4 in - 1 3/8 in	3/8 in	0.03 in	5DLH3	24
1 1/4 in - 1 1/2 in	3/8 in	0.03 in	2LPH1	24
1 1/4 in - 1 7/8 in	3/8 in	0.03 in	5DLH4	24
1 1/4 in - 2 1/4 in	3/8 in	0.03 in	2LPH2	24
1 3/4 in - 2 1/2 in	3/4 in	0.03 in	2LPH3	24

**BAND-IT®**

**Heavy-Duty Buckle-On Band Clamps**

■ Slotted-Lock band clamp type

Has a reinforced buckle and thick band for a strong hold. They are installed with a powered clamping tool for quick fastening. These clamps are suitable for high pressure applications.

Clamping Diameter	Band Width	Band Thickness	Item No.	Pkg. Qty.
<b>201 Stainless Steel Band</b>				
<b>201 Stainless Steel Closure</b>				
2 in - 1 3/4 in	3/4 in	0.03 in	802LX2	100
2 in - 2 1/2 in	3/4 in	0.03 in	802LW2	50
2 in - 2 3/4 in	3/4 in	0.03 in	802LW3	50
2 in - 3 1/4 in	3/4 in	0.03 in	802LW4	50
2 in - 3 3/4 in	3/4 in	0.03 in	802LW5	25
2 in - 4 1/4 in	3/4 in	0.03 in	802LW6	25
2 in - 4 3/4 in	3/4 in	0.03 in	802LW7	25
2 in - 5 1/4 in	3/4 in	0.03 in	802LX4	25
2 in - 5 3/4 in	3/4 in	0.03 in	802LW8	25
2 in - 6 1/2 in	3/4 in	0.03 in	802LW9	25
2 in - 6 3/4 in	3/4 in	0.03 in	802LX0	25
2 in - 7 3/4 in	3/4 in	0.03 in	802LX1	25
2 in - 8 3/4 in	3/4 in	0.03 in	802LX3	10
2 3/4 in - 3 3/4 in	3/4 in	0.03 in	2LPL3	12
2 3/4 in - 4 3/4 in	3/4 in	0.03 in	2LPL4	12
2 3/4 in - 5 3/4 in	3/4 in	0.03 in	2LPL5	12
2 3/4 in	3/4 in	0.03 in	2LPL2	12
4 in	3/4 in	0.03 in	802LV9	33
6 in	3/4 in	0.03 in	802LW0	25
8 1/2 in	3/4 in	0.03 in	802LW1	17
<b>304 Stainless Steel Closure</b>				
2 3/4 in - 6 3/4 in	3/4 in	0.03 in	2LPL6	12
2 3/4 in - 7 3/4 in	3/4 in	0.03 in	2LPL7	12
2 3/4 in - 8 3/4 in	3/4 in	0.03 in	2LPL8	8



**Jaw Pincers**

Used to close ear clamps. Made of forged steel.

Description	Length	Item No.
Standard Jaw Pincers	8 7/8 in	4E607



**Hose Clamp Assortments**

See Grainger.com for assortment contents.

No. of Sizes	Number of Clamps	Band Material	Brand	Item No.
<b>Worm Gear Hose Clamp Assortment</b>				
8	19	Stainless Steel	—	802UL1
8	26	Steel	—	802UL2
<b>Single Ear Hose Clamp Assortment</b>				
8	81	Stainless Steel	Oetiker	2PU26
<b>Double Ear Hose Clamp Assortment</b>				
9	124	Steel	Oetiker	4TX96



Double-Ear Clamp

Constant-Tension Single-Ear Clamps



**Crimp-On Ear Clamps**

**Double-ear clamps** have two ear-shaped protrusions to crimp and provide more clamping range than single-ear clamps. They require a crimping tool, such as pincer pliers, to install. These clamps are suitable for industrial air or fluid line applications.

**Constant-tension clamps** have one ear-shaped protrusion with a dimple that increases the clamping force on the ear. The clamp has a spring effect that compensates for thermal expansion to exert continuous pressure around the clamp's diameter. They require a crimping tool, such as pincer pliers, to install. They are suitable for flexible plumbing lines.

Clamping Diameter	Band Width	Band Thickness	Maximum Closing Force	Item No.
<b>Double-Ear Clamps</b>				
<b>Zinc-Plated Steel</b>				
1/8 in - 3/8 in	3/8 in	0.02 in	2,500 N	3DUL9
3/8 in - 1/2 in	3/8 in	0.026 in	2,500 N	3DUN2
1/2 in - 5/8 in	3/8 in	0.028 in	2,500 N	4E595
5/8 in - 3/4 in	3/8 in	0.039 in	2,500 N	4E596
3/4 in - 7/8 in	3/8 in	0.039 in	2,500 N	4E597
7/8 in - 3/4 in	3/8 in	0.039 in	2,500 N	4E598
3/4 in - 1 1/8 in	3/8 in	0.039 in	2,500 N	4E599
3/4 in - 1 1/4 in	3/8 in	0.047 in	2,500 N	3DUN3
1 1/8 in - 1 1/2 in	3/8 in	0.047 in	2,500 N	4E600
1 1/4 in - 1 3/4 in	3/8 in	0.059 in	2,500 N	4E601
1 3/4 in - 1 7/8 in	3/8 in	0.059 in	3,100 N	3DUN4
1 7/8 in - 2 in	3/8 in	0.059 in	3,100 N	4E602
2 in - 2 1/8 in	3/8 in	0.059 in	3,100 N	3DUN5
2 1/8 in - 2 1/4 in	3/8 in	0.059 in	3,100 N	4E603
2 1/4 in - 2 3/8 in	3/8 in	0.059 in	3,100 N	3DUN6
2 3/8 in - 2 1/2 in	3/8 in	0.059 in	3,100 N	3DUN7
2 1/2 in - 2 3/4 in	3/8 in	0.059 in	3,100 N	3DUN8
2 3/4 in - 2 7/8 in	3/8 in	0.059 in	3,100 N	3DUN9
2 7/8 in - 3 in	3/8 in	0.059 in	3,100 N	3DUP2
3 in - 3 1/8 in	3/8 in	0.059 in	3,100 N	4E604
<b>304 Stainless Steel</b>				
1/8 in - 3/8 in	3/8 in	0.024 in	2,500 N	4E583
3/8 in - 1/2 in	3/8 in	0.031 in	2,500 N	3DUP3
1/2 in - 5/8 in	3/8 in	0.024 in	2,500 N	4E585
5/8 in - 3/4 in	3/8 in	0.024 in	2,500 N	4E586
3/4 in - 7/8 in	3/8 in	0.024 in	2,500 N	4E587
7/8 in - 1 in	3/8 in	0.031 in	2,500 N	3DUP4
1 in - 1 1/8 in	3/8 in	0.024 in	2,500 N	4E588
1 1/8 in - 1 1/4 in	3/8 in	0.024 in	2,500 N	4E589
1 1/4 in - 1 3/8 in	3/8 in	0.039 in	3,600 N	3DUP5
1 3/8 in - 1 1/2 in	3/8 in	0.024 in	3,600 N	4E590
1 1/2 in - 1 5/8 in	3/8 in	0.024 in	3,600 N	4E591
1 5/8 in - 2 in	3/8 in	0.039 in	3,600 N	3DUP7
2 in - 2 1/8 in	3/8 in	0.024 in	3,600 N	4E592
<b>Constant-Tension Single-Ear Clamps</b>				
<b>304 Stainless Steel</b>				
1/8 in - 3/8 in	3/8 in	0.02 in	1,000 N	5EFC5
3/8 in - 1/2 in	3/8 in	0.02 in	1,000 N	5EFC7
1/2 in - 5/8 in	3/8 in	0.02 in	1,000 N	5EFC8
5/8 in - 3/4 in	3/8 in	0.024 in	2,100 N	3DUP8
3/4 in - 7/8 in	3/8 in	0.024 in	2,100 N	5EFD1
7/8 in - 1 in	3/8 in	0.024 in	2,100 N	3DUP9
1 in - 1 1/8 in	3/8 in	0.024 in	2,100 N	5EFD2
1 1/8 in - 1 1/4 in	3/8 in	0.024 in	2,100 N	5EFD3
1 1/4 in - 1 3/8 in	3/8 in	0.024 in	1,100 N	3DUR1
1 3/8 in - 1 1/2 in	3/8 in	0.024 in	2,100 N	4E572
1 1/2 in - 1 5/8 in	3/8 in	0.024 in	2,101 N	4E573
1 5/8 in - 2 in	3/8 in	0.024 in	2,100 N	3DUR4
2 in - 2 1/8 in	3/8 in	0.024 in	2,102 N	4E574
2 1/8 in - 2 1/4 in	3/8 in	0.024 in	1,100 N	3DUR6
2 1/4 in - 2 3/8 in	3/8 in	0.031 in	2,800 N	40PR12
2 3/8 in - 2 1/2 in	3/8 in	0.024 in	2,103 N	4E575
2 1/2 in - 2 3/4 in	3/8 in	0.024 in	2,400 N	5EFD4
2 3/4 in - 2 7/8 in	3/8 in	0.024 in	2,400 N	53AZ35
2 7/8 in - 3 in	3/8 in	0.024 in	2,400 N	53AZ34
3 in - 3 1/8 in	3/8 in	0.031 in	4,100 N	40PR09
3 1/8 in - 3 1/4 in	3/8 in	0.024 in	2,400 N	5EFD6
3 1/4 in - 3 1/2 in	3/8 in	0.039 in	7,000 N	40PR11
3 1/2 in - 3 3/4 in	3/8 in	0.024 in	2,400 N	5EFD7
3 3/4 in - 4 in	3/8 in	0.024 in	2,100 N	5EFD8