

Dayton

30mm Nonilluminated Push Buttons—Complete Units

■ NEMA 4 and 13 rated Direct-acting operation. UL Listed. CSA and CE Certified.

	► CHOOSE: Type of Operator	► CHOOSE: Color	► CHOOSE: Head Material	Contact Form	Item No.
Momentary Push					
Flush Button; Extended Button		Red; Green; Universal; Black	Metal Plastic	1NO/1NC 1NO/1NC	H7067 H7071
57mm Mushroom Head; 40mm Mushroom Head		Green; Black; Red	Metal; Plastic	1NC	H7085
Maintained Push / Maintained Pull					
40mm Mushroom Head		Red; Green; Black	Metal; Plastic	1NO/1NC	H7094



Dayton

30mm Selector Switches, Complete Units

■ NEMA 4 and 13 rated Include operator, key, and contact block. UL Listed. CSA and CE Certified.

Position	Action*	Contact Form	Cam	Key Removal	Switch Operation @ Position†			13, 4, 4X Item No.	13, 4 Item No.
					@ Pos. A	@ Pos. B	@ Pos. C		
Lever									
2	M / M	1NO/1NC	E	No Key	XO	OX	—	30G297	30G296
2	M / M	2NO/2NC	E	No Key	XOXO	OXOX	—	31XH91	30G298
2	M / S	1NO/1NC	D	No Key	OX	XO	—	—	30G299
3	M / M / M	1NO/1NC	F	No Key	OO	OX	XO	—	30G302
3	M / M / M	1NO/1NC	D	No Key	OO	OX	XO	31XH92	—
3	M / M / S	1NO/1NC	C	No Key	XO	OO	OX	30G306	30G305
3	S / M / S	1NO/1NC	C	No Key	XO	OO	OX	30G304	30G303
Extended Lever									
2	M / M	1NO/1NC	E	No Key	XO	OX	—	32UK01	30G308
2	M / S	1NO/1NC	D	No Key	OX	XO	—	—	30G310
3	M / M / S	1NO/1NC	C	No Key	XO	OO	OX	—	30G314
3	S / M / S	1NO/1NC	C	No Key	XO	OO	OX	—	30G312
Keyed									
2	M / M	1NO/1NC	E	Left	XO	OX	—	—	30G316
2	M / M	1NO/1NC	E	Left/Right	XO	OX	—	—	30G315
2	S / M	1NO/1NC	D	Right	OX	XO	—	—	30G317

* M—maintained contact, S=spring return momentary contact. † X=Closed/On, O=Open/Off.



Dayton

30mm Joystick Operators

Chrome-plated zinc die-cast construction. UL Listed. CSA and CE Certified.

No. of Directions	Action	Direction of Operation	Item No.
4	Momentary	Vertical and Horizontal	30G490



Dayton

30mm Contact Blocks

■ 10A @ 600VAC/DC
■ Direct-acting

Contact Form	Item No.
1NC	30G318
1NO	30G319
1NC/1NO	30G320



H7014

H6967



30G321

Dayton

30mm Potentiometers

■ 4mA
■ 500VAC
■ 2W
Feature a heavy-duty dial plate with graduation from 0% to 100%.

Ohms	NEMA Rating	Item No.
1,000	13, 4	30G484
2,500	13, 4	30G485
5,000	13, 4	30G486
5,000	13, 4, 4X	30G489
10,000	13, 4	30G487



30G484

Dayton

30mm Nonilluminated Push Buttons

■ NEMA 4 and 13 rated

Direct-acting operation. Contact blocks sold separately, this page.

	► CHOOSE: Type of Operator	► CHOOSE: Color	► CHOOSE: Basic Material	Item No.
Momentary Push				
Flush Button; Extended Button		Green; Red	Metal; Plastic	H7014
Flush Button; Extended Button		Multi	Metal; Plastic	H7015
40mm Mushroom Head		Black	Metal	H6966
60mm Mushroom Head		Red; Green	Metal; Plastic	H6967
Maintained Push / Maintained Pull				
40mm Mushroom Head		Red	Metal; Plastic	H7009
Maintained Push				
Emergency Break Glass Operator		Yellow	Plastic	30G321