



Arcair **CRC** **LOCTITE**

WALTER **WELD-AID**
Surface Technologies

Anti-Spatter

Nonflammable formulas help keep tools and workpieces clean for reduced downtime. Paint over without a separate cleaning step.

Description	Container	Item No.
Arcair Tip Dipping®, Gel	Jar, 16 oz	2XRN8
CRC Aerosol®, Liquid	Aerosol Can, 16 oz	2F137
Loctite SF 7900™, Lubricant	Aerosol Can, 9.5 fl oz	29FX35
Walter Surface Technologies Ceramic Chemical Compound	Aerosol Can, 13.5 oz	52HR21
Water Based	Drum, 55 gal	49YK13
Weld Aid HD Nozzle-Dip® Gel, Water Based	Plastic Jar, 1 pt	24A412
	Plastic Jar, 32 oz	24A413
Nozzle-Kleen® #2, Solvent	Aerosol Can, 16 oz	24A407
Nozzle-Kleen® HD, Solvent	Aerosol Can, 16 oz	24A406
	Aerosol Can, 16 oz	24A417
	Plastic Container, 32 oz	24A418
Weld Kleen® 350® Spray, Water Based	Plastic Container, 1 gal	24A419
	Plastic Container, 5 gal	24A420
	Metal Drum, 55 gal	24A421
Weld-Kleen® HD, Solvent	Aerosol Can, 20 oz	24A416



Brite Zinc Galvanizing Compounds

Paintable, rust-free coatings match the look of hot-dipped galvanizing. Pass ASTM A780 inspection. Galvanized bare steel can be unpainted. Dry time: 15 to 30 minutes. Bare Steel formula is 95% zinc-rich bare steel for maximum corrosion protection and mechanical durability. 24A431 and 24A433 have nonclogging aerosol spray head.

For Use With	Size	Coverage	Item No.
Galvanized Material	16 oz	26 sq ft	24A431
	1 gal	570 sq ft	24A432
Bare Steel	16 oz	26 sq ft	24A433
	1 gal	644 sq ft	24A434

WELD-AID
PROTECTION



24A431

Markal Tempit® Temperature Sticks

Accuracy: ± 1%

Temperature indicators mark surfaces with a chalky and dull marking that changes to see-through and glossy at the rated temperature. Can be used in annealing, forging, welding, bonding, forming, and similar applications. Include nonslip gravity-advance holder.



Temperature Stick
G6576

Temperature Sticks, Individual	Temp. Range	Tip Size	Brand	Item No.
				►CHOOSE:
150°F, 200°F, 250°F, 300°F, 350°F, 400°F		3/8 in	Markal	G6576
100°F, 125°F, 175°F, 213°F, 225°F, 275°F, 325°F, 375°F,		1/2 in	Markal	G6576
425°F, 450°F, 500°F, 550°F, 600°F, 650°F, 700°F				
100°F, 150°F, 175°F, 213°F, 250°F, 275°F, 300°F, 325°F, 350°F, 375°F,		3/8 in	Tempit	J4714
425°F, 450°F, 600°F, 650°F, 700°F, 800°F, 212°F, 248°F, 302°F, 392°F				



30AA61

2430 **GRAINGER**

Specialty Welding Regulators

Gas Service	Delivery Pressure Range	Inlet Connec.	Outlet Connec.	Gauge Size	Brand	Mfr. Model	Item No.
Air	0 to 125 psi	CGA-590	1/4 in MNPT	2 in	Harris	KH118	30AA63
Argon, Helium, Nitrogen	0 to 1500 psi	CGA-580	1/4 in NPT x 1/4 in Stainless Steel Tube Fitting	2 1/2 in	Harris	KH114	30AA59
	0 to 2000 psi	CGA-580	1/2 in SST Tube Fitting	2 1/2 in	Smith Equipment	825-8109	45PW93
Carbon Dioxide	0 to 3000 psi	CGA-680	1/4 in NPT x 1/4 in Stainless Steel Tube Fitting	2 1/2 in	Harris	KH116	30AA61
	0 to 125 psi	—	1/4 in FNPT	2 1/2 in	Harris	7051253201	30AA78
Nitrogen	20 to 400 psi	CGA-580	1/4 in Flare M	2 in	Uniweld	RHP400	39DM33
	50 to 800 psi	CGA-580	1/4 in Flare M	2 in	Uniweld	RHP800	39DM34
	200 to 3000 psi	CGA-680	1/4 in NPTF	2 in	Uniweld	RHP3680	39DM35
Non-Corrosive Inert	0 to 1000 psi	CGA-580	1/4 in FNPT	2 1/2 in	Smith Equipment	824-0009	2CVZ1
	0 to 2000 psi	CGA-580	1/4 in FNPT	2 1/2 in	Smith Equipment	825-0009	2CVZ2
	0 to 4000 psi	CGA-580	1/4 in FNPT	2 1/2 in	Smith Equipment	826-0009	2CVZ3

Find even **MORE** on **Grainger.com**®

1-800-GRAINGER (472-4643)



Welding Pencil, Markers & Soapstones

Welding Pencil And Markers—Use as an alternative to soapstone to create torch-resistant markings that will not rub, burn, or blow off. Reflective silver and red colors improve visibility when cutting or welding.

Soapstones—Produce highly visible layout lines on metal or concrete. 5KH41 and 5KH43 include holders with built-in sharpener and pocket clip.

Description	Brand	Item No.
Welding Pencil Red-Riter® 1/8 in Point Tip	Markal	32PK95
Welding Markers Silver-Streak® 1/8 in Round Tip	Markal	1XEG4
Soapstones Flat Soapstone, Pk. of 144	Uniweld	5KH40
Flat Soapstone, Pk. of 144	Markal	2F900
Round Soapstone, Pk. of 144	Uniweld	5KH42
Soapstone Kits 6-Pc. Flat Soapstone Kit with Holder	Uniweld	5KH41
6-Pc. Round Soapstone Kit with Holder	Uniweld	5KH43
Soapstone Holder Soapstone Holder, Flat	Markal	2F902



Red Felt Pads
24A429



Nozzle-Kleen®
Tools

Spatter Cleaning and Wire Lubrication Pads and Tools

Lube-Matic—Engineered to reduce tip and liner wear, burnback, and wire jams, and to promote smoother arc feed. Black felt pads are for all types of steel wire; pretreated with Lube-Matic liquid. Red felt pads are for cleaning all wire; excellent for aluminum. Liquid cleaner/lubricant helps reduce wire drag 60%.

Nozzle-Kleen—Remove spatter from nozzles, tips, and diffusers, and clean torches without disassembly.

Description	Size	Item No.
Lube-Matic® Felt Pads Black, for Lubricating Steel Wire	Pk. of 6	24A428
Red, for Cleaning Wire	Pk. of 6	24A429
Combo Pack - 1 Black, 1 Red	Pk. of 2	24A430
Lube-Matic® Liquid Cleaner/Lubricant	3.75 oz. Can	24A426
Nozzle-Kleen® Welding Tools 3/8" Nozzle	1/4" Tip Cleaner	24A401
1/2" Nozzle	3/16" Tip Cleaner	24A402
5/8" Nozzle	1/8" Tip Cleaner	24A403
	3/8" Tip Cleaner	24A404
3/4" Nozzle	1/4" Tip Cleaner	24A405

HARRIS **SMITH** **UNIWELED** **WELD-AID**