












Glass-Filled Nylon Push-To-Connect Fittings







- Max. pressure: 290 psi
- Temp. range: -4° to 175°F
- Pkg. qty.: 10, unless otherwise noted

Tube O.D. x NPT/UNF Male Connector	Tube Size	Pipe Size	Item No.
	1/8 in	1/16 in	1PFF4
	1/8 in	1/8 in	1PFF5
	1/8 in	1/4 in	1PFF6
	1/8 in	10-32	1PFW1
	5/32 in or 4mm	1/8 in	1PFF3
	5/32 in or 4mm	1/4 in	1PFW2
	5/32 in or 4mm	10-32	1PFF1
	3/16 in	1/8 in	1PFF7 #
	3/16 in	1/4 in	1PFF8 #
	1/4 in	1/8 in	1PFF9
	1/4 in	1/4 in	1PFG1
	1/4 in	3/8 in	1PFG2
	1/4 in	10-32	1PFF2
	5/16 in or 8mm	1/8 in	5WRZ5
	5/16 in or 8mm	1/4 in	5WRZ6
	5/16 in or 8mm	3/8 in	5WRZ7
	3/8 in	1/8 in	1PFG3
	3/8 in	1/4 in	1PFG4
	3/8 in	3/8 in	1PFG5
	3/8 in	1/2 in	1PFW3
	1/2 in	1/4 in	1PFG6
	1/2 in	3/8 in	1PFW4
	1/2 in	1/2 in	1PFG7
	6mm	1/8 in	5WRZ8
	6mm	1/4 in	5WRZ9
	10mm	1/4 in	5WTA0
	10mm	3/8 in	5WTA1
	10mm	1/2 in	5WTA2
	12mm	3/8 in	5WTA3
	12mm	1/2 in	5WTA4
Female Connector			
	1/8 in	1/8 in	1PEL4
	1/8 in	1/4 in	1DCD3
	1/8 in	10-32	5WTG5
	5/32 in	1/8 in	1PEL2
	5/32 in	1/4 in	1PEL3
	1/4 in	1/8 in	1PEL5
	1/4 in	1/4 in	1PEL6
	5/16 in	1/8 in	1XCW8
	5/16 in	1/4 in	1DCD1
	3/8 in	1/8 in	1DCD5
	3/8 in	1/4 in	1PEL8
	3/8 in	3/8 in	1PEL7
	3/8 in	1/2 in	5WTH0
	1/2 in	1/4 in	5WTH1
	1/2 in	3/8 in	1DCD7
	1/2 in	1/2 in	1DCD9
Male Elbow			
	1/8 in	1/16 in	1DCZ9
	1/8 in	1/8 in	1PFA5
	1/8 in	1/4 in	1PFA6
	1/8 in	10-32	1DDA2
	5/32 in or 4mm	1/8 in	1PFA2
	5/32 in or 4mm	1/4 in	1PFA3
	5/32 in or 4mm	10-32	1PFA4
	3/16 in	1/8 in	1PFA7
	1/4 in	1/8 in	1PFA8
	1/4 in	1/4 in	1PFA9
	1/4 in	3/8 in	1PFB5
	1/4 in	10-32	1PFB6
	5/16 in or 8mm	1/8 in	1DCP2
	5/16 in or 8mm	1/4 in	1DCP4
	5/16 in or 8mm	3/8 in	1DCP6
	3/8 in	1/8 in	1PFB7
	3/8 in	1/4 in	1PFB8
	3/8 in	3/8 in	1PFB9
	3/8 in	1/2 in	1PFC1
	1/2 in	1/4 in	1PFC2
	1/2 in	3/8 in	1PFC3
	1/2 in	1/2 in	1PFC4
	6mm	1/8 in	1DCN7
	6mm	1/4 in	1DCN9
	10mm	1/4 in	1DCY8
	10mm	3/8 in	1DCZ1
	10mm	1/2 in	1DCZ3
	12mm	3/8 in	1DCZ5
	12mm	1/2 in	1DCZ7
Extended 90° Male Elbow			
	1/8 in	1/8 in	1DDP7
	5/32 in or 4mm	1/8 in	1DDA4
	5/32 in or 4mm	1/4 in	1DDA6
	5/32 in or 4mm	10-32	5WRV6
	1/4 in	1/8 in	1PFD6
	1/4 in	1/4 in	1PFD7
	1/4 in	3/8 in	1DDP9
	5/16 in or 8mm	1/8 in	1DDA8
	5/16 in or 8mm	1/4 in	1DDP6
	3/8 in	1/8 in	1DDR1
	3/8 in	1/4 in	1PFD8
	3/8 in x 3/8 in	3/8 in	1PFD9

Stainless steel gripping ring allows you to create a secure, leak-free connection without tools; disconnects easily with the plastic release button. All threaded elbows, tees, and Y's swivel around the threaded, nickel-plated base for easy installation. Fitting bodies are a composite material—nylon and nickel-plated brass. Thread sealant is preapplied to all tapered threads. Buna N elastomer seals. Can be used with all pneumatic machines, as well as for food-processing, packaging equipment, textile machinery, robotics, and semiconductor applications. Use with semirigid nylon, flexible polyurethane, polyethylene, and PTFE tubing.

10-32 UNF threads include O-ring seal.

45° Male Elbow	Tube Size	Pipe Size	Item No.
	1/8 in	1/8 in	4GWY4
	1/4 in	1/8 in	4GWZ2
	1/4 in	1/4 in	4GWZ3
	5/16 in or 8mm	1/8 in	4GWZ5
	5/16 in or 8mm	1/4 in	4GWZ6
	3/8 in	1/8 in	4GWZ8
	3/8 in	1/4 in	4GWZ9
	3/8 in	3/8 in	4GXA1
90° Female Elbow			
	1/8 in	1/8 in	1XCW7
	5/32 in	1/8 in	1XCW8
	1/4 in	1/8 in	1XCW9
	1/4 in	1/4 in	1XCW2
	5/16 in	1/4 in	1XCW5
	3/8 in	1/4 in	1XCW4
	1/2 in	3/8 in	1XCW6
Male Branch Tee*			
	1/8 in	1/4 in	1PEW7
	1/8 in	3/8 in	1PEW8
	1/8 in	1/2 in	1PEX4
	1/8 in	10-32	1DCN3
	5/32 in or 4mm	1/8 in	1PEV9
	5/32 in or 4mm	1/4 in	1PEW1
	5/32 in or 4mm	10-32	1DCN8
	1/4 in	1/8 in	1PEW9
	1/4 in	1/4 in	1PEX1
	1/4 in	3/8 in	1PEX2
	5/16 in or 8mm	1/8 in	1DCD6
	5/16 in or 8mm	1/4 in	1DCD8
	5/16 in or 8mm	3/8 in	1DCN1
	3/8 in	1/8 in	1PEX3
	3/8 in	1/4 in	1PEX8
	3/8 in	3/8 in	1PEX9
	3/8 in	1/2 in	1DCN5
	1/2 in	1/4 in	1PEY1
	1/2 in	3/8 in	1PEY2
	1/2 in	1/2 in	1PEY3
	6mm	1/8 in	5WRV7
	6mm	1/4 in	5WRV8
	10mm	1/4 in	5WRV9
	10mm	3/8 in	5WRZ0
	10mm	1/2 in	5WRZ1
	12mm	3/8 in	5WRZ2
Male Run Tee*			
	1/8 in	1/4 in	5WTA6
	1/8 in	3/8 in	1PER4
	1/8 in	10-32	5WTA5
	5/32 in or 4mm	1/8 in	1PEP9
	5/32 in or 4mm	1/4 in	5WTA8
	5/32 in or 4mm	10-32	5WTA7
	1/4 in	1/8 in	1PER5
	1/4 in	1/4 in	1PER6
	1/4 in	3/8 in	1PER7
	5/16 in or 8mm	1/8 in	5WTC0
	5/16 in or 8mm	1/4 in	5WTC1
	5/16 in or 8mm	3/8 in	5WTC2
	3/8 in	1/8 in	5WTC3
	3/8 in	1/4 in	1PER8
	3/8 in	3/8 in	1PER9
	3/8 in	1/2 in	1PEU1
	1/2 in	1/4 in	5WTC4
	1/2 in	3/8 in	5WTC5
	1/2 in	1/2 in	1PEU2
	6mm	1/8 in	5WTC6
	6mm	1/4 in	5WTC7
Male Y Connector			
	1/8 in	1/8 in	5WRZ4
	5/32 in or 4mm	1/8 in	1PFE1
	5/32 in or 4mm	1/4 in	1PFE2
	1/4 in	1/4 in	1PFE4
	3/8 in	1/4 in	1PFV7
	3/8 in	3/8 in	1PFV8

Single Banjo	Tube Size	Pipe Size	Item No.
	1/8 in	10-32	4GXC5
	5/32 in or 4mm	10-32	4GXC6
	1/4 in	1/8 in	4GXD1
	1/4 in	1/4 in	4GXD2
	1/4 in	10-32	4GXC9
	3/8 in	1/4 in	4GXD6
Male Standpipe			
	1/4 in	1/4 in	4GXE3
	5/16 in or 8mm	1/4 in	4GXE5
	3/8 in	1/4 in	4GXE7
Female Bulkhead Adapter			
	5/32 in	1/4 in	1PEL9
	1/4 in	1/8 in	5WTG3
	1/4 in	1/4 in	1PEN1
	3/8 in	3/8 in	1PEN2
Tube O.D. x BSPP/Metric Male Connector			
	4mm	1/8 in	1PEN3
	4mm	1/4 in	1PEN4
	4mm	M3 x 0.5	5WTD3
	4mm	M5 x 0.8	1PEN5
	4mm	M7 x 1	5WTD4
	6mm	1/8 in	1PEL1
	6mm	1/4 in	1PEN6
	6mm	3/8 in	1DDZ9
	6mm	1/2 in	1DEB1
	6mm	M10 x 1	5WTD7
	6mm	M12 x 1.5	5WTD8
	6mm	M5 x 0.8	5WTD5
	6mm	M7 x 1	5WTD6
	8mm	1/8 in	1PEN7
	8mm	1/4 in	1PEN8
	8mm	3/8 in	1PEN9
	8mm	1/2 in	1DEB2
	8mm	M10 x 1	5WTD9
	8mm	M12 x 1.5	5WTD0
	10mm	1/4 in	1PEP1
	10mm	3/8 in	1PEP2
	10mm	1/2 in	1DEB3
	12mm	1/4 in	1DEB4
	12mm	3/8 in	1DEB5
	12mm	1/2 in	1DEB6
	14mm	3/8 in	1DEB7
	14mm	1/2 in	1DEB8
	16mm	3/8 in	19D041 **
	16mm	1/2 in	19D042 **
Female Connector			
	4mm	1/8 in	1DDZ3
	6mm	1/8 in	1DDZ5
	6mm	1/4 in	1DDZ6
	8mm	1/8 in	1DDZ7
	8mm	1/4 in	1DDZ8
	10mm	3/8 in	4GW12
	12mm	1/2 in	4GW14
	16mm	1/2 in	19D043 **
90° Male Elbow			
	4mm	1/8 in	1PFG8
	4mm	1/4 in	1PFG9
	4mm	M3 x 0.5	1DET6
	4mm	M5 x 0.8	1PFH1
	4mm	M7 x 1	1DET7
	6mm	1/8 in	1PFH2
	6mm	1/4 in	1PFH3
	6mm	3/8 in	1PFW5
	6mm	1/2 in	1DET8
	6mm	M10 x 1	1DEU1
	6mm	M12 x 1.5	1DEU2
	6mm	M5 x 0.8	1PFH4
	6mm	M7 x 1	1DET9
	8mm	1/8 in	1PFH5
	8mm	1/4 in	1PFH6
	8mm	3/8 in	1PFH7
	8mm	1/2 in	1DEU3
	8mm	M10 x 1	1DEU4
	8mm	M12 x 1.5	1DEU5
	10mm	1/4 in	1PFH8
	10mm	3/8 in	1PFH9
	10mm	1/2 in	1PFJ1
	12mm	1/4 in	1DEU6
	12mm	3/8 in	1DEU7
	12mm	1/2 in	1DEU8
	14mm	3/8 in	1DEU9
	14mm	1/2 in	1DEU1
	16mm	3/8 in	19D044 **
	16mm	1/2 in	19D046 **
	16mm	3/8 in	19D045 **
	16mm	1/2 in	19D047 **

* Tees read: run x run x outlet. † Pkg. qty.: 50. ** Sold as each.
Temp. range: 5 to 155°F; Max. pressure: 260 psi; Bare brass.

CONTINUED