Class Filled Nulan Duck To Connect Fittings

CONTINUED	Gla	ass-F	illed Ny	ion Push-	To-Conn	ect	Fittings			1	legris
	Tube Size	Pipe Size	ltem No.		Tube Size	Pipe Size	Item No.	T-1-0 D	Tube Size	Pipe Size	Item No.
5° Male Elbow	6mm	1/8 in	4GWT7	45° Male Elbow				Tube O.D. Union	4/: 4/:		485140
	6mm	½ in	4GWT8	1	4mm	1/8 in	4GWJ8		½ in x ¼ in ½ in		1PEW2 1PEV2
245	6mm	M5 x 0.8	5WTE2	6.	8mm	1/4 in	4GWK4		5/32 in x 1/4 in 5/32 in or 4mm		5WTJ5 1PEU9
ale Branch Tee*	Omm	WIO X 0.0	OWILL	Male Branch Tee*	5/32 in or 4mm	½ in	4GXH5		3/16 in 1/4 in		4GXJ5 1PEV6
%	4mm	1/8 in	4GWU7		1/4 in	1/8 in	4GXH7		5/16 in or 8mm 3/8 in x 1/4 in		1PEV1 1PEW5
	4mm 6mm	M5 x 0.8 1/8 in	5WTE5 4GWU9		1/4 in 3/8 in	1/4 in 1/4 in	4GXH8 4GXJ1	-	3% in x 1/2 in		5WTJ6
	6mm	1/4 in	4GWX1		3/8 in	3/8 in	4GXJ2	Street, or other Designation of the last o	3% in 1/2 in		1PEV7 1PEV8
	6mm 8mm	M5 x 0.8 1/8 in	5WTE6 4GWX2		4mm 6mm	1/4 in 1/8 in	4GWN3 4GWN4		4 x 6mm 6mm		5WTJ7 1DED8
	8mm	1/4 in	4GWX3		6mm	1/4 in	4GWN5		6 x 8mm 10mm x 12mm		5WTJ8 5WTJ9
	8mm 10mm	3/8 in 1/4 in	4GWX4 4GWX5		8mm 8mm	1/8 in 1/4 in	4GWN6 4GXH9		10mm 12mm	_	1DED9 1DEF1
	14mm	½ in	5WTG0		10mm	1/4 in	4GWN8 4GWN9		14mm		1DEF2
	16mm 16mm	3/8 in 3/8 in	19D050 ** 19D054 **		12mm 12mm	1/4 in 1/2 in	4GWP2	90° Union Elbo	16mm DW		19D056 **
	16mm	½ in	19D051 **			Pipe	Item		½ in ½ in x ¼ in		1PEP5 4GXK6
Male Run Tee*	16mm	½ in	19D055 **	Tube O.D. x Stem	Tube Size	Size	No.		5/32 in or 4mm		1PEP3
	4mm 4mm	1/8 in 1/8 in	4GWP5 1DEP7	Plug-In 90° Elbow	1/8 in		1DDU3		5/32 in x 1/4 in 3/16 in		4GXK7 5WTH4
	4mm	M5 x 0.8	1DEP9	_	5/32 in or 4mm		1DEK7		1/4 in 5/16 in or 8mm		1PEP6 1PEP4
	6mm 6mm	1/8 in 1/8 in	4GWP7 1DER1		5/32 in 1/4 in	_	1DDU2 1DDU4	24	3% in		1PEP7 4CJR9
	8mm	½ in	4GWP9		1/4 in		1DDU4 1DDU5		3/8 in x 1/4 in 3/8 in x 1/2 in	_	4CJT1
	8mm 8mm	1/4 in 1/4 in	4GWR1 1DER4	41	5/16 in or 8mm 3/8 in		1DEL3 1DDU6		½ in 4mm x 6mm	=	1PEP8 5WTH5
	8mm	3/8 in	4GWR2		1/2 in	_=	1DDU7		6mm 10mm		1DEB9 1DED1
	10mm 14mm	1/4 in 1/2 in	1DER6 1DET5	Extended 90° Plug	-In Elbow 5/32 in or 4mm		1DFV2		12mm 14mm		1DED2 1DED3
	16mm	3/8 in	19D048 **	2000				Haira Track	16mm	_	19D057 **
	16mm 16mm	3/8 in 1/2 in	19D052 ** 19D053 **		1/4 in	_	1DDV3	Union Tee*	1/8 in x 1/4 in	_	4GXJ6
emale Bulkhead Co		72 111	130000	4/	5/16 in or 8mm	_	1DEN2		½ in 32 in x ¼ in		1PEU5 4GXJ7
The state of the s	16mm	3/8 in	19D060 **	Plug-In Tee*					5/32 in or 4mm 3/16 in		1PEU3 5WTH7
-160					1/4 in	_	1DDV6		1/4 in x 1/8 in		4GXJ8 4GXJ9
	16mm	½ in	19D061 **	77			48580		1/4 in x 5/32 in 1/4 in x 3/8 in		4GXK1
	Tube Oies	Pipe	Item	4	5/16 in or 8mm		1DEP2		1/4 in 5/16 in or 8mm		1PEU6 1PEU4
ibe O.D. x BSPT/Me	Tube Size etric	Size	No.	Plug-In Run Tee*					3/8 in x 1/2 in 3/8 in x 1/4 in		4GXK3 4GXK2
ale Connector	½ in 3/32 in or 4m	1/8 in	4GXF1 4GXF2						3/8 in 1/2 in x 1/4 in		1PEU7 4GXK4
	5/32 in or 4m 5/32 in or 4m	m ½ in m ¼ in	4GXF2 4GXF3	Parel I	1⁄4 in	_	1DDU8	THE PERSON	½ in x ¾ in	_	4GXK5
	3/16 in 1/4 in	½ in ½ in	4GXF4 4GXF5						½ in 4mm x 6mm		1PEU8 5WTH8
	1/4 in	1/4 in	4GXF6	West Disease					6mm x 4mm 6mm x 8mm		5WTH9 5WTJ0
	5/16 in or 8m 3/8 in	1/4 in	4GXF7 4GXF8	Wye Plug-In	5/32 in or 4mm		1DEG8		6mm 8mm, 5/16		1DED4 5WTJ1
	3/8 in 1/2 in	3/s in 3/s in	4GXF9 4GXG1		1/4 in 5/16 in or 8mm		1DDR9 1DEH3		in x 6mm		
	½ in 6mm	½ in ⅓ in	4GXG2 4AAA1		3% in		1DDU1		8mm x 10mm 10mm x 8mm		5WTJ2 5WTJ3
	6mm	1/4 in	4GWH8	Plug-In Reducer					10mm 12mm		1DED5 1DED6
	8mm 8mm	1/8 in 3/8 in	4GWH9 4GWJ1	1 lug III lloudooi	1/8 in	1/4 in	1PFE6		14mm 16mm		1DED7 19D058 **
	10mm 12mm	½ in ¼ in	4GWJ2 4GWJ3		5/32 in 1/4 in	1/4 in 5/16 in	1PFE5 1PFV9	Wye Union	16mm x 12mm		19D059 **
	12mm 12mm	3/8 in 1/2 in	4GWJ4 4GWJ5		1/4 in	⅓ in	1PFE7	wye ulliuli	1/8 in	_	1DDR3
	14mm	3/8 in	4GWJ6		1/4 in 3/8 in	½ in ½ in	1PFE8 1PFE9		5/32 in or 4mm 5/32 in x 1/4 in		1DEF8 1DDR2
	14mm 16mm	½ in ¾ in	4GWJ7 19D039 **		4mm		1DEK4	-	3/16 in 1/4 in		5WTK0 1DDR5
0° Male Elbow	16mm	½ in	19D040 **		4mm 6mm		1DEK6 1DEK5		1/4 in x 3/8 in 5/16 in or 8mm		1DDR6 1DEG3
	1/8 in 5/32 in or 4m	⅓ in m ⅓ in	4GXG3 4GXG4		8mm		5WTH2		3∕8 in	_	1DDR7
	3/16 in 1/4 in	½ in ½ in	4GXG5 4GXG6	Plug	10mm		5WTH3		4 x 6mm 6mm	=	1DEF9 1DEG1
	1/4 in	1/4 in	4GXG7		1/8 in 5/32 in or 4mm		1PFD4 1PFC9 †		6 x 8mm 8 x 10mm		1DEG2 1DEG4
	5/16 in or 8m 3/8 in	m ½ in ¼ in	4GXG8 4GXG9		1/4 in		1PFC9 † 1PFD5		10mm 10 x 12mm	=	1DEG5 1DEG6
	3/8 in 1/2 in	3% in 3% in	4GXH1 4GXH2		5/16 in or 8mm 3/8 in		1PFD2 1PFV5	Faural Cross	12mm	_	1DEG7
	½ in 4mm	½ in ¼ in	4GXH3 4GWL1		1/2 in		1PFV6	Equal Cross	½ in		1DCE2
	6mm	⅓ in	4GWL2		6mm 10mm		1PFD1 † 1PFD3	And the			
	6mm 8mm	½ in % in	4GWL3 4GWL4		12mm	_	4GWX9	1	5/16 in or 8mm		1DCG9
	8mm 10mm	3/8 in 1/4 in	4GWL5 4GWL6		16mm	_	19D062 **		6mm		1DCE6
	12mm	1/4 in	4GWL7					Bulkhead Unio	on ⅓ in		1PFT9
	12mm 12mm	⅓ in ½ in ⅓ in	4GWL8 4GWL9						5∕32 in	_	1PFC5
	14mm 14mm	3/8 in 1/2 in	4GWN1 4GWN2					and faither	1/4 in 5/16 in or 8mm		1PFC6 1DEF4
								STATE OF THE PERSON.	3/8 in	_	1PFC7
									½ in 6mm		1PFV3 1DEF3
									10mm	_	1DEF5

^{*} Tees read: run x run x outlet. † Pkg. qty.: 50. ** Sold as each. # Temp. range: 5 to 155°F; Max. pressure: 260 psi; Bare brass.