



Portable 115VAC Electric Oil-Free Air Compressors

Speedaire—Has steel hotdog tank and rubber feet for added stability on uneven surfaces.

Rolair—Intake filter/silencer helps compressor operate at a quiet 60dB. Motor and pump are fully enclosed by a roll cage, for use in rugged environments. On-the-job life expectancy of approximately 2000 hr.

Thomas—Starts at 100 psi. 38-sec. recovery time.

DeWalt—Has a roll cage, 2 gauges, and a factory-installed coupler.

Porter Cable—1VAN5 has 2 couplers. Motor starts easily in cold weather; upgraded shroud has rugged carry handle.

| HP | Full Load Amps | Tank Size | Free Air CFM @ Max. Pressure | Max. Pressure | Weight | Overall | | | Brand | Mfr. Model | Item No. |
|----------------|----------------|-----------|------------------------------|---------------|--------|---------|----------|----------|--------------|------------|----------|
| | | | | | | L | W | H | | | |
| Hot Dog | | | | | | | | | | | |
| 0.3 hp | 2.6 | 1.0 gal | 0.3 | 135 psi | 24 lb | 19 in | 14.5 in | 9 in | DeWalt | D55140 | 1VAN7 |
| 0.5 hp | 4.2 | 2.0 gal | 0.7 | 125 psi | 26 lb | 16.5 in | 8 in | 16.81 in | Thomas | T-617 HDN | 5Z683 |
| 0.75 hp | 12.0 | 3.0 gal | 2.0 | 135 psi | 40 lb | 20 in | 9 in | 19 in | Speedaire | 45PL19 | 45PL19 |
| 1.0 hp | 7.5 | 2.5 gal | 0.2 | 150 psi | 45 lb | 16.5 in | 16.5 in | 14 in | Rolair | JC10PLUS | 413X03 |
| 1.1 hp | 12.0 | 2.5 gal | 1.6 | 200 psi | 37 lb | 20.5 in | 16.75 in | 12.5 in | DeWalt | DWFP55130 | 22YJ96 |
| 1.6 hp | 15.0 | 4.5 gal | 3.0 | 200 psi | 83 lb | 33.5 in | 23 in | 15 in | DeWalt | D55146 | 445K70 |
| Pancake | | | | | | | | | | | |
| 0.8 hp | 10.0 | 6.0 gal | — | 150 psi | 29 lb | 18 in | 18.37 in | 15 in | Porter Cable | C2002 | 1VAN5 |
| 0.8 hp | 10.0 | 6.0 gal | 2.0 | 150 psi | 30 lb | 18 in | 19 in | 18.31 in | Porter Cable | C2002-WK | 54DF06 |



1VAN7



45PL19



1VAN5



5Z683



413X03



Portable Electric Oil-Lubricated Air Compressors

Speedaire—11X355 has a cast-iron cylinder, heavy-duty roll bar, and vibration-absorbing rubber feet. 2MLW5 has an aluminum-head cylinder with cast-iron sleeve.

Rolair—Contractor-grade professional units have cast-iron cylinders and low amp-draw motors. 26JY35 and 26JY36 feature an easily maneuvered dolly cart design and a user-friendly control panel. 26JY35 also has a tool box for convenient storage.

Jenny—Unit features a heavy-duty steel tank and frame mounted on antivibration feet. Comes standard with cast-iron cylinder soft-start direct-drive pump, with safety valves, pressure regulator, and gauges.

Makita—Durable low-noise compressors feature pumps with oil-lubricated cast-iron cylinders and big-bore pistons; provide outstanding performance and fast recovery time.

DeWalt—Have a side-stack tank design, cast-iron cylinder, dual soft-start valves, and ball drain. 1VAN9 is wheeled.



22YJ55



1VAP1



11X355



26JY34



26JY10

| HP | Input Voltage | Full Load Amps | Tank Size | Free Air CFM @ Max. Pressure | Max. Pressure | Weight | L | Overall W | H | Brand | Mfr. Model | Item No. |
|-------------------|---------------|----------------|-----------|------------------------------|---------------|--------|----------|-----------|----------|-----------|-------------------|----------|
| Hot Dog | | | | | | | | | | | | |
| 2.0 hp | 120V AC | 15.0 | 4.0 gal | 4.1 | 200 psi | 132 lb | 26.18 in | 22.12 in | 19.87 in | Speedaire | 2MLW5 | 2MLW5 |
| 2.0 hp | 120V AC | 12.3 | 3.2 gal | 3.9 | 125 psi | 80 lb | 21 in | 21 in | 31 in | Rolair | VT20TB | 26JY35 |
| 2.0 hp | 120V AC | 12.4 | 2.6 gal | — | 130 psi | 52 lb | 19.5 in | 11.5 in | 23.5 in | Makita | MAC700 | 22YJ55 |
| 2.5 hp | 120V AC | 13.8 | 5.3 gal | 5.9 | 130 psi | 108 lb | 19 in | 19 in | 37 in | Rolair | VT25BIG | 26JY36 |
| 3.0 hp | 120V AC | 13.8 | 5.2 gal | — | 140 psi | 88 lb | 20.5 in | 30 in | 21 in | Makita | MAC5200 | 22YJ54 |
| Twin Stack | | | | | | | | | | | | |
| 1.1 hp | 120V AC | 14.0 | 4.0 gal | 2.7 | 125 psi | 54 lb | 18.5 in | 15 in | 16.75 in | DeWalt | D55151 | 1VAP1 |
| 1.1 hp | 120V AC | 14 | 4.0 gal | — | 125 psi | 87 lb | 22 in | 18.5 in | 23 in | DeWalt | D55154 | 1VAN9 |
| 1.3 hp | 120V AC | 15.0 | 4.0 gal | 4.0 | 125 psi | 71 lb | 19.62 in | 18.87 in | 17.87 in | Speedaire | 11X355 | 11X355 |
| 2.0 hp | 120V AC | 14.6 | 4.3 gal | 3.9 | 135 psi | 62 lb | 20 in | 15 in | 17 in | Rolair | FC2002 | 26JY34 |
| 2.0 hp | 120V AC | 12.6 | 4.2 gal | 3.3 | 125 psi | 58 lb | 20 in | 15.5 in | 16.5 in | Jenny | A2G246-HC4V-115/1 | 26JY10 |

Vehicle-Mounted 12V and 24VDC Oil-Lubricated Air Compressors

Designed to be mounted on service trucks, tow trucks, and maintenance vehicles, for commercial and industrial use. Fan-cooled cylinder head and motor. Mounts on a tank or with accessory packages, sold separately.



53XG20



22NW59

| HP | Free Air CFM @ Max. Pressure | Max. Pressure | Full Load Amps | Overall Length | Overall Width | Overall Height | Brand | Weight | Item No. |
|---------------|------------------------------|---------------|----------------|----------------|---------------|----------------|-------|---------|----------|
| 12V DC | | | | | | | | | |
| 2.2 hp | 8.0 | 200 psi | 160 | 40 in | 10 in | 26 in | Oasis | 152 lb. | 53XG20 |
| 2.2 hp | 8.0 | 200 psi | 180 | 21 in | 7 in | 11 in | Oasis | 67 lb | 22NW59 |
| 24V DC | | | | | | | | | |
| 2.2 hp | 8.0 | 200 psi | 90 | 21 in | 7 in | 11 in | Oasis | 67 lb | 22NW60 |
| 2.2 hp | 8.0 | 200 psi | 90 | 40 in | 10 in | 26 in | Oasis | 152 lb. | 53XG21 |

| Description | Item No. |
|--|----------|
| Vehicle Mounted Air Compressor Accessory Kit | 3MMC1 |

Sign in to **Grainger.com®** to see **YOUR Pricing** and **MORE**