

1-800-GRAINGER (472-4643)



DETEX® Spray Bottle

Empty trigger spray bottle with DETEX® metal and x-ray detectable plastic components provides convenient delivery of bulk-packaged cleaners, degreasers, and lubricants. Adjustable spray stream ensures proper application.



Container Size	Mfr. Model	Item No.
28 oz	57928	29FX95



Precision Spout Oiler

Flexible telescoping spout can reach up to 13" to lubricate hard-to-reach areas. Nondetergent SAE 10 turbine-grade oil for use on rotating and reciprocating motors, bearings, slides, and other equipment.



Container Size	Container Type	Mfr. Model	Item No.
4 oz	Bottle	79704	4NA76



Food Grade Machinery Oils

▪ NSF H1 Rated

CRC®—General-purpose lubricant is silicone-free, virtually odorless, and colorless. Will not harm metal, wood, plastic, or painted surfaces. Zero VOC. The Perma-Lock® integrated actuator will not detach.

LPS® with DETEX®—Features metal-detectable plastic components with DETEX®. Colorless, odorless, nonstaining oil loosens nuts and bolts and lubricates to reduce sticking, binding, and squeaking on bottling equipment, conveyors, food service racks, slicers, and other equipment. Safe on most surfaces. Silicone-free and VOC-free. No chlorinated solvents.

Sprayon® LU™700 Oil—Silicone-free lubricant loosens corrosion.

Tri-Flow™ Synthetic Oil with PTFE—Nonstaining oil does not emulsify in water.



2F132



19C659



6KHE5



4TA90

Description	Container Size	Temp. Range	Mfr. Model	Item No.
CRC®	11 oz	32° to 300°F	03081	2F132
LPS® with DETEX®	11 oz	0° to 385°F	01316	19C659
Sprayon® LU™700 Food Grade Machinery Oil	10 oz	-20° to 450°F	SC0700000	6KHE5
Tri-Flow™ Synthetic Oil with PTFE	12 oz	-10° to 400°F	TF230101	4TA90



Reusable Sprayer

Refillable sprayer uses compressed air to deliver a uniform, controlled mist spray of bulk lubricants, penetrants, degreasers, solvents, and cleaners. 80 to 150 psi operating pressure. Top-fill carbon steel canister with blue enamel coating. Not for use with paint.

Cap. (oz.)	Dia. (in.)	H (in.)	Item No.
32	4 in	7 7/8 in	31ER19



Hand-Applied Metalworking Lubricants

Tapmatic® Edge Lube—Biodegradable bar is packaged in a cylinder for rotating or stationary cutting tools. Excellent for sawing applications, eliminating heat buildup and belt loading. Low toxicity. Compatible with oil and water systems. Safe on all metals.

Tapmatic® Edge Creme—Biodegradable paste cutting fluid can be applied to tools before tapping or reaming. Use when drilling, tapping blind holes, forming, bending, precoating fasteners, and lubricating rubber seals.

Gel Paste—Vegetable-based gel lubricant with workable texture for taps, drills, and cutting tools. Safe for ferrous and non-ferrous metals. A1 and T1.

Stick Lubricants—Designed to reduce heat buildup in belt, disc, or wheel grinding operations.



4KK73



4KK72



1MKN8



1MKN7

Container Size	Container Style	Physical Form	Color	Brand	Mfr. Model	Item No.
Tapmatic® Edge Lube						
13 oz	Tube	Solid	White	LPS	43200	4KK73
Tapmatic® Edge Creme						
10 oz	Tube	Paste	White	LPS	43100	4KK72
Gel Paste						
8 oz	Jar	Paste	Dark Blue	Accu-Lube	79030	1MKN8
Stick Lubricants						
2.2 oz	Jar	Solid	Light Blue	Accu-Lube	79042	1MKN6
13 oz	Tube	Solid	Light Blue	Accu-Lube	79045	1MKN7

Sign in to **Grainger.com®** to see **YOUR Pricing** and **MORE**