



**SPEEDAIRE WILKERSON**  
**Compressed Air Liquid Separators**

These separators remove bulk water and oil from compressed air and are typically installed downstream from an air compressor and aftercooler to prevent water and oil from entering the air supply and damaging equipment such as air dryers.

								MOUNTING BRACKET
Inlet Size	Max. Flow Rate	Max. Operating Pressure	Max. Operating Temp.	Drain Type	Body Material	Brand	Item No.	Item No.
1/4 in NPT	22.5 cfm	235 psi	176 °F	Automatic	Aluminum	Speedaire	4GNL3	35GM64
3/8 in NPT	15 cfm	290 psi	176 °F	Automatic	Aluminum	Speedaire	53RG84	—
1/2 in NPT	60 cfm	290 psi	176 °F	Automatic	Aluminum	Speedaire	53RG86	—
1/2 in NPT	15 cfm	290 psi	176 °F	Automatic	Aluminum	Speedaire	53RG85	—
1/2 in NPT	50 cfm	200 psi	150 °F	Automatic	Cast Zinc	Wilkinson	52771	—
1/2 in NPT	60 cfm	235 psi	176 °F	Automatic	Aluminum	Speedaire	4GNL4	35GM65
1/2 in NPT	120 cfm	290 psi	176 °F	Automatic	Aluminum	Speedaire	53RG87	—
3/4 in NPT	100 cfm	200 psi	150 °F	Automatic	Zinc	Wilkinson	52614	4ZK72
3/4 in NPT	150 cfm	235 psi	176 °F	Automatic	Aluminum	Speedaire	4GNL5	35GM65
1 in NPT	120 cfm	290 psi	176 °F	Automatic	Aluminum	Speedaire	53RG88	—
1 in NPT	120 cfm	200 psi	150 °F	Automatic	Cast Zinc	Wilkinson	52615	4ZK72
1 1/4 in NPT	175 cfm	290 psi	176 °F	Automatic	Aluminum	Speedaire	53RG89	—
1 1/2 in NPT	175 cfm	290 psi	176 °F	Automatic	Aluminum	Speedaire	53RG90	—
1 in NPT	262.5 cfm	235 psi	176 °F	Automatic	Aluminum	Speedaire	4GNL6	35GM65
1 in NPT	350 cfm	290 psi	176 °F	Automatic	Aluminum	Speedaire	53RG91	—
1 1/4 in NPT	350 cfm	290 psi	176 °F	Automatic	Aluminum	Speedaire	53RG92	—
1 1/2 in NPT	525 cfm	235 psi	176 °F	Automatic	Aluminum	Speedaire	4GNL7	35GM66
1 1/4 in NPT	700 cfm	290 psi	176 °F	Automatic	Aluminum	Speedaire	53RG93	—
1 1/2 in NPT	700 cfm	290 psi	176 °F	Automatic	Aluminum	Speedaire	53RG94	—
1 1/2 in NPT	750 cfm	250 psi	175 °F	Semi-Automatic Manual	Metal w/Sight Glass	Speedaire	4ZL13	—
2 in NPT	750 cfm	250 psi	175 °F		Metal w/Sight Glass	Speedaire	4ZL15	—
2 in NPT	1,050 cfm	235 psi	176 °F	Automatic	Aluminum	Speedaire	4GNL8	35GM66
2 in NPT	1,300 cfm	290 psi	176 °F	Automatic	Aluminum	Speedaire	53RG95	—
3 in NPT	1,950 cfm	235 psi	176 °F	Automatic	Aluminum	Speedaire	4GNL9	35GM68
Description				Brand				Item No.
Accessory								
Float Drain, Replacement for 4GNL3 to 4GNL9				Speedaire				4GNN2
Float Drain, Replacement for 5Z771				Wilkinson				6B251



**>Hankison**  
**Air/Liquid Bypass Valve**

Service components without shutting down the system; simply push 1 button to change modes. Push-button can be locked in place to make valve tamperproof. Inlet and outlet fittings are compression type with rubber ferrule. Ideal for most brands of refrigerated dryers, 5 to 15 cfm. Can be used with liquid and gases compatible with nylon, Buna N, and brass.

Inlet Port	Outlet Port	Max. Operating Temp.	Mfr. Model	Item No.
3/8" O.D.	3/8" O.D.	120 °F	1701-2	5Z777

**QUICKLY ORDER**  
Items From This  
Catalog With the  
Grainger Mobile App!



Apple, the Apple logo and iPhone are trademarks of Apple Inc. App Store is a service mark of Apple Inc. Google Play is a trademark of Google Inc.

- Scan. Order. Done.
- Scan the Item Number
  - See Your Price
  - Place Your Order—Done

