



EPDM and Synthetic Rubber Air Hose Assemblies

- Temp. range: -20° to 210°F
- 4:1 safety factor

Use with air, water, and mild chemicals in low-pressure industrial, construction, and agricultural applications.

Hose L	Fitting Size	BLACK 200 PSI		RED 250 PSI		YELLOW 300 PSI		
		Outside Dia.	Item No.	Outside Dia.	Item No.	Outside Dia.	Item No.	
Coupled Assembly, EPDM								
¼ in Hose Inside Dia.								
5 ft	¼ in	½ in	55CL77	¾ in	55CM23	¾ in	55CM71	
		½ in	55CL80	¾ in	55CM26	¾ in	55CM74	
		½ in	55CL83	¾ in	55CM29	¾ in	55CM77	
½ in		55CL86	¾ in	55CM32	¾ in	55CM80		
½ in		55CL78	¾ in	55CM24	¾ in	55CM72		
½ in		55CL81	¾ in	55CM27	¾ in	55CM75		
½ in		55CL84	¾ in	55CM30	¾ in	55CM78		
½ in		55CL87	¾ in	55CM33	¾ in	55CM81		
½ in		55CL79	¾ in	55CM25	¾ in	55CM73		
½ in		55CL82	¾ in	55CM28	¾ in	55CM76		
½ in		55CL85	¾ in	55CM31	¾ in	55CM79		
½ in		55CL88	¾ in	55CM34	¾ in	55CM82		
25 ft		½ in	3JT63	—	—	—	—	
50 ft		½ in	3JT65	—	—	—	—	
100 ft		½ in	52TV33	¾ in	52TV37	¾ in	52TV41	
¾ in Hose Inside Dia.								
5 ft	¼ in	1 ½ in	55CL89	1 ½ in	55CM35	1 ½ in	55CM83	
		1 ½ in	55CL92	1 ½ in	55CM38	1 ½ in	55CM86	
		1 ½ in	55CL95	1 ½ in	55CM41	1 ½ in	55CM89	
1 ½ in		55CL98	1 ½ in	55CM44	1 ½ in	55CM92		
1 ½ in		55CL90	1 ½ in	55CM36	1 ½ in	55CM84		
1 ½ in		55CL93	1 ½ in	55CM39	1 ½ in	55CM87		
1 ½ in		55CL96	1 ½ in	55CM42	1 ½ in	55CM90		
1 ½ in		55CL99	1 ½ in	55CM45	1 ½ in	55CM93		
1 ½ in		55CL91	1 ½ in	55CM37	1 ½ in	55CM85		
1 ½ in		55CL94	1 ½ in	55CM40	1 ½ in	55CM88		
1 ½ in		55CL97	1 ½ in	55CM43	1 ½ in	55CM91		
1 ½ in		55CM01	1 ½ in	55CM46	1 ½ in	55CM94		
25 ft		¾ in	3JT68	—	—	—	—	
50 ft		¾ in	3JT69	—	—	—	—	
50 ft		¾ in	3JT71	—	—	—	—	
50 ft		¾ in	3JT72	—	—	—	—	
100 ft		¾ in	52TV34	1 ½ in	52TV38	1 ½ in	52TV42	
100 ft		¾ in	41TF12	—	—	—	—	
½ in Hose Inside Dia.								
5 ft	½ in	1 ¾ in	55CM02	1 ¾ in	55CM47	1 ¾ in	55CM95	
		1 ¾ in	55CM05	1 ¾ in	55CM50	1 ¾ in	55CM98	
		1 ¾ in	55CM08	1 ¾ in	55CM53	1 ¾ in	55CM02	
1 ¾ in		55CM11	1 ¾ in	55CM56	1 ¾ in	55CM05		
1 ¾ in		55CM03	1 ¾ in	55CM48	1 ¾ in	55CM96		
1 ¾ in		55CM06	1 ¾ in	55CM51	1 ¾ in	55CM99		
1 ¾ in		55CM09	1 ¾ in	55CM54	1 ¾ in	55CM03		
1 ¾ in		55CM12	1 ¾ in	55CM57	1 ¾ in	55CM06		
1 ¾ in		55CM04	1 ¾ in	55CM49	1 ¾ in	55CM97		
1 ¾ in		55CM07	1 ¾ in	55CM52	1 ¾ in	55CM01		
1 ¾ in		55CM10	1 ¾ in	55CM55	1 ¾ in	55CM04		
1 ¾ in		55CM13	1 ¾ in	55CM58	1 ¾ in	55CM07		
25 ft		¾ in	3JT73	—	—	—	—	
50 ft		¾ in	3JT75	—	—	—	—	
100 ft		¾ in	52TV35	1 ¾ in	52TV39	1 ¾ in	52TV43	
¾ in Hose Inside Dia.								
5 ft		¾ in	1 ½ in	55CM14	1 ½ in	55CM59	1 ½ in	55CM08
			1 ½ in	55CM17	1 ½ in	55CM62	1 ½ in	55CM11
			1 ½ in	55CM20	1 ½ in	55CM65	1 ½ in	55CM14
1 ½ in			55CM15	1 ½ in	55CM60	1 ½ in	55CM09	
1 ½ in			55CM18	1 ½ in	55CM63	1 ½ in	55CM12	
1 ½ in	55CM21		1 ½ in	55CM66	1 ½ in	55CM15		
1 ½ in	55CM16		1 ½ in	55CM61	1 ½ in	55CM10		
1 ½ in	55CM19		1 ½ in	55CM64	1 ½ in	55CM13		
1 ½ in	55CM22		1 ½ in	55CM67	1 ½ in	55CM16		
25 ft	1 ½ in		3JT78	—	—	—	—	
50 ft	1 ½ in		3JT79	—	—	—	—	
100 ft	1 ½ in		52TV36	1 ½ in	52TV40	1 ½ in	52TV44	
1 in Hose Inside Dia.								
25 ft	1 in	1 ½ in	52ZX56	—	—	—	—	
50 ft		1 ½ in	52ZX57	—	—	—	—	
100 ft		1 ½ in	52ZX58	—	—	—	—	

Hose L	Fitting Size	Outside Dia.	RED 200 PSI Item No.	YELLOW 300 PSI Item No.
Coupled Assembly, Synthetic Rubber				
¾ in Hose Inside Dia.				
100 ft	¼ in	1 ½ in	41TF13	41TF14



6Z788



Nitrile Air Hose Assemblies

- Temp. range: -20° to 210°F
- 4:1 safety factor
- Reinforcement: synthetic yarn
- Brass couplers

Use with air, water, and mild chemicals in low-pressure industrial, construction, and agricultural applications.

Hose Length	Fitting Size	RED 250 PSI Outside Dia.	Item No.	YELLOW 300 PSI Outside Dia.	Item No.
Coupled Assembly, Nitrile					
¼ in Hose Inside Dia.					
25 ft	¼ in	½ in	12666	¾ in	4XR48
50 ft	¼ in	½ in	22010	¾ in	4XR49
¾ in Hose Inside Dia.					
25 ft	¾ in	1 ½ in	6Z787	1 ½ in	4XR50
50 ft	¾ in	1 ½ in	4Z898	1 ½ in	4XR53
50 ft	¾ in	1 ½ in	6Z788	1 ½ in	4XR51
50 ft	¾ in	1 ½ in	4Z899	1 ½ in	4XR54
½ in Hose Inside Dia.					
25 ft	½ in	1 ¾ in	6Z789	¾ in	4XR55
50 ft	½ in	1 ¾ in	5Z331	¾ in	4XR57
¾ in Hose Inside Dia.					
25 ft	¾ in	1 ½ in	5Z332	1 ¾ in	4XR59
50 ft	¾ in	1 ½ in	5Z333	1 ¾ in	4XR60



Gorilla Premium Air Hose Assemblies

- Max. pressure: 500 psi
- Temp. range: -20° to 210°F
- 4:1 safety factor

Reinforced with Flexten fiber yarn to resist bending and pressure stresses. Yellow Carbryn synthetic rubber cover is nonconductive and has high abrasion resistance. Nitrile synthetic rubber tube resists oil, solvents, and aromatics. Factory-installed fittings on each end.



3JT55

Hose Outside Dia.	5 ft Item No.	10 ft Item No.	15 ft Item No.	25 ft Item No.	50 ft Item No.
Hose Fittings					
¼ in Hose Inside Dia.					
Carbon Steel ¼ in MNPT x Carbon Steel ¼ in MNPT	¾ in	—	—	3JT55	3JT56
¾ in Hose Inside Dia.					
Carbon Steel ¾ in M Quick Disconnect x Brass ¾ in F Quick-Disconnect	¾ in	55CN20	55CN21	55CN22	—
Brass ¾ in MNPT x Brass ¾ in MNPT	¾ in	55CN17	55CN18	55CN19	—
Carbon Steel ¾ in MNPT x Carbon Steel ¾ in MNPT	¾ in	—	—	3JT57	—
½ in Hose Inside Dia.					
Brass ½ in MNPT x Brass ½ in MNPT	¾ in	55CN23	55CN24	55CN25	—
Carbon Steel ½ in M Quick Disconnect x Brass ½ in F Quick-Disconnect	¾ in	55CN26	55CN27	55CN28	—
Carbon Steel ½ in MNPT x Carbon Steel ½ in MNPT	¾ in	—	—	3JT59	—
¾ in Hose Inside Dia.					
Brass ¾ in MNPT x Brass ¾ in MNPT	1 ½ in	55CN29	55CN30	55CN31	—
Carbon Steel ¾ in MNPT x Carbon Steel ¾ in MNPT	1 ½ in	—	—	3JT61	3JT62



5W021



Nitrile Bulk Air Hose

- Temp. range: -20° to 210°F
- 4:1 safety factor
- 500-ft. hose length can be made from 1 or 2 pieces of varying lengths

Constructed with a nitrile oil-resistant tube and cover. Hose is nonconductive. Suitable for use with air, water, and mild chemicals.

Hose Color	Max. Working Pressure @ 70°F	Hose Length	Outside Dia.	Brand	Item No.
Bulk Hose					
¼ in Hose Inside Dia.					
Blue	300 psi	1 000 ft	0.500 in	Continental	10A239
Red	250 psi	250 ft	0.500 in	Speedaire	5W019
Red	250 psi	500 ft	0.500 in	Speedaire	10A216
Yellow	300 psi	250 ft	0.543 in	Speedaire	4XR47
Yellow	300 psi	500 ft	0.543 in	Speedaire	10A217
¾ in Hose Inside Dia.					
Red	250 psi	250 ft	0.687 in	Speedaire	5W020
Red	250 psi	500 ft	0.653 in	Speedaire	10A218
Red	300 psi	250 ft	0.687 in	Speedaire	4XR52
Yellow	500 psi	500 ft	0.687 in	Speedaire	10A219
Yellow	500 psi	25 ft	0.625 in	Continental	55CK35
Yellow	500 psi	50 ft	0.625 in	Continental	55CK36
½ in Hose Inside Dia.					
Red	250 psi	250 ft	0.840 in	Speedaire	5W021
Red	250 psi	500 ft	0.812 in	Speedaire	10A250
Red	300 psi	250 ft	0.858 in	Speedaire	4XR56
Yellow	500 psi	500 ft	0.856 in	Speedaire	10A251
Yellow	500 psi	25 ft	0.875 in	Continental	55CK37
Yellow	500 psi	50 ft	0.875 in	Continental	55CK38
¾ in Hose Inside Dia.					
Red	250 psi	150 ft	1.125 in	Speedaire	5W731
Red	250 psi	500 ft	1.125 in	Speedaire	10A220
Red	300 psi	150 ft	1.189 in	Speedaire	4XR58
Yellow	500 psi	500 ft	1.189 in	Speedaire	10A221
Yellow	500 psi	25 ft	1.1875 in	Continental	55CK39
Yellow	500 psi	50 ft	1.1875 in	Continental	55CK40
1 in Hose Inside Dia.					
Red	250 psi	150 ft	1.500 in	Speedaire	5W732
Red	300 psi	500 ft	1.500 in	Speedaire	4XR61
Yellow	500 psi	25 ft	1.5 in	Continental	55CK41
Yellow	500 psi	50 ft	1.5 in	Continental	55CK42