Scan. Order. Done.
Details on page A1.

31A788 31A926 31A885 31A851 31A897 31A845 31A887 31A832 31A821

31A798 31A803 31A792 31A952 31A988 31A977 31A914

Hydraulic Quick Couplers

- Temp. range: -40 to 250°F, except 3000 Series are -22 to 230°F

For additional information, see Grainger.com®.

Coupling Size	Body Material*	Max. Flow Rate	Thread Size	COUPLER NIPPLE Mfr. Model	COUPLER NIPPLE Item No.	COUPLER BODY Mfr. Model	COUPLER BODY Item No.
3000, Female NPTF							
¼ in	S	11.36 lpm	¼"-18	3010-2	**31A790**	—	—
⅜ in	S	22.71 lpm	⅜"-18	3010-3	**31A791**	—	—
3000, Male NPTF							
¼ in	S	11.36 lpm	¼"-18	—	—	3050-2	**31A788**
⅜ in	S	22.71 lpm	⅜"-18	—	—	3050-3	**31A789**
4000, Female ORB							
¼ in	S	11.36 lpm	9⁄16"-18	4010-T6	**31A943**	4050-T6	**31A937**
½ in	S	45.42 lpm	¾"-16	—	—	4050-15	**31A926**
	S	45.42 lpm	¾"-16	—	—	4050-15P	**31A927**
	S	45.42 lpm	⅞"-14	—	—	4050-16	**31A928**
	S	45.42 lpm	⅞"-14	—	—	4050-16P	**31A929**
4000, NPTF							
¼ in	S	11.36 lpm	¼"-18	4010-2P	**31A940**	4050-2P	**31A930**
⅜ in	S	22.71 lpm	⅜"-18	4010-3P	**31A941**	4050-3P	**31A931**
½ in	S	45.42 lpm	½"-14	—	—	4050-4	**31A932**
	S	45.42 lpm	½"-14	—	—	4050-4P	**31A933**
	S	45.42 lpm	¾"-14	—	—	4050-5	**31A934**
	S	45.42 lpm	¾"-14	—	—	4050-5P	**31A935**
¾ in	S	105.99 lpm	¾"-14	—	—	4150-5	**31A938**
1 in	S	189.27 lpm	1"-11-1/2	4010-6P	**31A942**	—	—
	S	189.3 lpm	1"-11-1/2	—	—	4050-6P	**31A936**
4200, NPTF							
½ in	S	45.42 lpm	½"-14	—	—	4250-4	**31A939**
60, Female NPTF, ISO 7241-1 Series B							
⅛ in	S	3 lpm	⅛"-27	H1-63	**31A885**	H1-62	**31A851**
	303	3 lpm	⅛"-27	SH1-63	**31A897**	SH1-62	**31A863**
	316	3 lpm	⅛"-27	SSH1-63Y	**31A909**	SSH1-62Y	**31A874**
	B	3 lpm	⅛"-27	BH1-61	**31A879**	—	—
	B	3 lpm	⅛"-27	BH1-60	**31A845**	—	—
¼ in	B	11 lpm	¼"-18	BH2-61	**31A880**	BH2-60	**31A846**
	303	11 lpm	¼"-18	SH2-63	**31A898**	SH2-62	**31A864**
	316	11 lpm	¼"-18	SSH2-63Y	**31A910**	SSH2-62Y	**31A875**
	S	11 lpm	¼"-18	H2-62	**31A853**	—	—
	S	11 lpm	¼"-18	H2-63	**31A887**	—	—
⅜ in	B	23 lpm	⅜"-18	BH3-61	**31A881**	BH3-60	**31A847**
	303	23 lpm	⅜"-18	SH3-63	**31A901**	SH3-62	**31A866**
	S	23 lpm	⅜"-18	H3-62	**31A855**	—	—
	S	23 lpm	⅜"-18	H3-63	**31A889**	—	—
½ in	316	45 lpm	½"-14	SSH4-63Y	**31A911**	SSH4-62Y	**31A876**
	S	45 lpm	½"-14	H4-63	**31A891**	H4-62	**31A857**
	B	45 lpm	½"-14	BH4-61	**31A882**	BH4-60	**31A848**
	303	45 lpm	½"-14	SH4-63	**31A903**	SH4-62	**31A868**
¾ in	B	106 lpm	¾"-14	BH6-61	**31A883**	BH6-60	**31A849**
	S	106 lpm	¾"-14	H6-63	**31A893**	H6-62	**31A859**
	303	106 lpm	¾"-14	SH6-63	**31A905**	SH6-62	**31A870**
	316	106 lpm	¾"-14	SSH6-62Y	**31A877**	—	—
	316	106 lpm	¾"-14	SSH6-63Y	**31A912**	—	—
1 in	B	189 lpm	1"-11-1/2	BH8-61	**31A884**	BH8-60	**31A850**
	S	189 lpm	1"-11-1/2	H8-63	**31A895**	H8-62	**31A861**
	303	189 lpm	1"-11-1/2	SH8-63	**31A907**	SH8-62	**31A872**
	316	189 lpm	1"-11-1/2	SSH8-63Y	**31A913**	SSH8-62Y	**31A878**
60, Female ORB, ISO 7241-1 Series B							
⅛ in	S	3 lpm	7⁄16"-20	H1-63-T4	**31A886**	H1-62-T4	**31A852**
¼ in	S	11 lpm	9⁄16"-18	H2-63-T6	**31A888**	H2-62-T6	**31A854**
	303	11 lpm	9⁄16"-18	SH2-63-T6	**31A899**	SH2-62-T6	**31A865**
⅜ in	303	23 lpm	¾"-16	SH3-63-T8	**31A902**	SH3-62-T8	**31A867**
½ in	303	45 lpm	⅞"-14	SH4-63-T10	**31A904**	SH4-62-T10	**31A869**
¾ in	S	23 lpm	¾"-14	—	—	H3-62-T8	**31A856**
	S	23 lpm	¾"-16	H3-63-T8	**31A890**	—	—
	S	106 lpm	1 1⁄16"-12	H6-63-T12	**31A894**	H6-62-T12	**31A860**
	303	106 lpm	1 1⁄16"-12	SH6-63-T12	**31A906**	SH6-62-T12	**31A871**
⅞ in	S	45 lpm	⅞"-14	H4-63-T10	**31A892**	H4-62-T10	**31A858**
1 in	S	189 lpm	1 5⁄16"-12	H8-63-T16	**31A896**	H8-62-T16	**31A862**
	303	189 lpm	1 5⁄16"-12	SH8-63-T16	**31A908**	SH8-62-T16	**31A873**
6600, Female NPTF, ISO 7241-1 Series A							
¼ in	S	11.36 lpm	⅛"-27	6602-2-4	**31A835**	6601-2-4	**31A824**
	S	11.36 lpm	¼"-18	6602-4-4	**31A836**	6601-4-4	**31A825**
⅜ in	S	22.71 lpm	⅜"-18	6602-6-6	**31A837**	6601-6-6	**31A826**
½ in	S	45.42 lpm	¾"-14	6602-12-10	**31A832**	6601-12-10	**31A821**
	S	45.42 lpm	½"-14	6602-8-10	**31A838**	6601-8-10	**31A827**
¾ in	S	105.99 lpm	¾"-14	—	—	6601-12-12	**31A822**
	S	106 lpm	¾"-14	6602-12-12	**31A833**	—	—
1 in	S	189.27 lpm	1"-11-1/2	6602-16-16	**31A834**	6601-16-16	**31A823**
6600, ORB, ISO 7241-1 Series A							
⅜ in	S	22.71 lpm	9⁄16"-18	6610-6-6	**31A843**	6608-6-6	**31A830**
½ in	S	45.42 lpm	⅞"-14	6610-10-10	**31A839**	6608-10-10	**31A828**
	S	45.42 lpm	1 1⁄16"-12	6610-12-10	**31A840**	6608-12-10	**31A829**
	S	45.42 lpm	¾"-16	6610-8-10	**31A844**	6608-8-10	**31A831**
¾ in	S	106 lpm	1 1⁄16"-12	6610-12-12	**31A841**	—	—
1 in	S	189.3 lpm	1 5⁄16"-12	6610-16-16	**31A842**	—	—

Coupling Size	Body Material*	Max. Flow Rate	Thread Size	COUPLER NIPPLE Mfr. Model	COUPLER NIPPLE Item No.	COUPLER BODY Mfr. Model	COUPLER BODY Item No.
8010, Female ORB							
½ in	S	45.42 lpm	¾"-14	8010-15	**31A944**	—	—
	S	45.42 lpm	¾"-14	8010-15P	**31A945**	—	—
	S	45.42 lpm	⅞"-14	8010-16	**31A946**	—	—
	S	45.42 lpm	⅞"-14	8010-16P	**31A947**	—	—
8010, NPTF							
½ in	S	45.42 lpm	½"-14	8010-4	**31A948**	—	—
	S	45.42 lpm	½"-14	8010-4P	**31A949**	—	—
	S	45.42 lpm	¾"-14	8010-5	**31A950**	—	—
	S	45.42 lpm	¾"-14	8010-5P	**31A951**	—	—
FEM, Female NPSF, Flush Face, ISO 16028							
¼ in	S	11.36 lpm	¼"-18	FEM-252-4FP	**31A811**	FEM-251-4FP-NL	**31A798**
⅜ in	S	22.71 lpm	⅜"-18	FEM-372-6FP	**31A813**	FEM-371-6FP-NL	**31A801**
½ in	S	45.42 lpm	½"-14	FEM-502-8FP	**31A818**	FEM-501-8FP-NL	**31A807**
¾ in	S	98.42 lpm	¾"-14	FEM-752-12FP	**31A820**	FEM-751-12FP-NL	**31A810**
FEM, FSAE, Flush Face, ISO 16028							
½ in	S	45.42 lpm	1 1⁄16"-12	FEM-502-12FO	**31A816**	FEM-501-12FO-NL	**31A805**
9⁄16 in	S	11.36 lpm	9⁄16"-18	FEM-252-6FO	**31A812**	FEM-251-6FO-NL	**31A799**
⅝ in	S	75.71 lpm	1 1⁄16"-12	—	—	FEM-621-12FO-NL	**31A808**
¾ in	S	22.71 lpm	¾"-16	FEM-372-8FO	**31A814**	FEM-371-8FO-NL	**31A802**
	S	45.42 lpm	¾"-16	FEM-502-8FO	**31A817**	FEM-501-8FO-NL	**31A806**
	S	98.42 lpm	1 1⁄16"-12	FEM-752-12FO	**31A819**	FEM-751-12FO-NL	**31A809**
⅞ in	S	45.42 lpm	⅞"-14	FEM-502-10FO	**31A815**	FEM-501-10BMF-NL	**31A803**
	S	45.42 lpm	⅞"-14	—	—	FEM-501-10FO-NL	**31A804**
FF, FNPT, Flush Face							
⅜ in	S	22.71 lpm	⅜"-18	FF-372-6FP	**31A795**	FF-371-6FP	**31A792**
	S	22.71 lpm	½"-14	FF-372-8FP	**31A797**	FF-371-8FP	**31A794**
FF, FSAE, Flush Face							
⅜ in	S	22.71 lpm	¾"-16	FF-372-8FO	**31A796**	FF-371-8FO	**31A793**
ST, FNPT Straight Thru							
⅛ in	B	11.36 lpm	⅛"-27	BST-N1	**31A976**	BST-1	**31A952**
	303	11.36 lpm	⅛"-27	SST-N1	**31A988**	SST-1	**31A964**
	303	11.36 lpm	⅛"-27	SST-N1M	**31A989**	—	—
	B	11.36 lpm	⅛"-27	—	—	BST-1M	**31A953**
¼ in	B	22.71 lpm	¼"-18	BST-N2	**31A978**	BST-2	**31A954**
	303	22.71 lpm	¼"-18	SST-N2	**31A990**	SST-2	**31A966**
	B	22.71 lpm	¼"-18	—	—	BST-2M	**31A955**
⅜ in	B	45.42 lpm	⅜"-18	BST-N3	**31A980**	BST-3	**31A956**
	B	45.42 lpm	⅜"-18	—	—	BST-3M	**31A957**
	303	45.43 lpm	⅜"-18	SST-N3	**31A992**	SST-3	**31A968**
½ in	B	45.42 lpm	½"-14	BST-N4	**31A982**	BST-4	**31A958**
	B	45.42 lpm	½"-14	—	—	BST-4M	**31A959**
	303	45.43 lpm	½"-14	SST-N4	**31A994**	SST-4	**31A970**
¾ in	303	105.99 lpm	¾"-14	SST-N6	**31A996**	SST-6	**31A972**
	303	105.99 lpm	¾"-14	—	—	SST-6M	**31A973**
	B	106 lpm	¾"-14	BST-N6	**31A984**	BST-6	**31A960**
	B	106 lpm	¾"-14	—	—	BST-6M	**31A961**
1 in	303	189.27 lpm	1"-11-1/2	SST-N8	**31A998**	SST-8	**31A974**
	B	189.3 lpm	1"-11-1/2	BST-N8M	**31A987**	BST-8	**31A962**
	B	189.3 lpm	1"-11-1/2	BST-N8	**31A986**	—	—
ST, MNPT							
⅛ in	B	11.36 lpm	⅛"-27	BST-N1M	**31A977**	—	—
	303	11.36 lpm	⅛"-27	—	—	SST-1M	**31A965**
¼ in	B	22.71 lpm	¼"-18	BST-N2M	**31A979**	—	—
	303	22.71 lpm	¼"-18	SST-N2M	**31A991**	SST-2M	**31A967**
⅜ in	B	45.42 lpm	⅜"-18	BST-N3M	**31A981**	—	—
	303	45.43 lpm	⅜"-18	SST-N3M	**31A993**	SST-3M	**31A969**
½ in	B	45.42 lpm	½"-14	BST-N4M	**31A983**	—	—
	303	45.43 lpm	½"-14	SST-N4M	**31A995**	SST-4M	**31A971**
¾ in	303	105.99 lpm	¾"-14	SST-N6M	**31A997**	—	—
	B	106 lpm	¾"-14	BST-N6M	**31A985**	—	—
1 in	303	189.27 lpm	1"-11-1/2	SST-N8M	**31A999**	SST-8M	**31A975**
	B	189.3 lpm	1"-11-1/2	—	—	BST-8M	**31A963**

Description	PLUGS Mfr. Model	PLUGS Item No.	CAPS Mfr. Model	CAPS Item No.
Parker 60 Series Dust Plugs & Caps				
⅛ in	H1-65M	**31A920**	H1-66M	**31A914**
¼ in	H2-65M	**31A921**	H2-66M	**31A915**
⅜ in	H3-65M	**31A922**	H3-66M	**31A916**
½ in	H4-65M	**31A923**	H4-66M	**31A917**
¾ in	H6-65M	**31A924**	H6-66M	**31A918**
1 in	H8-65M	**31A925**	H8-66M	**31A919**

** B = Brass, 303 = 303 Stainless Steel, 316 = 316 Stainless Steel, S = Steel.*

Find even **MORE** on **Grainger.com®**