



### Duct Hoses for Metal Shavings

- Temp. range: -60° to 180°F
- Resistant to abrasion, punctures, moisture, UV rays, and ozone
- Hard-drawn spring steel wire helical support



Hose I.D.	Hose Length	Max. Working Pressure @ 70°F	Bend Radius	Vacuum Rating	BLACK Item No.	CLEAR Item No.
<b>Thermoplastic Polyurethane</b>						
3 in	25 ft	23 psi	3.4 in	24.00 in Hg	2TA27	2TA20
4 in	25 ft	18 psi	4.4 in	23.00 in Hg	2TA28	2TA21
5 in	25 ft	14 psi	5.2 in	18.00 in Hg	2TA29	2TA22
10 in	25 ft	10 psi	9.3 in	5.00 in Hg	2TA32	2TA25
12 in	25 ft	8 psi	10.3 in	3.00 in Hg	2TA33	—



### Urethane Lavatory Duct Hoses for Liquid Waste

- Temp. range: -60° to 160°F
- Translucent blue

Used to vacuum liquid waste in airline ground-support applications. These crush-resistant urethane hoses are air-tight and resist punctures.



Hose I.D.	Hose Length	Max. Working Pressure @ 70°F	Bend Radius	Vacuum Rating	Item No.
<b>Urethane</b>					
4 1/2 in	10 ft	10 psi	9 in	10.00 in Hg	3AYG2
	12 ft	10 psi	9 in	10.00 in Hg	3AYG3
	15 ft	10 psi	9 in	10.00 in Hg	3AYG4



### Duct Hose Connectors

These connectors provide a connection point for duct hose. Cuffs are threaded and connect to equipment inlets or tools, while couplers join duct hose to extend their length.



Connector Material	Connection Outside Dia.	Overall Length	Compatible Hose Grainger Part Number	Brand	Item No.
<b>Cuff</b>					
PVC	1 1/2 in	4 in	2RV79	Hi-Tech Duravent	2RV91
PVC	1 3/4 in	4 in	2RV81	Hi-Tech Duravent	2RV93
PVC	1 1/2 in	3 1/2 in	2RV51	Hi-Tech Duravent	2RV58
PVC	1 3/4 in	3 1/2 in	2RV53	Hi-Tech Duravent	2RV59
PVC	1 1/2 in	3 in	3AXK, 3AXN3, 3AXX1, 3AXY6, 3AYC8, 3AYE9	Hi-Tech Duravent	3AYV9
PVC	1 3/4 in	3 in	3AXK	Hi-Tech Duravent	3AYW1
PVC	2 5/8 in	4 in	2RV83	Hi-Tech Duravent	2RV95
PVC	2 7/8 in	4 in	2RV85	Hi-Tech Duravent	2RV97
PVC	2 5/8 in	3 1/2 in	2RV55	Hi-Tech Duravent	2RV60
PVC	2 in	3 1/2 in	3AXK, 3AXN3, 3AXX1, 3AXY6, 3AYC8, 3AYE9	Hi-Tech Duravent	3AYW2
PVC	2 1/4 in	3 1/2 in	3AXK	Hi-Tech Duravent	3AYW3
PVC	3 3/8 in	4 in	2RV87	Hi-Tech Duravent	2RV99
PVC	3 1/4 in	4 in	3AXK	Hi-Tech Duravent	3AYW4
PVC	4 1/4 in	4 1/2 in	3AXK, 3AXN3, 3AXX1, 3AXY6, 3AYC8, 3AYE9	Hi-Tech Duravent	3AYW5
<b>Straight Couplers</b>					
304 Stainless Steel	4 in	4 in	—	—	2TA34
304 Stainless Steel	5 in	4 in	—	—	2TA35
304 Stainless Steel	6 in	4 in	—	—	2TA36
304 Stainless Steel	8 in	4 in	—	—	2TA37
304 Stainless Steel	10 in	4 in	—	—	2TA38
304 Stainless Steel	12 in	4 in	—	—	2TA39



### Duct Hose for Fumes

- Temp. range: -65° to 140°F

Self-supporting and have excellent crush resistance. Resist damage from exposure to chemicals, moisture, and oils.



Hose I.D.	Hose Length	Max. Working Pressure @ 70°F	Bend Radius	Vacuum Rating	Item No.
<b>Polyethylene</b>					
1 1/4 in	50 ft	20 psi	3.5 in	20.00 in Hg	2RY51
2 1/2 in	25 ft	14 psi	4.6 in	16.00 in Hg	2RY56
2 in	25 ft	15 psi	4.3 in	18.00 in Hg	2RY55
3 in	25 ft	9 psi	5.1 in	11.00 in Hg	2RY57



### Automotive Exhaust Hoses & Connectors

- Crush-resistant
- Weld-free installation
- Corrugated body for flexibility and bendability

Automotive exhaust hoses are used on large trucks, commercial trucks, and buses to connect the vehicles' cross-over exhaust system to their muffler and exhaust stack.



**EPDM exhaust hoses** are all-rubber, airtight hoses constructed to safely handle CO2 emissions.

**304 stainless steel exhaust hoses** can withstand exposure to high-temperature exhaust and resists corrosion.

**Exhaust hose connectors** join and route automotive exhaust hoses. They have internal threading for a secure connection.

Hose I.D.	Hose Length	Temp. Range	Brand	Item No.
<b>Automotive Exhaust Hoses</b>				
<b>EPDM</b>				
2 in	11 ft	-20° to 600°F	Hi-Tech Duravent	3AYK3
2 1/2 in	11 ft	-20° to 375°F	Hi-Tech Duravent	3AYK4
3 in	11 ft	-20° to 375°F	Hi-Tech Duravent	3AYK5
3 1/2 in	11 ft	-20° to 375°F	Hi-Tech Duravent	3AYK6
4 in	11 ft	-20° to 375°F	Hi-Tech Duravent	3AYK7
4 in	20 ft	-20° to 375°F	Hi-Tech Duravent	3AYL3
5 in	11 ft	-20° to 375°F	Hi-Tech Duravent	3AYK8
6 in	11 ft	-20° to 375°F	Hi-Tech Duravent	3AYL2
<b>304 Stainless Steel</b>				
4 in	12 in	-65° to 1000°F	Dayco	4GKA3
4 in	18 in	-65° to 1000°F	Dayco	4GKA4
4 in	24 in	-65° to 1000°F	Dayco	4GKA5
5 in	12 in	-65° to 1000°F	Dayco	4GKA6
5 in	18 in	-65° to 1000°F	Dayco	4GKA7
5 in	24 in	-65° to 1000°F	Dayco	4GKA8

Material	Connec. Type	Connection Outside Dia.	Overall Length	Compatible Hose Grainger Part Number	Brand	Item No.
<b>Exhaust Hose Connectors</b>						
<b>Wye</b>						
Aluminum	Screw On	5 in	10 in	3AYK3, 3AYL3	Hi-Tech Duravent	3AYP9
Rubber	Screw On	3 in	10 in	3AYK3, 3AYL3	Hi-Tech Duravent	3AYP7
Rubber	Screw On	4 in	10 in	3AYK3, 3AYL3	Hi-Tech Duravent	3AYP8
<b>Universal Bell Adapter</b>						
Rubber	Screw On	3 1/2 in	10 in	3AYK3, 3AYL3	Hi-Tech Duravent	3AYL9
Rubber	Screw On	4 in	10 in	3AYK3, 3AYL3	Hi-Tech Duravent	3AYN1
Rubber	Screw On	4 in	10 in	3AYK3, 3AYL3	Hi-Tech Duravent	3AYN2
<b>Tailpipe Adapter</b>						
Rubber	Screw On	3 in	12 in	3AYK3, 3AYL3	Hi-Tech Duravent	3AYL4
Rubber	Screw On	3 1/2 in	12 in	3AYK3, 3AYL3	Hi-Tech Duravent	3AYL5
Rubber	Screw On	4 in	12 in	3AYK3, 3AYL3	Hi-Tech Duravent	3AYL6
Rubber	Screw On	4 in	10 in	3AYK3, 3AYL3	Hi-Tech Duravent	3AYL7
Rubber	Screw On	4 1/2 in	10 in	3AYK3, 3AYL3	Hi-Tech Duravent	3AYL8
Rubber	Screw On	4 1/2 in	12 in	3AYK3, 3AYL3	Hi-Tech Duravent	3AYN4
<b>Straight Splice Connector</b>						
Aluminum	Screw On	4 in	10 in	3AYK3, 3AYL3	Hi-Tech Duravent	3AYN9
Aluminum	Screw On	5 in	10 in	3AYK3, 3AYL3	Hi-Tech Duravent	3AYP1
Aluminum	Screw On	6 in	10 in	3AYK3, 3AYL3	Hi-Tech Duravent	3AYP2
Aluminum	Screw On	6 in	10 in	3AYK3, 3AYL3	Hi-Tech Duravent	3AYP3
Rubber	—	—	3 in	—	Continental	41ND37
Rubber	—	—	3 in	—	Continental	41ND38
<b>Stack Adapter</b>						
Rubber	Screw On	6 1/2 in	12 in	3AYK3, 3AYL3	Hi-Tech Duravent	3AYN5
Rubber	Screw On	7 in	12 in	3AYK3, 3AYL3	Hi-Tech Duravent	3AYN6
<b>Door Port</b>						
Aluminum	Slip On	4 in	4 in	3AYK3, 3AYL3	Hi-Tech Duravent	3AYP5
Aluminum	Slip On	5 in	4 in	3AYK3, 3AYL3	Hi-Tech Duravent	3AYP6
Rubber	Slip On	3 in	4 in	3AYK3, 3AYL3	Hi-Tech Duravent	3AYP4